EUROPEAN
COMMISSION

Brussels, 10.11.2026
COM(2026) 612 final

ANNEX

ANNEX

to the

Proposal for a COUNCIL REGULATION

amending Regulation (EU) 2021/2278 suspending the Common Customs Tariff duties referred to in Article 56(2), point (c), of Regulation (EU) No 952/2013 of the European Parliament and of the Council on certain agricultural and industrial products

ANNEX

‘ANNEX

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.3349	ex 0710 80 95	50	Bamboo shoots, frozen, not put up for retail sale	0 %	-	31.12.2029
0.2829	*ex 0711 59 00	11	Mushrooms, excluding mushrooms of the genera *Agaricus*, *Calocybe*, *Clitocybe*, *Lepista*, *Leucoagaricus*, *Leucopaxillus*, *Lyophyllum* and *Tricholoma*, provisionally preserved in brine, in sulphur water, or in other preservative solutions, but unsuitable in that state for immediate consumption, for the food-canning industry (1)	0 %	-	31.12.2031
0.2463	ex 0712 32 00 ex 0712 33 00 ex 0712 34 00 ex 0712 39 00	10 10 31 31	Mushrooms, excluding mushrooms of the genus *Agaricus*, dried, whole or in identifiable slices or pieces, for treatment other than simple repacking for retail sale (1)(2)	0 %	-	31.12.2029
0.3347	ex 0804 10 00	30	Dates, fresh or dried, for use in the manufacture (excluding packing) of products of drink or food industries (1)	0 %	-	31.12.2029
0.2864	*ex 1511 90 19 ex 1511 90 91 ex 1513 11 10 ex 1513 19 30 ex 1513 21 10 ex 1513 29 19 ex 1513 29 30	20 20 20 20 20 20 20	Palm oil, coconut (copra) oil, palm kernel oil, for the manufacture of: — industrial monocarboxylic fatty acids of subheading 3823 19 10, — methyl esters of fatty acids of heading 2915 or 2916, — fatty alcohols of subheadings 2905 17, 2905 19 and 3823 70, — fatty alcohols of subheading 2905 16, pure or mixed, — stearic acid of subheading 3823 11 00, — goods of heading 3401, or — fatty acids with high purity of heading 2915 (1)	0 %	-	31.12.2027
0.9085	ex 1515 60 99	20	Microbial oil, refined or semi-refined, but not chemically modified, containing by weight in the form of triglycerides: — 35 % or more but not more than 70 % of arachidonic acid — not more than 3 % by weight of docosahexaenoic acid	0 %	-	31.12.2030
0.7686	1516 20 10		Hydrogenated castor oil, so called 'opal-wax'	0 %	-	31.12.2029
0.4080	*ex 1517 90 99	30	Microbial oil, refined, containing by weight: — 25 % or more but not more than 70 % arachidonic acid and no more than 5 % docosahexenoic acid — standardised with vegetable oil	0 %	-	31.12.2031
0.2423	ex 1902 30 10	40	Glass noodles containing 60 % or more by weight of mung bean starch in immediate packings of 5 kg or more and not put up for retail sale	0 %	-	31.12.2029
0.2866	ex 2005 91 00	10	Bamboo shoots, prepared or preserved, in immediate packings of a net content of more than 5 kg	0 %	-	31.12.2029
0.5875	ex 2007 99 50 ex 2007 99 50	84 94	Papaya puree concentrate, obtained by cooking: — of the genus *Carica spp.*, — with a sugar content by weight of more than 13 % but not more than 30 % for use in the manufacture of products of food and drink industry (1)	7.8 % (3)	-	31.12.2029
0.5867	ex 2007 99 50 ex 2007 99 50	85 95	Guava puree concentrate, obtained by cooking: — of the genus *Psidium spp.*, — with a sugar content by weight of more than 13 % but not more than 30 % for use in the manufacture of products of food and drink industry (1)	6 % (3)	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.5587	ex 2008 99 49 ex 2008 99 99	70 11	Blanched vine leaves of the genus *Karakishmish*, in brine, containing by weight: — more than 6 % of salt concentration, — 0,1 % or more but not more than 1,4 % of acidity expressed as citric acid monohydrate and — whether or not but not more than 2 000 mg/kg of sodium benzoate according CODEX STAN 192-1995 for use in the manufacture of stuffed vine leaves with rice (1)	0 %	-	31.12.2027
0.7767	*ex 2008 99 99	35	Frozen pulp from acai berries: — hydrated and pasteurised, — separated from the kernels by the addition of water, — with a Brix value of less than 9,7, and — with a sugar content of less than 9 %	0 %	-	31.12.2029
0.6050	ex 2009 89 79	30	Frozen acerola juice concentrate : — with a Brix value of more than 48 but not more than 67, — in immediate packings of a content of 50 litres or more	0 %	l	31.12.2029
0.5206	*ex 2009 89 79	85	Acai berry juice concentrate: — of the species *Euterpe oleracea*, — frozen, — not sweetened, — not in powder form, — of a Brix value of 23 or more but not more than 32, in immediate packings of a content of 10 kg or more	0 %	-	31.12.2031
0.6152	*ex 2106 10 20	20	Soya protein concentrate having a protein content by weight, calculated on a dry weight basis, of 65 % or more but not more than 90 % in powder or textured form	0 %	-	31.12.2027
0.7284	ex 2106 90 92 ex 3504 00 90	50 10	Casein protein hydrolysate consisting of: — by weight 20 % or more but not more than 70 % free amino acids, and — peptones of which by weight more than 90 % having a molecular weight of not more than 2000 Da	0 %	-	31.12.2027
0.5246	*ex 2519 90 10	10	Fused magnesia with a purity by weight of 94 % or more	0 %	-	31.12.2031
0.6168	ex 2707 99 99	10	Heavy and medium oils, whose aromatic content exceeds their non-aromatic content, for use as refinery feedstock to undergo one of the specific processes described in Additional note 5 to Chapter 27 (1)	0 %	-	31.12.2029
0.8144	ex 2710 12 25	20	Mixture of C6 aliphatic hydrocarbons (CAS RN 92112-69-1), containing by weight 60 % or more but not more than 80 % of n-hexane (CAS RN 110-54-3), with: — a specific gravity of 0,666 or more but not more than 0,686, — a total of carbonyl compounds of less than 1 ppm, — a total of acetylenic compounds of less than 2 ppm	0 %	-	31.12.2030
0.7823	ex 2710 19 81 ex 2710 19 99	30 50	Catalytically hydroisomerized and dewaxed base oil of hydrogenated, highly isoparaffinic hydrocarbons, containing: — 90 % or more by weight of saturates, and — not more than 0,03 % by weight of sulphur, and with — a viscosity index of 80 or more, but less than 120, and — a kinematic viscosity less than 5,0 cSt at 100°C or more than 13,0 cSt at 100°C	0 %	-	31.12.2029
0.7822	ex 2710 19 81 ex 2710 19 99	40 60	Catalytically hydroisomerized and dewaxed base oil of hydrogenated, highly isoparaffinic hydrocarbons, containing: — 90 % or more by weight of saturates, and — not more than 0,03 % by weight of sulphur, with a viscosity index of 120 or more	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.6495	ex 2710 19 99	20	Catalytic de-waxed base oil, synthesised from gaseous hydrocarbons, followed by a heavy paraffin conversion process (HPC), containing: — not more than 1 mg/kg of sulphur — more than 99 % by weight of saturated hydrocarbons — more than 75 % by weight of n- and iso-paraffinic hydrocarbons with a carbon chain length of 18 or more but not more than 50; and — a kinematic viscosity at 40 °C of more than 6,5 mm^2/s, or — a kinematic viscosity at 40 °C of more than 11 mm^2/s with a viscosity index of 120 or more	0 %	-	31.12.2029
0.7393	ex 2712 90 99	10	Blend of 1-alkenes containing by weight 90 % or more 1-alkenes of a chain length of 24 carbon atoms or more but not more than 1 % 1-alkenes of a chain length of more than 70 carbon atoms	0 %	-	31.12.2027
0.8021	2804 70 10		Red phosphorus	0 %	-	31.12.2027
0.8022	2804 70 90		Phosphorus, other than red phosphorus	0 %	-	31.12.2029
0.6658	ex 2805 12 00	10	Calcium with a purity of 98 % or more by weight, in powder or wire form (CAS RN 7440-70-2)	0 %	-	31.12.2030
0.5609	ex 2805 19 90	20	Lithium metal (CAS RN 7439-93-2) of a purity by weight of 98,8 % or more	0 %	-	31.12.2027
0.2559	ex 2805 30 10	10	Alloy of cerium and other rare-earth metals, containing by weight 47 % or more of cerium	0 %	-	31.12.2029
0.4979	2805 30 21 2805 30 29 2805 30 31 2805 30 39 2805 30 40		Rare-earth metals, scandium and yttrium, of a purity by weight of 95 % or more	0 %	-	31.12.2030
0.6836	ex 2811 22 00	15	Amorphous silicon dioxide (CAS RN 60676-86-0) — in the form of powder — of a purity by weight of 99,0 % or more — with a median grain size of 0,7 µm or more, but not more than 2,1 µm — where 70 % of the particles have a diameter of not more than 3 µm	0 %	-	31.12.2029
0.7292	ex 2811 29 90	10	Tellurium dioxide (CAS RN 7446-07-3)	0 %	-	31.12.2027
0.3308	ex 2812 90 00	10	Nitrogen trifluoride (CAS RN 7783-54-2)	0 %	-	31.12.2029
0.5747	ex 2816 40 00	10	Barium hydroxide (CAS RN 17194-00-2)	0 %	-	31.12.2027
0.4640	ex 2818 20 00	10	Activated alumina with a specific surface area of at least 350 m^2/g	0 %	-	31.12.2029
0.6837	ex 2818 30 00	20	Aluminium hydroxide (CAS RN 21645-51-2) — in the form of powder, — with a purity by weight of 99,5 % or more, — with a decomposition point of 263°C or more, — with a particle size of 4 µm (± 1 µm), — with a Total-Na_2O-content by weight of not more than 0,06 %	0 %	-	31.12.2030
0.3306	ex 2818 30 00	30	Aluminium hydroxide oxide in the form of boehmite or pseudoboehmite (CAS RN 1318-23-6)	0 %	-	31.12.2029
0.5369	*ex 2819 90 90	10	Dichromium trioxide (CAS RN 1308-38-9) for use in metallurgy (1)	0 %	-	31.12.2027
0.5576	ex 2825 10 00	10	Hydroxylammonium chloride (CAS RN 5470-11-1)	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7897	*ex 2825 20 00	10	Lithium hydroxide monohydrate (CAS RN 1310-66-3) with a purity by weight of 99 % or more	2.6 %	-	31.12.2027
0.3800	*2825 30 00		Vanadium oxides and hydroxides	0 %	-	31.12.2031
0.3303	ex 2825 50 00	20	Copper (I or II) oxide containing by weight 78 % or more of copper and not more than 0,03 % of chloride	0 %	-	31.12.2029
0.6819	ex 2825 50 00	30	Copper (II) oxide (CAS RN 1317-38-0), with a particle size of not more than 100 nm	0 %	-	31.12.2030
0.5555	ex 2825 60 00	10	Zirconium dioxide (CAS RN 1314-23-4)	0 %	-	31.12.2027
0.7193	*ex 2825 70 00	20	Molybdic Acid (CAS RN 7782-91-4)	0 %	-	31.12.2027
0.5055	ex 2826 19 90	10	Tungsten hexafluoride (CAS RN 7783-82-6) with a purity by weight of 99,9 % or more	0 %	-	31.12.2030
0.8296	*ex 2826 90 80	30	Lithium hexafluorophosphate (CAS RN 21324-40-3) with a purity by weight of 99 % or more	2.7 %	-	31.12.2027
0.2865	ex 2827 39 85	10	Copper monochloride (CAS RN 7758-89-6) with a purity by weight of 96 % or more	0 %	-	31.12.2029
0.4180	*ex 2827 39 85	20	Antimony pentachloride (CAS RN 7647-18-9) of a purity by weight of 99 % or more	0 %	-	31.12.2031
0.6143	ex 2827 39 85	40	Barium chloride dihydrate (CAS RN 10326-27-9)	0 %	-	31.12.2029
0.8936	ex 2827 49 90	10	Zirconium dichloride oxide (CAS RN 7699-43-6) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.6463	ex 2827 60 00	10	Sodium iodide (CAS RN 7681-82-5)	0 %	-	31.12.2029
0.7596	ex 2828 10 00	10	Calcium hypochlorite (CAS RN 7778-54-3) having an active chlorine content of 65 % or more	0 %	-	31.12.2029
0.3859	ex 2833 29 80	20	Manganese sulphate monohydrate (CAS RN 10034-96-5)	0 %	-	31.12.2029
0.4338	ex 2835 10 00	10	Sodium hypophosphite monohydrate (CAS RN 10039-56-2)	0 %	-	31.12.2027
0.7452	ex 2835 10 00	30	Aluminium Phosphinate (CAS RN 7784-22-7)	0 %	-	31.12.2029
0.8448	ex 2835 10 00	40	Calcium phosphinate (CAS RN 7789-79-9) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.6144	ex 2835 10 00	50	Sodium hypophosphite (CAS RN 7681-53-0) with a purity by weight of 97 % or more or as aqueous solution containing by weight 55 % or more but not more than 65 % of sodium hypophosphite	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.2524	ex 2836 91 00	20	Lithium carbonate, containing one or more of the following impurities at the concentrations indicated: — 2 mg/kg or more of arsenic, — 200 mg/kg or more of calcium, — 200 mg/kg or more of chlorides, — 20 mg/kg or more of iron, — 150 mg/kg or more of magnesium, — 20 mg/kg or more of heavy metals, — 300 mg/kg or more of potassium, — 300 mg/kg or more of sodium, — 200 mg/kg or more of sulphates, determined according to the methods specified in the European Pharmacopœia	0 %	-	31.12.2029
0.2863	ex 2836 99 17	30	Zirconium (IV) basic carbonate (CAS RN 57219-64-4 or 37356-18-6) with a purity by weight of 96 % or more	0 %	-	31.12.2029
0.3300	ex 2837 19 00	20	Copper cyanide (CAS RN 544-92-3)	0 %	-	31.12.2029
0.4078	*ex 2837 20 00	10	Tetrasodium hexacyanoferrate (II) (CAS RN 13601-19-9)	0 %	-	31.12.2031
0.2861	ex 2839 90 00	20	Calcium silicate (CAS RN 1344-95-2)	0 %	-	31.12.2029
0.6632	ex 2840 20 90	10	Zinc borate (CAS RN 12767-90-7)	0 %	-	31.12.2030
0.8520	ex 2840 20 90	20	Barium borate (CAS RN 13701-59-2) with a purity by weight of 99 % or more	0 %	-	31.12.2027
0.6482	ex 2841 70 00	50	Hexaammonium heptamolybdate, anhydrous (CAS RN 12027-67-7) or as tetrahydrate (CAS RN 12054-85-2) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.4323	ex 2841 80 00	10	Diammonium wolframate (ammonium paratungstate) (CAS RN 11120-25-5)	0 %	-	31.12.2027
0.8441	ex 2841 80 00	20	Disodium wolframate (CAS RN 13472-45-2) with a purity by weight of 90 % or more	0 %	-	31.12.2027
0.7301	ex 2841 90 30	10	Potassium metavanadate (CAS RN 13769-43-2)	0 %	-	31.12.2027
0.5936	ex 2841 90 70	20	Potassium titanium oxide (CAS RN 12056-51-8) in powder form with a purity of 99 % or more	0 %	-	31.12.2029
0.4416	ex 2842 10 00	10	Synthetic beta zeolite powder	0 %	-	31.12.2029
0.4588	ex 2842 10 00	20	Synthetic chabasite zeolite powder	0 %	-	31.12.2029
0.7397	ex 2842 10 00	50	Fluorphlogopite (CAS RN 12003-38-2)	0 %	-	31.12.2027
0.7097	*ex 2842 10 00	60	Aluminosilicate (CAS RN 1318-02-1) with — a purity by weight of 94 % or more, — a zeolite structure of aluminophosphate-eighteen (AEI), and — a phase purity of 90 % or more for use in the manufacture of copper zeolite or washcoat used in the automotive catalyst production (1)	0 %	-	31.12.2031
0.4642	ex 2842 90 10	10	Sodium selenate (CAS RN 13410-01-0)	0 %	-	31.12.2029
0.3295	2845 10 00		Heavy water (deuterium oxide) (*Euratom*) (CAS RN 7789-20-0)	0 %	-	31.12.2029
0.4189	*2845 40 00		Helium-3 (CAS RN 14762-55-1)	0 %	-	31.12.2031
0.3297	2845 90 10		Deuterium and compounds thereof; hydrogen and compounds thereof, enriched in deuterium; mixtures and solutions containing these products (*Euratom*)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.4191	ex 2845 90 90	20	Water enriched at a level of 95 % or more by weight with oxygen-18 (CAS RN 14314-42-2)	0 %	-	31.12.2029
0.4190	*ex 2845 90 90	30	(^{13}C)Carbon monoxide (CAS RN 1641-69-6)	0 %	-	31.12.2027
0.8426	ex 2845 90 90	50	Ytterbium oxide (CAS RN 1380743-42-9), with a purity by weight of 99 % or more, enriched to 99,0 % or more but not more than 99,8 % of Ytterbium-176	0 %	-	31.12.2027
0.2859	ex 2846 10 00 ex 3824 99 96	10 53	Rare-earth concentrate containing by weight 60 % or more but not more than 95 % of rare-earth oxides and not more than 1 % each of zirconium oxide, aluminium oxide or iron oxide, and having a loss on ignition of 5 % or more by weight	0 %	-	31.12.2029
0.3296	ex 2846 10 00	20	Dicerium tricarbonate (CAS RN 537-01-9), whether or not hydrated	0 %	-	31.12.2029
0.3420	ex 2846 10 00	30	Cerium lanthanum carbonate, whether or not hydrated	0 %	-	31.12.2029
0.3227	2846 90 30 2846 90 40 2846 90 50 2846 90 60 2846 90 70 2846 90 90		Compounds, inorganic or organic, of rare-earth metals, of yttrium or of scandium or of mixtures of these metals, other than those of subheading 2846 10 00	0 %	-	31.12.2029
0.3418	ex 2850 00 20	10	Silane (CAS RN 7803-62-5)	0 %	-	31.12.2029
0.5497	*ex 2850 00 20	40	Germanium tetrahydride (CAS RN 7782-65-2)	0 %	-	31.12.2031
0.7302	ex 2850 00 20	60	Disilane (CAS RN 1590-87-0)	0 %	-	31.12.2027
0.7555	ex 2850 00 20	70	Cubic Boron nitride (CAS RN 10043-11-5)	0 %	-	31.12.2029
0.3419	ex 2850 00 20	80	Arsine (CAS RN 7784-42-1) with a purity by volume of 99,999 % or more, for use in the production of semiconductors (1)	0 %	-	31.12.2030
0.4492	ex 2850 00 60	10	Sodium azide (CAS RN 26628-22-8)	0 %	-	31.12.2029
0.3421	ex 2853 90 90	20	Phosphine (CAS RN 7803-51-2)	0 %	-	31.12.2029
0.8906	ex 2903 29 00	20	*trans*-1,2-Dichloroethylene (CAS RN 156-60-5) with a purity by weight of 99 % or more	0 %	-	31.12.2030
0.6633	2903 42 00		Difluoromethane (CAS RN 75-10-5)	0 %	-	31.12.2030
0.2854	ex 2903 49 30	10	Carbon tetrafluoride (tetrafluoromethane) (CAS RN 75-73-0)	0 %	-	31.12.2029
0.2852	ex 2903 49 30	20	Perfluoroethane (CAS RN 76-16-4)	0 %	-	31.12.2029
0.5803	ex 2903 51 00	10	2,3,3,3-Tetrafluoroprop-1-ene (2,3,3,3-tetrafluoropropene) (CAS RN 754-12-1)	0 %	-	31.12.2027
0.4517	ex 2903 51 00	20	*Trans*-1,3,3,3-tetrafluoroprop-1-ene (*Trans*-1,3,3,3-tetrafluoropropene) (CAS RN 29118-24-9)	0 %	-	31.12.2029
0.7324	ex 2903 59 00	40	1,1,2,3,4,4-Hexafluorobuta-1,3-diene (CAS RN 685-63-2)	0 %	-	31.12.2027
0.4066	*ex 2903 59 00	50	Hexafluoropropene (CAS RN 116-15-4) with a purity by weight of 99 % or more, for use in the manufacture of fluoropolymers or hydrofluorocarbons (1)	0 %	-	31.12.2031

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8553	ex 2903 69 19	25	(*E*)-1,4-Dibrombut-2-ene (CAS RN 821-06-7) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.8525	ex 2903 69 19	35	2,2-Dibromopropane (CAS RN 594-16-1) with a purity by weight of 99 % or more	0 %	-	31.12.2028
0.8318	ex 2903 69 19	50	Vinyl bromide (CAS RN 593-60-2) with a purity by weight of 98 % or more, or as a solution in tetrahydrofuran (CAS RN 109-99-9) containing by weight 23 % or more, but not more than 26 % vinylbromide	0 %	-	31.12.2027
0.7895	ex 2903 72 00	10	Dichloro-1,1,1-trifluoroethane (CAS RN 306-83-2) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.5212	*ex 2903 77 90	10	Chlorotrifluoroethylene (CAS RN 79-38-9)	0 %	-	31.12.2031
0.6485	ex 2903 79 30	10	Trans-1-chloro-3,3,3-trifluoropropene (CAS RN 102687-65-0)	0 %	-	31.12.2029
0.5765	ex 2903 89 70	50	Chlorocyclopentane (CAS RN 930-28-9)	0 %	-	31.12.2027
0.7304	ex 2903 89 70	60	Octafluorocyclobutane (CAS RN 115-25-3)	0 %	-	31.12.2027
0.8803	ex 2903 99 80	10	4-Bromo-2-fluorobiphenyl (CAS RN 41604-19-7) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.8492	ex 2903 99 80	18	1-Fluoronaphthalene (CAS RN 321-38-0) with a purity by weight of 99 % or more	0 %	-	31.12.2027
0.8557	ex 2903 99 80	23	3,5-*Bis*(trifluoromethyl) benzylbromide (CAS RN 32247-96-4) with a purity by weight of 95 % or more	0 %	-	31.12.2028
0.8017	ex 2903 99 80	25	2,2'-Dibromobiphenyl (CAS RN 13029-09-9) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.4529	ex 2903 99 80	28	Fluorobenzene (CAS RN 462-06-6) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.8018	ex 2903 99 80	35	2-Bromo-9,9'-spirobi[9H-fluoren] (CAS RN 171408-76-7) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.3411	ex 2903 99 80	40	2,6-Dichlorotoluene (CAS RN 118-69-4), of a purity by weight of 99 % or more and containing: — 0,001 mg/kg or less of tetrachlorodibenzodioxines, — 0,001 mg/kg or less of tetrachlorodibenzofurans, — 0,2 mg/kg or less of tetrachlorobiphenyls	0 %	-	31.12.2029
0.8076	ex 2903 99 80	45	1-Bromo-4-(*trans*-4-propylcyclohexyl)benzene (CAS RN 86579-53-5) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.8101	ex 2903 99 80	55	1-Bromo-4-(*trans*-4-ethylcyclohexyl)benzene (CAS RN 91538-82-8) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.8166	*ex 2903 99 80	65	2,6-Difluorobenzyl bromide (CAS RN 85118-00-9) with a purity by weight of 97 % or more	0 %	-	31.12.2031
0.8177	*ex 2903 99 80	70	1-[Chloro(phenyl)methyl]-2-methylbenzene (CAS RN 41870-52-4) with a purity by weight of 99 % or more	0 %	-	31.12.2031
0.5917	ex 2903 99 80	83	1-Bromo-3,4,5-trifluorobenzene (CAS RN 138526-69-9) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.3407	ex 2904 10 00	30	Sodium *p*-styrenesulphonate (CAS RN 2695-37-6)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.4686	ex 2904 10 00	50	Sodium 2-methylprop-2-ene-1-sulphonate (CAS RN 1561-92-8)	0 %	-	31.12.2029
0.3409	ex 2904 20 00	10	Nitromethane (CAS RN 75-52-5)	0 %	-	31.12.2030
0.3391	ex 2904 20 00	20	Nitroethane (CAS RN 79-24-3)	0 %	-	31.12.2027
0.3408	ex 2904 20 00	30	1-Nitropropane (CAS RN 108-03-2)	0 %	-	31.12.2030
0.3390	ex 2904 20 00	40	2-Nitropropane (CAS RN 79-46-9)	0 %	-	31.12.2029
0.2526	ex 2904 99 00	20	1-Chloro-2,4-dinitrobenzene (CAS RN 97-00-7)	0 %	-	31.12.2029
0.9094	*ex 2904 99 00	23	1-Bromo-5-fluoro-2-methyl-3-nitrobenzene (CAS RN 502496-33-5) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.6612	ex 2904 99 00	25	Difluoromethanesulphonyl chloride (CAS RN 1512-30-7)	0 %	-	31.12.2030
0.3388	ex 2904 99 00	30	Tosyl chloride (CAS RN 98-59-9)	0 %	-	31.12.2029
0.5745	ex 2904 99 00	40	4-Chlorobenzenesulphonyl chloride (CAS RN 98-60-2)	0 %	-	31.12.2027
0.6001	ex 2904 99 00	50	Ethanesulphonyl chloride (CAS RN 594-44-5)	0 %	-	31.12.2029
0.7957	ex 2904 99 00	55	2,4-Dichloro-1,3-dinitro-5-(trifluoromethyl)benzene (CAS RN 29091-09-6) with a purity by weight of 96 % or more	0 %	-	31.12.2030
0.6407	ex 2904 99 00	60	4,4'-Dinitrostilbene-2,2'-disulfonic acid (CAS RN 128-42-7)	0 %	-	31.12.2029
0.9064	ex 2904 99 00	75	Trifluoromethanesulfonic acid (CAS RN 1493-13-6) with a purity by weight of 99 % or more	0 %	-	31.12.2030
0.6560	ex 2904 99 00	78	1-Chloro-2-nitrobenzene (CAS RN 88-73-3) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.6186	ex 2905 11 00	10	Methanol (CAS RN 67-56-1) with a purity of 99,85 % by weight or more	0 %	-	31.12.2029
0.2967	ex 2905 19 00	11	Potassium tert-butanolate (CAS RN 865-47-4), whether or not in the form of a solution in tetrahydrofuran according to note 1e) to Chapter 29 of the CN	0 %	-	31.12.2029
0.6118	ex 2905 19 00	20	Butyltitanate monohydrate, homopolymer (CAS RN162303-51-7)	0 %	-	31.12.2029
0.6119	ex 2905 19 00	25	Tetra-(2-ethylhexyl) titanate (CAS RN 1070-10-6)	0 %	-	31.12.2029
0.5534	ex 2905 19 00	70	Titanium tetrabutanolate (CAS RN 5593-70-4)	0 %	-	31.12.2027
0.5533	ex 2905 19 00	80	Titanium tetraisopropoxide (CAS RN 546-68-9)	0 %	-	31.12.2027
0.6002	ex 2905 19 00	85	Titanium tetraethanolate (CAS RN 3087-36-3)	0 %	-	31.12.2029
0.6464	ex 2905 22 00	10	Linalool (CAS RN 78-70-6) containing by weight 90,7 % or more of (3R)-(-)-Linalool (CAS RN 126-91-0)	0 %	-	31.12.2029
0.7114	*ex 2905 22 00	30	(±)-β-Citronellol (CAS RN 106-22-9) with a purity by weight of 94 % or more	0 %	-	31.12.2031
0.7388	ex 2905 29 90	10	Cis-hex-3-en-1-ol (CAS RN 928-96-1)	0 %	-	31.12.2027
0.9088	ex 2905 29 90	50	Prop-2-yn-1-ol (CAS RN 107-19-7) with a purity by weight of 99 % or more	0 %	-	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8544	ex 2905 39 95	15	2,5-Dimethylhexane-2,5-diol (CAS RN 110-03-2) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.8619	ex 2905 39 95	25	Pinacol (CAS RN 76-09-5) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.5255	*ex 2905 39 95	30	2,4,7,9-Tetramethyl-4,7-decanediol (CAS RN 17913-76-7)	0 %	-	31.12.2031
0.8937	ex 2905 39 95	35	Propane-1,3-diol (CAS RN 504-63-2) with a purity by weight of 99 % or more	0 %	-	31.12.2030
0.5847	ex 2905 39 95	40	Decane-1,10-diol (CAS RN 112-47-0)	0 %	-	31.12.2027
0.8932	ex 2905 39 95	45	2,5,7,10,11,14-hexaoxa-1,6-distibabicyclo[4.4.4]tetradecane (CAS RN 29736-75-2) with a purity by weight of 99 % or more	0 %	-	31.12.2030
0.5908	ex 2905 39 95	50	2-Methyl-2-propylpropane-1,3-diol (CAS RN 78-26-2)	0 %	-	31.12.2029
0.7701	ex 2905 39 95	60	Dodecane-1,12-diol (CAS RN 5675-51-4)	0 %	-	31.12.2029
0.7914	ex 2905 39 95	70	2-Methylpropane-1,3-diol (CAS RN 2163-42-0) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.8370	ex 2905 39 95	80	Pentane-1,5-diol (CAS RN 111-29-5) with a purity by weight of 97 % or more	0 %	-	31.12.2027
0.4624	ex 2905 59 98	20	2,2,2-Trifluoroethanol (CAS RN 75-89-8)	0 %	-	31.12.2029
0.3378	ex 2906 19 00	10	Cyclohex-1,4-ylenedimethanol (CAS RN 105-08-8)	0 %	-	31.12.2027
0.3380	ex 2906 19 00	20	4,4'-Isopropylidenedicyclohexanol (CAS RN 80-04-6)	0 %	-	31.12.2029
0.8231	*ex 2906 19 00	60	5-Methyl-2-(prop-1-en-2-yl)cyclohexanol, mixture of isomers (CAS RN 7786-67-6) with a purity by weight of 90 % or more	0 %	-	31.12.2031
0.8721	ex 2906 19 00	70	(1*S*,2*S*,3*R*,5*S*)-(+)-2,3-Pinanediol (CAS RN 18680-27-8) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.6257	ex 2906 19 00	80	4-*tert*-Butylcyclohexanol (CAS RN 98-52-2) with a purity by weight of 97 % or more	0 %	-	31.12.2029
0.8929	ex 2906 29 00	25	(2-Bromo-5-iodophenyl)methanol (CAS RN 946525-30-0) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.7373	ex 2906 29 00	50	2,2'-(m-Phenylene)dipropan-2-ol (CAS RN 1999-85-5)	0 %	-	31.12.2027
0.7806	ex 2906 29 00	60	3-[3-(Trifluoromethyl)phenyl]propan-1-ol (CAS RN 78573-45-2)	0 %	-	31.12.2029
0.5855	ex 2906 29 00	85	2-Phenylethanol (CAS RN 60-12-8) with a purity by weight of 95 % or more	0 %	-	31.12.2027
0.6329	ex 2907 12 00	20	Mixture of meta-cresol (CAS RN 108-39-4) and para-cresol (CAS RN 106-44-5) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.6559	ex 2907 12 00	40	*p*-Cresol (CAS RN 106-44-5) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.5216	*ex 2907 15 90	10	2-Naphthol (CAS RN 135-19-3)	0 %	-	31.12.2031
0.6256	ex 2907 19 10	20	2,6-Xylenol (CAS RN 576-26-1) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.4480	ex 2907 19 90	20	Biphenyl-4-ol (CAS RN 92-69-3)	0 %	-	31.12.2029
0.7753	ex 2907 19 90	30	2-Methyl-5-(propan-2-yl)phenol (CAS RN 499-75-2)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.3372	ex 2907 21 00	10	Resorcinol (CAS RN 108-46-3)	0 %	-	31.12.2029
0.8482	ex 2907 29 00	13	4,4'-Methylenedi-2,6-xylenol (CAS RN 5384-21-4) with a purity by weight of 98,5 % or more	0 %	-	31.12.2027
0.6026	ex 2907 29 00	15	6,6'-Di-tert-butyl-4,4'-butylidenedi-m-cresol (CAS RN 85-60-9)	0 %	-	31.12.2029
0.3367	ex 2907 29 00	30	4,4',4"-Ethylidynetriphenol (CAS RN 27955-94-8)	0 %	-	31.12.2029
0.2584	ex 2907 29 00	33	2,2′,2″,6,6′,6″-Hexa-*tert*-butyl-*α,α′,α″*-(mesitylen-2,4,6-triyl)tri-*p*-cresol (CAS RN 1709-70-2) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.7402	ex 2907 29 00	38	Biphenyl-4,4'-diol (CAS RN 92-88-6) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.5432	*ex 2907 29 00	45	2-Methylhydroquinone (CAS RN 95-71-6)	0 %	-	31.12.2031
0.3848	ex 2907 29 00	85	Phloroglucinol anhydrous (CAS RN 108-73-6) or phloroglucinol dihydrate (CAS RN 6099-90-7) with a purity by weight of 95 % or more	0 %	-	31.12.2029
0.5914	ex 2908 19 00	20	4,4'-(Perfluoroisopropylidene)diphenol (CAS RN 1478-61-1)	0 %	-	31.12.2029
0.6260	ex 2908 19 00	30	4-Chlorophenol (CAS RN 106-48-9)	0 %	-	31.12.2029
0.3359	ex 2909 19 90	30	Mixture of isomers of nonafluorobutyl methyl ether or nonafluorobutyl ethyl ether, of a purity by weight of 99 % or more	0 %	-	31.12.2029
0.4035	*ex 2909 19 90	50	3-Ethoxy-perfluoro-2-methylhexane (CAS RN 297730-93-9)	0 %	-	31.12.2027
0.5407	*ex 2909 20 00	20	8-Methoxycedrane (CAS RN 19870-74-7) or methyl cedryl ether (CAS RN 67874-81-1) each with a purity by weight of 96 % or more	0 %	-	31.12.2031
0.5503	*ex 2909 30 39	20	1,1'-Propane-2,2-diylbis[3,5-dibromo-4-(2,3-dibromopropoxy)benzene] (CAS RN 21850-44-2)	0 %	-	31.12.2031
0.6649	ex 2909 30 39	30	1,1'-(1-Methylethylidene)bis[3,5-dibromo-4-(2,3-dibromo-2-methylpropoxy)]-benzene (CAS RN 97416-84-7)	0 %	-	31.12.2030
0.7828	ex 2909 30 39	50	2-(1-Adamantyl)-4-Bromoanisole (CAS RN 104224-63-7) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.4710	ex 2909 30 90	10	2-(Phenylmethoxy)naphthalene (CAS RN 613-62-7)	0 %	-	31.12.2029
0.4711	ex 2909 30 90	20	1,2-Bis(3-methyl-phenoxy)ethane (CAS RN 54914-85-1)	0 %	-	31.12.2029
0.7115	*ex 2909 30 90	25	1,2-Diphenoxyethane (CAS RN 104-66-5) in the form of powder or as an aqueous dispersion containing by weight 30 % or more but not more than 60 % of 1,2-diphenoxyethane	0 %	-	31.12.2031
0.6783	ex 2909 30 90	50	1-Ethoxy-2,3-difluorobenzene (CAS RN 121219-07-6)	0 %	-	31.12.2030
0.5117	ex 2909 30 90	55	3,4,5-Trimethoxytoluene (CAS RN 6443-69-2) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.6994	*ex 2909 30 90	70	*O,O,O*-1,3,5-trimethylresorcinol (CAS RN 621-23-8)	0 %	-	31.12.2031
0.7706	ex 2909 44 00	10	2-Propoxyethanol (CAS RN 2807-30-9)	0 %	-	31.12.2029
0.6927	*ex 2909 49 80	10	1-Propoxypropan-2-ol (CAS RN 1569-01-3)	0 %	-	31.12.2031

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8241	*ex 2909 49 80	30	3,4-Dimethoxybenzyl alcohol (CAS RN 93-03-8) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.8531	ex 2909 49 80	40	2,2'-*p*-Phenylenedioxydiethanol (CAS RN 104-38-1) with a purity by weight of 99 % or more	0 %	-	31.12.2028
0.8862	ex 2909 49 80	50	2,2'-[Oxy*bis*(methylene)]*bis*[2-ethylpropane-1,3-diol] (CAS RN 23235-61-2) with a purity by weight of 95 % or more	0 %	-	31.12.2029
0.3484	ex 2909 50 00	10	4-(2-Methoxyethyl)phenol (CAS RN 56718-71-9)	0 %	-	31.12.2029
0.7910	ex 2909 60 90	50	Solution of 3,6,9-(ethyl and/or propyl)-3,6,9-trimethyl-1,2,4,5,7,8-hexoxonanes (CAS RN 1613243-54-1) in mineral spirits (CAS RN 1174522-09-8), containing by weight 25 % or more, but not more than 41 % of the hexoxonanes	0 %	-	31.12.2029
0.7744	ex 2910 90 00	10	2-[(2-Methoxyphenoxy)methyl]oxirane (CAS RN 2210-74-4)	0 %	-	31.12.2029
0.5940	ex 2910 90 00	15	1,2-Epoxycyclohexane (CAS RN 286-20-4)	0 %	-	31.12.2029
0.7672	ex 2910 90 00	25	Phenyloxirane (CAS RN 96-09-3)	0 %	-	31.12.2029
0.2649	ex 2910 90 00	30	2,3-Epoxypropan-1-ol (glycidol) (CAS RN 556-52-5)	0 %	-	31.12.2029
0.6660	ex 2910 90 00	50	2,3-Epoxypropyl phenyl ether (CAS RN 122-60-1)	0 %	-	31.12.2030
0.4361	*ex 2910 90 00	80	Allyl glycidyl ether (CAS RN 106-92-3)	0 %	-	31.12.2031
0.7116	*ex 2912 19 00	10	Undecanal (CAS RN 112-44-7)	0 %	-	31.12.2031
0.8073	ex 2912 19 00	20	Acrylaldehyde (CAS RN 107-02-8) with a purity by weight of 98 % or more for the production of perfume or pharmaceutical intermediaries (1)	0 %	-	31.12.2030
0.6968	*ex 2912 29 00	15	2,6,6-Trimethylcyclohexenecarbaldehyde (alpha-beta isomers mixture) (CAS RN 52844-21-0)	0 %	-	31.12.2031
0.7314	ex 2912 29 00	35	Cinnamaldehyde (CAS RN 104-55-2)	0 %	-	31.12.2027
0.8604	ex 2912 29 00	65	Terephthalaldehyde (CAS RN 623-27-8) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.6072	ex 2912 29 00	70	4-tert-Butylbenzaldehyde (CAS RN 939-97-9)	0 %	-	31.12.2029
0.5135	ex 2912 49 00	30	Salicylaldehyde (CAS RN 90-02-8)	0 %	-	31.12.2030
0.7353	ex 2912 49 00	50	2,6-Dihydroxybenzaldehyde (CAS RN 387-46-2)	0 %	-	31.12.2027
0.8582	ex 2912 49 00	60	4-Hydroxybenzaldehyde (CAS RN 123-08-0) with a purity by weight of 96 % or more	0 %	-	31.12.2028
0.8911	ex 2912 49 00	70	5-(1,1-Dimethylethyl)-2-methoxybenzaldehyde (CAS RN 85943-26-6) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.7712	ex 2913 00 00	10	2-Nitrobenzaldehyde (CAS RN 552-89-6)	0 %	-	31.12.2029
0.8328	ex 2913 00 00	20	4-(Difluoromethoxy)-3-hydroxybenzaldehyde (CAS RN 151103-08-1) with a purity by weight of 98 % or more	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8552	ex 2913 00 00	30	2-Hydroxy-5-nitrobenzaldehyde (CAS RN 97-51-8) with a purity by weight of 95 % or more	0 %	-	31.12.2028
0.4228	ex 2914 19 90	20	Heptan-2-one (CAS RN 110-43-0)	0 %	-	31.12.2027
0.4275	ex 2914 19 90	40	Pentan-2-one (CAS RN 107-87-9)	0 %	-	31.12.2027
0.7554	ex 2914 19 90	60	Zinc acetylacetonate (CAS RN 14024-63-6)	0 %	-	31.12.2029
0.4274	ex 2914 19 90	80	3-Methylbutanone (CAS RN 563-80-4) with a purity by weight of 97 % or more	0 %	-	31.12.2027
0.7568	ex 2914 29 00	15	Oestr-5(10)-ene-3,17-dione (CAS RN 3962-66-1)	0 %	-	31.12.2029
0.3475	ex 2914 29 00	20	Cyclohexadec-8-enone (CAS RN 3100-36–5)	0 %	-	31.12.2029
0.7450	ex 2914 29 00	25	Cyclohex-2-enone (CAS RN 930-68-7)	0 %	-	31.12.2029
0.4933	ex 2914 29 00	30	(R)-*p*-Mentha-1(6),8-dien-2-one (CAS RN 6485-40-1)	0 %	-	31.12.2030
0.8015	ex 2914 29 00	35	4-(*trans*-4-Propylcyclohexyl)cyclohexanone (CAS RN 82832-73-3) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.7389	ex 2914 29 00	55	1-(Cedr-8-en-9-yl)ethanone (CAS RN 32388-55-9) with a purity by weight of more than 90 %	0 %	-	31.12.2029
0.8695	ex 2914 29 00	65	3-Methylcyclopent-2-enone (CAS RN 2758-18-1) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.3480	ex 2914 29 00	75	Bornan-2-one (CAS RN 76-22-2) with a purity by weight of 90 % or more	0 %	-	31.12.2029
0.6265	ex 2914 39 00	15	2,6-Dimethyl-1-indanone (CAS RN 66309-83-9)	0 %	-	31.12.2029
0.6447	ex 2914 39 00	25	1,3-Diphenylpropane-1,3-dione (CAS RN 120-46-7)	0 %	-	31.12.2029
0.4227	ex 2914 39 00	35	Benzophenone (CAS RN 119-61-9) with a purity by weight of 99 % or more	0 %	-	31.12.2027
0.4428	ex 2914 39 00	60	4-Methylbenzophenone (CAS RN 134-84-9)	0 %	-	31.12.2029
0.5739	ex 2914 39 00	70	Benzil (CAS RN 134-81-6)	0 %	-	31.12.2029
0.5535	ex 2914 39 00	80	4’-Methylacetophenone (CAS RN 122-00-9)	0 %	-	31.12.2027
0.8288	*ex 2914 40 90	10	Benzoin (CAS RN 119-53-9) with a purity by weight of 99 % or more	0 %	-	31.12.2027
0.7824	ex 2914 50 00	15	1,1-Dimethoxyacetone (CAS RN 6342-56-9) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.8168	*ex 2914 50 00	18	4'-Hydroxyacetophenone (CAS RN 99-93-4) with a purity by weight of 99 % or more	0 %	-	31.12.2031
0.5943	ex 2914 50 00	25	4'-Methoxyacetophenone (CAS RN 100-06-1)	0 %	-	31.12.2029
0.8195	*ex 2914 50 00	28	1,1'-{(2-Hydroxypropane-1,3-diyl)bis[oxy(6-hydroxybenzene-2,1-diyl)]}diethanone (CAS RN 16150-44-0) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.7797	ex 2914 50 00	35	2-Hydroxy-1-[4-[4-(2-hydroxy-2-methylpropanoyl)phenoxy]phenyl]-2-methylpropan-1-one (CAS-RN 71868-15-0)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.5435	*ex 2914 50 00	40	4-(4-Hydroxyphenyl)butan-2-one (CAS RN 5471-51-2)	0 %	-	31.12.2031
0.5809	ex 2914 50 00	45	3,4-Dihydroxybenzophenone (CAS RN 10425-11-3)	0 %	-	31.12.2027
0.8922	ex 2914 50 00	48	7-Hydroxy-3,4-dihydronaphthalen-1(2H)-one (CAS RN 22009-38-7) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.4235	ex 2914 50 00	60	2,2-Dimethoxy-2-phenylacetophenone (CAS RN 24650-42-8)	0 %	-	31.12.2027
0.4385	ex 2914 50 00	80	2',6'-Dihydroxyacetophenone (CAS RN 699-83-2)	0 %	-	31.12.2029
0.2647	ex 2914 69 80	10	2-Ethylanthraquinone (CAS RN 84-51-5)	0 %	-	31.12.2029
0.2643	ex 2914 69 80	30	1,4-Dihydroxyanthraquinone (CAS RN 81-64-1)	0 %	-	31.12.2029
0.5430	ex 2914 69 80	40	*p*-Benzoquinone (CAS RN 106-51-4)	0 %	-	31.12.2029
0.5782	ex 2914 79 00	20	2,4'-Difluorobenzophenone (CAS RN 342-25-6)	0 %	-	31.12.2027
0.7751	ex 2914 79 00	27	(2-Chloro-5-iodo-phenyl)-(4-fluoro-phenyl)-methanone (CAS RN 915095-86-2)	0 %	-	31.12.2029
0.7467	ex 2914 79 00	30	5-Methoxy-1-[4-(trifluoromethyl)phenyl]pentan-1-one (CAS RN 61718-80-7)	0 %	-	31.12.2029
0.8338	ex 2914 79 00	33	(4R)-4-(2-Fluorophenyl)-3,4-dihydro-2H-naphthalen-1-one (CAS RN 1234356-88-7) with a purity by weight of 99 % or more	0 %	-	31.12.2027
0.3474	ex 2914 79 00	40	Perfluoro(2-methylpentan-3-one) (CAS RN 756-13-8)	0 %	-	31.12.2029
0.8563	ex 2914 79 00	43	5-Chloropentan-2-one (CAS RN 5891-21-4) with a purity by weight of 95 % or more	0 %	-	31.12.2028
0.8591	ex 2914 79 00	48	2-Chloro-3',4'-dihydroxyacetophenone (CAS RN 99-40-1) with a purity by weight of 99 % or more	0 %	-	31.12.2028
0.2640	ex 2914 79 00	50	3'-Chloropropiophenone (CAS RN 34841-35-5)	0 %	-	31.12.2029
0.4948	*ex 2914 79 00	60	4'-*tert*-Butyl-2',6'-dimethyl-3',5'-dinitroacetophenone (CAS RN 81-14-1)	0 %	-	31.12.2031
0.5237	*ex 2914 79 00	70	4-Chloro-4'-hydroxybenzophenone (CAS RN 42019-78-3)	0 %	-	31.12.2031
0.6120	ex 2914 79 00	80	Tetrachloro-p-benzoquinone (CAS RN 118-75-2)	0 %	-	31.12.2029
0.7955	ex 2915 24 00	10	Acetic anhydride (CAS RN 108-24-7) with a purity by weight of 94 % or more	0 %	-	31.12.2030
0.8543	ex 2915 39 00	15	4-(2,2-Dichlorocyclopropyl)phenylacetate (CAS RN 144900-34-5) with a purity by weight of 97 % or more	0 %	-	31.12.2028
0.5121	*ex 2915 39 00	20	Dodeca-7,9-dienyl acetate (CAS RN 1011528-52-1) with a purity by weight of 93 % or more, stabilized with no more than 2 % by weight of 2,6-di-tert-butyl-p-cresol (CAS RN 128-37-0)	0 %	-	31.12.2030
0.6155	ex 2915 39 00	25	2-Methylcyclohexyl acetate (CAS RN 5726-19-2)	0 %	-	31.12.2029
0.5909	ex 2915 39 00	33	2-tert-Butylcyclohexyl acetate (CAS RN 88-41-5) with a purity by weight of 98 % or more, containing by weight 80 % or more of cis-2-tert-butylcyclohexyl acetate (CAS RN 20298-69-5)	0 %	-	31.12.2029
0.7433	ex 2915 39 00	35	Cis-3-hexenyl acetate (CAS RN 3681-71-8) with a purity by weight of 95 % or more	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.2957	ex 2915 39 00	40	*tert*-Butyl acetate (CAS RN 540-88-5)	0 %	-	31.12.2029
0.7423	ex 2915 39 00	45	4-*tert*-Butylcyclohexyl acetate (CAS RN 32210-23-4) with a purity by weight of 95 % or more	0 %	-	31.12.2027
0.5119	ex 2915 39 00	55	Dodec-8-enyl acetate (CAS RN 28079-04-1) with a purity by weight of 90 % or more	0 %	-	31.12.2030
0.5289	*ex 2915 39 00	75	Isobornyl acetate (CAS RN 125-12-2)	0 %	-	31.12.2031
0.5301	*ex 2915 39 00	80	1-Phenylethyl acetate (CAS RN 93-92-5)	0 %	-	31.12.2031
0.7834	ex 2915 40 00	10	Ethyl trichloroacetate (CAS RN 515-84-4) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.5858	ex 2915 60 19	20	Ethyl butyrate (CAS RN 105-54-4) with a purity by weight of 95 % or more	0 %	-	31.12.2027
0.7540	*ex 2915 70 40	10	Methyl palmitate (CAS RN 112-39-0) with a purity by weight of 97 % or more	0 %	-	31.12.2029
0.7541	*ex 2915 90 30	10	Methyl laurate (CAS RN 111-82-0) with a purity by weight of 97 % or more	0 %	-	31.12.2030
0.8495	ex 2915 90 30	20	Chloromethyl dodecanoate (CAS RN 61413-67-0) with a purity by weight of 97 % or more	0 %	-	31.12.2027
0.7407	ex 2915 90 90	20	Methyl (R)-2-fluoropropionate (CAS RN 146805-74-5)	0 %	-	31.12.2027
0.7542	ex 2915 90 90	25	Methyl octanoate (CAS RN 111-11-5), methyl decanoate (CAS RN 110-42-9) or methyl myristate (CAS RN 124-10-7)	0 %	-	31.12.2029
0.6003	ex 2915 90 90	27	Triethyl orthoformate (CAS RN 122-51-0) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.5767	ex 2915 90 90	30	3,3-Dimethylbutyryl chloride (CAS RN 7065-46-5)	0 %	-	31.12.2027
0.8154	*ex 2915 90 90	33	Ethyl 8-bromooctanoate (CAS RN 29823-21-0) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.8423	ex 2915 90 90	43	Trifluoroacetic anhydride (CAS RN 407-25-0) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.6255	ex 2915 90 90	45	Trimethyl orthoformate (CAS RN 149-73-5)	0 %	-	31.12.2029
0.8457	ex 2915 90 90	53	3-Chloro-2,2-dimethylpropanoyl chloride (CAS RN 4300-97-4) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.4954	ex 2915 90 90	60	Ethyl-6,8-dichlorooctanoate (CAS RN 1070-64-0)	0 %	-	31.12.2030
0.2585	ex 2916 12 00	10	2-*tert*-Butyl-6-(3-*tert*-butyl-2-hydroxy-5-methylbenzyl)-4-methylphenyl acrylate (CAS RN 61167-58-6)	0 %	-	31.12.2029
0.3466	ex 2916 13 00	30	Zinc monomethacrylate powder (CAS RN 63451-47-8) whether or not containing not more than 17 % by weight of manufacturing impurities	0 %	-	31.12.2030
0.3468	ex 2916 13 00	40	Zinc Dimethacrylate (CAS RN 13189-00-9) in the form of powder with a purity by weight of 99 % or more, with not more than 1 % of a stabiliser	0 %	-	31.12.2029
0.2638	ex 2916 14 00	10	2,3-Epoxypropyl methacrylate (CAS RN 106-91-2)	0 %	-	31.12.2029
0.9107	*ex 2916 14 00	60	3,3,4,4,5,5,6,6,7,7,8,8,8-Tridecafluorooctyl methacrylate (CAS RN 2144-53-8) with a purity by weight of 98 % or more	0 %	-	31.12.2031

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.5991	ex 2916 19 95	40	Sorbic acid (CAS RN 110-44-1) for use in the manufacture of animal feeds [(1)]	0 %	-	31.12.2029
0.6238	ex 2916 19 95	50	Methyl 2-fluoroacrylate (CAS RN 2343-89-7)	0 %	-	31.12.2029
0.7980	ex 2916 19 95	60	Methyl 2-fluoroprop-2-enoate (CAS RN 2343-89-7) with a purity by weight of 93 % or more, whether or not with not more than 7 % of the stabiliser 2,6-di-tert-butyl-p-cresol (CAS RN 128-37-0) and Tetrabutylammonium nitrite (CAS RN 26501-54-2)	0 %	-	31.12.2030
0.7940	ex 2916 19 95	70	Methyl 3-methyl-2-butenoate (CAS RN 924-50-5) with a purity by weight of 99,0 % or more	0 %	-	31.12.2030
0.7023	*ex 2916 20 00	15	Transfluthrin (ISO) (CAS RN 118712-89-3)	0 %	-	31.12.2031
0.7931	ex 2916 20 00	25	Cyclohexanecarbonyl chloride (CAS RN 2719-27-9) with a purity by weight of 99 % or more	0 %	-	31.12.2030
0.8336	ex 2916 20 00	55	Methyl 2,2-dimethyl-3-(2-methylprop-1-en-1-yl)cyclopropane-1-carboxylate (CAS RN 5460-63-9) with a purity by weight of 90 % or more	0 %	-	31.12.2027
0.4931	ex 2916 20 00	60	3-Cyclohexylpropionic acid (CAS RN 701-97-3)	0 %	-	31.12.2030
0.8352	ex 2916 20 00	65	Tefluthrin (ISO)(CAS RN 79538-32-2) with a purity by weight of 96 % or more	0 %	-	31.12.2027
0.5421	*ex 2916 31 00	10	Benzyl benzoate (CAS RN 120-51-4)	0 %	-	31.12.2031
0.8214	*ex 2916 31 00	20	Phenethyl benzoate (CAS RN 94-47-3) with a purity by weight of 95 % or more	0 %	-	31.12.2031
0.6248	ex 2916 39 90	13	3,5-Dinitrobenzoic acid (CAS RN 99-34-3)	0 %	-	31.12.2029
0.5214	*ex 2916 39 90	15	2-Chloro-5-nitrobenzoic acid (CAS RN 2516-96-3)	0 %	-	31.12.2031
0.2636	ex 2916 39 90	20	3,5-Dichlorobenzoyl chloride (CAS RN 2905-62-6)	0 %	-	31.12.2029
0.6557	ex 2916 39 90	23	(2,4,6-Trimethylphenyl)acetyl chloride (CAS RN 52629-46-6)	0 %	-	31.12.2029
0.7827	ex 2916 39 90	27	Methyl 6-Bromo-2-naphthoate (CAS RN 33626-98-1) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.4930	ex 2916 39 90	30	2,4,6-Trimethylbenzoyl chloride (CAS RN 938-18-1)	0 %	-	31.12.2030
0.9098	*ex 2916 39 90	32	4-Cyclopropyl-2-fluorobenzoic acid (CAS RN 1247927-81-6) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.5944	ex 2916 39 90	35	Methyl 4-*tert*-butylbenzoate (CAS RN 26537-19-9)	0 %	-	31.12.2029
0.9125	*ex 2916 39 90	37	3,5-Difluorobenzoic acid (CAS RN 455-40-3) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.8489	ex 2916 39 90	40	Ethyl 4-bromo-3-(bromomethyl)benzoate (CAS RN 347852-72-6) with a purity by weight of 97 % or more	0 %	-	31.12.2027
0.7734	ex 2916 39 90	43	2-(3,5-Bis(trifluoromethyl)phenyl)-2-methylpropanoic acid (CAS RN 289686-70-0)	0 %	-	31.12.2029
0.2634	ex 2916 39 90	50	3,5-Dimethylbenzoyl chloride (CAS RN 6613-44-1)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.4238	ex 2916 39 90	55	4-*tert*-Butylbenzoic acid (CAS RN 98-73-7)	0 %	-	31.12.2027
0.3462	ex 2916 39 90	58	Ibuprofen (INN) (CAS RN 15687-27-1) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.8369	ex 2916 39 90	67	Nitrobenzoic acid (CAS RN 62-23-7) with a purity by weight of 99 % or more	0 %	-	31.12.2027
0.5541	ex 2916 39 90	75	*m*-Toluic acid (CAS RN 99-04-7)	0 %	-	31.12.2027
0.5543	ex 2916 39 90	85	(2,4,5-Trifluorophenyl)acetic acid (CAS RN 209995-38-0)	0 %	-	31.12.2027
0.3457	ex 2917 11 00	20	Bis(*p*-methylbenzyl) oxalate (CAS RN 18241-31-1)	0 %	-	31.12.2029
0.4746	ex 2917 11 00	30	Cobalt oxalate (CAS RN 814-89-1)	0 %	-	31.12.2029
0.8946	ex 2917 12 00	30	Bis(3,4-epoxycyclohexylmethyl)adipate (CAS RN 3130-19-6) with a purity by weight of 97 % or more	0 %	-	31.12.2030
0.4684	ex 2917 19 10	10	Dimethyl malonate (CAS RN 108-59-8)	0 %	-	31.12.2029
0.5602	ex 2917 19 10	20	Diethyl malonate (CAS RN 105-53-3)	0 %	-	31.12.2027
0.7451	ex 2917 19 80	35	Diethyl methylmalonate (CAS RN 609-08-5)	0 %	-	31.12.2029
0.7880	ex 2917 19 80	45	Iron fumarate (CAS RN 141-01-5) with a purity by weight of 93 % or more	0 %	-	31.12.2029
0.4918	ex 2917 19 80	50	Tetradecanedioic acid (CAS RN 821-38-5)	0 %	-	31.12.2030
0.8302	ex 2917 19 80	55	Maleic acid (CAS RN 110-16-7) with a purity by weight of 99 % or more	0 %	-	31.12.2030
0.8530	ex 2917 19 80	60	Oxalyl dichloride (CAS RN 79-37-8) with a purity by weight of 99 % or more	0 %	-	31.12.2028
0.8728	ex 2917 19 80	65	20-*tert*-butoxy-20-oxoicosanoic acid (CAS RN 683239-16-9) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.3454	ex 2917 19 80	70	Itaconic acid (CAS RN 97-65-4)	0 %	-	31.12.2029
0.4790	ex 2917 19 80	75	Ethylene brassylate (CAS RN 105-95-3) with a purity by weight of 97 % or more	0 %	-	31.12.2029
0.8534	ex 2917 19 80	80	Ethyl chloroglyoxylate (CAS RN 4755-77-5) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.8945	ex 2917 19 80	85	Dibutyl itaconate (CAS RN 2155-60-4) with a purity by weight of 96 % or more	0 %	-	31.12.2030
0.2631	ex 2917 20 00	30	1,4,5,6,7,7-Hexachloro-8,9,10-trinorborn-5-ene-2,3-dicarboxylic anhydride (CAS RN 115-27-5)	0 %	-	31.12.2029
0.2627	ex 2917 20 00	40	3-Methyl-1,2,3,6-tetrahydrophthalic anhydride (CAS RN 5333-84-6)	0 %	-	31.12.2029
0.2954	ex 2917 34 00	10	Diallyl phthalate (CAS RN 131-17-9)	0 %	-	31.12.2029
0.4945	ex 2917 39 85	20	Dibutyl-1,4-benzenedicarboxylate (CAS RN 1962-75-0)	0 %	-	31.12.2030
0.6796	ex 2917 39 85	25	Naphthalene-1,8-dicarboxylic anhydride (CAS RN 81-84-5)	0 %	-	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.3640	ex 2917 39 85	30	Benzene-1,2:4,5-tetracarboxylic dianhydride (CAS RN 89-32-7)	0 %	-	31.12.2030
0.8255	*ex 2917 39 85	45	3-(4-Chlorophenyl)glutaric acid (CAS RN 35271-74-0) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.6553	ex 2917 39 85	50	1,4,5,8-Naphthalenetetracarboxylic acid-1,8-monoanhydride (CAS RN 52671-72-4)	0 %	-	31.12.2029
0.8526	ex 2917 39 85	55	3-Nitrophthalic acid (CAS RN 603-11-2) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.6554	ex 2917 39 85	60	Perylene-3,4:9,10-tetracarboxylic dianhydride(CAS RN 128-69-8)	0 %	-	31.12.2029
0.6366	ex 2918 19 30	10	Cholic acid (CAS RN 81-25-4)	0 %	-	31.12.2029
0.6367	ex 2918 19 30	20	3-α,12-α-Dihydroxy-5-β-cholan-24-oic acid (deoxycholic acid) (CAS RN 83-44-3)	0 %	-	31.12.2029
0.2950	ex 2918 19 98	20	L-Malic acid (CAS RN 97-67-6)	0 %	-	31.12.2029
0.8509	ex 2918 19 98	25	(*S*)-2-Hydroxy-2-phenylacetic acid (CAS RN 17199-29-0) with a purity by weight of 99 % or more	0 %	-	31.12.2027
0.7702	ex 2918 19 98	30	Ethyl 1-hydroxycyclopentanecarboxylate (CAS RN 41248-23-1)	0 %	-	31.12.2029
0.9188	*ex 2918 19 98	35	(*S*)-3-Hydroxy-2-phenylpropanoic acid (CAS RN 16202-15-6) with a purity by weight of 90 % or more	0 %	-	31.12.2031
0.7907	ex 2918 19 98	50	12-Hydroxyoctadecanoic acid (CAS RN 106-14-9) with a purity by weight of 90 % or more for use in the manufacture of polyglycerin-poly-12-hydroxyoctadecanoic acid esters (1)	0 %	-	31.12.2029
0.8044	ex 2918 19 98	60	*(R)-tert*-Butyl 2'-(1-hydroxyethyl)-3-methyl-[1,1'-biphenyl]-4-carboxylate (CAS RN 1246560-92-8) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.8422	ex 2918 19 98	70	Rac-*tert*-butyl 3-hydroxy-4-pentenoate (CAS RN 122763-67-1) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.9105	*ex 2918 29 00	20	4-Fluoro-3-hydroxybenzoic acid (CAS RN 51446-31-2) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.5781	ex 2918 29 00	35	Propyl 3,4,5-trihydroxybenzoate (CAS RN 121-79-9)	0 %	-	31.12.2027
0.8917	ex 2918 29 00	45	3-Hydroxy-2-naphthoic acid (CAS RN 92-70-6) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.6456	ex 2918 29 00	70	3,5-Diiodosalicylic acid (CAS RN 133-91-5)	0 %	-	31.12.2029
0.3638	ex 2918 29 00	85	Hexamethylene bis[3-(3,5-di-*tert*-butyl-4-hydroxyphenyl)propionate] (CAS RN 35074-77-2) with a purity by weight of 97 % or more	0 %	-	31.12.2029
0.4427	ex 2918 30 00	30	Methyl-2-benzoylbenzoate (CAS RN 606-28-0)	0 %	-	31.12.2029
0.7864	ex 2918 30 00	35	3-Oxocyclobutane-1-carboxylic acid with a purity by weight of 98 % or more (CAS RN 23761-23-1)	0 %	-	31.12.2029
0.8861	ex 2918 30 00	43	Ethyl 4-oxovalerate (CAS RN 539-88-8) with a purity by weight of 98 % or more	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8949	ex 2918 30 00	48	Prohexadione-calcium (ISOM) (CAS RN 127277-53-6) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.8950	ex 2918 30 00	53	2-(4-Chlorobenzoyl)benzoic acid (CAS RN 85-56-3) with a purity by weight of 99 % or more	0 %	-	31.12.2030
0.8256	*ex 2918 30 00	55	Methyl 3-oxo-pentanoate (CAS RN 30414-53-0) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.6250	ex 2918 30 00	60	4-Oxovaleric acid (CAS RN 123-76-2)	0 %	-	31.12.2029
0.6455	ex 2918 30 00	70	2-[4-Chloro-3-(chlorosulphonyl)benzoyl]benzoic acid (CAS RN 68592-12-1)	0 %	-	31.12.2029
0.8342	ex 2918 30 00	75	Methyl 2-((1*S*,2*R*)-3-oxo-2-pentylcyclopentyl)acetate (CAS RN 151716-35-7) with a purity by weight of 99 % or more	0 %	-	31.12.2027
0.7062	*ex 2918 30 00	80	Methyl benzoylformate (CAS RN 15206-55-0)	0 %	-	31.12.2031
0.7344	ex 2918 30 00	85	2-Fluoro-5-formylbenzoic acid (CAS RN 550363-85-4) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.5857	ex 2918 30 00	87	Ethyl acetoacetate (CAS RN 141-97-9) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.6814	ex 2918 99 90	13	3-Methoxy-2-methylbenzoyl chloride (CAS RN 24487-91-0)	0 %	-	31.12.2030
0.5856	ex 2918 99 90	15	Ethyl 2,3-epoxy-3-phenylbutyrate (CAS RN 77-83-8)	0 %	-	31.12.2027
0.6901	ex 2918 99 90	18	Ethyl 2-hydroxy-2-(4-phenoxyphenyl)propanoate (CAS RN 132584-17-9)	0 %	-	31.12.2030
0.6147	ex 2918 99 90	25	Methyl (E)-3-methoxy-2-(2-chloromethylphenyl)-2-propenoate (CAS RN 117428-51-0)	0 %	-	31.12.2029
0.7256	ex 2918 99 90	27	Ethyl 3-ethoxypropionate (CAS RN 763-69-9)	0 %	-	31.12.2027
0.6342	ex 2918 99 90	35	p-Anisic acid (CAS RN 100-09-4)	0 %	-	31.12.2029
0.7358	ex 2918 99 90	38	Diclofop-methyl (ISO) (CAS RN 51338-27-3)	0 %	-	31.12.2027
0.2945	ex 2918 99 90	40	*trans*-4-Hydroxy-3-methoxycinnamic acid (CAS RN 1135-24-6)	0 %	-	31.12.2029
0.6224	ex 2918 99 90	45	4-Methylcatechol dimethyl acetate (CAS RN 52589-39-6)	0 %	-	31.12.2029
0.2947	ex 2918 99 90	50	Methyl 3,4,5-trimethoxybenzoate (CAS RN 1916-07-0)	0 %	-	31.12.2029
0.8623	ex 2918 99 90	58	2,4-D (ISO) (CAS RN 94-75-7) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.2943	ex 2918 99 90	60	3,4,5-Trimethoxybenzoic acid (CAS RN 118-41-2)	0 %	-	31.12.2029
0.4742	ex 2918 99 90	67	Allyl-(3-methylbutoxy)acetate (CAS RN 67634-00-8) with a purity by weight of 95 % or more	0 %	-	31.12.2029
0.2948	ex 2918 99 90	73	Methyl (2*R*)-2-(4-hydroxyphenoxy)propionate (CAS RN 96562-58-2) with a purity by weight of 97 % or more	0 %	-	31.12.2029
0.8947	ex 2918 99 90	78	3,4-Epoxycyclohexylmethyl-3',4'-epoxycyclohexane carboxylate (CAS RN 2386-87-0) with a purity by weight of 91 % or more	0 %	-	31.12.2030
0.9104	*ex 2918 99 90	83	*p*-Anisoyl chloride (CAS RN 100-07-2) with a purity by weight of 99 % or more	0 %	-	31.12.2031

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.6747	ex 2918 99 90	85	Trinexapac-Ethyl (ISO) (CAS RN 95266-40-3) with a purity by weight of 96 % or more	0 %	-	31.12.2030
0.6188	ex 2919 90 00	60	Bisphenol-A bis(diphenyl phosphate) (CAS RN 5945-33-5)	0 %	-	31.12.2029
0.6413	ex 2919 90 00	70	Tris(2-butoxyethyl)phosphate (CAS RN 78-51-3)	0 %	-	31.12.2029
0.6253	ex 2920 19 00	30	2,2'-Oxybis(5,5-dimethyl-1,3,2-dioxaphosphorinane)-2,2'-disulphide (CAS RN 4090-51-1)	0 %	-	31.12.2029
0.3634	2920 23 00		Trimethyl phosphite (CAS RN 121-45-9)	0 %	-	31.12.2029
0.4158	*2920 24 00		Triethyl phosphite (CAS RN 122-52-1)	0 %	-	31.12.2031
0.2626	ex 2920 29 00	10	*O,O'*-Dioctadecyl pentaerythritol bis(phosphite) (CAS RN 3806-34-6)	0 %	-	31.12.2029
0.5038	ex 2920 29 00	20	Tris(methylphenyl)phosphite (CAS RN 25586-42-9)	0 %	-	31.12.2030
0.6004	ex 2920 29 00	25	Fosetyl-aluminium (ISOM)(CAS RN 39148-24-8) with a purity by weight of 96 % or more	0 %	-	31.12.2029
0.5045	ex 2920 29 00	40	Bis(2,4-dicumylphenyl)pentaerythritol diphosphite (CAS RN 154862-43-8)	0 %	-	31.12.2030
0.8942	ex 2920 29 00	45	Tris(2-chloroethyl) phosphite (CAS RN 140-08-9) with a purity by weight of 90 % or more	0 %	-	31.12.2030
0.7898	ex 2920 29 00	80	2,4,8,10-Tetrakis(1,1-dimethylethyl)-6-(2-ethylhexyloxy)-12H dibenzo[d,g][1,3,2]dioxaphosphocin (CAS RN 126050-54-2) with a purity by weight of 95 % or more	0 %	-	31.12.2029
0.8522	ex 2920 90 10	13	Tetraethyl orthocarbonate (CAS RN 78-09-1) with a purity by weight of 99 % or more	0 %	-	31.12.2028
0.2605	ex 2920 90 10	20	Diallyl 2,2'-oxydiethyl dicarbonate (CAS RN 142-22-3)	0 %	-	31.12.2029
0.8641	*ex 2920 90 10	23	1,3,2-Dioxathiolane 2,2-dioxide (CAS RN 1072-53-3) with a purity by weight of 99 % or more	3.2 %	-	31.12.2027
0.7559	*ex 2920 90 10	33	Ethyl methyl carbonate (CAS RN 623-53-0) with a purity by weight of 98 % or more	3.2 %	-	31.12.2027
0.3685	ex 2920 90 10	40	Dimethyl carbonate (CAS RN 616-38-6)	0 %	-	31.12.2029
0.8297	*ex 2920 90 10	45	Ethylene carbonate (CAS RN 96-49-1) with a purity by weight of 99 % or more	3.2 %	-	31.12.2027
0.3868	ex 2920 90 10	50	Di-*tert*-butyl dicarbonate (CAS RN 24424-99-5)	0 %	-	31.12.2029
0.8298	*ex 2920 90 10	55	Vinylene carbonate (CAS RN 872-36-6) with a purity by weight of 99,9 % or more	3.2 %	-	31.12.2027
0.8299	*ex 2920 90 10	65	Vinyl ethylene carbonate (CAS RN 4427-96-7) with a purity by weight of 99 % or more	3.2 %	-	31.12.2027
0.8511	*ex 2920 90 10	85	Diethyl carbonate (CAS RN 105-58-8) with a purity by weight of 99,9 % or more	3.2 %	-	31.12.2027
0.8542	ex 2920 90 70	10	Tris(2-propylheptyl) borate (CAS RN 1488321-95-4) with a purity by weight of 90 % or more	0 %	-	31.12.2028
0.7588	ex 2920 90 70	20	Diethyl phosphorochloridate (CAS RN 814-49-3)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8719	ex 2920 90 70	35	Triisopropyl borate (CAS RN 5419-55-6) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.5947	ex 2920 90 70	60	Bis(neopentylglycolato)diboron (CAS RN 201733-56-4)	0 %	-	31.12.2029
0.8490	ex 2920 90 70	70	4,4,5,5-Tetramethyl-1,3,2-dioxaborolane (CAS RN 25015-63-8) with a purity by weight of 97 % or more, containing not more than 1 % of the stabiliser triethylamine (CAS RN 121-44-8)	0 %	-	31.12.2027
0.6598	ex 2920 90 70	80	Bis(pinacolato)diboron (CAS RN 73183-34-3)	0 %	-	31.12.2030
0.3629	ex 2921 19 99	20	Ethyl(2-methylallyl)amine (CAS RN 18328-90-0)	0 %	-	31.12.2029
0.3631	ex 2921 19 99	30	Allylamine (CAS RN 107-11-9)	0 %	-	31.12.2029
0.8477	ex 2921 19 99	35	*N*-Ethyl-*N*-isopropylpropan-2-amine 2-(difluoromethoxy)acetate with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8562	ex 2921 19 99	55	2,2,2-Trifluoroethylamine hydrochloride (CAS RN 373-88-6) with a purity by weight of 99 % or more	0 %	-	31.12.2028
0.6269	ex 2921 19 99	80	Taurine (CAS RN 107-35-7), with 0,5 % addition of anti-caking agent silicon dioxide (CAS RN 112926-00-8)	0 %	-	31.12.2029
0.3630	ex 2921 29 00	20	Tris[3-(dimethylamino)propyl]amine (CAS RN 33329-35-0)	0 %	-	31.12.2029
0.3625	ex 2921 29 00	30	Bis[3-(dimethylamino)propyl]methylamine (CAS RN 3855-32-1)	0 %	-	31.12.2029
0.4917	ex 2921 29 00	40	Decamethylenediamine (CAS RN 646-25-3)	0 %	-	31.12.2030
0.5256	*ex 2921 29 00	50	*N*'-[3-(Dimethylamino)propyl]-*N*,*N*-dimethylpropane-1,3-diamine (CAS RN 6711-48-4)	0 %	-	31.12.2031
0.7947	ex 2921 29 00	70	N,N,N',N'-Tetramethylethylenediamine (CAS RN 110-18-9) with a purity by weight of 99 % or more	0 %	-	31.12.2030
0.5768	ex 2921 30 99	40	Cyclopropylamine (CAS RN 765-30-0)	0 %	-	31.12.2027
0.8529	ex 2921 30 99	60	Amantadine hydrochloride (CAS RN 665-66-7) with a purity by weight of 97 % or more	0 %	-	31.12.2028
0.3909	ex 2921 42 00	25	Sodium hydrogen 2-aminobenzene-1,4-disulphonate (CAS RN 24605-36-5)	0 %	-	31.12.2029
0.3978	ex 2921 42 00	38	2-Nitroaniline (CAS RN 88-74-4) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.2620	ex 2921 42 00	50	3-Aminobenzenesulfonic acid (CAS RN 121-47-1)	0 %	-	31.12.2029
0.7739	ex 2921 42 00	65	4-chloroaniline (CAS RN 106-47-8) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.3623	ex 2921 42 00	70	2-Aminobenzene-1,4-disulfonic acid (CAS RN 98-44-2)	0 %	-	31.12.2029
0.3622	ex 2921 42 00	80	4-Chloro-2-nitroaniline (CAS RN 89-63-4)	0 %	-	31.12.2029
0.5616	ex 2921 42 00	86	2,5-Dichloroaniline (CAS RN 95-82-9)	0 %	-	31.12.2027
0.5603	ex 2921 42 00	87	*N*-Methylaniline (CAS RN 100-61-8)	0 %	-	31.12.2027
0.5617	ex 2921 42 00	88	3,4-Dichloroaniline-6-sulphonic acid (CAS RN 6331-96-0)	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8433	ex 2921 43 00	25	6-Chloro-α,α,α-trifluoro-m-toluidine (CAS RN 121-50-6) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8568	ex 2921 43 00	35	3-Chloro-*o*-toluidine (CAS RN 87-60-5) with a purity by weight of 95 % or more	0 %	-	31.12.2028
0.3980	ex 2921 43 00	40	4-Aminotoluene-3-sulphonic acid (CAS RN 88-44-8)	0 %	-	31.12.2029
0.9071	ex 2921 43 00	45	α,α,α-Trifluoro-o-toluidine (CAS RN 88-17-5) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.9100	*ex 2921 43 00	55	3-Nitro-*p*-toluidine (CAS RN 119-32-4) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.5124	ex 2921 43 00	60	3-Aminobenzotrifluoride (CAS RN 98-16-8)	0 %	-	31.12.2030
0.3621	ex 2921 44 00	20	Diphenylamine (CAS RN 122-39-4)	0 %	-	31.12.2029
0.2609	ex 2921 45 00	15	*N*-1-Naphthylaniline (CAS RN 90-30-2) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.7316	ex 2921 45 00	60	1-Naphthylamine (CAS RN 134-32-7)	0 %	-	31.12.2027
0.7592	ex 2921 49 00	35	2-Ethylaniline (CAS RN 578-54-1)	0 %	-	31.12.2029
0.8019	ex 2921 49 00	45	2-(4-Biphenylyl)amino-9,9-dimethylfluoren (CAS RN 897671-69-1) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.8020	ex 2921 49 00	55	2-(2-Biphenylyl)amino-9,9-dimethylfluoren (CAS RN 1198395-24-2) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.6825	ex 2921 49 00	60	2,6-Diisopropylaniline (CAS RN 24544-04-5)	0 %	-	31.12.2030
0.8059	ex 2921 49 00	65	Bis-(9,9-dimethylfluoren-2-yl)amine (CAS RN 500717-23-7) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.8558	ex 2921 49 00	75	*N*-Methyl-1-(1-napthyl)methanamine (CAS RN 14489-75-9) with a purity by weight of 99 % or more	0 %	-	31.12.2028
0.3981	ex 2921 51 19	30	2-Methyl-*p*-phenylenediamine sulphate (CAS RN 615-50-9)	0 %	-	31.12.2029
0.4184	*ex 2921 51 19	40	*p*-Phenylenediamine (CAS RN 106-50-3)	0 %	-	31.12.2031
0.4498	ex 2921 51 19	50	2-Chloro-1,4-phenylendiamine (CAS RN 615-66-7) or 2,5-dichloro-1,4-phenylendiamine (CAS RN 20103-09-7)	0 %	-	31.12.2029
0.2612	ex 2921 59 90	15	Mixture of isomers of 3,5-diethyltoluenediamine (CAS RN 68479-98-1)	0 %	-	31.12.2028
0.3785	ex 2921 59 90	30	3,3'-Dichlorobenzidine dihydrochloride (CAS RN 612-83-9)	0 %	-	31.12.2027
0.3870	ex 2921 59 90	40	4,4'-Diaminostilbene-2,2'-disulphonic acid (CAS RN 81-11-8)	0 %	-	31.12.2029
0.7860	ex 2922 19 00	15	Aqueous solution, containing by weight: — 73 % or more 2-amino-2-methyl-1-propanol (CAS RN 124-68-5), — 4,5 % or more, but not more than 27 % water (CAS RN 7732-18-5)	0 %	-	31.12.2029
0.5757	ex 2922 19 00	20	2-(2-Methoxyphenoxy)ethylamine hydrochloride (CAS RN 64464-07-9)	0 %	-	31.12.2027
0.7946	ex 2922 19 00	29	N-Methyl-N-(2-hydroxyethyl)-p-toluidine (CAS RN 2842-44-6) with a purity by weight of 99 % or more	0 %	-	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.3617	ex 2922 19 00	30	*N,N,N',N'*-Tetramethyl-2,2'-oxybis(ethylamine) (CAS RN 3033-62-3)	0 %	-	31.12.2029
0.8337	ex 2922 19 00	33	2-Methoxyethan-1-amine (CAS RN 109-85-3) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.6947	ex 2922 19 00	43	2-[2-(Dimethylamino)ethoxy]ethanol (CAS RN 1704-62-7) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.7480	ex 2922 19 00	45	2-Methoxymethyl-p-phenylenediamine (CAS RN 337906-36-2)	0 %	-	31.12.2029
0.3616	ex 2922 19 00	53	2-(2-Methoxyphenoxy)ethanamine (CAS RN 1836-62-0) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.7587	ex 2922 19 00	55	3-Aminoadamantan-1-ol (CAS RN 702-82-9)	0 %	-	31.12.2029
0.3871	ex 2922 19 00	60	*N,N,N'*-Trimethyl-*N'*-(2-hydroxy-ethyl) 2,2'-oxybis(ethylamine), (CAS RN 83016-70-0)	0 %	-	31.12.2029
0.5905	ex 2922 19 00	65	*trans*-4-Aminocyclohexanol (CAS RN 27489-62-9)	0 %	-	31.12.2029
0.7935	ex 2922 19 00	70	2-Benzylaminoethanol (CAS 104-63-2) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.5986	ex 2922 19 00	75	2-Ethoxyethylamine (CAS RN 110-76-9)	0 %	-	31.12.2029
0.4665	ex 2922 19 00	80	*N*-[2-[2-(Dimethylamino)ethoxy]ethyl]-*N*-methyl-1,3-propanediamine (CAS RN 189253-72-3)	0 %	-	31.12.2029
0.5996	ex 2922 21 00	10	2-Amino-5-hydroxynaphthalene-1,7-disulphonic acid (CAS RN 6535-70-2)	0 %	-	31.12.2029
0.2703	ex 2922 21 00	30	6-Amino-4-hydroxynaphthalene-2-sulphonic acid (CAS RN 90-51-7)	0 %	-	31.12.2029
0.2704	ex 2922 21 00	40	7-Amino-4-hydroxynaphthalene-2-sulphonic acid (CAS RN 87-02-5)	0 %	-	31.12.2029
0.3873	ex 2922 21 00	50	Sodium hydrogen 4-amino-5-hydroxynaphthalene-2,7-disulphonate (CAS RN 5460-09-3)	0 %	-	31.12.2029
0.5997	ex 2922 21 00	60	4-Amino-5-hydroxynaphthalene-2,7-disulphonic acid with a purity by weight of 80 % or more (CAS RN 90-20-0)	0 %	-	31.12.2029
0.8564	ex 2922 29 00	13	2-(4-Chlorophenoxy)-5-(trifluoromethyl)aniline (CAS RN 349-20-2) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.9121	*ex 2922 29 00	14	4-Aminophenol (CAS RN 123-30-8) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.8832	ex 2922 29 00	18	Bis[(4-Methoxyphenyl)methyl]amine (CAS RN 17061-62-0) with a purity by weight of 96 % or more	0 %	-	31.12.2029
0.2702	ex 2922 29 00	20	3-Aminophenol (CAS RN 591-27-5)	0 %	-	31.12.2029
0.3982	ex 2922 29 00	25	5-Amino-*o*-cresol (CAS RN 2835-95-2)	0 %	-	31.12.2029
0.6624	ex 2922 29 00	30	1,2-Bis(2-aminophenoxy)ethane (CAS RN 52411-34-4)	0 %	-	31.12.2030
0.7642	ex 2922 29 00	33	o-Phenetidine (CAS RN 94-70-2)	0 %	-	31.12.2029
0.8934	ex 2922 29 00	38	4-Amino-2,3-dichlorophenol (CAS RN 39183-17-0) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.9016	ex 2922 29 00	53	*m*-Anisidine (CAS RN 536-90-3) with a purity by weight of 95 % or more	0 %	-	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.4627	ex 2922 29 00	65	4-Trifluoromethoxyaniline (CAS RN 461-82-5)	0 %	-	31.12.2029
0.7481	ex 2922 29 00	67	4-Chloro-2,5-dimethoxyaniline (CAS RN 6358-64-1)	0 %	-	31.12.2029
0.2692	ex 2922 29 00	70	4-Nitro-*o*-anisidine (CAS RN 97-52-9)	0 %	-	31.12.2029
0.7026	*ex 2922 29 00	73	Tris(4-aminophenyl) thiophosphate (CAS RN 52664-35-4)	0 %	-	31.12.2031
0.4956	ex 2922 29 00	75	4-(2-Aminoethyl)phenol (CAS RN 51-67-2)	0 %	-	31.12.2030
0.2696	ex 2922 29 00	80	3-Diethylaminophenol (CAS RN 91-68-9)	0 %	-	31.12.2029
0.4914	ex 2922 39 00	20	2-Amino-5-chlorobenzophenone (CAS RN 719-59-5)	0 %	-	31.12.2030
0.7713	ex 2922 39 00	30	(2-Fluorophenyl)-[2-(methylamino)-5-nitrophenyl]methanone (CAS RN 735-06-8)	0 %	-	31.12.2029
0.6761	ex 2922 39 00	35	5-Chloro-2-(methylamino)benzophenone (CAS RN 1022-13-5)	0 %	-	31.12.2030
0.7371	ex 2922 39 00	45	2-Amino-3,5-dibromobenzaldehyde (CAS RN 50910-55-9) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.3546	ex 2922 43 00	10	Anthranilic acid (CAS RN 118-92-3)	0 %	-	31.12.2029
0.3547	ex 2922 49 85	10	Ornithine aspartate (INNM) (CAS RN 3230-94-2)	0 %	-	31.12.2029
0.5037	ex 2922 49 85	17	Glycine (CAS RN 56-40-6) with a purity by weight of 95 % or more, whether or not with not more than 5 % addition of anti-caking agent silicon dioxide (CAS RN 112926-00-8)	0 %	-	31.12.2030
0.5619	ex 2922 49 85	20	3-Amino-4-chlorobenzoic acid (CAS RN 2840-28-0)	0 %	-	31.12.2027
0.6340	ex 2922 49 85	25	Dimethyl 2-aminobenzene-1,4-dicarboxylate (CAS RN 5372-81-6)	0 %	-	31.12.2029
0.8948	ex 2922 49 85	28	Magnesium diglycinate (CAS RN 14783-68-7) with a purity by weight of 99 % or more	0 %	-	31.12.2030
0.9110	*ex 2922 49 85	38	2-Amino-2-methylpropionic acid (CAS RN 62-57-7) with a purity by weight of 95 % or more	0 %	-	31.12.2031
0.3544	ex 2922 49 85	40	Norvaline (CAS RN 6600-40-4)	0 %	-	31.12.2029
0.8236	*ex 2922 49 85	43	(E)-Ethyl 4-(dimethylamino)but-2-enoate maleate (CAS RN 1690340-79-4) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.3983	ex 2922 49 85	50	D-(-)-Dihydrophenylglycine (CAS RN 26774-88-9)	0 %	-	31.12.2029
0.8340	ex 2922 49 85	53	(*S*)-ethyl 3-amino-3-phenylpropanoate hemi((2R,3R)-2,3-dihydroxysuccinate) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.4239	ex 2922 49 85	60	Ethyl-4-dimethylaminobenzoate (CAS RN 10287-53-3)	0 %	-	31.12.2027
0.8726	ex 2922 49 85	63	Glycine hydrochloride (CAS RN 6000-43-7) with a purity by weight of 95 % or more, whether or not containing not more than 5 % of anti-caking agent silicon dioxide (CAS RN 112926-00-8), used to produce food flavourings (1)	0 %	-	31.12.2029
0.7254	ex 2922 49 85	75	L-alanine isopropyl ester hydrochloride (CAS RN 62062-65-1)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7020	*ex 2922 50 00	10	2-(2-(2-Aminoethoxy)ethoxy)acetic acid hydrochloride (CAS RN 134979-01-4)	0 %	-	31.12.2031
0.7257	ex 2922 50 00	15	3,5-Diiodothyronine (CAS RN 1041-01-6)	0 %	-	31.12.2027
0.4702	ex 2922 50 00	20	1-[2-Amino-1-(4-methoxyphenyl)-ethyl]-cyclohexanol hydrochloride (CAS RN 130198-05-9)	0 %	-	31.12.2029
0.8445	ex 2922 50 00	25	L-Threonine (CAS RN 72-19-5)	0 %	-	31.12.2027
0.8473	ex 2922 50 00	45	(*S*)-2-Amino-2-(3-fluoro-5-methoxyphenyl)ethanol hydrochloride (CAS RN 2095692-22-9) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8364	ex 2922 50 00	55	1-{[4-(Benzyloxy)phenyl]-2-(dimethylamino)ethyl}cyclohexanol (CAS RN 93413-61-7) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8325	ex 2922 50 00	65	[4-[2-(Dimethylamino)ethoxy]phenyl](4-hydroxyphenyl)methanone (CAS RN 173163-13-8) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.3543	ex 2923 90 00	10	Tetramethylammonium hydroxide (CAS RN 75-59-2), in the form of an aqueous solution containing 25 % (± 0,5 %) by weight of tetramethylammonium hydroxide	0 %	-	31.12.2029
0.8715	ex 2923 90 00	13	*Bis*(*N*,*N*,*N*-trimethyladamantan-1-aminium) sulfate (CAS RN 1000777-61-6) with a purity by weight of 95 % or more, whether or not in aqueous solution containing 20 % or more *Bis*(*N*,*N*,*N*-trimethyladamantan-1-aminium) sulfate (CAS RN 1000777-61-6)	0 %	-	31.12.2029
0.8931	ex 2923 90 00	33	Calcium phosphoryl choline chloride tetrahydrate (CAS RN 72556-74-2) with a purity by weight of 90 % or more	0 %	-	31.12.2030
0.7879	ex 2923 90 00	50	Betaine hydrochloride (CAS RN 590-46-5), with a purity by weight of 93 % or more	0 %	-	31.12.2029
0.7089	*ex 2923 90 00	55	Tetrabutylammonium bromide (CAS RN 1643-19-2)	0 %	-	31.12.2031
0.7615	ex 2923 90 00	65	N,N,N-Trimethyl-tricyclo[3.3.1.13,7]decan-1-aminium hydroxide (CAS RN 53075-09-5) in form of an aqueous solution with a content of N,N,N-trimethyl-tricyclo[3.3.1.13,7]decan-1-aminium hydroxide by weight of 17,5 % or more but not more than 27,5 %	0 %	-	31.12.2029
0.5063	ex 2923 90 00	75	Tetraethylammonium hydroxide, in the form of an aqueous solution containing: — 35 % (± 0,5 %) by weight of tetraethylammonium hydroxide, — not more than 1 000 mg/kg of chloride, — not more than 2 mg/kg of iron, and — not more than 10 mg/kg of potassium	0 %	-	31.12.2030
0.3536	ex 2923 90 00	80	Diallyldimethylammonium chloride (CAS RN 7398-69-8) , in the form of an aqueous solution containing by weight 63 % or more but not more than 67 % of diallyldimethylammonium chloride	0 %	-	31.12.2029
0.6410	ex 2923 90 00	85	N,N,N-Trimethylanilinium chloride (CAS RN 138-24-9)	0 %	-	31.12.2029
0.8561	ex 2924 19 00	13	*N*-(*tert*-Butoxycarbonyl)glycine (CAS RN 4530-20-5) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.8000	ex 2924 19 00	18	2-(((Butylamino)carbonyl)oxy)ethyl acrylate (CAS RN 63225-53-6) with a purity by weight of 97 % or more	0 %	-	31.12.2030
0.8705	ex 2924 19 00	20	*Tert*-butyl *N*-methyl-*N*-(2-oxopropyl)carbamate (CAS RN 532410-39-2) with a purity by weight of 90 % or more	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.4380	ex 2924 19 00	25	Methylcarbamate (CAS RN 598-55-0) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.8027	ex 2924 19 00	28	(2*S*)-2-Amino-5-(carbamoylamino)pentanoic acid ; 2-hydroxybutanedioic acid (2:1) (CAS RN 54940-97-5) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.6549	ex 2924 19 00	35	Acetamide (CAS RN 60-35-5)	0 %	-	31.12.2029
0.8041	*ex 2924 19 00	38	Diethyl acetamidomalonate (CAS RN 1068-90-2) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8283	*ex 2924 19 00	48	*N*,*N*-Dimethylcarbamoyl chloride (CAS RN 79-44-7) with a purity by weight of 99 % or more	0 %	-	31.12.2027
0.8429	ex 2924 19 00	53	Aqueous solution of propamocarb hydrochloride (ISOM)(CAS RN 25606-41-1), containing by weight 64 % or more, but not more than 68 % of propamocarb hydrochloride	0 %	-	31.12.2027
0.7060	*ex 2924 19 00	55	2-Propynyl butylcarbamate (CAS RN 76114-73-3)	0 %	-	31.12.2031
0.4160	*ex 2924 19 00	58	*N*,*N*-Dimethylacrylamide (CAS RN 2680-03-7) with a purity by weight of 97 % or more	0 %	-	31.12.2031
0.9117	*ex 2924 19 00	68	*N*-(3-carboxy-1-oxopropyl)-L-alanyl-3-[[1-oxo-6-(trimethylammonio)hexyl]amino]-D-alanine 2-(1-methylethyl) ester, 1,2-ethanedisulfonate (2:1) (CAS RN 3109123-87-4) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.9191	*ex 2924 19 00	73	Methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate (CAS RN 1174627-68-9) with a purity by weight of 90 % or more	0 %	-	31.12.2030
0.5605	ex 2924 19 00	80	Tetrabutylurea (CAS RN 4559-86-8)	0 %	-	31.12.2027
0.2678	*ex 2924 19 00	83	2-Acrylamido-2-methylpropanesulphonic acid (CAS RN 15214-89-8) or its sodium salt (CAS RN 5165-97-9), or its ammonium salt (CAS RN 58374-69-9), each with a purity by weight of 90 % or more, also as an aqueous solution containing by weight 40 % or more of each substance	0 %	-	31.12.2029
0.6568	ex 2924 29 70	23	Benalaxyl-M (ISO) (CAS RN 98243-83-5)	0 %	-	31.12.2029
0.8153	*ex 2924 29 70	25	2-[2-(Methoxycarbonyl-phenyl-amino)-phenyl]-acetic acid (CAS RN 353497-35-5) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.7118	*ex 2924 29 70	30	Sodium 4-(4-methyl-3-nitrobenzoylamino)benzenesulphonate (CAS RN 84029-45-8)	0 %	-	31.12.2031
0.8621	ex 2924 29 70	34	Acetic acid—tert-butyl [(1-aminocyclohexyl)methyl]carbamate (1/1) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.6110	ex 2924 29 70	37	Beflubutamid (ISO) (CAS RN 113614-08-7)	0 %	-	31.12.2029
0.8595	ex 2924 29 70	38	2-Methyl-2-propanyl{(2*S*,3*R*)-3-hydroxy-4-[(2-methylpropyl)amino]-1-phenyl-2- butanyl}carbamate (CAS RN 160232-08-6) with a purity by weight of 97 % or more	0 %	-	31.12.2028
0.8696	ex 2924 29 70	39	*N*-[(9*H*-Fluoren-9-ylmethoxy)carbonyl]glycine (CAS RN 29022-11-5) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.5066	ex 2924 29 70	40	N,N'-1,4-Phenylenebis[3-oxobutyramide], (CAS RN 24731-73-5)	0 %	-	31.12.2030
0.8697	ex 2924 29 70	41	(2*S*)-6-amino-2-({[(9*H*-fluoren-9-yl)methoxy]carbonyl}amino)hexanoic acid hydrochloride (CAS RN 139262-23-0) with a purity by weight of 90 % or more	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8698	ex 2924 29 70	42	*N*-Benzyloxycarbonylglycine (CAS RN 1138-80-3) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.9012	ex 2924 29 70	44	4-(2,2-Diethoxyacetyl)-3,5-difluoro-*N*-methylbenzamide (CAS RN 3089027-90-4) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.7841	ex 2924 29 70	47	(S)-tert-Butyl (1-amino-3-(4-iodophenyl)-1-oxopropan-2-yl)carbamate (CAS RN 868694-44-4) with a purity by weight of 95 % or more	0 %	-	31.12.2029
0.8381	ex 2924 29 70	48	(3R)-*N*-(tert-butoxycarbonyl)-3-amino-4-(2,4,5-trifluorophenyl)butanoic acid (CAS RN 486460-00-8) with a purity by weight of 97 % or more	0 %	-	31.12.2027
0.8346	ex 2924 29 70	49	*tert*-Butyl [(1R,2S,5S)-2-amino-5-(dimethylcarbamoyl)cyclohexyl]carbamate ethanedioate (CAS RN 1210348-34-7) with a purity by weight of 95 % or more	0 %	-	31.12.2027
0.5622	ex 2924 29 70	53	4-Amino-*N*-[4-(aminocarbonyl)phenyl]benzamide (CAS RN 74441-06-8)	0 %	-	31.12.2027
0.8362	ex 2924 29 70	54	2-[4-(Benzyloxy)phenyl]-*N*,*N*-dimethylacetamide (CAS RN 919475-15-3) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.5069	ex 2924 29 70	55	N,N'-(2,5-Dimethyl-1,4-phenylene)bis[3-oxobutyramide] (CAS RN 24304-50-5)	0 %	-	31.12.2030
0.8315	ex 2924 29 70	56	Valifenalate (ISO) (CAS RN 283159-90-0) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8710	ex 2924 29 70	57	2-(Dimethylaminomethylidene)-4-methoxy-3-oxo-*N*-[(2,4,6-trifluorophenyl)methyl]butanamide (CAS RN 1846582-17-9) with a purity by weight of 95 % or more	0 %	-	31.12.2029
0.8043	ex 2924 29 70	58	2-Chloro-*N*-[1-(4-chloro-3-fluorophenyl)-2-methylpropan-2-yl]acetamide (CAS RN 787585-35-7) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.6266	ex 2924 29 70	59	2-(Trifluoromethyl)benzamide (CAS RN 360-64-5) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.6767	ex 2924 29 70	62	2-Chlorobenzamide (CAS RN 609-66-5)	0 %	-	31.12.2030
0.6766	ex 2924 29 70	64	N-(3',4'-dichloro-5-fluoro[1,1'-biphenyl]-2-yl)acetamide (CAS RN 877179-03-8)	0 %	-	31.12.2030
0.7632	ex 2924 29 70	67	N,N'-(2,5-Dichloro-1,4-phenylene)bis[3-oxobutyramide] (CAS RN 42487-09-2)	0 %	-	31.12.2029
0.8919	ex 2924 29 70	68	Sacubitril calcium (INNM) (CAS RN 1369773-39-6) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.9112	*ex 2924 29 70	71	*N*-[(Benzyloxy)carbonyl]glycyl-*N*-[(2*S*)-1-{4-[(*tert*-butoxycarbonyl)oxy]phenyl}-3-hydroxypropan-2-yl]-L-alaninamide (EC number 948-973-9) with a purity by weight of 90 % or more	0 %	-	31.12.2031
0.6480	ex 2924 29 70	73	Napropamide (ISO) (CAS RN 15299-99-7)	0 %	-	31.12.2029
0.2672	ex 2924 29 70	75	3-Amino-*p*-anisanilide (CAS RN 120-35-4)	0 %	-	31.12.2029
0.2673	ex 2924 29 70	85	*p*-Aminobenzamide (CAS RN 2835-68-9)	0 %	-	31.12.2029
0.4493	ex 2924 29 70	89	Flutolanil (ISO) (CAS RN 66332-96-5)	0 %	-	31.12.2029
0.3691	ex 2924 29 70	92	3-Hydroxy-2-naphthanilide (CAS RN 92-77-3)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.3692	ex 2924 29 70	93	3-Hydroxy-2'-methyl-2-naphthanilide (CAS RN 135-61-5)	0 %	-	31.12.2029
0.3693	ex 2924 29 70	94	2'-Ethoxy-3-hydroxy-2-naphthanilide (CAS RN 92-74-0)	0 %	-	31.12.2029
0.3863	ex 2924 29 70	97	1,1-Cyclohexanediacetic acid monoamide (CAS RN 99189-60-3)	0 %	-	31.12.2029
0.3526	ex 2925 11 00	40	1,2-Benzisothiazol-3(2*H*)-one 1,1-dioxide (CAS RN 81-07-2) or its sodium salt (CAS RN 128-44-9) or its sodium salt dihydrate (CAS RN 6155-57-3) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.2674	ex 2925 19 95	10	*N*-Phenylmaleimide (CAS RN 941-69-5)	0 %	-	31.12.2029
0.5612	ex 2925 19 95	20	4,5,6,7-Tetrahydroisoindole-1,3-dione (CAS RN 4720-86-9)	0 %	-	31.12.2027
0.5740	ex 2925 19 95	30	*N,N'*-(*m*-Phenylene)dimaleimide (CAS RN 3006-93-7)	0 %	-	31.12.2027
0.8704	ex 2925 19 95	50	2-{2-[2-(1,3-Dioxo-2,3-dihydro-1*H*-isoindol-2-yl)ethoxy]ethoxy}acetic acid (CAS RN 75001-09-1) with a purity by weight of 95 % or more	0 %	-	31.12.2029
0.9103	*ex 2925 19 95	60	*N*-[6-(2,5-Dihydro-2,5-dioxo-1*H*-pyrrol-1-yl)-1-oxohexyl]glycylglycyl-L-phenylalanyl-*N*-[(carboxymethoxy)methyl]-glycinamide (CAS RN 1599440-25-1) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.2934	ex 2925 29 00	10	Dicyclohexylcarbodiimide (CAS RN 538-75-0)	0 %	-	31.12.2029
0.5891	ex 2925 29 00	20	N-[3-(Dimethylamino)propyl]-N'-ethylcarbodiimide hydrochloride (CAS RN 25952-53-8)	0 %	-	31.12.2029
0.8339	ex 2925 29 00	25	1-(3-(2-Hydroxyethyl)phenyl)guanidinium methanesulfonate (CAS RN 2101429-50-7) with a purity by weight of 99 % or more	0 %	-	31.12.2027
0.8943	ex 2925 29 00	35	N-Amidinosarcosine hydrate (CAS RN 6020-87-7) with a purity by weight of 99 % or more	0 %	-	31.12.2030
0.7749	ex 2925 29 00	40	N-Amidinosarcosine (CAS RN 57-00-1)	0 %	-	31.12.2029
0.7832	ex 2925 29 00	50	(Chloromethylene)dimethyliminium chloride (CAS RN 3724-43-4) with a purity by weight of 95 % or more	0 %	-	31.12.2029
0.8040	ex 2925 29 00	70	Bromomethylidene(dimethyl)azanium bromide (CAS RN 24774-61-6) with a purity by weight of 97 % or more	0 %	-	31.12.2030
0.8873	ex 2925 29 00	80	Ethyl 4-[[(methylphenylamino)methylene]amino]benzoate (CAS RN 57834-33-0) with a purity of 99 % or more by weight	0 %	-	31.12.2029
0.7408	ex 2926 90 70	18	Flumethrin (ISO) (CAS RN 69770-45-2)	0 %	-	31.12.2027
0.7466	ex 2926 90 70	19	2-(4-Amino-2-chloro-5-methylphenyl)-2-(4-chlorophenyl) acetonitrile (CAS RN 61437-85-2)	0 %	-	31.12.2029
0.2668	ex 2926 90 70	20	2-(*m*-Benzoylphenyl)propiononitrile (CAS RN 42872-30-0)	0 %	-	31.12.2029
0.7458	ex 2926 90 70	21	4-Bromo-2-chlorobenzonitrile (CAS RN 154607-01-9)	0 %	-	31.12.2029
0.7514	ex 2926 90 70	22	Acetonitrile (CAS RN 75-05-8)	0 %	-	31.12.2029
0.7805	ex 2926 90 70	24	2-Hydroxy-2-methylpropiononitrile (CAS RN 75-86-5) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.5227	*ex 2926 90 70	25	2,2-Dibromo-3-nitrilopropionamide (CAS RN 10222-01-2)	0 %	-	31.12.2031

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.6149	ex 2926 90 70	27	Cyhalofop-butyl (ISO) (CAS RN 122008-85-9)	0 %	-	31.12.2029
0.8321	ex 2926 90 70	28	3-Bromo-6-chloro-2-fluorobenzonitrile (CAS RN 943830-79-3) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.7430	ex 2926 90 70	29	2-Cyclohexylidene-2-phenylacetonitrile (CAS RN 10461-98-0) with a purity by weight of 95 % or more	0 %	-	31.12.2027
0.7201	*ex 2926 90 70	30	4,5-Dichloro-3,6-dioxocyclohexa-1,4-diene-1,2-dicarbonitrile (CAS RN 84-58-2)	0 %	-	31.12.2031
0.3522	ex 2926 90 70	32	Ethyl cyanoacetate (CAS RN 105-56-6) or methyl cyanoacetate (CAS RN 105-34-0) with a purity by weight of 97 % or more	0 %	-	31.12.2029
0.7406	ex 2926 90 70	33	Deltamethrin (ISO) (CAS RN 52918-63-5)	0 %	-	31.12.2027
0.8907	ex 2926 90 70	34	2,3,3,3-Tetrafluoro-2-(trifluoromethyl)propanenitrile (CAS RN 42532-60-5) with a purity by weight of 99 % or more	0 %	-	31.12.2030
0.7034	*ex 2926 90 70	35	4-Cyano-2-methoxybenzaldehyde (CAS RN 21962-45-8)	0 %	-	31.12.2031
0.8908	ex 2926 90 70	36	3,4-Dimethoxybicyclo[4.2.0]octa-1,3,5,-triene-7-carbonitrile (CAS RN 35202-54-1) with a purity by weight of 97 % or more	0 %	-	31.12.2030
0.8217	*ex 2926 90 70	56	Methyl 2-cyano-2-propylpentanoate (CAS RN 66546-92-7) with a purity by weight of 97 % or more	0 %	-	31.12.2027
0.4182	*ex 2926 90 70	61	*m*-(1-Cyanoethyl)benzoic acid (CAS RN 5537-71-3)	0 %	-	31.12.2031
0.4802	ex 2926 90 70	70	Methacrylonitrile (CAS RN 126-98-7)	0 %	-	31.12.2029
0.3521	ex 2926 90 70	75	Ethyl 2-cyano-2-ethyl-3-methylhexanoate (CAS RN 100453-11-0)	0 %	-	31.12.2029
0.3516	ex 2926 90 70	80	Ethyl 2-cyano-2-phenylbutyrate (CAS RN 718-71-8)	0 %	-	31.12.2029
0.3514	ex 2926 90 70	86	Ethylenediaminetetraacetonitrile (CAS RN 5766-67-6)	0 %	-	31.12.2029
0.3515	ex 2926 90 70	89	Butyronitrile (CAS RN 109-74-0)	0 %	-	31.12.2029
0.7337	ex 2927 00 00	25	2,2'-Azobis(4-methoxy-2,4-dimethylvaleronitrile) (CAS RN 15545-97-8)	0 %	-	31.12.2027
0.2667	ex 2927 00 00	45	2,2´-Dimethyl-2,2´-azodipropionamidine dihydrochloride (CAS RN 2997-92-4) with a purity by weight of 97 % or more	0 %	-	31.12.2029
0.2810	ex 2927 00 00	55	4'-Aminoazobenzene-4-sulphonic acid (CAS RN 104-23-4) with a purity by weight of 90 % or more	0 %	-	31.12.2029
0.9096	*ex 2927 00 00	65	3-(*N*,*N*-Dimethylcarbamoylimido)-1,1-dimethylurea (CAS RN 10465-78-8) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.6479	ex 2928 00 90	13	Cymoxanil (ISO) (CAS RN 57966-95-7)	0 %	-	31.12.2029
0.6548	ex 2928 00 90	18	Acetone oxime (CAS RN 127-06-0) of a purity by weight of 99 % or more	0 %	-	31.12.2029
0.6871	ex 2928 00 90	23	Metobromuron (ISO) (CAS RN 3060-89-7) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.4929	ex 2928 00 90	25	Acetaldehyde oxime (CAS RN 107-29-9) in an aqueous solution	0 %	-	31.12.2030
0.6985	*ex 2928 00 90	28	Pentan-2-one oxime (CAS RN 623-40-5)	0 %	-	31.12.2031

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7448	ex 2928 00 90	33	4- Chlorophenylhydrazine Hydrochloride (CAS RN 1073-70-7)	0 %	-	31.12.2029
0.8061	ex 2928 00 90	38	Aqueous solution of methoxyammonium chloride (CAS RN 593-56-6), containing by weight: — 30 % or more but not more than 40 % of methoxyammonium chloride — not more than 4 % of hydrochloric acid	0 %	-	31.12.2030
0.8093	ex 2928 00 90	43	2-(3-Methoxy-3-oxopropyl)-1,1,1-trimethylhydrazinium bromide (CAS RN 106966-25-0) with a purity by weight of 99 % or more	0 %	-	31.12.2030
0.5919	ex 2928 00 90	45	Tebufenozide (ISO) (CAS RN 112410-23-8)	0 %	-	31.12.2029
0.8158	*ex 2928 00 90	48	1-{[(1H-Fluoren-9-ylmetoxi)carbonil]oxi}pyrrolidine-2,5-dione (CAS RN 82911-69-1) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.6635	ex 2928 00 90	50	Aqueous solution of 2,2'-(hydroxyimino) bisethanesulphonic acid disodium salt (CAS RN 133986-51-3) with a content by weight of more than 33,5 % but not more than 36,5 %	0 %	-	31.12.2030
0.8474	ex 2928 00 90	53	Ethyl chloro[(4-methoxyphenyl)hydrazono]acetate (CAS RN 27143-07-3) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8731	ex 2928 00 90	63	Daminozide (ISO) (CAS RN 1596-84-5) with a purity by weight of 97 % or more	0 %	-	31.12.2029
0.9010	ex 2928 00 90	68	Ethyl hydrazinoacetate hydrochloride (CAS RN 6945-92-2) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.4544	ex 2928 00 90	70	Butanone oxime (CAS RN 96-29-7)	0 %	-	31.12.2029
0.2661	ex 2928 00 90	73	3,3´-Bis(3,5-di-*tert*-butyl-4-hydroxyphenyl)-*N*,*N*´-bipropionamide (CAS RN 32687-78-8) with a purity by weight of 97 % or more	0 %	-	31.12.2029
0.5918	ex 2928 00 90	78	Aminoguanidinium hydrogen carbonate (CAS RN 2582-30-1) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.3510	ex 2928 00 90	80	Cyflufenamid (ISO) (CAS RN 180409-60-3)	0 %	-	31.12.2029
0.5827	ex 2929 10 00	20	Butyl isocyanate (CAS RN 111-36-4)	0 %	-	31.12.2027
0.4188	ex 2929 10 00	35	1,3-Bis(isocyanatomethyl)benzene (CAS RN 3634-83-1) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.2660	ex 2929 10 00	40	*m*-Isopropenyl-*α,α*-dimethylbenzyl isocyanate (CAS RN 2094-99-7)	0 %	-	31.12.2029
0.5033	ex 2929 10 00	45	2,5 (and 2,6)-Bis(isocyanatomethyl)bicyclo[2.2.1]heptane (CAS RN 74091-64-8) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.2657	ex 2929 10 00	50	*m*-Phenylenediisopropylidene diisocyanate (CAS RN 2778-42-9)	0 %	-	31.12.2029
0.3509	ex 2929 10 00	60	Trimethylhexamethylene diisocyanate, mixed isomers	0 %	-	31.12.2029
0.8451	ex 2929 10 00	65	Ethyl isocyanate (CAS RN 109-90-0) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8171	*ex 2929 90 90	40	*N*-Butylphosphorothioic triamide (CAS RN 94317-64-3) with a purity by weight of 97 % or more	0 %	-	31.12.2031
0.8172	*ex 2929 90 90	50	N-Propylphosphorothioic triamide (CAS RN 916809-14-8) with a purity by weight of 97 % or more	0 %	-	31.12.2031

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8611	ex 2929 90 90	60	(2*S*)-2-[[2-[2-[2-[2-[2-[2-[2-[2-[2-[2-(2-Azidoethoxy)ethoxy]ethoxy]ethoxy]ethoxy]ethoxy]ethoxy]ethoxy]ethylamino]-2-oxoethoxy]acetyl]amino]-*N*-[4-(hydroxymethyl)phenyl]-6-[[(4-methoxyphenyl)-diphenylmethyl]amino]hexanamide (CAS RN 1224601-12-0) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.8701	ex 2929 90 90	80	Wet paste or powder — with a content by weight of *N',N''*-[(2S,3E,5S)-1,6-diphenylhex-3-ene-2,5-diyl]*bis*(*N*,*N*-dimethylsulfuric diamide) (CAS RN 1247119-27-2) of 70 % or more, — with a content by weight of water of not more than 30 % — and with a dry weight purity of *N',N''*-[(2S,3E,5S)-1,6-diphenylhex-3-ene-2,5-diyl]*bis*(*N*,*N*-dimethylsulfuric diamide) (CAS RN 1247119-27-2) of 90 % or more	0 %	-	31.12.2029
0.4298	ex 2930 20 00	40	Prosulfocarb (ISO) (CAS RN 52888-80-9) with purity by weight of 97 % or more	0 %	-	31.12.2027
0.8036	*ex 2930 90 95	11	Benzyl (2*S*)-2-amino-3-[3-(methanesulphonylphenyl)]propanoate hydrochloride (CAS RN 1194550-59-8) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.6551	ex 2930 90 95	16	3-(Dimethoxymethylsilyl)-1-propanethiol (CAS RN 31001-77-1)	0 %	-	31.12.2029
0.5999	ex 2930 90 95	17	2-(3-Aminophenylsulphonyl)ethyl hydrogen sulphate (CAS RN 2494-88-4)	0 %	-	31.12.2029
0.7748	ex 2930 90 95	18	Dimethyl sulfone (CAS RN 67-71-0)	0 %	-	31.12.2029
0.8050	ex 2930 90 95	19	4-Amino-5-(ethanesulphonyl)-2-methoxybenzoic acid (CAS RN 71675-87-1) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.7799	ex 2930 90 95	20	4-(4-Methylphenylthio)benzophenone (CAS RN 83846-85-9)	0 %	-	31.12.2029
0.9006	ex 2930 90 95	22	4,4,5,5,5-Pentafluoropentyl carbamimidothioate—methanesulfonate (1:1) (CAS RN 1107606-68-7) with a purity by weight of 99 % or more	0 %	-	31.12.2030
0.9011	ex 2930 90 95	24	Trimethyloxosulfonium chloride (CAS RN 5034-06-0) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.6617	ex 2930 90 95	25	Bis(4-chlorophenyl)sulphone (CAS RN 80-07-9) with a purity by weight of 98 % or more	3.2 %	-	31.12.2027
0.6873	ex 2930 90 95	26	Folpet (ISO)(CAS RN 133-07-3) with a purity by weight of 97,5 % or more	0 %	-	31.12.2030
0.8069	ex 2930 90 95	28	Mesotrione (ISO) (CAS RN 104206-82-8) in form of wet cake or wet paste or in its crystalline form, with — a purity of 74 % or more by weight and, — a maximum water content of 23 % by weight	0 %	-	31.12.2030
0.9108	*ex 2930 90 95	29	4-Chlorobenzenethiol (CAS RN 106-54-7) with a purity by weight of 97 % or more	0 %	-	31.12.2031
0.6750	*ex 2930 90 95	30	[2,2'-Thio-bis(4-*tert*-octylphenolate)]-n-butylamine nickel (CAS RN 14516-71-3) with a purity by weight of 95 % or more, for use as light stabilizer in UV ink formulation (1)	0 %	-	31.12.2031
0.7833	ex 2930 90 95	31	(p-Toluenesulphonyl)methyl isocyanide (CAS RN 36635-61-7) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.6584	ex 2930 90 95	33	2-Amino-5-{[2-(sulfooxy)ethyl]sulfonyl}benzenesulfonIc acid (CAS RN 42986-22-1)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8510	ex 2930 90 95	36	Anhydrous potassium *O*-isopentyl-dithiocarbonate (CAS RN 928-70-1) with a purity by weight of 90 % or more	0 %	-	31.12.2027
0.8447	ex 2930 90 95	39	Thiodiacetic acid (CAS RN 123-93-3) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.2928	ex 2930 90 95	40	3,3´-Thiodi(propionic acid) (CAS RN 111-17-1)	0 %	-	31.12.2029
0.8481	ex 2930 90 95	41	2,2'-Diallyl-4,4'-sulphonyldiphenol (CAS RN 41481-66-7) with a purity by weight of 96 % or more	0 %	-	31.12.2027
0.6167	ex 2930 90 95	43	Trimethylsulfoxonium iodide (CAS RN 1774-47-6)	0 %	-	31.12.2029
0.2931	ex 2930 90 95	45	2-[(*p*-Aminophenyl)sulphonyl]ethyl hydrogen sulphate (CAS RN 2494-89-5)	0 %	-	31.12.2029
0.7689	ex 2930 90 95	50	3-Mercaptopropionic acid (CAS RN 107-96-0)	0 %	-	31.12.2029
0.5114	ex 2930 90 95	55	Thiourea (CAS RN 62-56-6)	0 %	-	31.12.2030
0.4629	ex 2930 90 95	64	3-Chloro-2-methylphenyl methyl sulphide (CAS RN 82961-52-2)	0 %	-	31.12.2029
0.4296	ex 2930 90 95	68	Clethodim (ISO) (CAS RN 99129-21-2)	0 %	-	31.12.2027
0.2999	ex 2930 90 95	80	Captan (ISO) (CAS RN 133-06-2)	0 %	-	31.12.2029
0.4694	ex 2930 90 95	81	Disodium hexamethylene-1,6-bisthiosulfate dihydrate (CAS RN 5719-73-3)	3 %	-	31.12.2029
0.8694	ex 2930 90 95	82	Propane-1,3-dithiol (CAS RN 109-80-8) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.7985	ex 2930 90 95	88	1-{4-[(4-Benzoylphenyl)sulphanyl]phenyl}-2-methyl-2-[(4-methylphenyl)sulphonyl]propan-1-one (CAS RN 272460-97-6) with a purity by weight of 94 % or more	0 %	-	31.12.2030
0.4094	*ex 2930 90 95	89	Potassium- or sodium-salt of O-ethyl-, O-isopropyl-, O-butyl-, O-isobutyl- or O-pentyl-dithiocarbonates	0 %	-	31.12.2031
0.7070	*ex 2930 90 95	93	1-Hydrazino-3-(methylthio)propan-2-ol (CAS RN 14359-97-8)	0 %	-	31.12.2031
0.7078	*ex 2930 90 95	95	*N*-(Cyclohexylthio)phthalimide (CAS RN 17796-82-6)	0 %	-	31.12.2031
0.7086	*ex 2930 90 95	97	Diphenyl sulphone (CAS RN 127-63-9)	0 %	-	31.12.2031
0.5741	ex 2931 49 80	08	Sodium diisobutyldithiophosphinate (CAS RN 13360-78-6) in an aqueous solution	0 %	-	31.12.2027
0.8546	ex 2931 49 80	10	Triethyl phosphonoacetate (CAS RN 867-13-0) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.5492	*ex 2931 49 80	13	Trioctylphosphine oxide (CAS RN 78-50-2)	0 %	-	31.12.2031
0.3492	ex 2931 49 80	20	Tetrabutylphosphonium acetate (CAS RN 30345-49-4) in the form of an aqueous solution, containing by weight 40 % or more but not more than 50 % of tetrabutylphosphonium acetate	0 %	-	31.12.2029
0.5758	ex 2931 49 80	25	(*Z*)-Prop-1-en-1-ylphosphonic acid (CAS RN 25383-06-6)	0 %	-	31.12.2027
0.7533	ex 2931 49 80	35	Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate (CAS RN 84434-11-7)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.2656	ex 2931 49 80	38	N-(Phosphonomethyl)iminodiacetic acid (CAS RN 5994-61-6) containing by weight not more than 15 % of water, and with a dry weight purity of 97 % or more	0 %	-	31.12.2029
0.5229	*ex 2931 49 80	40	Tetrakis(hydroxymethyl)phosphonium chloride (CAS RN 124-64-1)	0 %	-	31.12.2031
0.3987	ex 2931 49 80	55	3-(Hydroxyphenylphosphinoyl)propionic acid (CAS RN 14657-64-8)	0 %	-	31.12.2029
0.9092	*ex 2931 49 80	58	Tributylphosphine (CAS RN 998-40-3) with a purity by weight of 99 % or more	0 %	-	31.12.2031
0.7709	ex 2931 59 90	50	2-Chloroethylphosphonic acid (CAS RN 16672-87-0) solid or in aqueous solution, with a content by weight of 2-Chloroethylphosphonic acid of 65 % or more	0 %	-	31.12.2029
0.4515	ex 2931 90 00	15	Methylcyclopentadienyl manganese tricarbonyl (CAS RN 12108-13-3) containing not more than 4,9 % by weight of cyclopentadienyl manganese tricarbonyl	0 %	-	31.12.2029
0.9004	ex 2931 90 00	21	(2-Fluoro-4-phenoxyphenyl)boronic acid (CAS RN 1414356-30-1) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.8051	ex 2931 90 00	23	Ixazomib citrate (INNM) (CAS RN 1239908-20-3) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.8063	ex 2931 90 00	28	Triethoxy(3-isocyanatopropyl)silane (CAS RN 24801-88-5) with a purity by weight of 96 % or more	0 %	-	31.12.2030
0.8272	*ex 2931 90 00	30	*Tert*-Butylchlorodimethylsilane (CAS RN 18162-48-6) with a purity by weight of 99 % or more	0 %	-	31.12.2031
0.8316	ex 2931 90 00	38	2-(Trimethylsilyl)ethoxymethyl chloride (CAS RN 76513-69-4) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8442	ex 2931 90 00	40	Chlorotrimethylsilane (CAS RN 75-77-4) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8640	ex 2931 90 00	43	Trimethylindium (CAS RN 3385-78-2) with a purity by weight of 99 % or more	0 %	-	31.12.2028
0.8649	ex 2931 90 00	48	4-Phenoxybenzeneboronic acid (CAS RN 51067-38-0) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.4121	*ex 2931 90 00	50	Trimethylsilane (CAS RN 993-07-7)	0 %	-	31.12.2031
0.8554	ex 2931 90 00	55	3-(Hydroxymethyl)phenylboronic acid (CAS RN 87199-15-3) with a purity by weight of 95 % or more	0 %	-	31.12.2028
0.8652	ex 2931 90 00	58	Trimethylgallium (CAS RN 1445-79-0) with a purity by weight of 99 % or more	0 %	-	31.12.2028
0.8941	ex 2931 90 00	68	Hydrogen tetrakis(pentafluorophenyl)borate(1-)—N,N-dimethylaniline (1:1) (CAS RN 118612-00-3) with a purity by weight of 99 % or more	0 %	-	31.12.2030
0.3486	ex 2932 13 00	10	Tetrahydrofurfuryl alcohol (CAS RN 97-99-4)	0 %	-	31.12.2030
0.4590	ex 2932 14 00	20	1,6-Dichloro-1,6-dideoxy-β-D-fructofuranosyl-4-chloro-4-deoxy-α-D-galactopyranoside (CAS RN 56038-13-2) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.8615	ex 2932 19 00	15	2-Methylfuran (CAS RN 534-22-5) with a purity by weight of 98 % or more	0 %	-	31.12.2028

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8636	ex 2932 19 00	25	Methyl tetrahydro-2-furancarboxylate (CAS RN 37443-42-8) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.8605	ex 2932 19 00	35	(2*S*,3*S*,4*S*,5*R*)-3-(3,4-Difluoro-2-methoxyphenyl)-4,5-dimethyl-5-(trifluoromethyl)tetrahydrofuran-2-yl-4-nitrobenzoate (CAS RN 2875066-49-0) with a purity by weight of 97 % or more	0 %	-	31.12.2028
0.9013	ex 2932 19 00	38	(2,2-Diphenyltetrahydrofuran-3-yl)methanol (CAS RN 93651-75-3) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.4514	ex 2932 19 00	41	2,2 Di(tetrahydrofuryl)propane (CAS RN 89686-69-1)	0 %	-	31.12.2029
0.8252	*ex 2932 19 00	55	(3*S*)-3-[4-[(5-Bromo-2-chlorophenyl)methyl]phenoxy]tetrahydro-furan (CAS RN 915095-89-5) with a purity by weight of 97 % or more	0 %	-	31.12.2031
0.7614	ex 2932 19 00	65	Tefuryltrione (ISO) (CAS RN 473278-76-1)	0 %	-	31.12.2029
0.3487	ex 2932 19 00	70	Furfurylamine (CAS RN 617-89-0)	0 %	-	31.12.2029
0.5240	*ex 2932 19 00	80	5-Nitrofurfurylidene di(acetate) (CAS RN 92-55-7)	0 %	-	31.12.2031
0.5257	*ex 2932 20 90	15	Coumarin (CAS RN 91-64-5)	0 %	-	31.12.2031
0.7958	ex 2932 20 90	18	4-Hydroxycoumarin (CAS-RN 1076-38-6) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.8478	ex 2932 20 90	28	(*R*)-3-(3,4-difluoro-2-methoxyphenyl)-4,5-dimethyl-5-(trifluoromethyl)furan-2(5*H*)-one (CAS RN 2875066-35-4) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8532	ex 2932 20 90	33	6-Cyclohexyl-4-methyl-2*H*-pyran-2-one (CAS RN 14818-35-0) with a purity of 99 % by weight or more	0 %	-	31.12.2028
0.8944	ex 2932 20 90	38	6-Dimethylamino-3,3-bis(4-dimethylaminophenyl)phthalide (CAS RN 1552-42-7) with a purity by weight of 96 % or more	0 %	-	31.12.2030
0.5611	ex 2932 20 90	40	(*S*)-(−)-α-Amino-γ-butyrolactone hydrobromide (CAS RN 15295-77-9)	0 %	-	31.12.2027
0.9123	*ex 2932 20 90	43	2,3,4,6-Tetrakis-*O*-trimethylsilyl-D-gluconolactone (CAS RN 32384-65-9) with a purity by weight of 98 % or more	0 %	-	31.12.2032
0.6094	ex 2932 20 90	45	2,2-Dimethyl-1,3-dioxane-4,6-dione (CAS RN 2033-24-1)	0 %	-	31.12.2029
0.7283	ex 2932 20 90	50	L-Lactide (CAS RN 4511-42-6), D-lactide (CAS RN 13076-17-0), dilactide (CAS RN 95-96-5) or meso-lactide (CAS RN 13076-19-2), each with a purity by weight of 90 % or more	0 %	-	31.12.2027
0.7812	ex 2932 20 90	63	Selamectin (INN) 5Z-isomer (CAS RN 220119-17-5)	0 %	-	31.12.2029
0.6620	ex 2932 20 90	65	Sodium 4-(methoxycarbonyl)-5-oxo-2,5-dihydrofuran-3-olate (CAS RN 1134960-41-0)	0 %	-	31.12.2030
0.4161	*ex 2932 20 90	71	6'-(Dibutylamino)-3'-methyl-2'-(phenylamino)-spiro[isobenzofuran-1(3*H*),9'-[9*H*]xanthen]-3-one (CAS RN 89331-94-2)	0 %	-	31.12.2031
0.7599	ex 2932 20 90	75	3-Acetyl-6-methyl-2*H*-pyran-2, 4(3*H*)-dione (CAS RN 520-45-6)	0 %	-	31.12.2029
0.3990	ex 2932 20 90	80	Gibberellic acid (CAS RN 77-06-5) with a purity by weight of 88 % or more, for use in the manufacture of plant protection products (1)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.4403	ex 2932 20 90	84	Decahydro-3a,6,6,9a-tetramethylnaphth [2,1-b] furan-2 (1H)-one (CAS RN 564-20-5)	0 %	-	31.12.2029
0.9119	*ex 2932 93 00	10	Piperonal (CAS RN 120-57-0) with a purity by weight of 90 % or more	0 %	-	31.12.2031
0.8528	ex 2932 99 00	03	3,4-Dihydro-2-methoxy-2*H*-pyran (CAS RN 4454-05-1) with a purity by weight of 99 % or more	0 %	-	31.12.2028
0.5269	*ex 2932 99 00	15	1,3,4,6,7,8-Hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran (CAS RN 1222-05-5)	0 %	-	31.12.2031
0.7431	ex 2932 99 00	23	2-Ethyl-3-hydroxy-4-pyrone (CAS RN 4940-11-8)	0 %	-	31.12.2027
0.5759	ex 2932 99 00	25	1-(2,2-Difluorobenzo[d][1,3]dioxol-5-yl)cyclopropanecarboxylic acid (CAS RN 862574-88-7)	0 %	-	31.12.2027
0.7639	ex 2932 99 00	27	(2-Butyl-3-benzofuranyl)(4-hydroxy-3,5-diiodophenyl)methanone (CAS RN 1951-26-4) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.7535	ex 2932 99 00	33	3-Hydroxy-2-methyl-4-pyrone (CAS RN 118-71-8)	0 %	-	31.12.2029
0.8035	ex 2932 99 00	38	1-Benzofuran-6-carboxylic acid (CAS RN 77095-51-3) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.6243	ex 2932 99 00	43	Ethofumesate (ISO) (CAS RN 26225-79-6) with a purity by weight of 97 % or more	0 %	-	31.12.2029
0.5915	ex 2932 99 00	45	2-Butylbenzofuran (CAS RN 4265-27-4)	0 %	-	31.12.2029
0.8384	ex 2932 99 00	48	(20R,25R)-spirost-5-en-3β-ol (CAS RN 512-04-9) with a purity by weight of 95 % or more	0 %	-	31.12.2027
0.4907	ex 2932 99 00	50	7-Methyl-3,4-dihydro-2*H*-1,5-benzodioxepin-3-one (CAS RN 28940-11-6)	0 %	-	31.12.2029
0.4063	ex 2932 99 00	51	3-(3,4-Methylenedioxyphenyl)-2-methylpropanal (CAS RN 1205-17-0) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.6771	ex 2932 99 00	65	4,4-Dimethyl-3,5,8-trioxabicyclo[5,1,0]octane (CAS RN 57280-22-5)	0 %	-	31.12.2030
0.7954	ex 2932 99 00	83	6,11-Dihydrodibenz[b,e]oxepin-11-one (CAS RN 4504-87-4) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.3697	ex 2932 99 00	85	1,3:2,4-bis-O-(3,4-Dimethylbenzylidene)-D-glucitol (CAS RN 135861-56-2)	0 %	-	31.12.2029
0.6262	ex 2933 19 90	15	Pyrasulfotole (ISO) (CAS RN 365400-11-9) with a purity by weight of 96 % or more	0 %	-	31.12.2029
0.9114	*ex 2933 19 90	22	3-Chloro-1-ethyl-4-[(3-iodo-1-methyl-1*H*-pyrazol-4-yl)methyl]-1*H*-pyrazole (CAS RN 2739869-33-9) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.7836	ex 2933 19 90	27	3-(3,3,3-Trifluoro-2,2-dimethylpropoxy)-1H-pyrazole-4-carboxylic acid (CAS RN 2229861-20-3) with a purity by weight of 95 % or more	0 %	-	31.12.2029
0.9106	*ex 2933 19 90	29	3-(3,5-Dimethyl-1*H*-pyrazol-4-yl)propan-1-ol (CAS RN 1779428-05-5) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.7811	ex 2933 19 90	33	Fipronil (ISO) (CAS RN 120068-37-3) with a purity by weight of 95 % or more for the use in the manufacture of veterinary medicine (1)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8353	ex 2933 19 90	38	4,5-Dimethyl-1H-pyrazole-3-carboxylic acid (CAS RN 89831-40-3) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.3877	ex 2933 19 90	40	Edaravone (INN) (CAS RN 89-25-8)	0 %	-	31.12.2029
0.8046	ex 2933 19 90	48	1-(3-Iodo-1-isopropyl-1H-pyrazol-4-yl)ethanone (CAS RN 1269440-49-4) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.3992	ex 2933 19 90	50	Fenpyroximate (ISO) (CAS RN 134098-61-6)	0 %	-	31.12.2029
0.8603	ex 2933 19 90	58	1*H*-Pyrazole (CAS RN 288-13-1) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.4494	ex 2933 19 90	60	Pyraflufen-ethyl (ISO) (CAS RN 129630-19-9)	0 %	-	31.12.2029
0.6261	ex 2933 19 90	63	3-Difluoromethyl-1-methyl-1H-pyrazole-4-carboxylic acid (CAS RN 176969-34-9) with a purity by weight of 97 % or more	0 %	-	31.12.2029
0.8613	ex 2933 19 90	68	1-Methyl-1*H*-pyrazol-4-amine hydrochloride (CAS RN 127107-23-7) with a purity by weight of 95 % or more	0 %	-	31.12.2028
0.4404	ex 2933 19 90	70	4,5-Diamino-1-(2-hydroxyethyl)-pyrazolsulphate (CAS RN 155601-30-2)	0 %	-	31.12.2029
0.9015	ex 2933 19 90	78	3-(3-Methyl-5-oxo-4,5-dihydro-1*H*-pyrazol-1-yl)benzenesulfonic acid (CAS RN 119-17-5) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.9075	ex 2933 19 90	83	Isomeric mixture containing by weight 97 % or more of the two isomers — 2-(3,4-Dimethyl-1*H*-pyrazol-1-yl)succinic acid and — 2-(4,5-Dimethyl-1*H*-pyrazol-1-yl)succinic acid (CAS RN 2241455-89-8)	0 %	-	31.12.2030
0.8312	*ex 2933 21 00	45	Sodium (5*S*,8*S*)-8-methoxy-2,4-dioxo-1,3-diazaspiro[4.5]decan-3-ide (CAS RN 1400584-86-2) with a purity by weight of 90 % or more	0 %	-	31.12.2031
0.6835	ex 2933 21 00	55	1-Aminohydantoin hydrochloride (CAS RN 2827-56-7)	0 %	-	31.12.2030
0.4088	*ex 2933 21 00	60	DL-*p*-Hydroxyphenylhydantoin (CAS RN 2420-17-9)	0 %	-	31.12.2031
0.5115	ex 2933 21 00	80	5,5-Dimethylhydantoin (CAS RN 77-71-4)	0 %	-	31.12.2030
0.5972	ex 2933 29 90	15	Ethyl 4-(1-hydroxy-1-methylethyl)-2-propylimidazole-5-carboxylate (CAS RN 144689-93-0)	0 %	-	31.12.2029
0.9126	*ex 2933 29 90	33	Di-1*H*-imidazol-1-ylmethanone (CAS RN 530-62-1) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.8452	ex 2933 29 90	38	Cyazofamid (ISO) (CAS RN 120116-88-3) with a purity by weight of 94 % or more	0 %	-	31.12.2027
0.8639	ex 2933 29 90	43	2-Octyl-4,5-dihydro-1*H*-imidazole (CAS RN 10443-60-4) with a purity by weight of 95 % or more	0 %	-	31.12.2028
0.7120	*ex 2933 29 90	75	2,2'-Azobis[2-(2-imidazolin-2-yl)propane] dihydrochloride (CAS RN 27776-21-2)	0 %	-	31.12.2031
0.5821	ex 2933 29 90	80	Imazalil (ISO) (CAS RN 35554-44-0)	0 %	-	31.12.2027
0.6415	2933 39 50		Fluroxypyr (ISO) methyl ester (CAS RN 69184-17-4)	0 %	-	31.12.2029
0.8574	ex 2933 39 99	04	Methyl 4-aminopicolinate (CAS RN 71469-93-7) with a purity by weight of 98 % or more	0 %	-	31.12.2028

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8524	ex 2933 39 99	05	2,6-*Bis*-[1-(2-*tert*-butylphenylimino)-ethyl]pyridine (CAS RN 204203-17-8) with a purity by weight of 95 % or more	0 %	-	31.12.2028
0.8576	ex 2933 39 99	06	*Tert*-butyl (3*S*)-3-hydroxypiperidine-1-carboxylate (CAS RN 143900-44-1) with a purity by weight of 97 % or more	0 %	-	31.12.2028
0.8535	ex 2933 39 99	07	5-Bromo-2-methoxypyridine (CAS RN 13472-85-0) with a purity by weight of 99 % or more	0 %	-	31.12.2028
0.8485	ex 2933 39 99	08	Fluazinam (ISO) (CAS RN 79622-59-6) with a purity by weight of 97 % or more	0 %	-	31.12.2027
0.6462	ex 2933 39 99	11	2-(Chloromethyl)-4-(3-methoxypropoxy)-3-methylpyridine hydrochloride(CAS RN 153259-31-5)	0 %	-	31.12.2029
0.5608	ex 2933 39 99	12	2,3-Dichloropyridine (CAS RN 2402-77-9)	0 %	-	31.12.2027
0.8831	ex 2933 39 99	16	Tert-butyl (3*R*)-3-aminopiperidine-1-carboxylate (CAS RN 188111-79-7) with a purity by weight of 96 % or more	0 %	-	31.12.2029
0.8833	ex 2933 39 99	17	2,4-Dichloro-3-nitropyridine (CAS RN 5975-12-2) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.9008	ex 2933 39 99	19	5-Chloro-1-(4-piperidyl)-1*H*-benzimidazol-2(3*H*)-one (CAS RN 53786-28-0) with a purity by weight of 99 % or more	0 %	-	31.12.2030
0.8329	ex 2933 39 99	22	*N*-(5-bromo-3-methylpyridin-2-yl)-*N*-methylbenzamide (CAS RN 446299-80-5) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.9128	*ex 2933 39 99	23	(4*R*)-3,3-Difluoro-1-methyl-4-piperidinol (CAS RN 2306252-98-0) with a purity by weight of 96 % or more	0 %	-	31.12.2031
0.4594	ex 2933 39 99	24	2-Chloromethyl-4-methoxy-3,5-dimethylpyridine hydrochloride (CAS RN 86604-75-3)	0 %	-	31.12.2029
0.7091	*ex 2933 39 99	27	Pyridine-2,6-dicarboxylic acid (CAS RN 499-83-2)	0 %	-	31.12.2031
0.6368	ex 2933 39 99	28	Ethyl-3-[(3-amino-4-methylamino-benzoyl)-pyridin-2-yl-amino]-propionate (CAS RN 212322-56-0)	0 %	-	31.12.2029
0.9097	*ex 2933 39 99	29	*tert*-Butyl (3-(benzyloxy)-4-nitrophenyl)(4-methoxypyridin-3-yl)carbamate with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.6458	ex 2933 39 99	31	2-(Chloromethyl)-3-methyl-4-(2,2,2-trifluoroethoxy)pyridine hydrochloride(CAS RN 127337-60-4)	0 %	-	31.12.2029
0.7181	*ex 2933 39 99	33	5-(3-Chlorophenyl)-3-methoxypyridine-2-carbonitrile (CAS RN 1415226-39-9)	0 %	-	31.12.2031
0.8420	ex 2933 39 99	34	Pyridin-3-ol (CAS RN 109-00-2) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.3878	ex 2933 39 99	35	Aminopyralid (ISO) (CAS RN 150114-71-9)	0 %	-	31.12.2029
0.7296	ex 2933 39 99	36	1-[2-[5-Methyl-3-(trifluoromethyl)-1H-pyrazol-1-yl]acetyl]piperidine-4-carbothioamide (CAS RN 1003319-95-6)	0 %	-	31.12.2027
0.5230	*ex 2933 39 99	37	Aqueous solution of pyridine-2-thiol-1-oxide, sodium salt (CAS RN 3811-73-2)	0 %	-	31.12.2031
0.7348	ex 2933 39 99	38	(2-Chloropyridin-3-yl) methanol (CAS RN 42330-59-6)	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8356	ex 2933 39 99	40	2-Hydroxypyridine-N-oxide (CAS RN 13161-30-3) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8711	ex 2933 39 99	44	Fluroxypyr-meptyl (CAS RN 81406-37-3) with a purity by weight of 95 % or more	0 %	-	31.12.2029
0.8699	ex 2933 39 99	45	2,4-Dichloropyridine-3-carboxaldehyde (CAS RN 134031-24-6) with a purity by weight of 95 % or more	0 %	-	31.12.2029
0.4706	*ex 2933 39 99	47	(-)-*trans*-4-(4'-Fluorophenyl)-3-hydroxymethyl-*N*-methylpiperidine (CAS RN 105812-81-5)	0 %	-	31.12.2031
0.4749	ex 2933 39 99	48	Flonicamid (ISO) (CAS RN 158062-67-0)	0 %	-	31.12.2029
0.8335	ex 2933 39 99	49	2-Phenyl-2-(2-pyridyl)acetamide (CAS RN 7251-52-7) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.6812	ex 2933 39 99	50	N,4-Dimethyl-1-(phenylmethyl)- 3-piperidinamine hydrochloride (1:2) (CAS RN 1228879-37-5) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.8709	ex 2933 39 99	51	2-Amino-3-bromo-5-nitropyridine (CAS RN 15862-31-4) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.8637	ex 2933 39 99	53	5-Methyl-2-pyridylamine (CAS RN 1603-41-4) with a purity by weight of 99 % or more	0 %	-	31.12.2028
0.8729	ex 2933 39 99	54	2,5-Dichloro-4,6-dimethylpyridine-3-carbonitrile (CAS RN 91591-63-8) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.4646	ex 2933 39 99	55	Pyriproxyfen (ISO) (CAS RN 95737-68-1) of a purity by weight of 97 % or more	0 %	-	31.12.2029
0.8618	ex 2933 39 99	56	2-[[[3-Methyl-4-(2,2,2-trifluoroethoxy)pyridin-2-yl]methyl]sulfanyl]1*H*-benzimidazole (CAS RN 103577-40-8) with a purity by weight of 99 % or more	0 %	-	31.12.2028
0.5760	ex 2933 39 99	57	*Tert*-butyl 3-(6-amino-3-methylpyridin-2-yl)benzoate (CAS RN 1083057-14-0)	0 %	-	31.12.2027
0.8624	ex 2933 39 99	58	*Tert*-butyl *N*-[5-(trifluoromethyl)pyridin-3-yl]carbamate (CAS RN 1187055-61-3) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.2750	ex 2933 39 99	60	2-Fluoro-6-(trifluoromethyl)pyridine (CAS RN 94239-04-0) with a purity by weight of 90 % or more	0 %	-	31.12.2029
0.7577	ex 2933 39 99	62	Ethyl 2,6-Dichloronicotinate (CAS RN 58584-86-4)	0 %	-	31.12.2029
0.8527	ex 2933 39 99	63	1-Methyl-4-piperidone (CAS RN 1445-73-4) with a purity by weight of 97 % or more	0 %	-	31.12.2028
0.3602	ex 2933 39 99	65	Acetamiprid (ISO) (CAS RN 135410-20-7)	0 %	-	31.12.2029
0.8656	ex 2933 39 99	66	(2*S*,4*S*)-4-Ethoxy-2-[4-(methoxycarbonyl)phenyl]piperidin-1-ium(2Z)-3-carboxyprop-2-enoate (CAS RN 2408761-21-5) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.7616	ex 2933 39 99	68	1-(3-Chloropyridin-2-yl)-3-[[5-(trifluoromethyl)-2H-tetrazol-2-yl]methyl]-1H-pyrazole-5-carboxylic acid (CAS RN 1352319-02-8) with a purity by weight of 85 % or more	0 %	-	31.12.2029
0.9160	*ex 2933 39 99	69	Pyriofenone (ISO) (CAS RN 688046-61-9) with a purity by weight of 96 % or more	0 %	-	31.12.2031

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.5494	*ex 2933 39 99	70	2,3-Dichloro-5-trifluoromethylpyridine (CAS RN 69045-84-7)	0 %	-	31.12.2031
0.8707	ex 2933 39 99	72	*N*-[(1*S*,5*R*)-8-Benzyl-8-azabicyclo[3.2.1]octane-3-yl]-2-methylpropanamide (CAS RN 376348-67-3) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.7737	ex 2933 39 99	73	6-Chloro-4-(4-fluoro-2-methylphenyl)pyridin-3-amine hydrochloride	0 %	-	31.12.2029
0.8072	ex 2933 39 99	75	Clodinafop-propargyl (ISO) (CAS RN 105512-06-9) with a purity by weight of 90 % or more	0 %	-	31.12.2030
0.7813	ex 2933 39 99	76	Apalutamide (INN) (CAS RN 956104-40-8)	0 %	-	31.12.2029
0.7818	ex 2933 39 99	78	Niraparib tosylate monohydrate (INNM) (CAS RN 1613220-15-7)	0 %	-	31.12.2029
0.8074	ex 2933 39 99	80	Tert-Butyl (3R)-3-(4-amino-2-oxo-2,3-dihydro-1H-imidazo[4, 5-c]pyridin-1-yl)piperidine-1-carboxylate (CAS RN 1971921-33-1) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.7906	ex 2933 39 99	81	4-Hydroxy-3-pyridinesulphonic acid (CAS RN 51498-37-4) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.7866	ex 2933 39 99	82	Picloram (ISO) (CAS RN 1918-02-1) containing by weight not more than 15 % of water and with a dry weight purity of 92 % or more	0 %	-	31.12.2029
0.7925	ex 2933 39 99	84	Diethyl(3-pyridyl)borane (CAS RN 89878-14-8) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.5129	ex 2933 39 99	85	2-Chloro-5-chloromethylpyridine (CAS RN 70258-18-3)	0 %	-	31.12.2030
0.8912	ex 2933 39 99	88	(1R,2S,4R)-2-Benzhydrylquinuclidin-3-one (2R,3R)-2,3-dihydroxysuccinate (CAS RN 683206-54-4) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.8096	ex 2933 39 99	89	1-Benzyl-4-phenylpiperidine-4-carbonitrile monohydrochloride (CAS RN 71258-18-9) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.6545	ex 2933 39 99	93	Boscalid (ISO) (CAS RN 188425-85-6) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.9060	ex 2933 39 99	94	Cyantraniliprole (ISO) (CAS RN 736994-63-1) with a purity by weight of 90 % or more	0 %	-	31.12.2030
0.9095	*ex 2933 39 99	96	2-Amino-5-bromopyridin-3-ol (CAS RN 39903-01-0) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.4525	ex 2933 49 10	20	3-Hydroxy-2-methylquinoline-4-carboxylic acid (CAS RN 117-57-7)	0 %	-	31.12.2029
0.6339	ex 2933 49 10	40	4,7-Dichloroquinoline (CAS RN 86-98-6)	0 %	-	31.12.2029
0.3603	ex 2933 49 10	70	Quinmerac (ISO) (CAS RN 90717-03-6) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.7098	*ex 2933 49 90	25	Cloquintocet-mexyl (ISO) (CAS RN 99607-70-2)	0 %	-	31.12.2031
0.4927	ex 2933 49 90	30	Quinoline (CAS RN 91-22-5)	0 %	-	31.12.2030
0.9101	*ex 2933 49 90	33	(2*R*,5*S*,8*S*,11*S*)-8-(4-Aminobutyl)-5,11-bis(carboxymethyl)-16-((4-((2-((*S*)-2-cyano-4,4-difluoropyrrolidin-1-yl)-2-oxoethyl)carbamoyl)quinolin-8-yl)amino)-2-(mercaptomethyl)-4,7,10,13,16-pentaoxo-3,6,9,12-tetraazahexadecanoic acid (CAS RN 2639365-70-9) with a purity by weight of 98 % or more	0 %	-	31.12.2031

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.9151	*ex 2933 49 90	43	7-Methyl-8-nitroquinoline (CAS RN 7471-63-8) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.8037	ex 2933 49 90	55	2-(*tert*-Butoxycarbonyl)-5,7-dichloro-1,2,3,4-tetrahydroisoquinoline-6-carboxylic acid (CAS RN 851784-82-2) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.3880	ex 2933 49 90	70	Quinolin-8-ol (CAS RN 148-24-3)	0 %	-	31.12.2029
0.8358	ex 2933 49 90	75	2-Methyl-4-(1-methyl-1H-1,2,4-triazol-5-yl)quinolin-8-ol (CAS RN 1174132-59-2) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8556	ex 2933 49 90	85	(2*R*,4*S*)-2-Ethyl-6-(trifluoromethyl)-1,2,3,4-tetrahydroquinolin-4-amine methanesulfonate (CAS RN 952582-02-4) with a purity by weight of 95 % or more	0 %	-	31.12.2028
0.4043	*ex 2933 52 00	10	Malonylurea (barbituric acid) (CAS RN 67-52-7)	0 %	-	31.12.2031
0.6468	ex 2933 59 95	10	6-Amino-1,3-dimethyluracil (CAS RN 6642-31-5)	0 %	-	31.12.2029
0.6151	ex 2933 59 95	13	2-Diethylamino-6-hydroxy-4-methylpyrimidine (CAS RN 42487-72-9)	0 %	-	31.12.2029
0.8597	ex 2933 59 95	14	2-Chloro-7-cyclopentyl-*N*,*N*-dimethyl-7H-pyrrolo[2,3-d]pyrimidine-6-carboxamide (CAS RN 1211443-61-6) with a purity by weight of 97 % or more	0 %	-	31.12.2028
0.8580	ex 2933 59 95	16	*Tert*-butyl 4-(6-aminopyridin-3-yl)piperazine-1-carboxylate (CAS RN 571188-59-5) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.8555	ex 2933 59 95	19	*Tert*-butyl 4-[(2-chloropyrimidin-5-yl)oxy]butanoate (CAS RN 945771-55-1) with a purity by weight of 95 % or more	0 %	-	31.12.2028
0.2745	ex 2933 59 95	20	2,4-Diamino-6-chloropyrimidine (CAS RN 156-83-2)	0 %	-	31.12.2029
0.5912	ex 2933 59 95	27	2-[(2-Amino-6-oxo-1,6-dihydro-9H-purin-9-yl)methoxy]-3-hydroxypropylacetate (CAS RN 88110-89-8)	0 %	-	31.12.2029
0.8157	*ex 2933 59 95	29	2-Amino-4-(4-methylpiperazin-1-yl) benzoic acid tert-butyl ester (CAS RN 1034975-35-3) with a purity by weight of 95 % or more	0 %	-	31.12.2027
0.8376	ex 2933 59 95	31	Sotorasib (INN) (CAS RN 2296729-00-3) with a purity by weight of 99 % or more	0 %	-	31.12.2027
0.8456	ex 2933 59 95	32	5-Chloro-3-nitropyrazolo[1,5-a]pyrimidine (CAS RN 1363380-51-1) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.6240	ex 2933 59 95	33	4,6-Dichloro-5-fluoropyrimidine (CAS RN 213265-83-9)	0 %	-	31.12.2029
0.7370	ex 2933 59 95	34	6-chloro-1,3-dimethyluracil (CAS RN 6972-27-6) with a purity by weight of 97 % or more	0 %	-	31.12.2029
0.8997	ex 2933 59 95	35	3-Iodo-1*H*-pyrazolo[3,4-d]pyrimidin-4-amine (CAS RN 151266-23-8) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.7345	ex 2933 59 95	36	1-(Cyclopropylcarbonyl)piperazine hydrochloride (CAS RN 1021298-67-8) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.9061	ex 2933 59 95	40	Pirimiphos-methyl (ISO) (CAS RN 29232-93-7) with a purity by weight of 90 % or more	0 %	-	31.12.2030
0.8484	ex 2933 59 95	44	1,4,5,6-Tetrahydro-1,2-dimethylpyrimidine (CAS RN 4271-96-9) with a purity by weight of 98 % or more	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.4704	ex 2933 59 95	45	1-[3-(Hydroxymethyl)pyridin-2-yl]-4-methyl-2-phenylpiperazine (CAS RN 61337-89-1)	0 %	-	31.12.2029
0.8488	ex 2933 59 95	46	Trilaciclib (CAS RN 1374743-00-6) with a purity by weight of 99 % or more	0 %	-	31.12.2027
0.6677	ex 2933 59 95	47	6-Methyl-2-oxoperhydropyrimidin-4-ylurea (CAS RN 1129-42-6) with a purity of 94 % or more	0 %	-	31.12.2030
0.4699	ex 2933 59 95	50	2-(2-Piperazin-1-ylethoxy)ethanol (CAS RN 13349-82-1)	0 %	-	31.12.2029
0.8612	ex 2933 59 95	51	(1*R*,5*S*)-8-Benzyl-3,8-diazabicyclo[3.2.1]octane ; 4-(4-hydroxyphenyl)phenol (2:1) (CAS RN 2642049-87-2) with a purity by weight of 95 % or more	0 %	-	31.12.2028
0.8602	ex 2933 59 95	54	2-Chloro-4-methylpyrimidine (CAS RN 13036-57-2) with a purity by weight of 99 % or more	0 %	-	31.12.2028
0.8834	ex 2933 59 95	56	Ruxolitinib phosphate (INNM) (CAS RN 1092939-17-7) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.2578	ex 2933 59 95	58	Sitagliptin phosphate monohydrate (INNM) (CAS RN 654671-77-9) with a purity by weight of 95 % or more, and containing by weight not more than 1 % of a stabiliser	0 %	-	31.12.2027
0.9129	*ex 2933 59 95	59	3-Methyl-4-([1,2,4]triazolo[1,5-*c*]pyrimidin-7-yloxy)benzenamine (CAS RN 2414057-07-9) with a purity by weight of 96 % or more	0 %	-	31.12.2031
0.2744	ex 2933 59 95	60	2,6-Dichloro-4,8-dipiperidinopyrimido[5,4-*d*]pyrimidine (CAS RN 7139-02-8)	0 %	-	31.12.2029
0.8717	ex 2933 59 95	61	4-Methyl-7*H*-pyrrolo[2,3-d]pyrimidine (CAS RN 945950-37-8) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.9099	*ex 2933 59 95	62	4,6-Dichloropyrimidin-5-ol (CAS RN 425394-89-4) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.7578	ex 2933 59 95	63	1-(3-Chlorophenyl) piperazine (CAS RN 6640-24-0)	0 %	-	31.12.2029
0.8730	ex 2933 59 95	64	Thiopental (INNM) (CAS RN 76-75-5) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.4772	ex 2933 59 95	65	1-Chloromethyl-4-fluoro-1,4-diazoniabicyclo[2.2.2]octane bis(tetrafluoroborate) (CAS RN 140681-55-6)	0 %	-	31.12.2029
0.8700	ex 2933 59 95	66	Piperazin-2-one (CAS RN 5625-67-2) with a purity by weight of 96 % or more	0 %	-	31.12.2029
0.9130	*ex 2933 59 95	67	Azoxystrobin (ISO) (CAS RN 131860-33-8) with a purity by weight of 95 % or more	0 %	-	31.12.2031
0.7825	ex 2933 59 95	68	Guanine (CAS RN 73-40-5) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.9124	*ex 2933 59 95	69	6-(2-Chloro-5-fluoro-4-pyrimidinyl)-4-fluoro-2-methyl-1-(1-methylethyl)-1*H*-benzimidazole (CAS RN 1231930-42-9) with a purity by weight of 95 % or more	0 %	-	31.12.2031
0.2735	ex 2933 59 95	70	*N*-(4-Ethyl-2,3-dioxopiperazin-1-ylcarbonyl)-D-2-phenylglycine (CAS RN 63422-71-9)	0 %	-	31.12.2029
0.9127	*ex 2933 59 95	71	5-Fluoro-6-methoxy-4(3*H*)-quinazolinone (CAS RN 2414057-08-0) with a purity by weight of 97 % or more	0 %	-	31.12.2031
0.5542	ex 2933 59 95	77	3-(Trifluoromethyl)-5,6,7,8-tetrahydro[1,2,4]triazolo[4,3-a]pyrazine hydrochloride (1:1) (CAS RN 762240-92-6)	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7071	*ex 2933 59 95	87	5-Bromo-2,4-dichloropyrimidine (CAS RN 36082-50-5)	0 %	-	31.12.2027
0.6621	ex 2933 69 80	15	2-Chloro-4,6-dimethoxy-1,3,5-triazine (CAS RN 3140-73-6)	0 %	-	31.12.2030
0.6951	*ex 2933 69 80	17	Benzoguanamine (CAS RN 91-76-9)	0 %	-	31.12.2031
0.7721	ex 2933 69 80	23	1,3,5-Tris(2,3-dibromopropyl)-1,3,5-triazinane-2,4,6-trione (CAS RN 52434-90-9)	0 %	-	31.12.2029
0.7600	ex 2933 69 80	27	Troclosene sodium dihydrate (INNM) (CAS RN 51580-86-0)	0 %	-	31.12.2029
0.7952	ex 2933 69 80	33	2,4,6-Trichloro-1,3,5-triazine (CAS RN 108-77-0) with a purity by weight of 99 % or more	0 %	-	31.12.2030
0.9058	ex 2933 69 80	38	Tris({[1,1'-biphenyl]-4-yl})-1,3,5-triazine (CAS RN 31274-51-8) with a purity by weight of 97 % or more	0 %	-	31.12.2030
0.5272	*ex 2933 69 80	40	Troclosene sodium (INNM) (CAS RN 2893-78-9)	0 %	-	31.12.2031
0.8718	ex 2933 69 80	43	4-(4,6-*Bis*((biphenyl-4-yl)-1,3,5-triazine-2-yl)-1,3-benzodiole (CAS RN 182918-16-7) with a purity by weight of 96 % or more	0 %	-	31.12.2029
0.7464	ex 2933 69 80	48	2-(4,6-Bis-(2,4-dimethylphenyl)-1,3,5-triazin-2-yl)-5-(octyloxy)-phenol (CAS RN 2725-22-6) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.5131	ex 2933 69 80	55	Terbutryn (ISO) (CAS RN 886-50-0) for use as a raw material for the production of technical preservatives, in other sectors than for pesticides (1)	0 %	-	31.12.2030
0.4957	ex 2933 69 80	60	Cyanuric acid (CAS RN 108-80-5)	0 %	-	31.12.2030
0.6127	ex 2933 69 80	65	1,3,5-Triazine-2,4,6(1H,3H,5H)-trithione, trisodium salt (CAS RN 17766-26-6)	0 %	-	31.12.2029
0.6477	ex 2933 69 80	75	Metamitron (ISO) (CAS RN 41394-05-2)	0 %	-	31.12.2029
0.3882	ex 2933 69 80	80	Tris(2-hydroxyethyl)-1,3,5-triazinetrione (CAS RN 839-90-7)	0 %	-	31.12.2029
0.6960	*ex 2933 79 00	15	Ethyl *N*-(*tert*-Butoxycarbonyl)-L-pyroglutamate (CAS RN 144978-12-1)	0 %	-	31.12.2031
0.8354	ex 2933 79 00	23	(*S*)-2-Amino-3-[(*S*)-2-oxopyrrolidin-3-yl]propanamide hydrochloride (CAS RN 2628280-48-6) with a purity by weight of 95 % or more	0 %	-	31.12.2027
0.7346	ex 2933 79 00	25	Methyl 2-oxo-2,3-dihydro-1H-indole-6-carboxylate (CAS RN 14192-26-8)	0 %	-	31.12.2029
0.9111	*ex 2933 79 00	28	3-Nitropyridin-2-ol (CAS RN 6332-56-5) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.4294	ex 2933 79 00	30	5-Vinyl-2-pyrrolidone (CAS RN 7529-16-0)	0 %	-	31.12.2027
0.8038	ex 2933 79 00	45	1-Phenyl-3H-indol-2-one (CAS RN 3335-98-6) with a purity by weight of 99 % or more	0 %	-	31.12.2030
0.8212	*ex 2933 79 00	65	1-Dodecyl-2-pyrrolidone (CAS RN 2687-96-9) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.8351	ex 2933 79 00	75	*N*-(n-octyl)-2-pyrrolidone (CAS RN 2687-94-7) with a purity by weight of 99 % or more	0 %	-	31.12.2027
0.8545	ex 2933 79 00	85	3,5-Dibromo-1-methyl-2(1*H*)-pyridinone (CAS RN 14529-54-5) with a purity by weight of 97 % or more	0 %	-	31.12.2028

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8547	ex 2933 99 80	01	3-Cyanoindole (CAS RN 5457-28-3) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.8548	ex 2933 99 80	02	(*S*)-1-Benzyl-3-pyrrolidinol (CAS RN 101385-90-4) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.8581	ex 2933 99 80	03	*Tert*-butyl 4-formyl-5-methoxy-7-methyl-1*H*-indole-1-carboxylate (CAS RN 1481631-51-9) with a purity by weight of 97 % or more	0 %	-	31.12.2028
0.8523	ex 2933 99 80	04	(*S*)-2,5-Dihydro-pyrrole-1,2-dicarboxylic acid 1-*tert*-butyl ester 2-methyl ester (CAS RN 74844-93-2) with a purity by weight of 97 % or more	0 %	-	31.12.2028
0.8156	*ex 2933 99 80	07	4-(2-Oxo-2,3-dihydro-1H-benzimidazol-1-yl)butanoic acid (CAS RN 3273-68-5) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.8180	*ex 2933 99 80	08	Prothioconazole (ISO) (CAS RN 178928-70-6) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.8324	ex 2933 99 80	10	(*R*)-2-(2,5-difluorophenyl)pyrrolidine hydrochloride (CAS RN 1218935-60-4) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.5243	*ex 2933 99 80	13	5-Difluoromethoxy-2-mercapto-1-H-benzimidazole (CAS RN 97963-62-7)	0 %	-	31.12.2031
0.6872	ex 2933 99 80	16	Pyridate (ISO)(CAS RN 55512-33-9) with a purity by weight of 90 % or more	0 %	-	31.12.2030
0.8290	*ex 2933 99 80	18	2-(2-Ethoxyphenyl)-5-methyl-7-propylimidazolo[5,1-f][1,2,4]-triazin-4(3H)-one (CAS RN 224789-21-3) with a purity by weight of 95 % or more	0 %	-	31.12.2031
0.6829	ex 2933 99 80	21	1-(Bis(dimethylamino)methylene)-1*H*-[1,2,3]triazolo[4,5-b]pyridinium 3-oxide hexafluorophosphate(V) (CAS RN 148893-10-1)	0 %	-	31.12.2030
0.5625	ex 2933 99 80	24	1,3-Dihydro-5,6-diamino-2*H*-benzimidazol-2-one (CAS RN 55621-49-3)	0 %	-	31.12.2027
0.8089	ex 2933 99 80	25	6-(4-Benzylamino-3-nitrophenyl)-5-methyl-4,5-dihydro-2H-pyridazin-3-one (CAS RN 77469-62-6) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.8418	ex 2933 99 80	26	Benzotriazole-1-yl-oxy-tris-pyrrolidino-phosphonium hexafluorophosphate (CAS RN 128625-52-5) with a purity by weight of 97 % or more	0 %	-	31.12.2027
0.6409	ex 2933 99 80	27	5,6-Dimethylbenzimidazole (CAS RN 582-60-5)	0 %	-	31.12.2029
0.8357	ex 2933 99 80	28	7-(2-Methyl-4-nitrophenoxy)-[1,2,4]triazolo[1,5-a]pyridine (CAS RN 937263-44-0) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8804	ex 2933 99 80	29	1,1-Dimethylethyl (4*S*)-3-amino-2-(4-fluoro-3,5-dimethylphenyl)-2,4,6,7-tetrahydro-4-methyl-5*H*-pyrazolo[4,3-c]pyridine-5-carboxylate (CAS RN 2212021-59-3) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.3593	ex 2933 99 80	30	Quizalofop-P-ethyl (ISO) (CAS RN 100646-51-3)	0 %	-	31.12.2029
0.8805	ex 2933 99 80	31	2-(2*H*-Benzotriazol-2-yl)-6-(2-phenylpropan-2-yl)-4-(2,4,4-trimethylpentan-2-yl)phenol (CAS RN 73936-91-1) with a purity by weight of 97 % or more	0 %	-	31.12.2029
0.8284	*ex 2933 99 80	32	1H-1,2,3-Triazole (CAS RN 288-36-8) or 2H-1,2,3-triazole (CAS RN 288-35-7) with a purity by weight of 99 % or more	0 %	-	31.12.2031
0.6249	ex 2933 99 80	33	Penconazole (ISO) (CAS RN 66246-88-6)	0 %	-	31.12.2029
0.7043	*ex 2933 99 80	34	2,4-Dihydro-5-methoxy-4-methyl-3*H*-1,2,4-triazol-3-on (CAS RN 135302-13-5)	0 %	-	31.12.2031

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8643	ex 2933 99 80	35	2-[6-Methyl-2-(4-methylphenyl)imidazo[1,2-a]pyridin-3-yl]acetic acid (CAS RN 189005-44-5) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.4695	ex 2933 99 80	37	8-Chloro-5,10-dihydro-11*H*-dibenzo [*b*,*e*] [1,4]diazepin-11-one (CAS RN 50892-62-1)	0 %	-	31.12.2029
0.9102	*ex 2933 99 80	39	Monomethyl auristatin E (CAS RN 474645-27-7) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.3591	ex 2933 99 80	40	*trans*-4-Hydroxy-L-proline (CAS RN 51-35-4)	0 %	-	31.12.2029
0.7273	ex 2933 99 80	41	5-[4'-(Bromomethyl)biphenyl-2-yl]-1-trityl-1H-tetrazole (CAS RN 124750-51-2)	0 %	-	31.12.2027
0.8455	ex 2933 99 80	43	4-([1,2,4]Triazolo[1,5-a]pyridin-7-yloxy)-3-methylaniline (CAS RN 937263-71-3) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8914	ex 2933 99 80	44	(2R,3R)-2-(2,4-Difluorophenyl)-1-(1H-1,2,4-triazol-1-yl)butane-2,3-diol methanesulfonate (CAS RN 1175536-50-1) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.7269	ex 2933 99 80	46	(S)-Indoline-2-carboxylic acid (CAS RN 79815-20-6)	0 %	-	31.12.2027
0.7410	ex 2933 99 80	48	5-Amino-6-methyl-2-benzimidazolone (CAS RN 67014-36-2)	0 %	-	31.12.2027
0.8713	ex 2933 99 80	49	*Tert*-butyl (2*S*)-2-carbamoylpyrrolidine-1-carboxylate (CAS RN 35150-07-3) with a purity by weight of 97 % or more	0 %	-	31.12.2029
0.8722	ex 2933 99 80	50	*Tert*-butyl (3*R*)-3-aminopyrrolidine-1-carboxylate (CAS RN 147081-49-0) with a purity by weight of 97 % or more	0 %	-	31.12.2029
0.8702	ex 2933 99 80	51	(1*R*,5*R*)-Ethyl 3-benzyl-3-azabicyclo[3.1.0]hexane-1-carboxylate hydrochloride (CAS RN 2914217-81-3) with a purity by weight of 97 % or more	0 %	-	31.12.2029
0.8703	ex 2933 99 80	52	(*S*)-2-Methylpyrrolidine-2-carboxylic acid hydrochloride (CAS RN 1508261-86-6) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.4585	ex 2933 99 80	55	Pyridaben (ISO) (CAS RN 96489-71-3)	0 %	-	31.12.2029
0.7457	ex 2933 99 80	56	Methyl 3,5-diamino-6-chloropyrazine-2-carboxylate (CAS RN 1458-01-1) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.5901	ex 2933 99 80	57	2-(5-Methoxyindol-3-yl)ethylamine (CAS RN 608-07-1)	0 %	-	31.12.2029
0.7927	ex 2933 99 80	60	2-[(6,11-Dihydro-5H-dibenz[b,e]azepin-6-yl)-methyl]-1H-isoindole-1,3(2H)-dione (CAS RN 143878-20-0) with a purity by weight of 99 % or more	0 %	-	31.12.2030
0.7624	ex 2933 99 80	61	(1R,5S)-8-Benzyl-8-azabicyclo(3.2.1)octan-3-one hydrochloride (CAS RN 83393-23-1)	0 %	-	31.12.2029
0.8809	ex 2933 99 80	62	6-O-*tert*-butyl 4a-O-methyl (4a)-1-(4-fluorophenyl)-4,5,7,8-tetrahydropyrazolo[3,4-g]isoquinoline-4a,6-dicarboxylate (CAS RN 864972-21-4) with a purity by weight of 95 % or more	0 %	-	31.12.2029
0.7680	ex 2933 99 80	63	L-Prolinamide (CAS RN 7531-52-4)	0 %	-	31.12.2029
0.8359	ex 2933 99 80	64	(1*R*,2*S*,5*S*)-3-[(*S*)-3,3-dimethyl-2-(2,2,2-trifluoroacetamido)butanoyl]-6,6-dimethyl-3-azabicyclo[3.1.0]hexane-2-carboxylic acid (CAS RN 2755812-45-2) with a purity by weight of 95 % or more	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.2732	ex 2933 99 80	65	2-(2H-Benzotriazol-2-yl)-4,6-bis(1-methyl-1-phenylethyl)phenol (CAS RN 70321-86-7) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.7679	ex 2933 99 80	68	5-((1S,2S)-2-((2R,6S,9S,11R,12R,14aS,15S,16S,20R,23S,25aR)-9-Amino-20-((R)-3-amino-1-hydroxy-3-oxopropyl)-2,11,12,15-tetrahydroxy-6-((R)-1-hydroxyethyl)-16-methyl-5,8,14,19,22,25-hexaoxotetracosahydro-1H-dipyrrolo[2,1-c:2',1'-l][1,4,7,10,13,16]hexaazacyclohenicosin-23-yl)-1,2-dihydroxyethyl)-2-hydroxyphenyl hydrogen sulphate (CAS RN 168110-44-9)	0 %	-	31.12.2029
0.7971	ex 2933 99 80	70	5-(Bis-(2-hydroxyethyl)-amino)-1-methyl-1H-benzimidazole-2-butanoic acid ethyl ester (CAS RN 3543-74-6) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.4384	ex 2933 99 80	71	10-Methoxyiminostilbene (CAS RN 4698-11-7)	0 %	-	31.12.2029
0.4503	ex 2933 99 80	72	1,4,7-Trimethyl-1,4,7-triazacyclononane (CAS RN 96556-05-7)	0 %	-	31.12.2029
0.8817	ex 2933 99 80	74	N,N-Dimethyl-*N*-octadecyl-1-octadecanaminium (SP-4-2)-[29*H*,31*H*-phthalocyanine-2-sulfonato-*N*29,*N*30,*N*31,N32]cuprate (CAS RN 70750-63-9) with a purity by weight of 90 % or more	0 %	-	31.12.2029
0.7759	ex 2933 99 80	75	1-[Bis(dimethylamino)methylene]-1H-benzotriazolium hexafluorophosphate(1-) 3-oxide (CAS RN 94790-37-1)	0 %	-	31.12.2029
0.8054	*ex 2933 99 80	76	2-Methylindoline (CAS RN 6872-06-6) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.4382	ex 2933 99 80	78	3-Amino-3-azabicyclo (3.3.0) octane hydrochloride (CAS RN 58108-05-7)	0 %	-	31.12.2029
0.4164	*ex 2933 99 80	81	1,2,3-Benzotriazole (CAS RN 95-14-7)	0 %	-	31.12.2031
0.4165	ex 2933 99 80	82	Tolytriazole (CAS RN 29385-43-1)	0 %	-	31.12.2029
0.9009	ex 2933 99 80	83	1-(3-Chloropropyl)-1,3-dihydro-2*H*-benzimidazol-2-one (CAS RN 62780-89-6) with a purity by weight of 97 % or more	0 %	-	31.12.2030
0.8994	ex 2933 99 80	84	Allyl (2S,4S)-4-benzoylsulfanyl-2-(dimethylcarbamoyl)pyrrolidine-1-carboxylate (CAS RN 141818-73-7) with a purity by weight of 96 % or more	0 %	-	31.12.2030
0.6933	ex 2933 99 80	87	Carfentrazone-ethyl (ISOM) (CAS RN 128639-02-1) with a purity by weight of 90 % or more	0 %	-	31.12.2030
0.9187	*ex 2933 99 80	88	Methyl 3,4-bis(chloromethyl)-2,5-dihydro-1*H*-pyrrole-1-carboxylate (CAS RN 3039559-83-3) with a purity by weight of 90 % or more	0 %	-	31.12.2031
0.3579	ex 2934 10 00	10	Hexythiazox (ISO) (CAS RN 78587-05-0)	0 %	-	31.12.2029
0.2725	ex 2934 10 00	20	2-(4-Methylthiazol-5-yl)ethanol (CAS RN 137-00-8)	0 %	-	31.12.2029
0.5538	ex 2934 10 00	35	(2-Isopropylthiazol-4-yl)-*N*-methylmethanamine dihydrochloride (CAS RN 1185167-55-8)	0 %	-	31.12.2027
0.6264	ex 2934 10 00	45	2-Cyanimino-1,3-thiazolidine (CAS RN 26364-65-8)	0 %	-	31.12.2029
0.4750	ex 2934 10 00	60	Fosthiazate (ISO) (CAS RN 98886-44-3)	0 %	-	31.12.2029
0.7312	ex 2934 20 80	15	Benthiavalicarb-isopropyl (ISO) (CAS RN 177406-68-7)	0 %	-	31.12.2027
0.4346	ex 2934 20 80	25	1,2-Benzisothiazol-3(2H)-one (CAS RN 2634-33-5) in the form of a powder with a purity by weight of 95 % or more, or in an aqueous mixture containing by weight 20 % or more of 1,2-benzisothiazol-3(2H)-one	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8712	ex 2934 20 80	35	3-Methyl-1,2-benzothiazole-1,1-dioxide (CAS RN 34989-82-7) with a purity by weight of 95 % or more	0 %	-	31.12.2029
0.4910	ex 2934 20 80	70	*N*,*N*-Bis(1,3-benzothiazol-2-ylsulphanyl)-2-methylpropan-2-amine (CAS RN 3741-80-8)	0 %	-	31.12.2030
0.5537	ex 2934 30 90	10	2-Methylthiophenothiazine (CAS RN 7643-08-5)	0 %	-	31.12.2027
0.8571	ex 2934 99 90	04	Silthiofam (ISO) (CAS RN 175217-20-6) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.8551	ex 2934 99 90	05	(*S*)-2-Methyl-1-(6-nitropyridin-3-yl)-4-(oxetan-3-yl)piperazine (CAS RN 1895867-67-0) with a purity by weight of 97 % or more	0 %	-	31.12.2028
0.8560	ex 2934 99 90	06	*Cis*-[2-(2,4-Dichlorodiphenyl)-2-(1*H*-imidazol-1-ylmethyl)-1,3-dioxolan-4yl]methyl-4-methylbenzenesulfonate (CAS RN 134071-44-6) with a purity by weight of 99 % or more	0 %	-	31.12.2028
0.8487	ex 2934 99 90	07	Cedazuridine (INN) (CAS RN 1141397-80-9) with a purity by weight of 99 % or more	0 %	-	31.12.2027
0.8472	ex 2934 99 90	08	*(R)-tert*-butyl 2-(6-(5-chloro-2-((tetrahydro-2H-pyran-4-yl)amino)pyrimidin-4-yl)-1-oxoisoindolin-2-yl)propanoate (CAS RN 2095665-45-3) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8449	ex 2934 99 90	09	3-[2-{(2*R*,3*S*)-3-[(1*R*)-1-{[*tert*-butyl(dimethyl)silyl]oxy}ethyl]-4-oxoazetidin-2-yl}propanoyl]-4,4-dimethyl-1,3-oxazolidin-2-one (isomeric mixture of CAS RNs 114341-89-8 and 114418-63-2) with a purity by weight of 99 % or more	0 %	-	31.12.2027
0.6492	ex 2934 99 90	10	Fluralaner (INN) (CAS RN 864731-61-3)	0 %	-	31.12.2029
0.8388	ex 2934 99 90	11	Aqueous solution of d(P-thio)(T-G-A-C-T-G-T-G-A-A-C-G-T-T-C-G-A-G-A-T-G-A) deoxyribonucleic acid (CAS RN 937402-51-2), containing by weight 15 % or more, but not more than 25 % of oligodeoxynucleotide	0 %	-	31.12.2027
0.5924	ex 2934 99 90	12	Dimethomorph (ISO) (CAS RN 110488-70-5)	0 %	-	31.12.2029
0.8348	ex 2934 99 90	13	(6*S*)-6-methyl-5,6-Dihydro-4H-thieno[2,3-b]thiopyran4-one-7,7-dioxide (CAS RN 148719-91-9) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8326	ex 2934 99 90	14	2-Mercaptoadenosine (CAS RN 43157-50-2) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.7843	ex 2934 99 90	17	(S)-4-(Tert-butoxycarbonyl)-1,4-oxazepane-2-carboxylic acid (CAS RN 1273567-44-4) with a purity by weight of 95 % or more	0 %	-	31.12.2029
0.8250	*ex 2934 99 90	18	Methyl (1R,3R)-1-(1,3-benzodioxol-5-yl)-2-(2-chloroacetyl)-1,3,4,9-tetrahydropyrido[5,4-b]indole-3-carboxylate (CAS RN 171489-59-1) with a purity by weight of 99 % or more	0 %	-	31.12.2031
0.8720	ex 2934 99 90	19	(4*R*,6*S*)-6-Methyl-7,7-dioxo-5,6-dihydro-4*H*-thieno[2,3-b]thiopyran-4-ol (CAS RN 147128-77-6) with a purity by weight of 94 % or more	0 %	-	31.12.2029
0.4715	ex 2934 99 90	20	Thiophene (CAS RN 110-02-1)	0 %	-	31.12.2029
0.8253	*ex 2934 99 90	22	4-(Oxiran-2-ylmethoxy)-9H-carbazole (CAS RN 51997-51-4) with a purity by weight of 97 % or more	0 %	-	31.12.2031
0.6252	ex 2934 99 90	26	4-Methylmorpholine 4-oxide in an aqueous solution (CAS RN 7529-22-8)	0 %	-	31.12.2029
0.6362	ex 2934 99 90	27	2-(4-Hydroxyphenyl)-1-benzothiophene-6-ol (CAS RN 63676-22-2)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.5242	*ex 2934 99 90	28	11-(Piperazin-1-yl)dibenzo[b,f][1,4]thiazepine dihydrochloride (CAS RN 111974-74-4)	0 %	-	31.12.2031
0.4700	ex 2934 99 90	30	Dibenzo[b,f][1,4]thiazepin-11(10H)-one (CAS RN 3159-07-7)	0 %	-	31.12.2029
0.8724	ex 2934 99 90	31	Thenoic acid (CAS RN 1918-77-0) with a purity by weight of 97 % or more	0 %	-	31.12.2029
0.8996	ex 2934 99 90	32	(6R,7R)-Benzhydryl 3-hydroxy-8-oxo-7-(2-phenylacetamido)-5-thia-1-azabicyclo[4.2.0]oct-2-ene-2-carboxylate (CAS RN 54639-48-4) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.9005	ex 2934 99 90	34	Benzyl 4-(oxetan-3-yl)piperazine-1-carboxylate (CAS RN 1254115-22-4) with a purity by weight of 99 % or more	0 %	-	31.12.2030
0.9007	ex 2934 99 90	36	Nadide phosphate (INNM) disodium salt (CAS RN 24292-60-2) with a purity by weight of 97 % or more	0 %	-	31.12.2030
0.5813	ex 2934 99 90	37	4-Propan-2-ylmorpholine (CAS RN 1004-14-4)	0 %	-	31.12.2027
0.8642	ex 2934 99 90	38	2-Chloro-9*H*-thioxanthen-9-one (CAS RN 86-39-5) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.6824	ex 2934 99 90	39	4-(Oxiran-2-ylmethoxy)-9*H*-carbazole (CAS RN 51997-51-4)	0 %	-	31.12.2030
0.6823	ex 2934 99 90	41	11-[4-(2-Chloro-ethyl)-1-piperazinyl]dibenzo(b,f)(1,4)thiazepine (CAS RN 352232-17-8)	0 %	-	31.12.2030
0.9093	*ex 2934 99 90	44	1,3,5,7-Tetramethyl-6-phenyl-2,4,8-trioxa-6-phosphaadamantane (CAS RN 97739-46-3) with a purity by weight of 98 % or more	0 %	-	31.12.3031
0.8380	ex 2934 99 90	45	4-[4-[(5s)-5-(Aminomethyl)-2-oxo-3-oxazolidinyl] phenyl]-3-morpholinone, hydrochloride (CAS RN 898543-06-1) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8993	ex 2934 99 90	46	(6R-trans)-7-Amino-8-oxo-3-[[(1,2,5,6-tetrahydro-2-methyl-5,6-dioxo-1,2,4-triazin-3-yl)thio]methyl]-5-thia-1-azabicyclo[4.2.0]oct-2-ene-2-carboxylic acid (CAS RN 58909-56-1) with a purity by weight of 97 % or more	0 %	-	31.12.2030
0.4942	ex 2934 99 90	47	2,4-Diethyl-9*H*-thioxanthen-9-one (CAS RN 82799-44-8) with a purity by weight of 97 % or more	0 %	-	31.12.2030
0.5453	*ex 2934 99 90	48	Olanzapine (INN) hydrate 2-propanol solvate (2:2:1) (CAS RN 864743-41-9) with a purity by weight of 97 % or more	0 %	-	31.12.2031
0.7188	*ex 2934 99 90	49	Cytidine 5'-(disodium phosphate) (CAS RN 6757-06-8)	0 %	-	31.12.2031
0.8601	ex 2934 99 90	50	Vutrisiran (INN) (CAS RN 1867157-35-4) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.8330	ex 2934 99 90	51	Uridine 5'-triphosphate trisodium salt (CAS RN 19817-92-6) with a dry weight purity of 90 % or more	0 %	-	31.12.2027
0.9109	*ex 2934 99 90	53	(6*R-trans*)-7-Amino-3-(hydroxymethyl)-8-oxo-5-thia-1-azabicyclo[4.2.0]oct-2-ene-2-carboxylic acid (CAS RN 15690-38-7) with a purity by weight of 97 % or more	0 %	-	31.12.2031
0.9113	*ex 2934 99 90	54	(3*S*)-5-Fluoro-1,3-dihydro-1-hydroxy-3-methyl-2,1-benzoxaborole (CAS RN 2921961-53-5) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.8031	ex 2934 99 90	55	Uridine (CAS RN 58-96-8) with a purity by weight of 98 % or more	0 %	-	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7297	ex 2934 99 90	56	1-[5-(2,6-Difluorophenyl)-4,5-dihydro-1,2-oxazol-3-yl]ethanone (CAS RN 1173693-36-1)	0 %	-	31.12.2027
0.3575	ex 2934 99 90	57	Dimethenamide-P (ISO) (CAS RN 163515-14-8) with a purity by weight of 93 % or more	0 %	-	31.12.2029
0.7387	ex 2934 99 90	59	Dolutegravir (INN) (CAS RN 1051375-16-6) or dolutegravir sodium (CAS RN 1051375-19-9)	0 %	-	31.12.2027
0.2718	ex 2934 99 90	60	DL-Homocysteine thiolactone hydrochloride (CAS RN 6038-19-3)	0 %	-	31.12.2029
0.7459	ex 2934 99 90	61	5-(1,2-Dithiolan-3-yl)valeric acid (CAS RN 1077-28-7)	0 %	-	31.12.2029
0.7537	ex 2934 99 90	63	(2b,3a,5a,16b,17b)-2-(Morpholin-4-yl)-16-(pyrrolidin-1-yl)androstane-3,17-diol (CAS RN 119302-20-4)	0 %	-	31.12.2029
0.7449	ex 2934 99 90	64	2-Bromo-5-benzoylthiophene (CAS RN 31161-46-3)	0 %	-	31.12.2029
0.7926	*ex 2934 99 90	65	Benzo[b]thiophen-10-methoxycycloheptanone (CAS RN 59743-84-9) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.4512	ex 2934 99 90	66	Tetrahydrothiophene-1,1-dioxide (CAS RN 126-33-0)	0 %	-	31.12.2029
0.7842	ex 2934 99 90	69	3-Methyl-5-(4,4,5,5-tetramethyl-1,3,2-dioxaborolan-2-yl)benzo[d]oxazol-2(3H)-one (CAS RN 1220696-32-1) with a purity by weight of 95 % or more	0 %	-	31.12.2029
0.7944	ex 2934 99 90	70	1,3,4-Thiadiazolidine-2,5-dithione (CAS RN 1072-71-5) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.8289	*ex 2934 99 90	71	3,4-Dichloro-1,2,5-thiadiazole (CAS RN 5728-20-1) with a purity by weight of 99 % or more	0 %	-	31.12.2031
0.8317	ex 2934 99 90	72	2-Trifluoromethyl-9-allyl-9-thioxanthen-ol (CAS RN 850808-70-7) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.4249	ex 2934 99 90	74	2-Isopropylthioxanthone (CAS RN 5495-84-1)	0 %	-	31.12.2027
0.4052	*ex 2934 99 90	75	(4*R*-*cis*)-1,1-Dimethylethyl-6-[2[2-(4-fluorophenyl)-5-(1-isopropyl)-3-phenyl-4-[(phenylamino)carbonyl]-1*H*-pyrrol-1-yl]ethyl]-2,2-dimethyl-1,3-dioxane-4-acetate (CAS RN 125971-95-1)	0 %	-	31.12.2031
0.8933	ex 2934 99 90	76	Nedosiran sodium (INNM) (CAS RN 2247026-22-6) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.8221	*ex 2934 99 90	77	Tazemetostat (INN) (CAS 1403254-99-8) with a purity by weight of 99 % or more and its salts	0 %	-	31.12.2031
0.8930	ex 2934 99 90	78	Disodium uridine-5'-monophosphate (CAS RN 3387-36-8) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.8048	ex 2934 99 90	81	1-(4-Aminophenyl)-5-(morpholin-4-yl)-2,3-dihydropyridin-6-one (CAS RN 1267610-26-3) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.7815	ex 2934 99 90	82	Rel-(3a*R*,12b*R*)-11-Chloro-2,3,3a,12b-tetrahydro-2-methyl-1H-dibenz[2,3:6,7]oxepino[4,5-*c*]pyrrol-1-one (CAS RN 129385-59-7) with a purity by weight of 97 % or more	0 %	-	31.12.2029
0.4643	ex 2934 99 90	83	Flumioxazin (ISO) (CAS RN 103361-09-7) of a purity by weight of 96 % or more	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.9116	*ex 2934 99 90	84	3-[[(2-Hydroxyacetyl)amino]methyl]-L-phenylalanyl-1-[6-[[[4-(2-aminoethyl)phenyl]methyl]amino]hexyl]-5-fluoro-L-tryptophyl-(3S)-3-hydroxy-L-prolyl-L-threonyl-O-methyl-L-tyrosyl-2-methyl-L-proline, (6→2)-lactam, cyclic (1→3)-ether, hydrochloride (1:2) (CAS RN 3109123-85-2) with a purity by weight of 90 % or more	0 %	-	31.12.2031
0.5133	ex 2934 99 90	86	Dithianon (ISO) (CAS RN 3347-22-6)	0 %	-	31.12.2030
0.5136	ex 2934 99 90	87	2,2'-(1,4-Phenylene)bis(4H-3,1-benzoxazin-4-one) (CAS RN 18600-59-4)	0 %	-	31.12.2030
0.7738	ex 2934 99 90	88	(7S,9aS)-7-((Benzyloxy)methyl)octahydropyrazino[2,1-c][1,4]oxazine dioxalate (CAS RN 1268364-46-0)	0 %	-	31.12.2029
0.8905	ex 2934 99 90	89	6R-[6α,7β(Z)]]-7-[2-Furyl(methoxyimino)acetamido]-3-(hydroxymethyl)-8-oxo-5-thia-1-azabicyclo[4.2.0]oct-2-ene-2-carboxylic acid (CAS RN 56271-94-4) with a purity by weight of 96 % or more	0 %	-	31.12.2030
0.6486	ex 2935 90 90	10	Florasulam (ISO) (CAS RN 145701-23-1)	0 %	-	31.12.2029
0.8479	ex 2935 90 90	16	2-Bromo-*N*-(4,5-dimethyl-1,2-oxazol-3-yl)-*N*-(methoxymethyl) benzene-1-sulfonamide (CAS RN 415697-57-3) with a purity by weight of 97 % or more	0 %	-	31.12.2027
0.3565	ex 2935 90 90	20	Toluenesulphonamides	0 %	-	31.12.2029
0.8224	*ex 2935 90 90	21	Encorafenib (INN) (CAS 1269440-17-6) with a purity by weight of 99 % or more	0 %	-	31.12.2027
0.8276	*ex 2935 90 90	22	Methyl 2-(chlorosulfonyl)-4-(methylsulfonamidomethyl)benzoate (CAS RN 393509-79-0) with a purity by weight of 90 % or more	0 %	-	31.12.2031
0.5239	*ex 2935 90 90	23	*N*-[4-(2-Chloroacetyl)phenyl]methanesulphonamide (CAS RN 64488-52-4)	0 %	-	31.12.2031
0.8277	*ex 2935 90 90	24	3-({[(4-methylphenyl)sulfonyl]carbamoyl}amino)phenyl 4-methylbenzenesulfonate (CAS RN 232938-43-1) with a purity by weight of 99 % or more	0 %	-	31.12.2031
0.8467	ex 2935 90 90	26	5-(2-Fluorophenyl)-1-(pyridin-3-ylsulfonyl)-1*H*-pyrrole-3-carbaldehyde (CAS RN 881677-11-8) with a purity by weight of 97 % or more	0 %	-	31.12.2027
0.8350	ex 2935 90 90	29	Vemurafenib (INN) (CAS RN 918504-65-1) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8413	ex 2935 90 90	31	5-(*N*-3-methylphenyl-sulfonylamido)-(*N*',*N*''-bis-(3-methylphenyl)-isophthalicacid-diamide) (CAS RN 2375645-78-4) with a purity by weight of 95 % or more	0 %	-	31.12.2027
0.8693	ex 2935 90 90	32	4-Chloro-3-nitro-5-sulphamoylbenzoic acid (CAS RN 22892-96-2) with a purity by weight of 96 % or more	0 %	-	31.12.2029
0.7677	ex 2935 90 90	33	4-Chloro-3-pyridinesulphonamide (CAS RN 33263-43-3)	0 %	-	31.12.2029
0.9186	*ex 2935 90 90	34	2,3-Dihydro-[1,4]dioxino[2,3-b]pyridine-7-sulfonamide (CAS RN 3028146-26-8) with a purity by weight of 98 % or more	0 %	-	31.12.2031
0.7572	ex 2935 90 90	37	1,3-Dimethyl-1H-pyrazole-4-sulfonamide (CAS RN 88398-53-2)	0 %	-	31.12.2029
0.7438	ex 2935 90 90	40	Venetoclax (INN) (CAS 1257044-40-8)	0 %	-	31.12.2027
0.8606	ex 2935 90 90	41	Lenacapavir sodium (INNM) (CAS RN 2283356-12-5) with a purity by weight of 98 % or more	0 %	-	31.12.2028

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.5036	ex 2935 90 90	42	Penoxsulam (ISO) (CAS RN 219714-96-2)	0 %	-	31.12.2030
0.7928	ex 2935 90 90	44	4-[2-(7-Methoxy-4,4-dimethyl-1,3-dioxo-3,4-dihydroisoquinolin-2(1H)-yl)ethyl]bezenesulphonamide (CAS RN 33456-68-7) with a purity by weight of 99,5 % or more	0 %	-	31.12.2030
0.3562	ex 2935 90 90	45	Rimsulfuron (ISO) (CAS RN 122931-48-0)	0 %	-	31.12.2029
0.5451	*ex 2935 90 90	48	(3R,5S,6E)-7-[4-(4-Fluorophenyl)-2-[methyl(methylsulfonyl)amino]-6-(propan-2-yl)pyrimidin-5-yl]-3,5-dihydroxyhept-6-enoic acid -- 1-[(R)-(4-chlorophenyl)(phenyl)methyl]piperazine (1:1) (CAS RN 1235588-99-4)	0 %	-	31.12.2031
0.2843	ex 2935 90 90	50	4,4'-Oxydi(benzenesulphonohydrazide) (CAS RN 80-51-3)	0 %	-	31.12.2029
0.4636	ex 2935 90 90	53	2,4-Dichloro-5-sulphamoylbenzoic acid (CAS RN 2736-23-4)	0 %	-	31.12.2029
0.6777	ex 2935 90 90	54	Propoxycarbazone-sodium (ISO) (CAS RN 181274-15-7) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.3560	ex 2935 90 90	55	Thifensulfuron-methyl (ISO) (CAS RN 79277-27-3)	0 %	-	31.12.2029
0.6903	ex 2935 90 90	57	N-{2-[(phenylcarbamoyl)amino]phenyl}benzenesulphonamide (CAS RN 215917-77-4)	0 %	-	31.12.2030
0.6664	ex 2935 90 90	59	Flazasulfuron (ISO) (CAS RN 104040-78-0) with a purity of 94 % by weight or more	0 %	-	31.12.2030
0.4586	ex 2935 90 90	63	Nicosulphuron (ISO), (CAS RN 111991-09-4) of a purity by weight of 91 % or more	0 %	-	31.12.2029
0.3561	ex 2935 90 90	65	Tribenuron-methyl (ISO) (CAS RN 101200-48-0)	0 %	-	31.12.2029
0.7854	ex 2935 90 90	70	(4S)-4-Hydroxy-2-(3-methoxypropyl)-3,4-dihydro-2H-thieno[3,2-e]thiazine-6-sulfonamide-1,1-dioxide (CAS RN 154127-42-1) with a purity by weight of 97 % or more	0 %	-	31.12.2029
0.8055	ex 2935 90 90	80	4-Chloro-3-sulphamoylbenzoic acid (CAS RN 1205-30-7) with a purity by weight of 97 % or more	0 %	-	31.12.2030
0.3704	ex 2935 90 90	88	N-(2-(4-Amino-N-ethyl-m-toluidino)ethyl)methanesulphonamide sesquisulphate monohydrate (CAS RN 25646-71-3)	0 %	-	31.12.2029
0.4048	*ex 2935 90 90	89	3-(3-Bromo-6-fluoro-2-methylindol-1-ylsulphonyl)-*N*,*N*-dimethyl-1,2,4-triazol-1-sulphonamide (CAS RN 348635-87-0)	0 %	-	31.12.2031
0.4944	ex 2938 90 30	10	Ammonium glycyrrhizate (CAS RN 53956-04-0)	0 %	-	31.12.2030
0.3554	ex 2938 90 90	10	Hesperidin (CAS RN 520-26-3)	0 %	-	31.12.2029
0.5927	ex 2938 90 90	20	Ethylvanillin beta-D-glucopyranoside (CAS RN 122397-96-0)	0 %	-	31.12.2029
0.7329	ex 2938 90 90	30	Rebaudioside A (CAS RN 58543-16-1)	0 %	-	31.12.2027
0.7047	*ex 2940 00 00	30	D(+)- Trehalose dihydrate (CAS RN 6138-23-4)	0 %	-	31.12.2031
0.8424	ex 2940 00 00	60	Methyl α-D-mannopyranoside (CAS RN 617-04-9) with a purity by weight of 98 % or more	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8635	ex 2940 00 00	70	Alpha-D-Mannopyranose, 6-acetate 2,3,4-tribenzoate 1-(2,2,2-trichloroethanimidate) (CAS RN 346441-49-4) with a purity by weight of 95 % or more	0 %	-	31.12.2028
0.5233	*ex 2941 20 30	10	Dihydrostreptomycin sulphate (CAS RN 5490-27-7)	0 %	-	31.12.2031
0.6984	*ex 2942 00 00	10	Sodium triacetoxyborohydride (CAS RN 56553-60-7)	0 %	-	31.12.2031
0.8614	ex 2942 00 00	20	Dimethylamine—borane (1:1) (CAS RN 74-94-2) with a purity by weight of 98 % or more	0 %	-	31.12.2028
0.3555	3201 20 00		Wattle extract	0 %	-	31.12.2029
0.7943	ex 3201 90 20	10	*Rhus chinensis* gall (*Galla chinensis*) water-based extract, with a tannin content by weight of 85 % or less	0 %	-	31.12.2030
0.3553	ex 3201 90 90	20	Tanning extracts derived from gambier and myrobalan fruits	0 %	-	31.12.2029
0.6183	ex 3204 11 00	15	Colourant C.I. Disperse Blue 360 (CAS RN 70693-64-0) and preparations based thereon with a colourant C.I. Disperse Blue 360 content of 99 % or more by weight	0 %	-	31.12.2029
0.6277	ex 3204 11 00	25	N-(2-Chloroethyl)-4-[(2,6-dichloro-4-nitrophenyl)azo]-N-ethyl-m-toluidine (CAS RN 63741-10-6)	0 %	-	31.12.2029
0.5264	ex 3204 11 00	50	Colourant C.I. Disperse Blue 72 (CAS RN 81-48-1) and preparations based thereon with a colourant C.I. Disperse Blue 72 content of 95 % or more by weight	0 %	-	31.12.2027
0.6972	*ex 3204 12 00	15	Colourant C.I. Acid Brown 75 (CAS RN 8011-86-7) and preparations based thereon with a colourant C.I. Acid Brown 75 content of 75 % or more by weight	0 %	-	31.12.2031
0.6975	*ex 3204 12 00	17	Colourant C.I. Acid Brown 355 (CAS RN 84989-26-4 or 60181-77-3) and preparations based thereon with a colourant C.I. Acid Brown 355 content of 75 % or more by weight	0 %	-	31.12.2031
0.6976	*ex 3204 12 00	27	Colourant C.I. Acid Brown 425 (CAS RN 75234-41-2 or 119509-49-8) and preparations based thereon with a colourant C.I. Acid Brown 425 content of 75 % or more by weight	0 %	-	31.12.2031
0.6963	*ex 3204 12 00	35	Colourant C.I. Acid Black 234 (CAS RN 157577-99-6) and preparations based thereon with a colourant C.I. Acid Black 234 content of 75 % or more by weight	0 %	-	31.12.2031
0.6964	*ex 3204 12 00	37	Colourant C.I. Acid Black 210 sodium salt (CAS RN 201792-73-6) and preparations based thereon with a colourant C.I. Acid Black 210 sodium salt content of 50 % or more by weight	0 %	-	31.12.2031
0.5925	ex 3204 12 00	40	Liquid dye preparation containing anionic acid dye C.I. Acid Blue 182 (CAS RN 12219-26-0)	0 %	-	31.12.2029
0.6965	*ex 3204 12 00	45	Colourant C.I. Acid Blue 161/193 (CAS RN 12392-64-2) and preparations based thereon with a colourant C.I. Acid Blue 161/193 content of 75 % or more by weight	0 %	-	31.12.2031
0.6971	*ex 3204 12 00	47	Colourant C.I. Acid Brown 58 (CAS RN 70210-34-3 or 12269-87-3) and preparations based thereon with a colourant C.I. Acid Brown 58 content of 75 % or more by weight	0 %	-	31.12.2031

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.6973	*ex 3204 12 00	55	Colourant C.I. Acid Brown 165 (CAS RN 61724-14-9) and preparations based thereon with a colourant C.I. Acid Brown 165 content of 75 % or more by weight	0 %	-	31.12.2027
0.6974	*ex 3204 12 00	57	Colourant C.I. Acid Brown 282 (CAS RN 70236-60-1 or 12219-65-7) and preparations based thereon with a colourant C.I. Acid Brown 282 content of 75 % or more by weight	0 %	-	31.12.2031
0.6535	ex 3204 12 00	60	Colourant C.I. Acid Red 52 (CAS RN 3520-42-1) and preparations based thereon with a colourant C.I. Acid Red 52 content of 97 % or more by weight	0 %	-	31.12.2029
0.6977	*ex 3204 12 00	65	Colourant C.I. Acid Brown 432 (CAS RN 119509-50-1) and preparations based thereon with a colourant C.I. Acid Brown 432 content of 75 % or more by weight	0 %	-	31.12.2031
0.6652	ex 3204 12 00	70	Colourant C.I. Acid blue 25 (CAS RN 6408-78-2) and preparations based thereon with a colourant C.I. Acid blue 25 content of 80 % or more by weight	0 %	-	31.12.2030
0.4065	ex 3204 13 00	10	Colourant C.I. Basic Red 1 (CAS RN 989-38-8) and preparations based thereon with a colourant C.I. Basic Red 1 content of 50 % or more by weight	0 %	-	31.12.2029
0.7394	ex 3204 13 00	15	Colourant C.I. Basic Blue 41 (CAS RN 12270-13-2) and preparations based thereon with a colourant C.I. Basic Blue 41 content of 50 % or more by weight	0 %	-	31.12.2027
0.7396	ex 3204 13 00	35	Colourant C.I. Basic Yellow 28 (CAS RN 54060-92-3) and preparations based thereon with a colourant C.I. Basic Yellow 28 content of 50 % or more by weight	0 %	-	31.12.2027
0.5805	ex 3204 13 00	40	Colourant C.I. Basic Violet 1 (CAS RN 603-47-4 or CAS RN 8004-87-3) and preparations based thereon with a colourant C.I. Basic Violet 1 content of 90 % or more by weight	0 %	-	31.12.2027
0.6475	ex 3204 13 00	60	Colourant C.I Basic Red 1:1 (CAS RN 3068-39-1) and preparations based thereon with a colourant C.I Basic Red 1:1 content of 90 % or more by weight	0 %	-	31.12.2029
0.8888	ex 3204 13 00	85	Mixture containing by weight: — 25 % or more but not more than 40 % of Colourant C.I. Basic Blue 3 (CAS RN 33203-82-6) and — 25 % or more but not more than 40 % of C.I. Basic Blue 159 (CAS RN 105953-73-9)	0 %	-	31.12.2029
0.6569	ex 3204 14 00	10	Colourant C.I. Direct Black 80 (CAS RN 8003-69-8) and preparations based thereon with a colourant C.I. Direct Black 80 content of 90 % or more by weight	0 %	-	31.12.2030
0.6571	ex 3204 14 00	30	C.I. Colourant Direct Red 23 (CAS RN 3441-14-3) and preparations based thereon with a colourant C.I. Direct Red 23 content of 90 % or more by weight	0 %	-	31.12.2029
0.8537	ex 3204 15 00	15	Colourant C.I. Vat Blue 1 (CAS RN 482-89-3) and preparations based thereon with a colourant C.I. Vat Blue 1 content of 94 % or more by weight	0 %	-	31.12.2028
0.6129	ex 3204 15 00	70	Colourant C.I. Vat Red 1 (CAS RN 2379-74-0)	0 %	-	31.12.2029
0.6325	ex 3204 16 00	30	Preparations based on Colourant Reactive Black 5 (CAS RN 17095-24-8) with a content thereof of 60 % or more but not more than 75 % by weight, and including one or more of the following: — Colourant Reactive Yellow 201 (CAS RN 27624-67-5), — 1-Naphthalenesulphonicacid,4-amino-3-[[4-[[2-(sulphooxy)ethyl]sulphonyl]phenyl]azo]-, disodium salt (CAS RN 250688-43-8), or — 3,5-diamino-4-[[4-[[2-(sulphooxy)ethyl]sulphonyl]fenyl]azo]-2-[[2-sulfo-4-[[2-(sulphooxy)ethyl]sulfonyl]phenyl]azobenzoic acid sodium salt (CAS RN 906532-68-1)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7367	ex 3204 16 00	40	Aqueous solution of Colourant C.I. Reactive Red 141 (CAS RN 61931-52-0) — with a colourant C.I. Reactive Red 141 content of 13 % or more by weight, and — containing a preservative	0 %	-	31.12.2027
0.2517	ex 3204 17 00	10	Colourant C.I. Pigment Yellow 81 (CAS RN 22094-93-5) and preparations based thereon with a colourant C.I. Pigment Yellow 81 content of 50 % or more by weight	0 %	-	31.12.2029
0.5433	*ex 3204 17 00	15	Colourant C.I. Pigment Green 7 (CAS RN 1328-53-6) and preparations based thereon with a colourant C.I. Pigment Green 7 content of 40 % or more by weight	0 %	-	31.12.2031
0.7092	*ex 3204 17 00	18	Colourant C.I. Pigment Orange 16 (CAS RN 6505-28-8) and preparations based thereon with a colourant C.I. Pigment Orange 16 content of 90 % or more by weight	0 %	-	31.12.2031
0.6130	ex 3204 17 00	19	Colourant C.I. Pigment Red 48:2 (CAS RN 7023-61-2) and preparations based thereon with a colourant C.I. Pigment Red 48:2 content of 85 % or more by weight	0 %	-	31.12.2029
0.5505	*ex 3204 17 00	20	Colourant C.I. Pigment Blue 15:3 (CAS RN 147-14-8) and preparations based thereon with a colourant C.I. Pigment Blue 15:3 content of 35 % or more by weight	0 %	-	31.12.2031
0.6279	ex 3204 17 00	21	Colourant C.I. Pigment Blue 15:4 (CAS RN 147-14-8) and preparations based thereon with a colourant C.I. Pigment Blue 15:4 content of 35 % or more by weight	0 %	-	31.12.2029
0.5259	*ex 3204 17 00	22	Colourant C.I. Pigment Red 169 (CAS RN 12237-63-7) and preparations based thereon with a colourant C.I. Pigment Red 169 content of 50 % or more by weight	0 %	-	31.12.2031
0.6246	ex 3204 17 00	23	Colourant C.I. Pigment Brown 41 (CAS RN 211502-16-8 or CAS RN 68516-75-6)	0 %	-	31.12.2029
0.6453	ex 3204 17 00	24	Colourant C.I. Pigment Red 57:1 (CAS RN 5281-04-9) and preparations based thereon with a Colourant C.I. Pigment Red 57:1 content of 20 % or more by weight	0 %	-	31.12.2029
0.5427	*ex 3204 17 00	25	Colourant C.I. Pigment Yellow 14 (CAS RN 5468-75-7) and preparations based thereon with a colourant C.I. Pigment Yellow 14 content of 25 % or more by weight	0 %	-	31.12.2031
0.7261	ex 3204 17 00	26	Colourant C.I. Pigment Orange 13 (CAS RN 3520-72-7) and preparations based thereon with a colourant C.I. Pigment Orange 13 content of 80 % or more by weight	0 %	-	31.12.2027
0.8678	ex 3204 17 00	28	Colourant C.I. Pigment Yellow 12 (CAS RN 6358–85-6) and preparations based thereon with a colourant C.I. Pigment Yellow 12 content of 21 % or more by weight	0 %	-	31.12.2028
0.7659	ex 3204 17 00	31	Colourant C.I. Pigment Red 63:1 (CAS RN 6417-83-0) and preparations based thereon with a colourant C.I. Pigment Red 63:1 content of 70 % or more by weight	0 %	-	31.12.2029
0.9056	ex 3204 17 00	32	Colourant C.I. Pigment Violet 23 (CAS RN 215247-95-3) and preparations based thereon with a colourant C.I. Pigment Violet 23 content of 70 % or more by weight	0 %	-	31.12.2030
0.6603	ex 3204 17 00	33	Colourant C.I. Pigment Blue 15:1 (CAS RN 147-14-8) and preparations based thereon with a colourant C.I. Pigment Blue 15:1 content of 35 % or more by weight	0 %	-	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.5426	*ex 3204 17 00	35	Colourant C.I. Pigment Red 202 (CAS RN 3089-17-6) and preparations based thereon with a colourant C.I. Pigment Red 202 content of 70 % or more by weight	0 %	-	31.12.2031
0.7565	ex 3204 17 00	37	Colourant C.I. Pigment Red 81:2 (CAS RN 75627-12-2) and preparations based thereon with a colourant C.I. Pigment Red 81:2 content of 30 % or more by weight	0 %	-	31.12.2029
0.8827	ex 3204 17 00	51	Colourant C.I. Pigment Yellow 174 (CAS RN 78952-72-4) and preparations based thereon with a colourant C.I. Pigment Yellow 174 content of 50 % or more by weight.	0 %	-	31.12.2029
0.8801	ex 3204 17 00	54	Colourant C.I. Pigment Yellow 65 (CAS RN 6528-34-3) and preparations based thereon with a colourant C.I. Pigment Yellow 65 content of 90 % or more by weight	0 %	-	31.12.2029
0.8816	ex 3204 17 00	56	Colourant C.I. Pigment Red 146 (CAS RN 5280-68-2) and preparations based thereon with a colourant C.I. Pigment Red 146 content of 90 % or more by weight	0 %	-	31.12.2029
0.8821	ex 3204 17 00	57	Colourant C.I. Pigment Yellow 13 (CAS RN 5102-83-0) and preparations based thereon with a content of colourant C.I. Pigment Yellow 13 of 50 % or more by weight	0 %	-	31.12.2029
0.8892	ex 3204 17 00	58	Colourant C.I. Pigment Yellow 17 (CAS RN 4531-49-1) and preparations based thereon with a colourant C.I. Pigment Yellow 17 content of 90 % or more by weight	0 %	-	31.12.2029
0.5832	ex 3204 17 00	75	Colourant C.I. Pigment Orange 5 (CAS RN 3468-63-1) and preparations based thereon with a colourant C.I. Pigment Orange 5 content of 80 % or more by weight	0 %	-	31.12.2027
0.5700	ex 3204 17 00	85	Colourant C.I. Pigment Blue 61 (CAS RN 1324-76-1) and preparations based thereon with a colourant C.I. Pigment Blue 61 content of 35 % or more by weight	0 %	-	31.12.2027
0.5680	ex 3204 17 00	88	Colourant C.I. Pigment Violet 3 (CAS RN 1325-82-2 or CAS RN 101357-19-1) and preparations based thereon with a colourant C.I. Pigment Violet 3 content of 90 % or more by weight	0 %	-	31.12.2027
0.6979	*ex 3204 19 00	13	Colourant C.I. Sulphur Black 1 (CAS RN 1326-82-5) and preparations based thereon with a colourant C.I. Sulphur Black 1 content of 75 % or more by weight	0 %	-	31.12.2031
0.9165	*ex 3204 19 00	23	Red colourant preparation, in a form of dry press cake, containing by weight: — 68 % or more of 1-[[4-(phenylazo)phenyl]azo]naphthalen-2-ol methyl derivatives (CAS RN 70879-65-1), — not more than 8 % of Colourant C.I. Solvent Orange 2 (CAS RN 2646-17-5), and — not more than 4 % of Colourant C.I. Solvent Yellow 14 (CAS RN 842-07-9)	0 %	-	31.12.2031
0.8881	*ex 3204 19 00	33	Colourant C.I. Solvent Red 135 (CAS RN 20749-68-2) and preparations based thereon with a colourant C.I. Solvent Red 135 content of 90 % or more by weight	0 %	-	31.12.2029
0.5100	*ex 3204 19 00	73	Colourant C.I. Solvent Blue 104 (CAS RN 116-75-6) and preparations based thereon with a colourant C.I. Solvent Blue 104 content of 97 % or more by weight	0 %	-	31.12.2031
0.8883	ex 3204 19 00	76	Colourant C.I. Solvent Red 52 (CAS RN 81-39-0) and preparations based thereon with a colourant C.I. Solvent Red 52 content of 90 % or more by weight	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.5282	*ex 3204 19 00	77	Colourant C.I. Solvent Yellow 98 (CAS RN 27870-92-4 or CAS RN 12671-74-8) and preparations based thereon with a colourant C.I. Solvent Yellow 98 content of 95 % or more by weight	0 %	-	31.12.2031
0.8880	ex 3204 19 00	78	Colourant C.I. Solvent Yellow 114 (CAS RN 17772-51-9) and preparations based thereon with a colourant C.I. Solvent Yellow 114 content of 90 % or more by weight	0 %	-	31.12.2029
0.4058	*ex 3204 20 00	10	Colourant C.I. Fluorescent Brightener 184 (CAS RN 7128-64-5) and preparations based thereon with a colourant C.I. Fluorescent Brightener 184 content of 20 % or more by weight	0 %	-	31.12.2031
0.5395	*ex 3204 20 00	30	Colourant C.I. Fluorescent Brightener 351 (CAS RN 27344-41-8) and preparations based thereon with a colourant C.I. Fluorescent Brightener 351 content of 90 % or more by weight	0 %	-	31.12.2031
0.6473	ex 3204 90 00	10	Colourant C.I Solvent Yellow 172 (also known as C.I. Solvent Yellow 135) (CAS RN 68427-35-0) and preparations based thereon with a colourant C.I Solvent Yellow 172 (also known as C.I. Solvent Yellow 135) content of 90 % or more by weight	0 %	-	31.12.2029
0.7658	ex 3205 00 00	20	Colourant C.I. Solvent Red 48 (CAS RN 13473-26-2) preparation, in a form of dry powder, containing by weight: — 16 % or more but not more than 25 % of Colourant C.I. Solvent Red 48 (CAS RN 13473-26-2) — 65 % or more but not more than 75 % of aluminium hydroxide (CAS RN 21645-51-2)	0 %	-	31.12.2029
0.7699	ex 3205 00 00	30	Colourant C.I. Pigment Red 174 (CAS RN 15876-58-1) preparation, in a form of dry powder, containing by weight: — 16 % or more but not more than 21 % of Colourant C.I. Pigment Red 174 (CAS RN 15876-58-1) — 65 % or more but not more than 69 % of aluminium hydroxide (CAS RN 21645-51-2)	0 %	-	31.12.2029
0.5378	*ex 3206 19 00	10	Preparation containing by weight: — 72 % (± 2 %) of mica (CAS RN 12001-26-2), and — 28 % (± 2 %) of titanium dioxide (CAS RN 13463-67-7)	0 %	-	31.12.2031
0.8770	ex 3206 20 00	50	Nickel iron chromite black spinel (C.I. pigment black 30) (CAS RN 71631-15-7)	0 %	-	31.12.2029
0.8765	ex 3206 20 00	60	Cobalt chromite green spinel (C.I. pigment green 26) (CAS RN 68187-49-5)	0 %	-	31.12.2029
0.8768	ex 3206 20 00	70	Copper chromite black spinel (C.I. pigment black 28) (CAS RN 68186-91-4)	0 %	-	31.12.2029
0.8874	ex 3206 41 00	10	Colourant C.I. Pigment Blue 29 (CAS RN 57455-37-5) and preparations based thereon with a colourant C.I. Pigment Blue 29 content of 90 % or more by weight	0 %	-	31.12.2029
0.6245	ex 3206 49 70	20	Colourant C.I. Pigment Blue 27 (CAS RN 14038-43-8)	0 %	-	31.12.2029
0.7390	ex 3206 49 70	40	Colourant C.I. Pigment Blue 27 (CAS RN 25869-00-5) and preparations thereon with a colourant C.I. Pigment Blue 27 content of 85 % or more by weight	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8211	*ex 3206 49 70	50	Concentrated mixture of pigments (masterbatch) in the form of pellets containing by weight: — 50 % or more but not more than 70 % of polyamide-6.6 (CAS RN 32131-17-2), — 15 % or more but not more than 20 % of iron powder (CAS RN 7439-89-6), — 5 % or more but not more than 15 % of barium sulphate (CAS RN 7727-43-7), and — 5 % or more but not more than 10 % of blue pigment, consisting of a mixture of Titanium dioxide (CAS RN 13463-67-7) and Copper(II) phtalocyanine(CAS RN 147-14-8)	0 %	-	31.12.2031
0.8800	ex 3206 49 70	60	Colourant C.I. Pigment Yellow 164 (CAS RN 68412-38-4) and preparations based thereon with a colourant C.I. Pigment Yellow 164 content of 90 % or more by weight	0 %	-	31.12.2029
0.3673	3206 50 00		Inorganic products of a kind used as luminophores	0 %	-	31.12.2029
0.8676	ex 3207 30 00	30	Silver paste, containing by weight: — 45 % or more, but not more than 90 % silver (CAS RN 7440-22-4) and — 59 % or more, but not more than 92 % of the total solids (including silver) for use as conductor in the production of solar cells (1)	0 %	-	31.12.2028
0.8630	ex 3207 30 00	40	Aluminium paste, containing by weight: — 72 % or more but not more than 82 % aluminium (CAS RN 7429-90-5) — with a viscosity of 10 or more, but not more than 100 Pa.s (Brookfield RVT, 14 Spindle, 20 rpm, 25°C±0,5°C) — with an aluminium particle size of not more than 25 µm for use in the production of solar cells (1)	0 %	-	31.12.2028
0.2511	ex 3208 20 10	10	Copolymer of *N*-vinylcaprolactam, *N*-vinyl-2-pyrrolidone and dimethylaminoethyl methacrylate, in the form of a solution in ethanol containing by weight 34 % or more but not more than 40 % of copolymer	0 %	-	31.12.2029
0.4511	ex 3208 20 10	20	Immersion topcoat solution containing by weight 0,5 % or more but not more than 15 % of acrylate-methacrylate-alkenesulphonate copolymers with fluorinated side chains, in a solution of n-butanol and/or 4-methyl-2-pentanol and/or diisoamylether	0 %	-	31.12.2029
0.8412	ex 3208 20 10 ex 3905 91 00	50 25	Copolymer of vinylcaprolactam and vinylpyrrolidone (CAS RN 51987-20-3) in the form of a solution in 2-butoxyethanol (CAS RN 111-76-2) containing by weight 45 % or more but not more than 58 % of copolymer	0 %	-	31.12.2027
0.8137	ex 3208 90 19 ex 3911 90 99	13 63	Mixture, containing by weight: — 20 % or more but not more than 40 % of a copolymer of methyl vinyl ether and monobutyl maleate (CAS RN 25119-68-0), — 7 % or more but not more than 20 % of a copolymer of methyl vinyl ether and monoethyl maleate (CAS RN 25087-06-3), — 40 % or more, but not more than 65 % of ethanol (CAS RN 64-17-5), — 1 % or more but not more than 7 % of butan-1-ol (CAS RN 71-36-3)	0 %	-	31.12.2030
0.3967	ex 3208 90 19	15	Chlorinated polyolefins, in a solution	0 %	-	31.12.2029
0.2504	ex 3208 90 19	40	Polymer of methylsiloxane, in the form of a solution in a mixture of acetone, butanol, ethanol and isopropanol, containing by weight 5 % or more but not more than 11 % of polymer of methylsiloxane	0 %	-	31.12.2029
0.6154	ex 3208 90 19 ex 3824 99 92	45 63	Polymer consisting of a polycondensate of formaldehyde and naphthalenediol, chemically modified by reaction with an alkyne halide, dissolved in propylene glycol methyl ether acetate	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.6989	*ex 3208 90 19	47	Solution containing by weight: — 0.1 % or more but not more than 20 % of alkoxygroups containing siloxane polymer with alkyl or aryl substituents — 75 % or more of an organic solvent containing one or more of propyleneglycolethylether (CAS RN 1569-02-4), propylene glycol mono methylether acetate (CAS RN 108-65-6) or propyleneglycol propylether (CAS RN 1569-01-3)	0 %	-	31.12.2031
0.2502	*ex 3208 90 19	50	Solution containing by weight: — (63,5 ±10) % of gamma-butyrolactone (CAS RN 96-48-0), — (30 ± 10) % of aromatic polyhydroxyamide resin, — (3,5 ± 1,5) % of naphthoquinone ester derivative, — (1,5 ± 0,5) % of arylsilicic acid, — (1,5 ± 0,5) % of [3-(trimethoxysilyl)propyl]urea (CAS RN 23843-64-3)	0 %	-	31.12.2031
0.6726	*ex 3208 90 19	55	Preparation of 5 % or more but not more than 20 % by weight of a copolymer of propylene and maleic anhydride, or a blend of polypropylene and a copolymer of propylene and maleic anhydride, or a blend of polypropylene and a copolymer of propylene, isobutene and maleic anhydride in an organic solvent	0 %	-	31.12.2031
0.4037	*ex 3208 90 19	60	Copolymer of hydroxystyrene with one or more of the following: — styrene — alkoxystyrene — alkylacrylates dissolved in ethyl lactate	0 %	-	31.12.2031
0.6005	ex 3208 90 19	65	Silicones containing 50 % by weight or more of xylene and not more than 25 % by weight of silica, of a kind used for the manufacture of long term surgical implants	0 %	-	31.12.2029
0.5777	ex 3215 19 00	20	Ink: — consisting of a polyester polymer and a dispersion of silver (CAS RN 7440-22-4) and silver chloride (CAS RN 7783-90-6) in methyl propyl ketone (CAS RN 107-87-9), — with a total solid content by weight of 55 % or more, but not more than 57 %, and — with a specific density of 1,40 g/cm^3 or more, but not more than 1,60 g/cm^3, for use in the manufacture of electrodes (1)	0 %	l	31.12.2027
0.2501	ex 3215 90 70	20	Heat sensitive ink fixed on a plastic film	0 %	-	31.12.2029
0.4533	ex 3215 90 70	30	Disposable cartridge ink, containing by weight: — 1 % or more, but not more than 10 % of amorphous silicon dioxide or — 3,8 % or more of dye C.I. Solvent Black 7 in organic solvents for use in the marking of integrated circuits (1)	0 %	-	31.12.2029
0.3661	ex 3301 12 10	10	Essential oil of sweet orange (CAS RN 8028-48-6) or essential oil of sour orange (CAS RN 72968-50-4), not deterpenated	0 %	-	31.12.2029
0.4863	*ex 3402 39 90	10	Sodium lauroyl methyl isethionate (CAS RN 156572-81-5)	0 %	-	31.12.2031
0.4002	ex 3402 42 00	10	Vinyl copolymer surface active agent based on polypropylene glycol	0 %	-	31.12.2029
0.4277	ex 3402 42 00	20	Surfactant containing 1,4-dimethyl-1,4-*bis*(2-methylpropyl)-2-butyne-1,4-diyl ether, polymerised with oxirane, methyl terminated	0 %	-	31.12.2027
0.6285	ex 3402 90 10	10	Surface-active mixture of methyltri-C8-C10-alkylammonium chlorides (CAS RN 63393-96-4)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8758	ex 3402 90 10	15	Silicone surfactant consisting of a mixture of: — 60 % or more but not more than 85 % by weight of Polyalkyleneoxidedimethylsiloxane copolymer (CAS RN 68937-55-3), — 15 % or more but not more than 40 % by weight of poly(oxy-1,2-ethanediyl),α-hydro-ω-hydroxy-Ethane-1,2-diol, ethoxylated (CAS RN 25322-68-3), — 0,8 % or more but not more than 1,5 % by weight Octamethylcyclotetrasiloxane (CAS RN 556-67-2), — 0,6 % or more but not more than 1,0 % by weight Decamethylcyclopentasiloxane (CAS RN 541-02-6), — 0,2 % or more but not more than 0,5 % by weight Dodecamethylcyclohexasiloxane(CAS RN 540-97-6)	0 %	-	31.12.2029
0.3660	ex 3402 90 10	80	Mixture, containing by weight: — 80 % or more but not more than 90 % of docusate sodium (INN) (CAS RN 577-11-7), and — 10 % or more but not more than 20 % of sodium benzoate (CAS RN 532-32-1)	0 %	-	31.12.2029
0.4313	ex 3506 91 90	40	Acrylic pressure sensitive adhesive with a thickness of 0,076 mm or more but not more than 0,127 mm, put up in rolls of a width of 45,7 cm or more but not more than 132 cm supplied on a release liner with an initial peel adhesion release value of not less than 15 N/25 mm (measured according to ASTM D3330)	0 %	-	31.12.2029
0.6293	ex 3507 90 90	10	Preparation of *Achromobacter lyticus* protease (CAS RN 123175-82-6) for use in the manufacture of human and analogue insulin products (1)	0 %	-	31.12.2029
0.7050	*ex 3507 90 90	30	Salicylate 1-monooxygenase (CAS RN 9059-28-3) in aqueous solution with — an enzyme concentration of 6,0 U/ml or more, but not more than 7,4 U/ml , — a concentration by weight of sodium azide (CAS RN 26628-22-8) of not more than 0,09 % and — a pH value of 6,5 or more, but not more than 8,5	0 %	-	31.12.2031
0.4922	*ex 3601 00 00	20	Pyrotechnical mixture in cylindrical shape or granulate form, composed of strontium nitrate or copper nitrate or basic copper nitrate in a matrix of nitroguanidine or guanidine nitrate, also containing a binder and additives, used as a component of airbag inflators (1)	0 %	-	31.12.2031
0.7318	ex 3603 50 00	10	Igniters for gas generators with: — an overall maximum length of 15,5 mm or more but not more than 29,4 mm, and — a pin length of 6,4 mm or more but not more than 12,6 mm	0 %	-	31.12.2028
0.9173	*ex 3603 50 00	20	Seatbelt safety igniter mechanism composed of ignitor, cable and connector, with: — an ignitor length of 28 mm or more but not more than 31 mm; — a length of exposed leadwire of not more than 13 mm; — a connecting cables diameter of not more than 4,9 mm; — two-pin connectors	0 %	-	31.12.2031
0.5465	*ex 3801 90 00	10	Expandable graphite (CAS RN 90387-90-9 and CAS RN 12777-87-6)	0 %	-	31.12.2031
0.6759	ex 3802 10 00	10	Mixture of activated carbon and polyethylene, in form of powder	0 %	-	31.12.2030
0.7368	ex 3802 10 00	40	Chemically activated carbon for the absorption and desorption of vapors, in a defined or irregular shape with an effective butane capacity of 5 g butane / 100 ml or more (according to ASTM D 5228) (1)	0 %	-	31.12.2027
0.2987	3805 90 10		Pine oil	1.7 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.2988	ex 3808 91 90	30	Preparation containing endospores or spores and protein crystals derived from either: — *Bacillus thuringiensis Berliner* subsp. *aizawai* and *kurstaki* or, — *Bacillus thuringiensis* subsp. *kurstaki* or, — *Bacillus thuringiensis* subsp. *israelensis* or, — *Bacillus thuringiensis* subsp. *aizawai* or, — *Bacillus thuringiensis* subsp. *tenebrionis*	0 %	-	31.12.2029
0.2983	ex 3808 91 90	40	Spinosad (ISO)	0 %	-	31.12.2029
0.5710	ex 3808 91 90	60	Spinetoram (ISO) (CAS RN 935545-74-7), preparation of two spinosyn components (3'-ethoxy-5,6-dihydro spinosyn J) and (3'-ethoxy- spinosyn L)	0 %	-	31.12.2027
0.4753	ex 3808 93 90	10	Preparation, in the form of granules, containing by weight: — 38,8 % or more but not more than 41,2 % of Gibberellin A3, or — 9,5 % or more but not more than 10,5 % of Gibberellin A4 and A7	0 %	-	31.12.2029
0.8727	ex 3808 93 90	70	Preparation in the form of powder, containing by weight 90 % or more of gibberellin A4 and gibberellin A7 combined (CAS RN 8030-53-3)	0 %	-	31.12.2029
0.6532	ex 3808 94 20	30	Bromochloro-5,5-dimethylimidazolidine-2,4-dione (CAS RN 32718-18-6) containing: — 1,3-Dichloro-5,5-dimethylimidazolidine-2,4-dione (CAS RN 118-52-5), — 1,3-Dibromo-5,5-dimethylimidazolidine-2,4-dione (CAS RN 77-48-5), — 1-Bromo,3-chloro-5,5-dimethylimidazolidine-2,4-dione (CAS RN 16079-88-2), and/or — 1-Chloro,3-bromo-5,5-dimethylimidazolidine-2,4-dione (CAS RN 126-06-7)	0 %	-	31.12.2029
0.8904	ex 3808 99 90	30	Milbemycin oxime (CAS RN 129496-10-2), mixture of methyl analogue and ethyl analogue, with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.8830	ex 3809 91 00	30	Aqueous antimony pentoxide mixture containing by weight: — 46 % or more but not more than 55 % of antimony pentoxide (CAS RN 1314-60-9), and — 1 % or more but not more than 10 % of triethanolamine (CAS RN 102-71-6), or — 1 % or more but not more than 10 % of triethanolamine phosphate (CAS RN 10017-56-8)	0 %	-	31.12.2029
0.9074	ex 3810 10 00	10	Tin or zinc based, halide free, surface mount technology processing solder paste: — with metal contents of 87,5 % or more, but not more than 90,1 % by weight, — with an alloy solidus temperature of 210°C or more, — with a viscosity of 178 Pa·s or more, but not more than 235 Pa·s, — with a particle size of 40 µm or less, — with a silver content either of 3,15 % or more, but not more than 3,5 % by weight for tin based paste or of 0,25 % or more, but not more than 0,28 % by weight for zinc based paste, — with or without bismuth content of 2,55 % or more, but not more than 2,71 % by weight, — with or without copper content of 0,6 % or more, but not more than 0,7 % by weight	0 %	-	31.12.2030
0.4510	ex 3811 19 00	10	Solution of more than 61 % but not more than 63 % by weight of methylcyclopentadienyl manganese tricarbonyl in an aromatic hydrocarbon solvent, containing by weight not more than: — 4,9 % of 1,2,4-trimethyl-benzene, — 4,9 % of naphthalene, and — 0,5 % of 1,3,5-trimethyl-benzene	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7223	ex 3811 21 00	11	Dispersing agent and oxidation inhibitor containing : — o-amino polyisobutylenephenol (CAS RN 78330-13-9), — more than 30 % by weight but not more than 50 % by weight of mineral oils, used in the manufacture of blends of additives for lubricating oils (1)	0 %	-	31.12.2029
0.6904	*ex 3811 21 00	12	Dispersing agent containing : — esters of polyisobutenyl succinic acid and pentaerythritol (CAS RN 103650-95-9), — 35 % or more but not more than 55 % by weight of mineral oils, and — with a chlorine content of not more than 0,05 % by weight, used in the manufacture of blends of additives for lubricating oils (1)	0 %	-	31.12.2027
0.6018	ex 3811 21 00	13	Additives containing : — borated magnesium (C16-C24) alkylbenzene sulphonates and — mineral oils, having a total base number (TBN) of more than 250, but not more than 350, for use in the manufacture of lubricating oils (1)	0 %	-	31.12.2027
0.6906	ex 3811 21 00	14	Dispersing agent : — containing polyisobutene succinimide derived from reaction products of polyethylenepolyamines with polyisobutenyl succinic anhydride (CAS RN 147880-09-9), — containing 35 % or more but not more than 55 % by weight of mineral oils, — with a chlorine content by weight of not more than 0,05 %, — having a total base number of less than 15, used in the manufacture of blends of additives for lubricating oils (1)	0 %	-	31.12.2030
0.6907	ex 3811 21 00	16	Detergent containing : — Calcium salt of beta-aminocarbonyl alkylphenol (reaction product Mannich base of alkylphenol) — 40 % or more but not more than 60 % by weight of mineral oils and — having a total base number more than 120 used in the manufacture of blends of additives for lubricating oils (1)	0 %	-	31.12.2030
0.6430	ex 3811 21 00	19	Additives containing: — a polyisobutylene succinimide based mixture, and — more than 30 % but not more than 50 % by weight of mineral oils, having a total base number of more than 40, for use in the manufacture of lubricating oils (1)	0 %	-	31.12.2029
0.3449	ex 3811 21 00	20	Additives for lubricating oils, based on complex organic molybdenum compounds, in the form of a solution in mineral oil	0 %	-	31.12.2029
0.8583	ex 3811 21 00	21	Additive containing by weight: — 90 % or more but not more than 97 % of reaction products of butyl-cyclohex-3-enecarboxylate and sulphur (CAS RN 160305-95-3), — 3 % or more but not more than 10 % of mineral oil, for use in the manufacture of blends of additives for lubricating oils (1)	0 %	-	31.12.2028
0.8197	*ex 3811 21 00	24	Additive consisting essentially of: — Polyisobutenyl succinic anhydride reaction product with polyethylenepolyamines, borated (CAS RN 134758-95-5), with a chlorine content by weight of 0,05 % or more but not more than 0,25 % and a total base number (TBN) of more than 20, — 45 % and more by weight and no more than 55 % by weight of mineral oil, used in the manufacture of blends of additives for lubricating oils (1)	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.6012	ex 3811 21 00	25	Additives containing: — a (C8-18) alkyl polymethacrylate copolymer with N-[3-(dimethylamino)propyl]methacrylamide, of an average molecular weight (Mw) of more than 10 000 but not more than 20 000, and — more than 15 %, but not more than 30 % by weight of mineral oils, for use in the manufacture of lubricating oils (1)	0 %	-	31.12.2029
0.8198	*ex 3811 21 00	26	Additive consisting essentially of: — Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and isopropyl) esters, zinc salts (CAS RN 84605-29-8), — 7 % or more by weight but not more than 12 % by weight of mineral oil, used in the manufacture of blends of additives for lubricating oils (1)	0 %	-	31.12.2031
0.6022	ex 3811 21 00	27	Additives containing: — 10 % or more by weight of an ethylene-propylene copolymer chemically modified by succinic anhydride groups reacted with 3-nitroaniline, and — mineral oils, for use in the manufacture of lubricating oils (1)	0 %	-	31.12.2029
0.8199	*ex 3811 21 00	28	Additive consisting essentially of: — Zinc bis(O,O-bis(2-ethylhexyl)) bis (dithiophosphate) (CAS RN 4259-15-8); — triphenyl phosphite (CAS RN 101-02-0) more than 0,5 % by weight but not more than 6 % by weight, — O,O,O-triphenyl phosphorothioate (CAS RN 597-82-0) more than 0,5 % by weight but not more than 6 % by weight, and not more than 7,5 % by weight of the combination of triphenylphosphorus compounds — 10 % or more by weight but not more than 20 % by weight of mineral oils, used in the manufacture of blends of additives for lubricating oils (1)	2.6 %	-	31.12.2027
0.5727	ex 3811 21 00	29	Additive containing by weight: — 25 % or more but not more than 40 % of calcium C16-24 alkylbenzenesulphonates (CAS RN 70024-69-0), — 30 % or more but not more than 65 % of mineral oils, for use in the manufacture of blends of additives for lubricating oils (1)	0 %	-	31.12.2027
0.5717	ex 3811 21 00	30	Additives for lubricating oils, containing mineral oils, consisting of calcium salts of reaction products of polyisobutylene substituted phenol with salicylic acid and formaldehyde, used as a concentrated additive for the manufacture of engine oils through a blending process	0 %	-	31.12.2027
0.8201	*ex 3811 21 00	32	Additive consisting essentially of: — Zinc O,O,O',O'-tetrakis (1,3-dimethylbutyl) bis(phosphorodithioate) (CAS RN 2215-35-2), — 4 % or more by weight but not more than 12 % by weight of mineral oil, used in the manufacture of blends of additives for lubricating oils (1)	0 %	-	31.12.2027
0.6013	ex 3811 21 00	33	Additives containing: — calcium salts of heptylphenol reaction products with formaldehyde (CAS RN 84605-23-2), and — mineral oils, having a total base number (TBN) of more than 40 but not more than 100, for use in the manufacture of lubricating oils or overbased detergents for use in lubricating oils (1)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.6905	ex 3811 21 00	34	Detergent containing: — benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts (CAS RN 722503-68-6), — more than 30 % but not more than 60 % by weight of mineral oils, and, — having a total base number of more than 310 but not more than 340, used in the manufacture of blends of additives for lubricating oils (1)	0 %	-	31.12.2030
0.6016	ex 3811 21 00	37	Additives containing: — a styrene-maleic anhydride copolymer esterified with C4-C20 alcohols, modified by aminopropylmorpholine, and — more than 50 % but not more than 75 % by weight of mineral oils, for use in the manufacture of lubricating oils (1)	0 %	-	31.12.2029
0.3448	ex 3811 21 00 ex 3811 90 00	38 60	Solution of mineral oils (CAS RN 64742-52-5, 64742-53-6, 64742-56-9 or blends thereof) containing by weight: — 25 % or more but not more than 55 % of the barium, calcium, magnesium or zinc salt of dinonylnaphthylsulphonic acid (CAS RN 25619-56-1, 28015-99-8, 28016-00-4, or 57855-77-3) — whether or not, not more than 25 % of the barium, calcium, magnesium or zinc salt of a mixture of C3-C24 carboxylic acids (CAS RN 68990-37-4)	0 %	-	31.12.2029
0.6435	ex 3811 21 00	48	Additives containing: — overbased magnesium (C20-C24) alkylbenzenesulphonates (CAS RN 231297-75-9) and — by weight more than 25 % but not more than 50 % of mineral oils, — having a total base number of more than 350, but not more than 450, for use in the manufacture of lubricating oils or for use in the manufacture of blends of additives for lubricating oils (1)	0 %	-	31.12.2029
0.6437	ex 3811 21 00	53	Additives containing: — overbased calcium petroleum sulphonates (CAS RN 68783-96-0) with a sulphonate content by weight of 15 % or more, but not more than 30 % and — by weight more than 40 % but not more than 60 % of mineral oils, having a total base number of 280 or more but not more than 420, for use in the manufacture of lubricating oils (1)	0 %	-	31.12.2029
0.6434	ex 3811 21 00	55	Additives containing: — low base number calcium polypropylbenzenesulphonate (CAS RN 75975-85-8) and — by weight more than 40 % but not more than 60 % of mineral oils, having a total base number of more than 10 but not more than 25, for use in the manufacture of lubricating oils (1)	0 %	-	31.12.2029
0.5724	ex 3811 21 00	60	Additives for lubricating oils, containing mineral oils, — based on calcium polypropylenyl substituted benzenesulphonate (CAS RN 75975-85-8) with a content by weight of 25 % or more but not more than 35 %, — with a total base number (TBN) of 280 or more but not more than 320, used as a concentrated additive for the manufacture of engine oils through a blending process	0 %	-	31.12.2027
0.6431	ex 3811 21 00	63	Additives containing: — an overbased mixture of calcium petroleum sulphonates (CAS RN 61789-86-4) and synthetic calcium alkylbenzenesulphonates (CAS RN 68584-23-6 and CAS RN 70024-69-0) with a total sulphonate content by weight of 15 % or more, but not more than 25 % and — by weight more than 40 % but not more than 60 % of mineral oils, having a total base number of 280 or more but not more than 320, for use in the manufacture of lubricating oils (1)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.6429	ex 3811 21 00	65	Additives containing: — a polyisobutylene succinimide based mixture (CAS RN 160610-76-4), and — more than 35 % but not more than 50 % by weight of mineral oils, having a sulphur content of more than 0,7 % but not more than 1,3 % by weight, having a total base number of more than 8, for use in the manufacture of lubricating oils (1)	0 %	-	31.12.2029
0.5711	ex 3811 21 00	70	Additives for lubricating oils, — containing polyisobutylene succinimide derived from reaction products of polyethylenepolyamines with polyisobutenyl succinic anhydride (CAS RN 84605-20-9), — containing mineral oils, — with a chlorine content by weight of 0,05 % or more but not more than 0,25 %, — with a total base number (TBN) of more than 20, used as a concentrated additive for the manufacture of engine oils through a blending process	0 %	-	31.12.2027
0.6017	ex 3811 21 00	73	Additives containing: — borated succinimide compounds (CAS RN 134758-95-5), — mineral oils, and — having a total base number (TBN) greater than 40, for use in the manufacture of additive mixtures for lubricating oils (1)	0 %	-	31.12.2029
0.6671	ex 3811 21 00	75	Additives containing: — Calcium (C10-C14) dialkylbenzenesulfonates, — more than 40 %, but not more than 60 % by weight of mineral oils, with a total base number of not more than 10, for use in the manufacture of blends of additives for lubricating oils (1)	0 %	-	31.12.2027
0.6669	ex 3811 21 00	77	Antifoam additives consisting of: — a copolymer of 2-ethylhexyl acrylate and ethyl acrylate, and — more than 50 % but not more than 80 % by weight of mineral oils, for use in the manufacture of additive blends for lubricating oils (1)	0 %	-	31.12.2027
0.6666	ex 3811 21 00	80	Additives containing : — polyisobutylene aromatic polyamine succinimide, — more than 40 % but not more than 60 % by weight of mineral oils, with a nitrogen content of more than 0,6 % but not more than 0,9 % by weight, for use in the manufacture of additive blends for lubricating oils (1)	0 %	-	31.12.2027
0.6498	ex 3811 21 00	83	Additives containing: — polyisobutene succinimide derived from reaction of polyethylenepolyamines with polyisobutenyl succinic anhydride (CAS RN 84605-20-9), — more than 31,9 % but not more than 43,3 % by weight of mineral oils, — not more than 0,05 % by weight chlorine, and — having a total base number (TBN) greater than 20, for use in the manufacture of additives blends for lubricating oils (1)	0 %	-	31.12.2029
0.5718	ex 3811 21 00	85	Additives: — containing more than 20 % but not more than 45 % by weight of mineral oils, — based on a mixture of branched dodecylphenol sulfide calcium salts, whether or not carbonated, for use in the manufacture of blends of additives (1)	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.5721	ex 3811 29 00	20	Additives for lubricating oils, consisting of reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with propylene oxide, phosphorus oxide, and amines with C12-14 alkyl chains, used as a concentrated additive for the manufacture of lubricating oils	0 %	-	31.12.2027
0.8655	ex 3811 29 00	23	Additive for lubricating oils consisting of molybdenum, *bis*(dibutylcarbamodithioato)di-μ-oxodioxodi-, sulfurized (CAS RN 68412-26-0)	0 %	-	31.12.2028
0.5723	ex 3811 29 00	30	Additives for lubricating oils, consisting of reaction products of butyl-cyclohex-3-enecarboxylate, sulphur and triphenyl phosphite (CAS RN 93925-37-2), used as a concentrated additive for the manufacture of engine oils through a blending process	0 %	-	31.12.2027
0.5719	ex 3811 29 00	33	Additives for lubricating oils, consisting of a mixture of *N,N*-dialkyl -2-hydroxyacetamides with alkyl chain lengths between 12 and 18 carbon atoms (CAS RN 866259-61-2), used in the manufacture of blends of additives for lubricating oils (1)	0 %	-	31.12.2027
0.6432	ex 3811 29 00	38	Additives consisting of the C12-C14-tert-alkylamine salts of the esters of C14-C18 saturated and C18 unsaturated alcohols with phosphorus pentoxide (CAS RN 1471315-74-8), for use in the manufacture of blends of additives for lubricating oils or greases (1)	0 %	-	31.12.2029
0.5728	ex 3811 29 00	40	Additives for lubricating oils, consisting of reaction products of 2-methyl-prop-1-ene with sulphur monochloride and sodium sulphide (CAS RN 68511-50-2), with a chlorine content by weight of 0,01 % or more but not more than 0,5 %, used as a concentrated additive for the manufacture of lubricating oils	0 %	-	31.12.2027
0.6433	ex 3811 29 00	43	Reaction products of C14-C18 (branched and linear) and C18 (unsaturated) fatty acids with tetraethylenepentamine (linear, branched, cyclic) (CAS RN 68784-17-8), for use in the manufacture of lubricating oils (1)	0 %	-	31.12.2029
0.6436	ex 3811 29 00	45	Additives consisting of a mixture of (C7-C9) dialkyl adipates, in which diisooctyl adipate (CAS RN 1330-86-5) is more than 85 % by weight of the mixture, for use in the manufacture of lubricating oils (1)	0 %	-	31.12.2029
0.6020	ex 3811 29 00	48	Mixed C12-C20-alkyl and C14-C18-unsaturated alkyl derivates of phosphonic acid (CAS RN 93925-25-8), containing by weight more than 80 % of oleyl, palmityl and stearyl groups, for use in the manufacture of lubricating oils (1)	0 %	-	31.12.2029
0.7205	ex 3811 29 00	75	Oxidation inhibitor mainly containing a mixture of isomers of 1-(tert-dodecylthio)propan-2-ol (CAS RN 67124-09-8), used in the manufacture of blends of additives for lubricating oils (1)	0 % (1)	-	31.12.2029
0.6023	ex 3811 29 00	85	Additives consisting of a mixture of 3-((C9-11)-isoalkyloxy)tetrahydrothiophene 1,1-dioxide, C10-rich (CAS RN 398141-87-2), for use in the manufacture of lubricating oils (1)	0 %	-	31.12.2029
0.5565	ex 3811 90 00	40	Solution of a quaternary ammonium salt based on polyisobutenyl succinimide, containing by weight 10 % or more but not more than 29,9 % of 2-ethylhexanol	0 %	-	31.12.2027
0.5147	*ex 3812 10 00	10	Rubber accelerator based on diphenyl guanidine granules (CAS RN 102-06-7)	0 %	-	31.12.2031

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8962	ex 3812 10 00	30	Vulcanization accelerator, consisting by weight of: — 98 % or more of N-tert-butyl bis(2-benzothiazolesulfen) amide (CAS RN 3741-80-8) — not more than 2 % of white mineral oil (CAS RN 8042-47-5)	0 %	-	31.12.2030
0.6045	ex 3812 20 90	10	Plasticiser, containing: — bis(2-ethylhexyl)-1,4-benzene dicarboxylate (CAS RN 6422-86-2) — more than 10 % but not more than 60 % by weight of dibutylterephthalate (CAS RN 1962-75-0)	0 %	-	31.12.2029
0.8872	ex 3812 39 90	23	UV stabilizer, containing by weight: — more than 97 % but not more than 99,8 % of *bis*(2,4-dicumylphenyl)pentaerythritol diphosphite (CAS RN 154862-43-8) and — more than 0,2 % but not more than 2 % of triisopropanolamine (CAS RN 122-20-3)	0 %	-	31.12.2029
0.6055	ex 3812 39 90	25	UV photo stabiliser containing: — α-[3-[3-(2H-Benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω-hydroxypoly(oxy-1,2-ethanediyl) (CAS RN 104810-48-2); — α-[3-[3-(2H-Benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]poly (oxy-1,2-ethanediyl) (CAS RN 104810-47-1); — polyethylene glycol of a weight average molecular weight (Mw) of 300 (CAS RN 25322-68-3) — bis (1,2,2,6,6-pentamethyl-4-piperidyl)sebacate (CAS RN 41556-26-7), and — methyl-1,2,2,6,6-pentamethyl-4- piperidyl sebacate (CAS RN 82919-37-7)	0 %	-	31.12.2029
0.8806	ex 3812 39 90	28	UV stabilizer based on a mixture of — reaction mass of Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2*H*-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy- and Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2*H*-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy] (EC number 400-830-7) with a purity by weight of 60 % or more, but not more than 80 %, and — reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (CAS RN 1065336-91-5) with a purity by weight of 25 % or more, but not more than 40 %	0 %	-	31.12.2029
0.8807	ex 3812 39 90	33	UV stabilizer based on: — a mixture of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates (CAS RN 127519-17-9) with a content by weight of 40 % or more, but not more than 60 %, and — a mixture of: *bis*(2,2,6,6-tetramethyl-1-octyloxypiperidin-4-yl)-1,10-decanedioate and 1,8-*bis*[(2,2,6,6-tetramethyl-4-((2,2,6,6-tetramethyl-1-octyloxypiperidin-4-yl)-decan-1,10-dioyl)piperidin-1-yl)oxy]octane (CAS RN 129757-67-1) with a content by weight of 40 % or more, but not more than 60 %	0 %	-	31.12.2029
0.6054	ex 3812 39 90	35	Mixture containing by weight: — 25 % or more but not more than 55 % of a mixture of C15-18 tetramethylpiperidinyl esters (CAS RN 86403-32-9) — not more than 20 % of other organic compounds — on a carrier of polypropylene (CAS RN 9003-07-0) or amorphous silica (CAS RN 7631-86-9 or 112926-00-8)	0 %	-	31.12.2029
0.8864	ex 3812 39 90	38	UV stabiliser containing by weight: — 75 % or more but not more than 95 % of the reaction product of 2-(4,6-*bis*(2,4-dimethylphenyl)-1,3,5-triazin-2-yl)-5-hydroxyphenol with ((C10-16, rich in C12-13 alkyloxy) methyl) oxyrane — 5 % or more but not more than 25 % of 1-methoxy-2-propanol (CAS RN 107-98-2)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.4861	ex 3812 39 90	40	Mixture of: — 80 % (± 10 %) by weight of 2-ethylhexyl 10-ethyl-4,4-dimethyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate (CAS RN 57583-35-4), and — 20 % (± 10 %) by weight of 2-ethylhexyl 10-ethyl-4-[[2-[(2-ethylhexyl)oxy]-2-oxoethyl]thio]-4-methyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate (CAS RN 57583-34-3)	0 %	-	31.12.2029
0.8870	ex 3812 39 90	43	Reaction mass containing by weight: — more than 45 % but not more than 49 % of Octyl 3-[3-*tert*-butyl-4-hydroxy-5-(5-chloro-2*H*-benzotriazol-2-yl)phenyl]propionate (CAS RN 83044-89-7), and — more than 49 % but not more than 53 % of 2-Ethylhexyl 3-[3-*tert*-butyl-4-hydroxy-5-(5-chloro-2*H*-benzotriazol-2-yl) phenyl]propionate (CAS RN 83044-90-0)	0 %	-	31.12.2029
0.8273	*ex 3812 39 90	45	2-Aminoethanol reaction products with cyclohexane and peroxidized N-butyl-2,2,6,6-tetramethyl-4-piperidinamine-2,4,6-trichloro-1,3,5-triazine reaction products (CAS RN 191743-75-6) with a purity by weight of 99 % or more	0 %	-	31.12.2031
0.3444	ex 3812 39 90	48	UV stabilizer (CAS RN 129757-67-1), reaction mass containing by weight 97 % or more of: — bis[2,2,6,6-tetramethyl-1-(octyloxy)piperidin-4-yl] decanedioate, and — 1,1'-bis[2,2,6,6-tetramethyl-1-(octyloxy)piperidin-4-yl] 10,10'-{octane-1,8-diylbis[oxy(2,2,6,6- tetramethylpiperidine-1,4-diyl)]} didecanedioate	0 %	-	31.12.2029
0.8366	ex 3812 39 90	53	Light stabilizer, containing by weight more than 90 % of reaction products of stearate methyl ester with 1-(2-hydroxy-2-methylpropoxy)-2,2,6,6-tetramethyl-4-piperidinol (CAS RN 300711-92-6)	0 %	-	31.12.2027
0.5477	*ex 3812 39 90	55	UV-stabilizer, containing: — 2-(4,6-bis(2,4-dimethylphenyl)-1,3,5-triazin-2-yl)-5-(octyloxy)-phenol (CAS RN 2725-22-6) and — either N,N'-bis(1,2,2,6,6-pentamethyl-4-piperidinyl)-1,6-hexanediamine, polymer with 2,4- dichloro-6-(4-morpholinyl)-1,3,5-triazine (CAS RN 193098-40-7) or — N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-1,6-hexanediamine, polymer with 2,4- dichloro-6-(4-morpholinyl)-1,3,5-triazine (CAS RN 82451-48-7)	0 %	-	31.12.2031
0.5483	*ex 3812 39 90	65	Stabiliser for plastic material containing: — 2-ethylhexyl 10-ethyl-4,4-dimethyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate (CAS RN 57583-35-4), — 2-ethylhexyl 10-ethyl-4-[[2-[(2-ethylhexyl)oxy]-2-oxoethyl]thio]-4-methyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate (CAS RN 57583-34-3), and — 2-ethylhexyl mercaptoacetate (CAS RN 7659-86-1)	0 %	-	31.12.2031
0.8533	ex 3812 39 90	75	UV stabilizer containing a mixture of: — branched and linear C7 to C9 alkyl esters of [3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxy]-1-phenylpropanoic acid (CAS RN 127519-17-9) with a content by weight of 85 % or more, and — 2-Methoxy-1-methylethyl acetate (CAS RN 108-65-6) with a content by weight of not more than 8 %	0 %	-	31.12.2028
0.5822	ex 3812 39 90	80	UV-stabilizer, consisting of: — a hindered amine: *N,N'*-bis(1,2,2,6,6-pentamethyl-4-piperidinyl)-1,6-hexanediamine, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine (CAS RN 193098-40-7) and — either an o-hydroxyphenyl triazine UV light absorber or — a chemically modified phenolic compound	0 %	-	31.12.2027
0.3731	ex 3814 00 90	40	Azeotrope mixtures containing isomers of nonafluorobutyl methyl ether and/or nonafluorobutyl ethyl ether	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.9073	ex 3815 12 00	40	Catalyst used to obtain paraxylene and orthoxylene by isomerization of methaxylene containing by weight: — 60 % or more but not more than 95 % of aluminum oxide (CAS RN 1344-28-1), — 5 % or more but not more than 15 % of aluminosilicate (CAS RN 1327-36-2), — not more than 2 % of platinum (CAS RN 7440-06-4), — not more than 2 % aluminum chloride hydroxide (CAS RN 12042-91-0), — not more than 0,2 % of hydrogen sulfide (CAS RN 7783-06-4)	0 %	-	31.12.2030
0.2800	ex 3815 12 00	50	Catalyst in the form of granules, wheels or ring-shaped structures — of a diameter of 3 mm or more, but not exceeding 10 mm, — containing 8 % or more but not more than 40 % by weight of silver — on a carrier based on aluminium oxide, — with one or more promoters	0 %	-	31.12.2029
0.3435	ex 3815 19 90	30	Catalyst containing titanium tetrachloride supported on magnesium dichloride, for use in the manufacture of polypropylene [(1)]	0 %	-	31.12.2029
0.9086	ex 3815 19 90	33	Catalyst, in powder form, consisting of a mixture of metal oxides fixed to a silicon dioxide support, with a total content by weight of molybdenum, bismuth and iron of 20 % or more but not more than 50 %, for use in the manufacture of acrylonitrile [(1)]	0 %	-	31.12.2030
0.8745	ex 3815 19 90	55	Components for a catalyst system, imported as single components or as set, made up of at least one of the following preparations: — ceramic material (CAS RN 66402-68-4), — molybdenum oxide and nickel oxide supported on aluminium oxide, — molybdenum oxide, nickel oxide and aluminium phosphate supported on aluminium oxide, — molybdenum oxide, nickel oxide, aluminium phosphate, silica, and molybdenum supported on aluminium oxide, for use against organic and inorganic impurities in kerosene production [(1)]	0 %	-	31.12.2029
0.2791	ex 3815 19 90	70	Catalyst consisting of organo-metallic compounds of aluminium and zirconium, fixed on a support of silicon dioxide	0 %	-	31.12.2029
0.2790	ex 3815 19 90	75	Catalyst consisting of organo-metallic compounds of aluminium and chromium, fixed on a support of silicon dioxide	0 %	-	31.12.2029
0.2793	ex 3815 19 90	80	Catalyst consisting of organo-metallic compounds of magnesium and titanium, fixed on a support of silicon dioxide, in the form of a suspension in mineral oil	0 %	-	31.12.2029
0.2788	ex 3815 19 90	85	Catalyst consisting of organo-metallic compounds of aluminium, magnesium and titanium, fixed on a support of silicon dioxide, in the form of powder	0 %	-	31.12.2029
0.3899	ex 3815 19 90	86	Catalyst containing titanium tetrachloride supported on magnesium dichloride, for use in the manufacture of polyolefins [(1)]	0 %	-	31.12.2029
0.4005	ex 3815 90 90	16	Initiator based on dimethylaminopropyl urea	0 %	-	31.12.2027
0.7998	ex 3815 90 90	38	Photoinitiator, containing by weight: — 80 % or more of polyethylene glycol di[β-4-[4-(2-dimethylamino-2-benzyl)butanoylphenyl]piperazine]propionate (CAS RN 886463-10-1), — not more than 17 % of polyethylene glycol [β-4-[4-(2-dimethylamino-2-benzyl)butanoylphenyl]piperazine]propionate	0 %	-	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7243	ex 3815 90 90	43	Catalyst in powder form consisting by weight of — 92,50 % (± 2) % titanium dioxide (CAS RN 13463-67-7), — 5 % (± 1) % silicon dioxide (CAS RN 112926-00-8), and — 2,5 % (± 1,5) % sulphur trioxide (CAS RN 7446-11-9)	0 %	-	31.12.2027
0.7999	ex 3815 90 90	48	Photoinitiator containing by weight: — 88 % or more of α-(2-benzoylbenzoyl)-ω-[(2-benzoylbenzoyl)oxy]-poly(oxy-1,2-ethanediyl) (CAS RN 1246194-73-9), — not more than 12 % of α-(2-benzoylbenzoyl)-ω-hydroxy-poly(oxy-1,2-ethanediyl) (CAS RN 1648797-60-7)	0 %	-	31.12.2030
0.3433	ex 3815 90 90	50	Catalyst containing titanium trichloride, in the form of a suspension in hexane or heptane containing by weight, in the hexane- or heptane-free material, 9 % or more but not more than 30 % of titanium	0 %	-	31.12.2029
0.8840	ex 3815 90 90	55	Catalytic Additives for fluid catalytic cracking (FCC), not containing Y type zeolite (CAS RN 308079-79-0), and not being a FCC (Fluid Catalytic Cracking) base catalyst, in the form of powder, consisting of a mixture of one or more of the following active substances: — calcium carbonate (CAS RN 471-34-1), — copper oxide (CAS RN 1217-38-0), — iron oxide (CAS RN 1309-37-1), — aluminium magnesium vanadium oxide (CAS RN 70621-8-0), — vanadium pentoxide (CAS RN 1314-62-1), — aluminium phosphate (CAS RN 7784-30-7), — cerium oxide (CAS RN 1306-38-3), — ZSM-5 type zeolite (CAS RN 308081-08-5), and one or more of the following inert substances: — magnesium oxide (CAS RN 1309-48-8), — aluminium oxide (CAS RN 1344-28-1), — kaolin (CAS RN 1332-58-7)	0 %	-	31.12.2029
0.8940	ex 3815 90 90	58	1,1′-Bis(4-triethylsilylphenyl)methylene(cyclopentadienyl)(2,7-di-tert-butyl-9-fluorenyl)dimethylhafnium (CAS RN 264926-41-2) in the form of a hexane (CAS RN 110-54-3) solution, containing by weight 2,0 % or more but not more than 2,5 % of 1,1′-bis(4-triethylsilylphenyl)methylene(cyclopentadienyl)(2,7-di-tert-butyl-9-fluorenyl)dimethylhafnium	0 %	-	31.12.2030
0.2783	*ex 3815 90 90	60	Dinonylnaphthalenedisulfonic acid (CAS RN 60223-95-2) with a content by weight of 50 % or more but not more than 65 %, in the form of a solution in isobutanol (CAS RN 78-83-1)	0 %	-	31.12.2027
0.3430	ex 3815 90 90	81	Catalyst, containing by weight 69 % or more but not more than 79 % of (2-hydroxy-1-methylethyl)trimethylammonium 2-ethylhexanoate (CAS RN 62314-22-1)	0 %	-	31.12.2029
0.2782	ex 3815 90 90	85	Catalyst based on aluminosilicate (zeolite), for the alkylation of aromatic hydrocarbons, for the transalkylation of alkylaromatic hydrocarbons or for the oligomerization of olefins [(1)]	0 %	-	31.12.2027
0.3732	ex 3815 90 90	88	Catalyst, consisting of titanium tetrachloride and magnesium chloride, containing by weight on an oil- and hexane-free basis: — 4 % or more but not more than 10 % of titanium and — 10 % or more but not more than 20 % magnesium	0 %	-	31.12.2029
0.3427	ex 3817 00 80	10	Mixture of alkylnaphthalenes, containing by weight: — 88 % or more but not more than 98 % of hexadecylnaphthalene — 2 % or more but not more than 12 % of dihexadecylnaphthalene	0 %	-	31.12.2029
0.4581	ex 3817 00 80	20	Mixture of branched alkyl benzenes mainly containing dodecyl benzenes	0 %	-	31.12.2029
0.5479	*ex 3817 00 80	30	Mixed alkylnaphthalenes, modified with aliphatic chains, of a chain-length varying from 12 to 56 carbon atoms	0 %	-	31.12.2031

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.6038	ex 3823 19 30 ex 3823 19 30	20 30	Palm fatty acid distillate, whether or not hydrogenated, with free fatty acid content 80 % or more for use in the manufacture of: — industrial monocarboxylic fatty acids of heading 3823, — stearic acid of heading 3823, — stearic acid of heading 2915, — palmitic acid of heading 2915, or — animal feed preparations of heading 2309 (1)	0 %	-	31.12.2027
0.6037	ex 3823 19 90 ex 3823 19 90	20 30	Palm acid oils from refining for use in the manufacture of: — industrial monocarboxylic fatty acids of heading 3823, — stearic acid of heading 3823, — stearic acid of heading 2915, — palmitic acid of heading 2915, or — animal feed preparations of heading 2309 (1)	0 %	-	31.12.2027
0.8365	*ex 3824 99 92	22	Solution containing: — 30 % or more but not more than 40 % by weight of lithium hexafluorophosphate (CAS RN 21324-40-3), and — 60 % or more but not more than 70 % by weight of ethyl methyl carbonate (CAS RN 623-53-0), or dimethyl carbonate (CAS RN 616-38-6)	3.2 %	-	31.12.2027
0.6810	ex 3824 99 92	23	Butylphosphato complexes of titanium(IV) (CAS RN 109037-78-7), dissolved in ethanol and propan-2-ol	0 %	-	31.12.2030
0.8835	ex 3824 99 92	25	Mixture containing by weight: — 55 % or more but not more than 65 % of (2S,3S,4S,5R,6R)-2-(((2R,3R,5S,6R)-4-(((2R,3S,4S,5R,6R)-3-acetoxy-4,5-bis(benzyloxy)-6-((benzyloxy)methyl)tetrahydro-2H-pyran-2-yl)oxy)-3,5-bis(benzyloxy)-6-(4-methoxy-4-oxobutoxy)tetrahydro-2H-pyran-2-yl)methoxy)-6-((((2S,3S,4S,5R,6R)-3-acetoxy-4,5-bis(benzyloxy)-6-((benzyloxy)methyl)tetrahydro-2H-pyran-2-yl)oxy)methyl)tetrahydro-2H-pyran-3,4,5-triyl tribenzoate (CAS RN 1233475-58-5), — 35 % or more but not more than 45 % of toluene (CAS RN 108-88-3)	0 %	-	31.12.2029
0.8921	*ex 3824 99 92	27	Methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate (CAS RN 1174627-68-9) with a purity by weight of 75 % or more, but less than 90 %	0 %	-	31.12.2030
0.8886	ex 3824 99 92	28	Preparation containing by weight: — 30 % or more, but not more than 60 % of 3a,4,4a,5,8,8a,9,9a-octahydro-4,9:5,8-dimethano-1H-benz[f]indene (CAS RN 7158-25-0), — 10 % or more, but not more than 50 % of 3a,4,7,7a-tetrahydro-4,7-methanoindene (CAS RN 77-73-6), and — whether or not 10 % or more, but not more than 40 % of petroleum hydrocarbon resin (CAS RN 68132-00-3)	0 %	-	31.12.2029
0.4909	ex 3824 99 92	29	Preparation containing by weight: — 85 % or more but not more than 99 % of polyethylene glycol ether of butyl 2-cyano 3-(4-hydroxy-3-methoxyphenyl) acrylate, and — 1 % or more but not more than 15 % of polyoxyethylene (20) sorbitan trioleate	0 %	-	31.12.2030
0.8955	ex 3824 99 92	30	Mixture of C10-C14 tert-alkyl amines (EC number: 701-175-2)	0 %	-	31.12.2030
0.3083	ex 3824 99 92 ex 3824 99 93 ex 3824 99 96	33 40 40	Anti-corrosion preparations consisting of salts of dinonylnaphthalenesulphonic acid, either: — on a support of mineral wax, whether or not modified chemically, or — in the form of a solution in an organic solvent	0 %	-	31.12.2029
0.4523	ex 3824 99 92	37	Mixture of acetates of 3-butene-1,2-diol with a content by weight of 65 % or more of 3-butene-1,2-diol diacetate (CAS RN 18085-02-4)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.6779	ex 3824 99 92	40	Solution of 2-chloro-5-(chloromethyl)-pyridine (CAS RN 70258-18-3) in organic diluent	0 %	-	31.12.2030
0.8706	ex 3824 99 92	44	Mixture, containing by weight: — 90 % or more but not more than 95 % of cresol ethoxylate (CAS RN 37281-57-5), and — 5 % or more but not more than 10 % of xylenol ethoxylate (CAS RN 61723-82-8)	0 %	-	31.12.2029
0.8887	ex 3824 99 92	48	Preparation containing by weight: — 80 % or more, but not more than 90 % of 3a,4,7,7a-tetrahydro-4,7-methanoindene (CAS RN 77-73-6), and — not more than 10 % of 3a,4,4a,5,8,8a,9,9a-octahydro-1H-4,9:5,8-dimethanocyclopenta[b]naphtalene (CAS RN 7158-25-0), and — 0,5 % or more, but not more than 3 % of 2,6-di-tert-butyl-p-cresol (CAS RN 128-37-0)	0 %	-	31.12.2029
0.4279	ex 3824 99 92	49	Preparation based on 2,5,8,11-tetramethyl-6-dodecyn-5,8-diol ethoxylate (CAS RN 169117-72-0)	0 %	-	31.12.2027
0.3065	ex 3824 99 92	51	Mixture containing by weight 40 % or more but not more than 50 % of 2-hydroxyethyl methacrylate and 40 % or more but not more than 50 % of glycerol ester of boric acid	0 %	-	31.12.2029
0.4434	*ex 3824 99 92	54	Poly(tetramethylene glycol) bis[(9-oxo-9H-thioxanthen-1-yloxy)acetate] with an average polymer chain length of less than 5 monomer units (CAS RN 813452-37-8)	0 %	-	31.12.2031
0.6025	ex 3824 99 92	55	Additives for paints and coatings, containing: — a mixture of esters of phosphoric acid obtained from the reaction of phosphoric anhydride with 4-(1,1-dimethylpropyl) phenol and copolymers of styrene-allyl alcohol (CAS RN 84605-27-6), and — 30 % or more but not more than 35 % by weight of isobutyl alcohol	0 %	-	31.12.2028
0.4707	ex 3824 99 92	58	Mixture containing by weight: — 56 % or more but not more than 85 % of divinylbenzene isomers (CAS RN 1321-74-0) — 15 % or more but not more than 44 % of ethylvinylbenzene isomers (CAS RN 28106-30-1)	0 %	-	31.12.2029
0.5050	ex 3824 99 92	61	3',4',5'-Trifluorobiphenyl-2-amine, in the form of a solution in toluene containing by weight 80 % or more but not more than 90 % of 3',4',5'-trifluorobiphenyl-2-amine	0 %	-	31.12.2030
0.7831	ex 3824 99 92	62	Solution of 9-borabicyclo[3.3.1]nonane (CAS RN 280-64-8) in tetrahydrofurane (CAS RN 109-99-9), containing by weight 6 % or more 9-borabicyclo[3.3.1]nonane	0 %	-	31.12.2029
0.6720	ex 3824 99 92	68	Preparation containing by weight: — 20 % (±1 %) ((3-(sec-butyl)-4-(decyloxy)phenyl)methanetriyl) Tribenzene (CAS RN 1404190-37-9) Dissolved in: — 10 % (± 5 %) 2-sec-Butylphenol (CAS RN 89-72-5) — 64 %(±7 %) Solvent naphtha (petroleum), heavy aromatic (CAS RN 64742-94-5) and — 6 % (± 1.0 %) Naphthalene (CAS RN 91-20-3)	0 %	-	31.12.2030
0.6719	*ex 3824 99 92	69	Preparation containing by weight: — 80 % or more but not more than 92 % of bisphenol-A bis(diphenyl phosphate) (CAS RN 5945-33-5) — 7 % or more but not more than 20 % oligomers of bisphenol-A bis(diphenyl phosphate) and — not more than 1 % triphenyl phosphate (CAS RN 115-86-6)	0 %	-	31.12.2031

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.4409	ex 3824 99 92	70	Mixture of 80 % (± 10 %) of 1-[2-(2-aminobutoxy)ethoxy]but-2-ylamine and 20 % (± 10 %) of 1-({[2-(2-aminobutoxy)ethoxy]methyl} propoxy)but-2-ylamine	0 %	-	31.12.2029
0.8471	ex 3824 99 92	73	*Tri*-C8-10-alkyl amines (CAS RN 68814-95-9) with a purity by weight of 95 % or more	0 %	-	31.12.2027
0.8486	ex 3824 99 92	75	Mixture, containing by weight: — 75 % or more of tetrabutyltin (CAS RN 1461-25-2), — not more than 20 % of tributyltin chloride (CAS RN 1461-22-9), — not more than 4 % of dibutyltin dichloride (CAS RN 683-18-1), for use in the production of butyltin compounds, used in glass manufacture and tributyltin chloride used as a catalyst in the pharmaceutical industry (1)	3.2 %	-	31.12.2027
0.8506	ex 3824 99 92	79	Mixture, containing by weight: — tributyltin chloride (CAS RN 1461-22-9) with a purity by weight of 80 % or more, — not more than 5 % tetrabutyltin (CAS RN 1461-25-2), — not more than 6 % dibutyltin dichloride (CAS RN 683-18-1), — not more than 11 % o-xylene (CAS RN 95-47-6), for use in the production of tributyltin chloride used as a catalyst in the pharmaceutical industry (1)	3.2 %	-	31.12.2027
0.7462	ex 3824 99 92	81	Reaction mass of 3- [(diphenoxyphosphoryl)oxy]phenyl triphenyl 1,3-phenylene bis(phosphate) and tetraphenyl 1,3-phenylene bis(phosphate)	0 %	-	31.12.2028
0.6546	ex 3824 99 92	82	T-butylchloride dimethylsilane (CAS RN 18162-48-6) solution in toluene	0 %	-	31.12.2029
0.8517	ex 3824 99 92	83	1-(Cedr-8-en-9-yl)ethanone (CAS RN 32388-55-9) with a purity by weight of 70 % or more, but not more than 90 %	0 %	-	31.12.2029
0.3074	ex 3824 99 92	84	Preparation consisting by weight of 83 % or more of 3a,4,7,7a-tetrahydro-4,7-methanoindene (dicyclopentadiene), a synthetic rubber, whether or not containing by weight 7 % or more of tricyclopentadiene, and: — either an aluminium-alkyl compound, — or an organic complex of tungsten — or an organic complex of molybdenum	0 %	-	31.12.2029
0.8499	ex 3824 99 92	86	Tall oil *N*,*N*-dimethyl fatty amides (CAS RN 68308-74-7) with a purity by weight of 99 % or more	0 %	-	31.12.2027
0.3069	ex 3824 99 92	88	2,4,7,9-Tetramethyldec-5-yne-4,7-diol, hydroxyethylated (CAS RN 9014-85-1)	0 %	-	31.12.2030
0.8083	ex 3824 99 92	92	Solution consisting of: — 50 (± 2) % by weight sodium mentholate (CAS RN 19321-38-1), and — 50 (± 2) % by weight light aliphatic solvent naphtha (petroleum) (CAS RN 64742-89-8)	0 %	-	31.12.2030
0.5961	ex 3824 99 93	30	Powder Mixture containing by weight: — 85 % or more of zinc diacrylate (CAS RN 14643-87-9), — not more than 5 % of 2,6-di-tert-butyl-alpha-dimethylamino-p-cresol (CAS RN 88-27-7), and — not more than 10 % of zinc stearate (CAS RN 557-05-1)	0 %	-	31.12.2029
0.8714	ex 3824 99 93	31	Reaction mass of dihexadecyl hydrogen phosphate (CAS RN 2197-63-9) and hexadecyl dihydrogen phosphate (CAS RN 3539-43-3)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8498	ex 3824 99 93	33	Preparation containing by weight — 60 % or more but not more than 70 % of calcium *rel*-(1*R*,2*S*)-cyclohexane-1,2-dicarboxylate (CAS RN 491589-22-1), — 30 % or more but not more than 40 % of zinc stearate (CAS RN 557-05-1), — 1 % or more but not more than 5 % of CI Pigment Blue 29 (CAS RN 57455-37-5) and — 1 % or more but not more than 5 % of CI Pigment Violet 15 (CAS RN 12769-96-9)	0 %	-	31.12.2027
0.4719	ex 3824 99 93	35	Paraffin with a level of chlorination of 70 % or more (CAS RN 63449-39-8)	0 %	-	31.12.2029
0.8497	ex 3824 99 93	36	Preparation containing by weight 60 % or more but not more than 70 % of calcium *rel*-(1*R*,2*S*)-cyclohexane-1,2-dicarboxylate (CAS RN 491589-22-1) and 30 % or more but not more than 40 % of zinc stearate (CAS RN 557-05-1)	0 %	-	31.12.2027
0.4527	ex 3824 99 93	42	Mixture of bis{4-(3-(3-phenoxycarbonylamino)tolyl)ureido}phenylsulphone, diphenyltoluene-2,4-dicarbamate and 1-[4-(4-aminobenzenesulphonyl)-phenyl]-3-(3-phenoxycarbonylamino-tolyl)-urea	0 %	-	31.12.2029
0.7153	*ex 3824 99 93	45	Sodium hydrogen 3-aminonaphthalene-1,5-disulphonate (CAS RN 4681-22-5) containing by weight: — not more than 20 % of disodium sulphate, and — not more than 10 % of sodium chloride	0 %	-	31.12.2027
0.7786	ex 3824 99 93	48	Nonhalogenated flame retardant containing by weight: — 50 % or more, but not more than 65 % of piperazine pyrophosphate (CAS RN 66034-17-1), — 35 % or more, but not more than 45 % of a phosphoric acid derivative and — not more than 6 % of zinc oxide (CAS RN 1314-13-2)	0 %	-	31.12.2029
0.6215	ex 3824 99 93	53	Zinc dimethacrylate (CAS RN 13189-00-9), containing not more than 2,5 % by weight of 2,6-di-tert-butyl-alpha-dimethyl amino-p-cresol (CAS RN 88-27-7), in the form of powder	0 %	-	31.12.2029
0.2939	ex 3824 99 93	61	Disodium 7,7'-(carbonyldiimino)*bis*(4-hydroxynaphthalene-2-sulphonate) (CAS RN 20324-87-2) with a purity by weight of 80 % or more	0 %	-	31.12.2028
0.4290	ex 3824 99 93	63	Mixture of phytosterols, not in the form of powder, containing by weight: — 75 % or more of sterols, — not more than 25 % of stanols, for use in the manufacture of stanols/sterols or stanol/sterol esters [(1)]	0 %	-	31.12.2027
0.7460	ex 3824 99 93	65	Reaction mass of 1,1'-(isopropylidene)bis[3,5-dibromo-4-(2,3-dibromo-2-methylpropoxy)benzene] (CAS RN 97416-84-7) and 1,3-dibromo-2-(2,3-dibromo-2-methylpropoxy)-5-{2-[3,5-dibromo-4-(2,3,3-tribromo-2-methylpropoxy)phenyl]propan-2-yl}benzene	0 %	-	31.12.2029
0.8371	ex 3824 99 93	74	1,3-Propanediamine, N1,N1'-1,2-ethanediylbis-, reaction products with cyclohexane and peroxidized N-butyl-2,2,6,6-tetramethyl-4-piperidinamine-2,4,6-trichloro-1,3,5-triazine reaction products (CAS RN 191680-81-6)	0 %	-	31.12.2027
0.4336	ex 3824 99 93	88	Mixture of phytosterols containing by weight: — 60 % or more, but not more than 80 % of sitosterols, — less than 15 % of campesterols, — less than 5 % of stigmasterols, and — less than 15 % of betasitostanols	0 %	-	31.12.2027
0.3078	ex 3824 99 96	35	Calcined bauxite (refractory grade)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.9062	ex 3824 99 96	38	Low outgassing thermally conductive silicone paste: — with thermal conductivity when cured of 3,45 W/(m·K) or more but not more than 3,55 W/(m·K), — with continuous use temperature minimum range from -60 °C to 200 °C, — with heat capacity when cured of 0,75 J/g·K or more but not more than 0,85 J/g·K, — with volume resistivity when cured of 1010 Ω·m or more, — packaged in containers of 30 kg or more	0 %	-	31.12.2030
0.8514	ex 3824 99 96	43	2-(Ethylthio)ethanethiol functionalized silicagel with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.6628	ex 3824 99 96	46	Manganese zinc ferrite granulate, containing by weight: — 52 % or more but not more than 76 % of iron(III)oxide, — 13 % or more but not more than 42 % of manganese oxide, and — 2 % or more but not more than 22 % of zinc oxide	0 %	-	31.12.2030
0.6749	ex 3824 99 96	48	Zirconium oxide (ZrO_2), calcium oxide stabilised (CAS RN 68937-53-1) with a zirconium oxide content by weight of 92 % or more but not more than 97 %	0 %	-	31.12.2030
0.5607	ex 3824 99 96	50	Nickel hydroxide, doped with 12 % or more but not more than 18 % by weight of zinc hydroxide and cobalt hydroxide, of a kind used to produce positive electrodes for accumulators	0 %	-	31.12.2027
0.6145	ex 3824 99 96	55	Carrier in powder form, consisting of: — ferrite (Iron oxide) (CAS RN 1309-37-1) — manganese oxide (CAS RN 1344-43-0) — magnesium oxide (CAS RN 1309-48-4) — styrene acrylate copolymer to be mixed with the toner powder, in the manufacturing of ink/toner filled bottles or cartridges for facsimile machines, computer printers and copiers (1)	0 %	-	31.12.2029
0.5141	*ex 3824 99 96	60	Fused magnesia containing by weight 15 % or more of dichromium trioxide	0 %	-	31.12.2031
0.8587	ex 3824 99 96	62	Viscous preparation essentially containing: — by weight more than 5 % but not more than 15 % of poly(vinyl alcohol) (CAS RN 9002-89-5), — by weight more than 10 % but not more than 20 % of 1-methoxy-2-propanol (CAS RN 107-98-2), — water, for use as a protective coating for wafers during the slicing process in the manufacture of semiconductors (1)	0 %	-	31.12.2028
0.3050	ex 3824 99 96	65	Aluminium sodium silicate, in the form of spheres of a diameter of: — either 1,6mm or more but not more than 3,4 mm, — or 4mm or more but not more than 6 mm	0 %	-	31.12.2029
0.8875	ex 3824 99 96	66	Vulcanizing agent containing by weight: — 78 % or more but not more than 82 % of insoluble sulphur (CAS RN 9035-99-8), — 18 % or more but not more than 22 % of naphthenic oil (CAS RN 64742-52-5), and — not more than 0,2 % of methyl styrene (CAS RN 98-83-9)	0 %	-	31.12.2029
0.3119	ex 3824 99 96	73	Reaction product, containing by weight: — 1 % or more but not more than 40 % of molybdenum oxide, — 10 % or more but not more than 50 % of nickel oxide, — 30 % or more but not more than 70 % of tungsten oxide	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7010	*ex 3824 99 96	74	Mixture with a non-stoichiometric composition: — with a crystalline structure, — with a content of fused magnesia-alumina spinel and with admixtures of silicate phases and aluminates, at least 75 % by weight of which consists of fractions with a grain size of 1-3 mm and at most 25 % consists of fractions with a grain size of 0-1 mm	0 %	-	31.12.2031
0.8935	ex 3824 99 96	78	Zirconium oxide stabilized with yttrium oxide (CAS RN 64417-98-7) containing by weight 90 % or more of zirconium oxide	0 %	-	31.12.2030
0.5820	ex 3824 99 96	87	Platinum oxide (CAS RN 12035-82-4) fixed on a porous support of aluminium oxide (CAS RN 1344-28-1), containing by weight: — 0,1 % or more but not more than 1 % of platinum, and — 0,5 % or more but not more than 5 % of ethylaluminium dichloride (CAS RN 563-43-9)	0 %	-	31.12.2027
0.6132	ex 3901 10 10 ex 3901 40 00	20 10	High flow linear low density polyethylene-1-butene / LLDPE (CAS RN 25087-34-7) in form of powder, with — a melt flow rate (MFR 190 °C/2,16 kg) of 16g/10min or more, but not more than 24 g/10 min and — a density (ASTM D 1505) of 0,922 g/cm^3 or more, but not more than 0,926 g/cm^3 and — a vicat softening temperature of min. 94 °C	0 %	m³	31.12.2029
0.8378	ex 3901 10 10 ex 3901 40 00	50 50	Copolymer of ethylene and 1-butene (CAS RN 25087-34-7) with: — a density (ASTM D 1505) of 0,924 g/cm³ or more but not more than 0,928 g/cm³, — a melt flow rate (190 °C/2,16 kg) of 48 g/10 min or more but not more than 52 g/10 min, and — a peak melting temperature of 120 °C or more but not more than 124 °C	0 %	-	31.12.2027
0.8379	ex 3901 10 10 ex 3901 40 00	60 60	Copolymer of ethylene and 1-butene (CAS RN 25087-34-7) with: — a density (ASTM D 1505) of 0,922 g/cm^3 or more but not more than 0,926 g/cm^3 and — a melt flow rate (190 °C/2,16 kg) of 18 g/10 min or more but not more than 22 g/10 min	0 %	-	31.12.2029
0.5142	*ex 3901 10 90	30	Polyethylene granules, containing by weight 10 % or more but not more than 25 % of copper	0 %	-	31.12.2031
0.8757	ex 3901 30 00	20	Copolymer of ethylene and vinyl acetate (CAS RN 24937-78-8) — containing by weight 28 % or more but not more than 49 % of vinyl acetate, — with a melt flow rate of less than 5g/10 min (190 °C/2.16 kg, ASTM D1238), — in the form of pellets	0 %	-	31.12.2029
0.8732	ex 3901 30 00	30	Terpolymer of ethylene, vinyl acetate and methacrylic acid (CAS RN 26375-31-5)	0 %	-	31.12.2029
0.6897	ex 3901 40 00	30	Octene linear low-density polyethylene (LLDPE) produced by a Ziegler-Natta catalyst method in the form of pellets with: — more than 10 % but not more than 20 % by weight of copolymer, — a melt flow rate (MFR 190 °C/2,16 kg) of 0,7 g/10 min or more but not more than 0,9 g/10 min, and — a density (ASTM D4703) of 0,911 g/cm³ or more, but not more than 0,913 g/cm³, for use in the co-extrusion processing of films for flexible food packaging [(1)]	0 %	m³	31.12.2030
0.6920	ex 3901 90 80	53	Copolymer of ethylene and acrylic acid (CAS RN 9010-77-9) with: — an acrylic acid content of 18,5 % or more, but not more than 49,5 % by weight (ASTM D4094), and — a melt flow rate of 10g/10 min or more (125°C/2,16 kg, ASTM D1238)	0 %	m³	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.6734	ex 3901 90 80	55	Zinc or sodium salt of an ethylene and acrylic acid copolymer, with: — an acrylic acid content of 6 % or more but not more than 50 % by weight, and — a melt flow rate of 1g/10 min or more at 190 °C/2,16 kg (measured using ASTM D1238)	0 %	-	31.12.2030
0.5049	ex 3901 90 80	67	Copolymer made exclusively from ethylene and methacrylic acid monomers in which the methacrylic acid content is 11 % by weight or more	0 %	-	31.12.2030
0.6998	*ex 3901 90 80	73	Mixture containing by weight — 80 % or more, but not more than 94 % of chlorinated polyethylene (CAS RN 64754-90-1) and — 6 % or more, but not more than 20 % of styrene-acrylic copolymer (CAS RN 27136-15-8)	0 %	-	31.12.2031
0.8739	ex 3901 90 80	75	Terpolymer of ethylene, isobutyl acrylate and methacrylic acid (CAS RN 37433-35-5), in the form of pellets	0 %	-	31.12.2029
0.8736	ex 3901 90 80	85	Terpolymer of ethylene, n-butyl acrylate and carbon monoxide (CAS RN 61843-70-7) in the form of pellets	0 %	-	31.12.2029
0.2902	ex 3901 90 80	91	Ionomer resin consisting of a salt of a copolymer of ethylene with methacrylic acid	0 %	-	31.12.2029
0.3906	ex 3901 90 80	92	Chlorosulphonated polyethylene	0 %	-	31.12.2029
0.2899	ex 3901 90 80	93	Copolymer of ethylene, vinyl acetate and carbon monoxide, for use as a plasticiser in the manufacture of roof sheets [(1)]	0 %	-	31.12.2029
0.3186	ex 3901 90 80	94	Mixtures of A-B block copolymer of polystyrene and ethylene-butylene copolymer and A-B-A block copolymer of polystyrene, ethylene-butylene copolymer and polystyrene, containing by weight not more than 35 % of styrene	0 %	-	31.12.2029
0.2898	ex 3901 90 80	97	Chlorinated polyethylene, in the form of powder	0 %	-	31.12.2029
0.2895	ex 3902 10 00	20	Polypropylene, containing no plasticiser, — of a melting point of more than 150 °C (as determined by the ASTM D 3417 method), — of a heat of fusion of 15 J/g or more but not more than 70 J/g, — of an elongation at break of 1 000 % or more (as determined by the ASTM D 638 method), — of a tensile modulus of 69 MPa or more but not more than 379 MPa (as determined by the ASTM D 638 method)	0 %	-	31.12.2029
0.3179	ex 3902 20 00	20	Hydrogenated polyisobutene, in liquid form	0 %	-	31.12.2029
0.8125	ex 3902 30 00	20	Hydrogenated block copolymer of styrene and isoprene (CAS RN 68648-89-5), containing by weight less than 37 % of styrene	0 %	-	31.12.2030
0.8232	*ex 3902 30 00	30	Hydrogenated copolymer of styrene, isoprene and butadiene, containing by weight 28 % or more, but not more than 55 % of propylene	0 %	-	31.12.2031
0.4768	ex 3902 90 90	60	Non-hydrogenated 100 % aliphatic resin (polymer), with the following characteristics: — liquid at room temperature — obtained by cationic polymerisation of C-5 alkenes monomers — with a number average molecular weight (Mn) of 370 (± 50) — with a weight average molecular weight (Mw) of 500 (± 100)	0 %	-	31.12.2029
0.8999	ex 3902 90 90	63	Hydrogenated poly(1-octene) (CAS RN 70693-43-5)	0 %	-	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7950	ex 3902 90 90	65	Brominated butadiene-styrene copolymer (CAS RN 1195978-93-8) with a bromine content of 60 % by weight or more but not more than 68 %, in forms as defined in Note 6 (b) to Chapter 39	0 %	-	31.12.2030
0.4040	*ex 3902 90 90	70	Synthetic poly-alpha-olefin with a viscosity of 3 or more but not more than 9 centistokes (measured at 100 ° Celsius according to the ASTM D 445 method), obtained by polymerization of dodecene with or without: — not more than 40 % by weight of tetradecene and/or — not more than 2 % by weight decene and/or — not more than 2 % by weight of hexadecene	0 %	-	31.12.2031
0.6214	ex 3902 90 90	94	Chlorinated polyolefins, whether or not in a solution or dispersion	0 %	-	31.12.2029
0.4166	*ex 3903 19 00	40	Crystalline polystyrene with: — a melting point of 268 °C or more but not more than 272 °C — a setting point of 232 °C or more but not more than 247 °C, — whether or not containing additives and filling material	0 %	-	31.12.2031
0.7417	ex 3903 90 90 ex 3904 69 80	38 88	Polytetrafluoroethylene (CAS RN 9002-84-0) encapsulated with an acrylonitrile-styrene copolymer (CAS RN 9003-54-7), with a content by weight of each polymer of 50 % (± 1 %)	0 %	-	31.12.2027
0.8415	ex 3903 90 90	43	Mixture of polymers consisting by weight of: — 10 % or more but not more than 30 % of a styrene-ethylene-butylene-styrene block copolymer (CAS RN 66070-58-4), — 25 % or more but not more than 45 % of mineral oil (CAS RN 8042-47-5), — 25 % or more but not more than 45 % of calcium carbonate (CAS RN 1317-65-3), — 10 % or more but not more than 20 % of polypropylene (CAS RN 9003-07-0), and — 1 % or more but not more than 3 % of a copolymer of α-methylstyrene and vinyltoluene (CAS RN 9017-27-0)	0 %	-	31.12.2027
0.6804	ex 3903 90 90	70	Copolymer in the form of granules containing by weight: — 75 % (± 7 %) styrene and — 25 % (± 7 %) methylmethacrylate	0 %	m^3	31.12.2030
0.4410	ex 3903 90 90	86	Mixture containing by weight: — 45 % or more but not more than 65 % of polymers of styrene, — 30 % or more but not more than 45 % of poly(phenylene ether), and — not more than 11 % of additives	0 %	-	31.12.2029
0.2885	ex 3904 61 00	20	Copolymer of tetrafluoroethylene and trifluoro(heptafluoropropoxy)ethylene, containing 3,2 % or more but not more than 4,6 % by weight of trifluoro(heptafluoropropoxy)ethylene and less than 1 mg/kg of extractable fluoride ions	0 %	-	31.12.2029
0.7675	ex 3904 69 80	20	Copolymer of tetrafluoroethylene, heptafluoro-1-pentene and ethene (CAS RN 94228-79-2)	0 %	-	31.12.2029
0.7626	ex 3904 69 80	30	Copolymer of tetrafluoroethylene, hexafluoropropene and ethene	0 %	-	31.12.2029
0.5560	ex 3904 69 80	85	Copolymer of ethylene and chlorotrifluoroethylene, whether or not modified with hexafluoroisobutylene, whether or not containing fillers	0 %	-	31.12.2027
0.2883	ex 3904 69 80	96	Polychlorotrifluoroethylene, in one of the forms mentioned in note 6 (a) and (b) to Chapter 39	0 %	-	31.12.2029
0.3745	ex 3904 69 80	97	Copolymer of chlorotrifluoroethylene and vinylidene difluoride	0 %	-	31.12.2029
0.8414	ex 3905 91 00	35	Aqueous solution of a copolymer of vinylpyrrolidone and *N*,*N*-dimethylaminopropyl methacrylamide sulfate (CAS RN 175893-71-7), containing by weight 8 % or more, but not more than 12 % of copolymer	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.5774	ex 3905 91 00	40	Water soluble copolymer of ethylene and vinyl alcohol (CAS RN 26221-27-2), containing by weight not more than 38 % of the monomer unit ethylene	0 %	-	31.12.2027
0.8126	ex 3905 91 00	50	Aqueous solution consisting by weight of: — 10 % or more but not more than 20 % of a copolymer of vinyl pyrrolidone, N,N-dimethylaminopropyl methacrylamide and 3 (methacryloylamino)propyllauryldimethylammonium chloride (CAS RN 306769-73-3), — not more than 1 % preservatives	0 %	-	31.12.2030
0.8145	ex 3905 91 00	60	Copolymer of vinylpyrrolidone, vinyl caprolactam and dimethylaminoethyl methacrylate (CAS RN 102972-64-5) in solid form, or as an aqueous solution containing by weight: — 27 % or more but not more than 33 % of copolymer, — not more than 1,5 % of ethanol (CAS RN 64-17-5), — not more than 1 % of preservatives	0 %	-	31.12.2030
0.8138	ex 3905 91 00	70	Aqueous solution, containing by weight: — 25 % or more but not more than 35 % of a copolymer of vinyl caprolactam, vinyl pyrrolidone, N,N-dimethylaminopropyl methacrylamide and 3-(methacryloylamino)propyllauryldimethylammonium chloride (CAS RN 748809-45-2), — 10 % or more but not more than 16 % of ethanol (CAS RN 64-17-5) whether or not denatured with tert-butyl alcohol (CAS RN 75-65-0) and/or denatonium benzoate (CAS RN 3734-33-6)	0 %	-	31.12.2030
0.8139	ex 3905 91 00	80	Copolymer of vinylpyrrolidone, acrylic acid and dodecyl methacrylate (CAS RN 83120-95-0)	0 %	-	31.12.2030
0.3283	ex 3905 99 90	95	Hexadecylated or eicosylated polyvinylpyrrolidone	0 %	-	31.12.2029
0.2880	ex 3905 99 90	96	Polymer of vinyl formal, in one of the forms mentioned in note 6 (b) to Chapter 39, of a weight average molecular weight (M_w) of 25 000 or more but not more than 150 000 and containing by weight: — 9,5 % or more but not more than 13 % of acetyl groups evaluated as vinyl acetate and — 5 % or more but not more than 6,5 % of hydroxy groups evaluated as vinyl alcohol	0 %	-	31.12.2029
0.3278	ex 3905 99 90	98	Poly(vinyl pyrrolidone) partially substituted by triacontyl groups, containing by weight 78 % or more but not more than 82 % of triacontyl groups	0 %	-	31.12.2029
0.3276	3906 90 60		Copolymer of methyl acrylate with ethylene and a monomer containing a non-terminal carboxy group as a substituent, containing by weight 50 % or more of methyl acrylate, whether or not mixed with silicon dioxide	0 %	-	31.12.2029
0.7347	ex 3906 90 90	23	Copolymer of methylmethacrylate, butylacrylate, glycidylmethacrylate and styrene (CAS RN 37953-21-2), with an epoxy equivalent weight of not more than 500, in form of ground flakes with a particle size of not more than 1 cm	0 %	-	31.12.2027
0.6672	ex 3906 90 90	28	Mixture containing by weight: — 80 % or more but not more than 90 % of a core shell polymer of butyl acrylate, ethyl acrylate, methyl-acrylate and allyl methacrylate (CAS RN 73026-23-0) and — 10 % or more but not more than 20 % of a copolymer of methyl methacrylate and ethyl acrylate (CAS RN 9010-88-2)	0 %	-	31.12.2030
0.7125	*ex 3906 90 90	43	Copolymer of methacrylic esters, butylacrylate and cyclic dimethylsiloxanes (CAS RN 143106-82-5)	0 %	-	31.12.2031

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.2886	ex 3906 90 90	50	Polymers of esters of acrylic acid with one or more of the following monomers in the chain: — chloromethyl vinyl ether, — chloroethyl vinyl ether, — chloromethylstyrene, — vinyl chloroacetate, — methacrylic acid, — butenedioic acid monobutyl ester, — butenedioic acid monocyclohexyl ester, containing by weight not more than 5 % of each monomer unit	0 %	-	31.12.2029
0.8579	ex 3906 90 90	58	Mixture of polymers, containing by weight: — 77 % or more but not more than 81 % of polyacrylamide (CAS RN 9003-05-8), — 18 % or more but not more than 21 % of polyethylene glycol (CAS RN 25322-68-3)	0 %	-	31.12.2028
0.7499	ex 3906 90 90	60	Aqueous dispersion containing by weight: — more than 10 % but not more than 15 % of ethanol, and — more than 7 % but not more than 11 % of a reaction product of poly(epoxyalkylmethacrylate-co-divinylbenzene) with a glycerol derivative	0 %	-	31.12.2029
0.8828	ex 3906 90 90	71	Acrylonitrile-styrene-acrylate copolymer in the form of granules containing by weight: — 48 % of styrene, — 22 % of acrylonitrile, — 29 % of butylacrylate, and — 1 % of dihydrodicyclopentadienyl acrylate	0 %	-	31.12.2029
0.6425	ex 3906 90 90	73	Preparation containing by weight: — 33 % or more but not more than 37 % of butyl methacrylate - methacrylic acid copolymer, — 24 % or more but not more than 28 % of propylene glycol, and — 37 % or more but not more than 41 % of water	0 %	-	31.12.2029
0.3272	ex 3907 29 11	10	Poly(ethylene oxide) of a number average molecular weight (M_n) of 100 000 or more	0 %	-	31.12.2029
0.4378	ex 3907 29 11	20	Bis[Methoxypoly[ethyleneglycol)]-maleimidopropionamide, chemically modified with lysine, of a number average molecular weight (M_n) of 40 000	0 %	-	31.12.2029
0.8882	ex 3907 29 11	30	Mixture containing by weight: — 75 % or more of polyethyleneglycol modified butyl-2-cyano-3-(4-hydroxy-3-methoxyphenyl) acrylate, with an ethylene oxide chain length of not more than 30 (CAS RN 780763-40-8) — not more than 25 % of ethoxylated sorbitan trioleate (CAS RN 9005-70-3)	0 %	-	31.12.2029
0.8896	ex 3907 29 11	40	Ethoxylated glycerol (CAS RN 31694-55-0) with a hydroxyl number of 541 or more but not more than 587 (ASTM 4274)	0 %	-	31.12.2029
0.7532	ex 3907 29 20	35	Mixture containing by weight: — 5 % or more but not more than 15 % of a copolymer of glycerol, propylene oxide and ethylene oxide (CAS RN 9082-00-2), and — 85 % or more but not more than 95 % of a copolymer of sucrose, propylene oxide and ethylene oxide (CAS RN 26301-10-0)	0 %	-	31.12.2029
0.4013	ex 3907 29 20	40	Copolymer of tetrahydrofuran and tetrahydro-3-methylfuran (CAS RN 38640-26-5) with a number average molecular weight (Mn) of 900 or more but not more than 3 600	0 %	-	31.12.2028

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.6351	ex 3907 29 20	50	Poly(*p*-phenylene oxide) in the form of powder with: — a glass-transition temperature of 210 °C or more, — a weight average molecular weight (Mw) of 35 000 or more but not more than 80 000, — an inherent viscosity of 0,2 or more but not more than 0,6 dl/gram	0 %	-	31.12.2029
0.9078	ex 3907 29 20	63	Preparation containing by weight — 5 % or more but not more than 15 % of polyethylene-polypropylene glycol (CAS RN 9003-11-6) and — 85 % or more but not more than 95 % of oxirane, 2-methyl-,polymer with oxirane, ether with 5-(2-(4-(bis(2-hydroxyethyl)amino)-2-methylphenyl)diazenyl)-3-methyl-2,4-thiophenedicarbonitrile (2:1) (CAS RN 515857-23-5)	0 %	-	31.12.2030
0.9079	ex 3907 29 20	65	Preparation containing by weight — 40 % or more but not more than 60 % of oxirane, 2-methyl-, polymer with oxirane, ether with 2,2-[[3-methyl-4-[(4-methyl-2-benzothiazolyl)azo]phenyl]imino]bis[ethanol] (2:1) (CAS RN 229306-55-2) and — 40 % or more but not more than 60 % of polyethylene-polypropylene glycol (CAS RN 9003-11-6)	0 %	-	31.12.2030
0.9077	ex 3907 29 20	68	Preparation containing by weight — 90 % or more but not more than 99 % of oxirane, 2-methyl-,polymer with oxirane, ether with ethyl 3-(4-(bis(2-hydroxyethyl)amino)phenyl)-2-cyano-2-propenoate (2:1) (CAS RN 152286-82-3) and — 1 % or more but not more than 10 % of polyethylene-polypropylene glycol (CAS RN 9003-11-6)	0 %	-	31.12.2030
0.9081	ex 3907 29 20	70	Preparation containing by weight — 50 % or more but not more than 70 % of oxirane, methyl-polymer with oxirane, ether with bis(4-[bis(2-hydroxyethyl)amino)phenyl] (2-sulfophenyl)methyl (4:1), monosodium salt block (CAS RN 126042-89-5) and — 30 % or more but not more than 50 % of polyethylene-polypropylene glycol (CAS RN 9003-11-6)	0 %	-	31.12.2030
0.9082	ex 3907 29 20	73	Preparation containing by weight of — 23 % or more but not more than 36 % of oxirane, 2-methyl-,polymer with oxirane, ether with bis(4-(bis(2-hydroxyethyl)amino)phenyl)(2-sulfophenyl)methyl (4:1), monosodium salt, block (CAS RN 126042-89-5), — 4 % or more but not more than 20 % of polyethylene-polypropylene glycol (CAS RN 9003-11-6), — 25 % or more but not more than 30 % of oxirane, 2-methyl-,polymer with oxirane, ether with 2,2'-((3-methyl-4-((4-methyl-2-benzothiazolyl)azo)phenyl)imino)bis(ethanol)(2:1) (CAS RN 229306-55-2), — 5 % or more but not more than 10 % of oxirane, 2-methyl-,polymer with oxirane, ether with 5-(2-(4-(bis(2-hydroxyethyl)amino)-2-methylphenyl)diazenyl)-3-methyl-2,4-thiophenedicarbonitrile (2:1) (CAS RN 515857-23-5) and — 15 % or more but not more than 25 % of oxirane, 2-methyl-,polymer with oxirane, ether with ethyl 3-(4-bis(2-hydroxyethyl)amino)phenyl)-2-cyano-2-propenoate (2:1) (CAS RN 152286-82-3)	0 %	-	31.12.2030
0.9080	ex 3907 29 20	75	Preparation containing by weight — 60 % or more but not more than 80 % of Oxirane, 2-methyl-,polymer with oxirane, ether with 2,2',2",2"'-(sulfonylbis(4,1-phenylene)-2,1-diazenediyl(3-methyl-4,1-phenylene)nitrilo))tetrakis(ethanol) (4:1) (CAS RN 927432-39-1) and — 20 % or more but not more than 40 % of polyethylene-polypropylene glycol (CAS RN 9003-11-6)	0 %	-	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7478	ex 3907 29 99	20	2,3-Bis(methylpolyoxyethylene-oxy)-1-[(3-maleimido-1-oxopropyl)amino]propyloxy propane (CAS RN 697278-30-1) with a number average molecular weight (Mn) of at least 20 kDa whether or not modified with a chemical entity enabling a linkage between the PEG and a protein or a peptide	0 %	-	31.12.2029
0.2920	ex 3907 29 99	30	Homopolymer of 1-chloro-2,3-epoxypropane (epichlorohydrin)	0 %	-	31.12.2029
0.3269	ex 3907 29 99	45	Copolymer of ethylene oxide and propylene oxide, having aminopropyl and methoxy end-groups	0 %	-	31.12.2029
0.4536	ex 3907 29 99	50	Vinyl-silyl terminated perfluoropolyether polymer or an assortment of two components consisting of the same type of vinyl-silyl terminated perfluoropolyether polymer as the main ingredient	0 %	-	31.12.2029
0.4546	ex 3907 29 99	55	Succinimidyl ester of methoxy poly(ethylene glycol)propionic acid, of a number average molecular weight (Mn) of 5 000	0 %	-	31.12.2029
0.8491	ex 3907 29 99	70	Poly(oxy-1,4-phenyleneoxy-1,4-phenylenecarbonyl-1,4-phenylene) (CAS RN 29658-26-2) containing by weight not more than 35 % of additives	0 %	-	31.12.2027
0.2759	ex 3907 30 00	40	Epoxide resin, containing by weight 70 % or more of silicon dioxide, for the encapsulation of goods of headings 8504, 8533, 8535, 8536, 8541, 8542 or 8548 (1)	0 %	-	31.12.2029
0.7427	ex 3907 30 00	70	Preparation of epoxy resin (CAS RN 29690-82-2) and phenolic resin (CAS RN 9003-35-4) containing by weight: — 65 % or more but not more than 75 % of silicon dioxide (CAS RN 60676-86-0), and — none or not more than 0,5 % of carbon black (CAS RN 1333-86-4)	0 %	-	31.12.2027
0.2541	ex 3907 40 00	35	α-Phenoxycarbonyl-ω-phenoxypoly[oxy(2,6-dibromo-1,4-phenylene) isopropylidene(3,5-dibromo-1,4-phenylene)oxycarbonyl] (CAS RN 94334-64-2)	0 %	-	31.12.2029
0.2564	ex 3907 40 00	45	α-(2,4,6-Tribromophenyl)-ω-(2,4,6-tribromophenoxy)poly[oxy(2,6-dibromo-1,4-phenylene)isopropylidene(3,5-dibromo-1,4-phenylene)oxycarbonyl] (CAS RN 71342-77-3)	0 %	-	31.12.2029
0.9050	*ex 3907 40 00	55	Polycarbonate (CAS RN 235420-85-6) of phosgene and bisphenol A: — containing by weight 12 % or more but not more than 26 % of a copolymer of isophthaloyl chloride, terephthaloyl chloride and resorcinol, — with *p*-cumylphenol endcaps, and — with a weight average molecular weight (Mw) of 29900 or more but not more than 31900	0 %	-	31.12.2030
0.3263	*ex 3907 69 90	10	Copolymer of terephthalic acid and isophthalic acid with ethylene glycol, butane-1,4-diol and hexane-1,6-diol	0 %	-	31.12.2029
0.2980	3907 70 00		Poly(lactic acid)	0 %	-	31.12.2029
0.2918	ex 3907 91 90	10	Diallyl phthalate prepolymer, in powder form	0 %	-	31.12.2029
0.5639	ex 3907 99 80	25	Copolymer, containing 72 % by weight or more of terephthalic acid and/or isomers thereof and cyclohexanedimethanol	0 %	-	31.12.2027
0.4940	ex 3907 99 80 ex 3913 90 00	30 20	Poly(hydroxyalkanoate), predominantly consisting of poly(3-hydroxybutyrate)	0 %	-	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7491	ex 3907 99 80	35	Copolymer in form of a clear, pale yellow liquid, consisting of — phthalic acid isomers and/or aliphatic dicarboxylic acids, — aliphatic diols, and — fatty acid end-caps with: — a hydroxyl number of 120 mg KOH or more but not more than 350 mg KOH, — a viscosity at 25 °C of 2000 cPs or more but not more than 8000 cPs, and — an acid value less than 10 mg KOH/g	0 %	-	31.12.2029
0.5057	ex 3907 99 80	80	Copolymer, consisting of 72 % by weight or more of terephthalic acid and/ or derivatives thereof and cyclohexanedimethanol, completed with linear and/ or cyclic dioles	0 %	-	31.12.2030
0.2923	ex 3908 90 00	10	Poly(iminomethylene-1,3-phenylenemethyleneiminoadipoyl), in one of the forms mentioned in note 6 (b) to Chapter 39	0 %	-	31.12.2029
0.7428	ex 3909 20 00	10	Polymer mixture, containing by weight: — 60 % or more but not more than 75 % of melamine resin (CAS RN 9003-08-1), — 15 % or more but not more than 25 % of silicon dioxide (CAS RN 14808-60-7 or 60676-86-0), — 5 % or more but not more than 15 % of cellulose (CAS RN 9004-34-6), and — 1 % or more but not more than 15 % of phenolic resin (CAS RN 25917-04-8)	0 %	-	31.12.2027
0.6423	ex 3909 50 90	20	Preparation containing by weight: — 14 % or more but not more than 18 % of ethoxylated polyurethane modified with hydrophobic groups, — 3 % or more but not more than 5 % of enzymatically modified starch, and — 77 % or more but not more than 83 % of water	0 %	-	31.12.2029
0.6420	ex 3909 50 90	30	Preparation containing by weight: — 16 % or more but not more than 20 % of ethoxylated polyurethane modified with hydrophobic groups, — 19 % or more but not more than 23 % of diethylene glycol butyl ether, and — 60 % or more but not more than 64 % of water	0 %	-	31.12.2029
0.6424	ex 3909 50 90	40	Preparation containing by weight: — 34 % or more but not more than 36 % of ethoxylated polyurethane modified with hydrophobic groups, — 37 % or more but not more than 39 % of propylene glycol, and — 26 % or more but not more than 28 % of water	0 %	-	31.12.2029
0.6921	*ex 3910 00 00	15	Dimethyl, methyl(propyl(polypropylene oxide)) siloxane (CAS RN 68957-00-6), trimethylsiloxy-terminated	0 %	-	31.12.2031
0.3260	ex 3910 00 00	20	Block copolymer of poly(methyl-3,3,3-trifluoropropylsiloxane) and poly[methyl(vinyl)siloxane]	0 %	-	31.12.2029
0.7057	*ex 3910 00 00	25	Preparations containing by weight: — 10 % or more, 2-hydroxy-3-[3-[1,3,3,3-tetramethyl-1-[(trimethylsilyl)oxy] disiloxanyl] propoxy] propyl-2-methyl-2-propenoate (CAS RN 69861-02-5), and — 10 % or more, α-Butyldimethylsilyl- ω -3-[(2-methyl-1-oxo-2-propen-1-yl) oxy]propyl-terminated silicone polymer (CAS RN 146632-07-7)	0 %	-	31.12.2031
0.7058	*ex 3910 00 00	35	Preparations containing by weight: — 30 % or more, α -Butyldimethylsilyl- ω -(3-methacryloxy-2-hydroxypropyloxy)propyldimethylsilyl-polydimethylsiloxane (CAS RN 662148-59-6) and — 10 % or more, N,N – Dimethylacrylamide (CAS RN 2680-03-7)	0 %	-	31.12.2031

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.4049	*ex 3910 00 00	40	Silicones of a kind used in the manufacture of long term surgical implants	0 %	-	31.12.2031
0.4300	ex 3910 00 00	50	Silicone based pressure sensitive adhesive in solvent containing copoly(dimethylsiloxane/diphenylsiloxane) gum	0 %	-	31.12.2027
0.7218	*ex 3910 00 00	55	Preparation containing by weight: — 55 % or more but not more than 65 % of vinyl terminated polydimethylsiloxane (CAS RN 68083-19-2), — 30 % or more but not more than 40 % of dimethylvinylated and trimethylated silica (CAS RN 68988-89-6), and — 1 % or more but not more than 5 % of silicic acid, sodium salt, reaction products with chlorotrimethylsilane and isopropyl alcohol (CAS RN 68988-56-7)	0 %	-	31.12.2031
0.5926	ex 3910 00 00	70	Passivating silicon coating in primary form, to protect edges and prevent short circuits in semiconductor devices	0 %	-	31.12.2029
0.8670	ex 3910 00 00	85	Two-component silicone, with a viscosity of the mixture of 3 000 cps or more, but not more than 6 000 cps (according to standard GB/T 2794) for use as an electrical insulation material in solar panels junction box in the production of solar panels [(1)]	0 %	-	31.12.2028
0.4413	ex 3911 10 00	81	Non-hydrogenated hydrocarbon resin, obtained by polymerization of more than 75 % by weight C-5 to C-12 cycloaliphatic alkenes and more than 10 % but not more than 25 % by weight aromatic alkenes yielding a hydrocarbon resin with: — an iodine value of more than 120 and — a Gardner Colour of more than 10 for the pure product or — a Gardner Colour of more than 8 for a 50 % solution by weight in toluene (as determined by the ASTM method D6166)	0 %	-	31.12.2029
0.8220	*ex 3911 90 19	15	Polyetherimide of — 5,5′-[(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione) and 1,3-benzenediamine whether or not as a copolymer with 3-aminopropyl terminated dimethylsilicones (CAS RN 61128-46-9 or 99904-16-2), or — 5,5′-[(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione) and 1,4-benzenediamine (CAS RN 61128-47-0), or — 4,4′-[(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione), 5,5′-[(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione), 4,5′-[(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione), pyromellitic dianhydride, 1,2-benzenediamine, 1,3-benzenediamine and 1,4-benzenediamine with phthalic anhydride endcaps (CAS RN 96557-46-9)	0 %	-	31.12.2031
0.8920	ex 3911 90 19	25	Polyamideimide of — 4-Chloroformylphthalic anhydride and 4,4′-methylenedianiline (CAS RN 35463-82-2), or — 4-Chloroformyphthalic anhydride, 4,4′-oxydianiline and 1,3-phenylenediamine (CAS RN 25928-85-2), containing by weight not more than 35 % of additives	0 %	-	31.12.2030
0.4280	ex 3911 90 19	30	Copolymer of ethyleneimine and ethyleneimine dithiocarbamate, in an aqueous solution of sodium hydroxide	0 %	-	31.12.2027
0.5145	*ex 3911 90 19	40	m-Xylene formaldehyde resin	0 %	-	31.12.2031
0.8218	*ex 3911 90 99	23	Aqueous solution consisting of by weight 25 % or more, but not more than 40 % of a poly(isobutylene-maleic anhydride) modified with: — N,N-dimethylpropane-1,3-diamine, — a copolymer of ethylene oxide and propylene oxide, having aminopropyl and methoxy end-groups, — ethanol (CAS RN 497926-97-3)	0 %	-	31.12.2031

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.3257	ex 3911 90 99	25	Copolymer of vinyltoluene and *α*-methylstyrene	0 %	-	31.12.2029
0.5109	ex 3911 90 99	35	Alternated copolymer of ethylene and maleic anhydride (EMA)	0 %	-	31.12.2030
0.8009	ex 3911 90 99	38	Mixture containing by weight: — 90 % (± 1 %) of 1,4:5,8- Dimethanonaphthalene, 2-ethylidene-1,2,3,4,4a,5,8,8a-octahydro-,polymer with 3a,4,7,7a- tetrahydro- 4,7-methano-1H-indene, hydrogenated (CAS RN 881025-72-5), and — 10 % (± 1 %) of a hydrogenated styrene butadiene copolymer (CAS RN 66070-58-4)	0 %	-	31.12.2030
0.3221	ex 3911 90 99	40	Mixed calcium and sodium salt of a copolymer of maleic acid and methyl vinyl ether, having a calcium content of 9 % or more but not more than 16 % by weight	0 %	-	31.12.2029
0.3256	ex 3911 90 99	45	Copolymer of maleic acid and methyl vinyl ether	0 %	-	31.12.2029
0.8010	ex 3911 90 99	48	Mixture containing by weight: — 90 % (± 1 %) of 1,4:5,8-dimethanonaphthalene, 2-ethylidene-1,2,3,4,4a,5,8,8a-octahydro-, polymer with 3a,4,7,7a-tetrahydro-4,7-methano-1H-indene, hydrogenated (CAS RN 881025-72-5), and — 10 % (± 1 %) of an ethylene-propylene copolymer (CAS RN 9010-79-1)	0 %	-	31.12.2030
0.3255	ex 3911 90 99	65	Calcium zinc salt of a copolymer of maleic acid and methyl vinyl ether	0 %	-	31.12.2029
0.8918	ex 3911 90 99	73	A mixture containing by weight: — 89 % or more but not more than 91 % of 1,4:5,8-dimethanonaphthalene, 2-ethylidene-1,2,3,4,4a,5,8,8a-octahydro-, polymer with 3a,4,7,7a-tetrahydro-4,7-methano-1H-indene, hydrogenated (CAS RN 881025-72-5), and — 9 % or more but not more than 11 % of polypropylene homopolymer (CAS RN 9003-07-0)	0 %	-	31.12.2030
0.4091	*ex 3911 90 99	86	Copolymer of methyl vinyl ether and maleic acid anhydride (CAS RN 9011-16-9)	0 %	-	31.12.2031
0.4912	*ex 3912 11 00	30	Cellulose triacetate (CAS RN 9012-09-3)	0 %	-	31.12.2031
0.4953	ex 3912 11 00	40	Cellulose diacetate powder	0 %	-	31.12.2030
0.3251	ex 3912 39 85	10	Ethylcellulose, not plasticized	0 %	-	31.12.2029
0.3253	ex 3912 39 85	20	Ethylcellulose, in the form of an aqueous dispersion containing hexadecan-1-ol and sodium dodecyl sulphate, containing by weight 27 (± 3) % of ethylcellulose	0 %	-	31.12.2029
0.3252	ex 3912 39 85	30	Cellulose, both hydroxyethylated and alkylated with alkyl chain-lengths of 3 or more carbon atoms	0 %	-	31.12.2029
0.6718	ex 3912 39 85	50	Polyquaternium 10 (CAS RN 68610-92-4)	0 %	-	31.12.2030
0.4017	ex 3912 90 10	20	Hydroxypropyl methylcellulose phthalate	0 %	-	31.12.2029
0.3749	ex 3913 90 00	85	Sterile sodium hyaluronate (CAS RN 9067-32-7)	0 %	-	31.12.2029
0.3249	ex 3913 90 00	95	Chondroitinsulphuric acid, sodium salt (CAS RN 9082-07-9)	0 %	-	31.12.2029
0.8323	ex 3914 00 00	10	Aqueous suspension, containing by weight — 20 % or more but not more than 30 % of beaded agarose, modified with nitrilotriacetic acid and loaded with divalent nickel ions (CAS RN 1615227-97-8), and — 20 % or more but not more than 30 % of ethanol (CAS RN 64-17-5)	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.5988	ex 3916 90 10	10	Rods with cellular structure, containing by weight: — polyamide-6 or poly(epoxy anhydride) — 7 % or more but not more than 9 % of polytetrafluorethylene if present — 10 % or more but not more than 25 % of inorganic fillers	0 %	-	31.12.2029
0.8268	ex 3917 32 00	30	Heat shrinkable tube: — containing by weight 80 % or more polymer, — with an insulation resistance of 90 MΩ or more, — with a dielectric strength of 35 kV / mm or more, — with a wall thickness of 0,04 mm or more, but not more than 0,9 mm, — with a lay-flat width of 18 mm or more, but not more than 156 mm, for use in the manufacture of aluminium electrolytic capacitors [(1)]	0 %	-	31.12.2029
0.4641	ex 3917 40 00	91	Plastic connectors containing O-rings, a retainer clip and a release system for insertion into car fuel hoses	0 %	-	31.12.2029
0.2421	ex 3919 10 19 ex 3919 10 80 ex 3919 90 80	10 25 31	Reflecting film, consisting of a layer of polyurethane, with, on one side, security imprints against counterfeiting, alteration or substitution of data or duplication, or an official mark for an intended use, and embedded glass beads and, on the other side, an adhesive layer, covered on one side or on both sides with a release film	0 %	-	31.12.2029
0.4800	ex 3919 10 80 ex 3919 90 80	27 20	Polyester film: — coated on one side with an acrylic thermal release adhesive that debonds at temperatures of 90 °C or more but not more than 200 °C, and a polyester liner, and — on the other side not coated or coated with an acrylic pressure sensitive adhesive or with an acrylic thermal release adhesive that debonds at temperatures of 90 °C or more but not more than 200 °C, and a polyester liner	0 %	-	31.12.2027
0.2910	ex 3919 10 80	35	Reflecting film, consisting of a layer of poly(vinyl chloride), a layer of alkyd polyester, with, on one side, security imprints against counterfeiting, alteration or substitution of data or duplication, or an official mark for an intended use, only visible by means of a retroreflecting lighting, and embedded glass beads and, on the other side, an adhesive layer, covered on one side or on both sides with a release film	0 %	-	31.12.2029
0.4303	ex 3919 10 80 ex 3919 90 80	45 45	Reinforced polyethylene foam tape, coated on both sides with an acrylic micro channelled pressure sensitive adhesive and on one side a liner, with an application thickness of 0,38 mm or more but not more than 1,53 mm	0 %	-	31.12.2027
0.3036	ex 3919 10 80 ex 3919 90 80	55 53	Acrylic foam tape: — covered on one side with a heat activatable adhesive or an acrylic pressure sensitive adhesive, — covered on the other side with an acrylic pressure sensitive adhesive, — covered on one or both sides with a release sheet, — with a peel adhesion of more than 25 N/cm (at an angle of 90 ° as determined by the ASTM D 3330 method)	0 %	-	31.12.2027
0.2416	ex 3919 10 80 ex 3919 90 80 ex 3920 61 00	57 30 30	Reflecting sheet: — of a polycarbonate or acrylic polymer film embossed on one side in a regular shaped pattern — covered on one or both sides with one or more layers of plastic or metallisation, and — whether or not covered on one side with a self-adhesive layer and a release sheet	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.6886	ex 3919 10 80	63	Reflecting film consisting of — a layer of an acrylic resin with imprints against counterfeiting, alteration or substitution of data or duplication, or an official mark for an intended use, — a layer of an acrylic resin having embedded glass beads, — a layer of an acrylic resin hardened by a melamine cross-linking agent, — a metal layer, — an acrylic adhesive, and — a release film	0 %	-	31.12.2030
0.4545	ex 3919 10 80 ex 3919 90 80	73 50	Self-adhesive reflecting sheet whether or not in segmented pieces, — whether or not containing a watermark, — with or without an application tape coated on one side with an adhesive; the reflective sheet consists of: — a layer of acrylic or vinyl polymer, — a layer of poly(methyl methacrylate) or polycarbonate containing microprisms, — a layer of metallisation, — an adhesive layer, and — a release sheet — whether or not containing an additional layer of polyester	0 %	-	31.12.2029
0.5166	*ex 3919 10 80 ex 3919 90 80	75 80	Self-adhesive reflecting film, consisting of several layers including: — a copolymer of acrylic resin, — polyurethane, — a metallised layer with, on one side, laser imprints against counterfeiting, alteration or substitution of data or duplications, or an official mark for an intended use, — glass microspheres, and — an adhesive layer, with a release liner on one or both sides	0 %	-	31.12.2031
0.8667	ex 3919 10 80 ex 3919 90 80	78 48	Polytetrafluoroethylene film, — with a thickness of 50 µm or more, — with a width of 6,30 mm or more but not more than 740 mm, — an elongation at break of not more than 200 %, and — coated on one side with a pressure sensitive silicone adhesive with a thickness of not more than 50 µm	0 %	-	31.12.2028
0.3243	ex 3919 90 80	23	Film consisting of 1 to 3 laminated layers of poly(ethylene terephthalate) and a copolymer of terephthalic acid, sebacic acid and ethylene glycol, coated on one side with an acrylic abrasion resistant coating and on the other side with an acrylic pressure sensitive adhesive, a water soluble methylcellulose coating and a poly(ethylene terephthalate) protective liner	0 %	-	31.12.2029
0.4760	ex 3919 90 80	24	Reflecting laminated sheet: — consisting of an epoxy acrylate layer embossed on one side in a regular shaped pattern, — covered on both sides with one or more layers of plastic material and — covered on one side with an adhesive layer and a release sheet	0 %	-	31.12.2029
0.4415	ex 3919 90 80	33	Transparent poly(ethylene) self-adhesive film, free from impurities or faults, coated on one side with an acrylic pressure sensitive adhesive, with a thickness of 60 µm or more, but not more than 70 µm, and with a width of more than 1 245 mm but not more than 1 255 mm	0 %	-	31.12.2029
0.4445	ex 3919 90 80	49	Reflecting laminated sheet consisting of a film of poly(methyl methacrylate) embossed on one side in a regular shaped pattern, a film of a polymer containing glass microspheres, an adhesive layer and a release sheet	0 %	-	31.12.2029
0.4532	ex 3919 90 80	54	Poly(vinyl chloride) film, on one side covered with — a polymer layer — an adhesive layer — a release liner, on one side embossed, containing oblate spheres; whether or not on the other side covered with an adhesive layer and a metallised polymer layer	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8629	ex 3919 90 80	55	Black polyvinyl chloride film: — with a gloss of more than 25 degrees according to ASTM D 2457, — whether or not covered on one side with a protective film of polyethylene terephthalate and on the other side with a micro-structured pressure sensitive acrylic adhesive and a release liner for use in the manufacture of die-cut films for interior and exterior surfaces of cars [(1)]	0 %	-	31.12.2028
0.4314	ex 3919 90 80	56	Transparent polyethylene film coated on one side with an aqueous acrylic adhesive, of a thickness of 30 µm to 50 µm, put up in rolls of a width of 52 cm or more but not more than 154 cm	0 %	-	31.12.2029
0.9001	ex 3919 90 80	57	Self-adhesive polycarbonate film, printed, whether or not arched, with: — a thickness of 0,3 mm or more, but not more than 0,4 mm, — minimum dimensions of 63 mm x 15 mm, — maximum dimensions of 278 mm x 117 mm, — a weight of not more than 5 g per piece, intended for integration into combined instrument panels of passenger cars	0 %	-	31.12.2030
0.5507	ex 3919 90 80	58	Biaxially-oriented film of poly(methyl methacrylate), with a thickness of 20 µm or more but not more than 90 µm, covered on one side with an adhesive layer and a release sheet	0 %	-	31.12.2029
0.4947	ex 3919 90 80	65	Self-adhesive film with a thickness of 40 µm or more, but not more than 475 µm, consisting of one or more layers of transparent, metallised or dyed poly(ethylene terephthalate), covered on one side with a scratch resistant coating and on the other side with a pressure sensitive adhesive and a release liner	0 %	-	31.12.2030
0.4925	ex 3919 90 80	70	Self-adhesive polishing discs of microporous polyurethane, whether or not coated with a pad	0 %	-	31.12.2030
0.4964	ex 3919 90 80	82	Reflecting film consisting of: — a polyurethane layer, — a glass microspheres layer, — a metallised aluminium layer, and — an adhesive, covered on one or both sides with a release liner, — whether or not a poly(vinyl chloride) layer, — a layer whether or not incorporating security imprints against counterfeiting, alteration or substitution of data or duplication, or an official mark for an intended use	0 %	-	31.12.2030
0.4459	ex 3919 90 80	83	Reflector or diffuser sheets, in rolls, — for protection against ultraviolet or infra-red heat radiation, to be affixed to windows or — for equal transmission and distribution of light, intended for LCD modules	0 %	-	31.12.2027
0.3754	ex 3920 10 89	40	Composite sheet containing an acrylic coating and laminated to a high-density polyethylene layer, of a total thickness of 0,8 mm or more but not more than 1,2 mm	0 %	-	31.12.2027
0.3028	ex 3920 20 29	70	Mono-axial oriented film, consisting of three layers, each layer consisting of a mixture of polypropylene and a copolymer of ethylene and vinyl acetate, with a core layer whether or not containing titanium dioxide, having: — a thickness of 55 µm or more but not more than 97 µm, — a tensile modulus in the machine direction of 0,30 GPa or more but not more than 1,45 GPa, and — a tensile modulus in the transverse direction of 0,20 GPa or more but not more than 0,70 GPa	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.5167	ex 3920 20 29	94	Mono-axial oriented, co-extruded film: — consisting of 3 to 5 layers, — each layer mainly consisting of polypropylene and/or polyethylene, — each layer containing not more than 10 % by weight of other polymers, — whether or not containing titanium dioxide in the core layer, — of an overall thickness of not more than 75 µm	0 %	-	31.12.2027
0.8848	ex 3920 30 00	30	Opaque layer, whether or not printed, biaxially oriented, high impact polystyrene foil in rolls with: — a thickness of 0,229 mm or more but not more than 0,279 mm, — an titanium dioxide content by weight of 3 % or more but not more than 3,5 %, — on one side a highly hydrophobic, chemically neutral and non-reactive coating	0 %	-	31.12.2029
0.3024	ex 3920 43 10	92	Sheeting of poly(vinyl chloride), stabilized against ultraviolet rays, without any holes, even microscopic, of a thickness of 60 µm or more but not more than 80 µm, containing 30 or more but not more than 40 parts of plasticiser to 100 parts of poly(vinyl chloride)	0 %	-	31.12.2029
0.3026	ex 3920 43 10	95	Reflecting laminated sheet, consisting of a film of poly(vinyl chloride) and a film of an other plastic totally embossed in a regular pyramidal pattern, covered on one side with a release sheet	0 %	-	31.12.2029
0.5930	ex 3920 49 10	30	Film of a (polyvinyl)chloride-copolymer — containing by weight 45 % or more of fillers — on a support	0 %	-	31.12.2027
0.3021	ex 3920 51 00	20	Plate of poly(methyl methacrylate) containing aluminium trihydroxide, of a thickness of 3,5 mm or more but not more than 19 mm	0 %	-	31.12.2029
0.5506	ex 3920 51 00	30	Biaxially-oriented film of poly(methyl methacrylate), of a thickness of 50 µm or more but not exceeding 125 µm	0 %	-	31.12.2029
0.5753	ex 3920 51 00	40	Sheets of polymethylmethacrylate conforming to standard EN 4366 (MIL-PRF-25690)	0 %	-	31.12.2029
0.7949	ex 3920 61 00	40	Extruded thermoplastic foils or films of polycarbonate with: — matt surface texture on both sides — a thickness of more than 50 µm but not more than 200 µm, — a width of 800 mm or more, but not more than 1 500 mm, and — a length of 300 m or more, but not more 2500 m for use in the production of retroreflective products [(1)]	0 %	-	31.12.2030
0.7418	ex 3920 62 19 ex 3920 62 90	05 10	Poly(ethylene terephthalate) film in rolls: — with a thickness of 0,335 mm or more but not more than 0,365 mm, and — coated with a gold layer with a thickness of 0,03 µm or more but not more than 0,06 µm	0 %	-	31.12.2027
0.3234	ex 3920 62 19	08	Poly(ethylene terephthalate) film, not coated with an adhesive, of a thickness of not more than 25 µm, either: — only dyed in the mass, or — dyed in the mass and metallised on one side	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8438	ex 3920 62 19	28	Non-transparent film of poly(ethylene terephthalate) or poly(vinyl difluoride): — each outer layer with a thickness of 7 µm or more but not more than 80 µm, — with a tensile strength of 300 N/cm^2 or more (ASTM D-882), — with a total thickness of 200 µm or more but not more than 350 µm, and — with a width of 600 mm or more but not more than 1 600 mm, — covered on one side with a layer of a fluoropolymer, and on the other side with an adhesive and a layer of polyvinylidene difluoride, or coated on both sides with polyvinylidene difluoride or polyvinyl fluoride based on fluorinated polymer composites	0 %	-	31.12.2027
0.4520	ex 3920 62 19	32	Transparent poly(ethylene terephthalate) film: — having thickness of both sides of 7 nm or more but not more than 80 nm, or thickness of both sides of 7 µm or more but not more than 80 µm, whether coated with an acrylic-based organic material or not, — with a surface tension of 36 Dyne/cm or more but not more than 39 Dyne/cm, or transparent 3 or 4 layers, second layer of PET, and other layers contain fluorine resin, — with a light transmittance of more than 70 %, — with a haze value of not more than 1,3 %, — with a total thickness of 10 µm or more but not more than 350 µm, — with a width of 800 mm or more but not more than 1 600 mm	0 %	-	31.12.2028
0.3356	ex 3920 62 19	38	Poly(ethylene terephthalate) film, of a thickness of not more than 12 µm, coated on one side with a layer of aluminium oxide of a thickness of not more than 35 nm	0 %	-	31.12.2029
0.3357	ex 3920 62 19	48	Sheets or rolls of poly(ethylene terephthalate): — coated on both sides with a layer of epoxy acrylic resin, — of a total thickness of 37 µm (± 3 µm)	0 %	-	31.12.2030
0.2589	ex 3920 62 19	52	Film of polyethylene terephthalate, polyethylene naphthalate or similar polyester, coated on one side with metal and/or metal oxides, containing by weight less than 0,1 % of aluminium, of a thickness of not more than 300 µm and having a surface resistivity of not more than 10 000 ohms (per square) (as determined by the ASTM D257 method)	0 %	-	31.12.2029
0.4344	ex 3920 62 19	60	Poly(ethylene terephthalate) film: — of a thickness of not more than 20 µm, — coated on at least one side with a gas barrier layer consisting of a polymeric matrix in which silica or aluminium oxide has been dispersed and of a thickness of not more than 2µm	0 %	-	31.12.2027
0.9057	ex 3920 62 19	70	Poly(ethylene terephthalate) film in rolls with: — a thickness of 35 µm or more, but not more than 75 µm, — a tensile strength of 40 MPa or more in the machine direction (MD) and 200 MPa or more in the transverse direction (TD), — an elongation at break of 400 % or more in MD and 30 % or more in TD, — a heat shrinkage (in water at 90 °C/10s) in MD of 0,49 % or more, but not more than 0,51 %, — a dynamic heat shrinkage (between 55 °C and 70 °C) in TD of not more than 20 percentage points, — a light transmittance of 85 % or more, — a haze ratio of not more than 6 %, — a surface tension of 38 mN/m or more, — a density of 1,30 g/cm^3 or more, but not more than 1,34 g/cm^3, — a shelf life declared by the manufacturer of not less than 12 months	0 %	-	31.12.2030
0.8927	ex 3920 62 19	79	Reflective film of polyethylene terephthalate, embossed in a pyramidal pattern, with — a thickness of 0.07 mm or more but not more than 0.15 mm — a width of 762 mm or more but not more than 1350 mm	0 %	m²	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8839	ex 3920 62 19	85	Three-layer transparent plastic film consisting of a 15 µm fluorinated polymer (FCC) (EVA) layer, a 275 µm polyethylene terephthalate (PET) layer and a 25 µm fluorinated polymer (FCC) layer with: — a total thickness of 300 µm or more, but not more than 330 µm, — a tensile strength of 375 N/cm or more in both the longitudinal and transverse directions (ASTM D-882), — a low thermal shrinkage of 1 % or less at 150 °C for 30 minutes, — a low water vapor permeability of 2,5 g/m²•d or less, and — a high breakdown voltage of 18 kV or more and — a partial discharge voltage of 1500 VDC or more (BG/T 123542.2-2009) to be used as a protective layer on the back of photovoltaic modules	0 %	-	31.12.2029
0.3328	ex 3920 69 00	20	Film of poly(ethylene naphthalene-2,6-dicarboxylate)	0 %	-	31.12.2029
0.7882	ex 3920 69 00	30	Mono- or multilayer, transverse oriented, shrink film: — composed of more than 85 % by weight of polylactic acid, not more than 5 % by weight of inorganic or organic additives and not more than 10 % by weight of additives based on biodegradable polyesters, — with a thickness of 20 µm or more but not more than 100 µm, — with a length of 2 385 m or more but not more than 9 075 m, — biodegradable and compostable (as determined by the method EN 13432)	0 %	-	31.12.2029
0.7883	ex 3920 69 00	70	Mono- or multilayer, biaxially oriented film: — composed of more than 85 % by weight of polylactic acid, not more than 5 % by weight of inorganic or organic additives, and not more than 10 % by weight of additives based on biodegradable polyesters, — with a thickness of 9 µm or more but not more than 120 µm, — with a length of 1 395 m or more but not more than 21 560 m, — biodegradable and compostable (as determined by the method EN 13432)	0 %	-	31.12.2029
0.4766	ex 3920 91 00	52	Poly(vinyl butyral) film: — containing by weight 26 % or more but not more than 30 % of triethyleneglycol bis(2-ethyl hexanoate) as a plasticiser, — with a thickness of 0,73 mm or more but not more than 1,50 mm	0 %	-	31.12.2029
0.3329	ex 3920 91 00	91	Poly(vinyl butyral) film having a graduated coloured band	3 %	-	31.12.2029
0.3136	ex 3920 91 00	93	Film of poly(ethylene terephthalate), whether or not metallised on one or both sides, or laminated film of poly(ethylene terephthalate) films, metallised on the external sides only, and having the following characteristics: — a visible light transmission of 50 % or more, — coated on one or both sides with a layer of poly(vinyl butyral) but not coated with an adhesive or any other material except poly(vinyl butyral), — a total thickness of not more than 0,2 mm without taking the presence of poly(vinyl butyral) into account and a thickness of poly(vinyl butyral) of more than 0,2 mm	0 %	-	31.12.2029
0.4508	ex 3920 91 00	95	Co-extruded trilayer poly(vinyl butyral) film with a graduated colour band containing by weight 29 % or more but not more than 31 % of 2,2'-ethylenedioxydiethyl bis(2-ethylhexanoate) as a plasticiser	0 %	-	31.12.2029
0.3917	ex 3920 99 28	40	Polymer film containing the following monomers: — poly (tetramethylene ether glycol), — bis (4-isocyanotocyclohexyl) methane, — 1,4-butanediol or 1,3-butanediol, — with a thickness of 0,25 mm or more but not more than 5,0 mm, — embossed with a regular pattern on one surface, — and covered with a release sheet	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.6579	ex 3920 99 28	65	Matt, thermoplastic polyurethane foil in rolls with: — a width of 1640 mm (± 10 mm), — a gloss of 3,3 degrees or more but not more than 3,8 (as determined by the method ASTM D2457), — a surface roughness of 1,9 Ra or more but not more than 2,8 Ra (as determined by the method ISO 4287), — a thickness of more than 365 µm but not more than 760 µm, — a hardness of 90 (± 4) (as determined by the method: Shore A (ASTM D2240)), — an elongation to break of 470 % (as determined by the method: EN ISO 527)	0 %	m²	31.12.2029
0.3326	ex 3920 99 59	25	Poly(1-chlorotrifluoroethylene) film	0 %	-	31.12.2029
0.3135	ex 3920 99 59	65	Film of a vinyl alcohol copolymer, soluble in cold water, of a thickness of 34 µm or more but not more than 90 µm, a tensile strength at break of 20 MPa or more but not more than 55 MPa and an elongation at break of 250 % or more but not more than 900 %	0 %	-	31.12.2029
0.6066	ex 3921 19 00	30	Blocks with cellular structure, containing by weight: — polyamide-6 or poly(epoxy anhydride) — 7 % or more but not more than 9 % of polytetrafluorethylene if present — 10 % or more but not more than 25 % of inorganic fillers	0 %	-	31.12.2029
0.9055	ex 3921 19 00	53	Sheets of closed-cell silicone foam with: — a thickness of 2,0 mm or more but not more than 4,8 mm, — a thermal insulation of more than 0,25 Km²/W but not more than 0,4 Km²/W (according to ASTM-C518) — a dielectric strength of more than 3,0 Kv/mm but not more than 3,8 Kv/mm (according to ASTM- D149)	0 %	-	31.12.2030
0.8913	ex 3921 19 00	55	Strip of microporous polytetrafluoroethylene on a support of a non-woven — wound on a roll on a core of 3 inches, — with a width of 69.5mm, 40.8mm, 36.5mm, 20mm, 13.5mm or 10mm for use in the manufacture of filters for kidney dialysis equipment and intravenous application (1)	0 %	m²	31.12.2030
0.6911	*ex 3921 19 00	65	Transparent, microporous, acrylic acid grafted polyethylene film, in the form of rolls, for the manufacture of alkaline battery separators with: — a width of 98 mm or more but not more than 170 mm, — a thickness of 15 µm or more but not more than 36 µm,	3.2 %	-	31.12.2027
0.7263	*ex 3921 19 00	75	Microporous monolayer film of polypropylene or a microporous trilayer film of polypropylene, polyethylene and polypropylene, each film with: — zero shrinkage in the transversal production direction, — a total thickness of 8 µm or more but not more than 40 µm, — a width of 15 mm or more but not more than 900 mm, — a length of more than 200 m, but not more than 8 000 m, — an average pore size of 0,02 µm or more but not more than 0,1 µm, — whether or not laminated with a polypropylene non-woven fabric with a thickness of 50 µm or more but not more than 200 µm, — whether or not coated with surfactant, — whether or not coated on 1 or 2 sides with a ceramic layer with a thickness of 1 µm or more but not more than 5 µm, — whether or not coated on 1 or 2 sides with a sticky binder of polyvinyl difluoride or a similar polymer with a thickness of 0,5 µm or more, but not more than 5 µm	3.2 %	-	31.12.2027
0.3002	ex 3921 19 00	95	Film of polyethersulfone, of a thickness of not more than 200 µm	0 %	-	31.12.2029
0.3003	ex 3921 90 10	10	Composite plate of poly(ethylene terephthalate) or of poly(butylene terephthalate), reinforced with glass fibres	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.6156	ex 3921 90 10	30	Multilayer film consisting of: — a poly(ethylene terephthalate) film with a thickness of more than 100 µm but not more than 150 µm, — a primer of phenolic material with a thickness of more than 8 µm but not more than 15 µm, — an adhesive layer of a synthetic rubber with a thickness of more than 20 µm but not more than 30 µm, — and a transparent poly(ethylene terephthalate) liner with a thickness of more than 35 µm but not more than 40 µm	0 %	m²	31.12.2029
0.4844	ex 3921 90 55	25	Prepreg sheets or rolls containing polyimide resin	0 %	-	31.12.2029
0.7510	ex 3921 90 55	35	Glass fiber impregnated with epoxy resin for use in the manufacture of smart cards (1)	0 %	m²	31.12.2029
0.6742	ex 3921 90 55	40	Three layered fabric sheet, in rolls, — comprising a core layer of 100 % Nylon Taffeta or Nylon/Polyester blended Taffeta, — coated on both sides with polyamide, — of a total thickness not more than 135 µm, — of a total weight not more than 80 g/m^2	0 %	m²	31.12.2030
0.9135	*ex 3921 90 55	45	Prepregs (sheets and films, rectangular) consisting of epoxy resins and glass fiber fabric	0 %	-	31.12.2031
0.5396	*ex 3923 10 90	10	Photomask or wafer compacts: — consisting of antistatic materials or blended thermoplastics proving special electrostatic discharge (ESD) and outgassing properties, — having non porous, abrasion resistant or impact resistant surface properties, — fitted with a specially designed retainer system that protects the photomask or wafers from surface or cosmetic damage and — with or without a gasket seal, of a kind used in the photolithography or other semiconductor production to house photomasks or wafers	0 %	-	31.12.2031
0.7630	ex 3926 30 00	40	Plastic internal door handle used in the manufacture of motor vehicles (1)	0 %	-	31.12.2029
0.7335	ex 3926 30 00 ex 3926 90 97	50 48	Coated interior or exterior decorative parts consisting of: — a copolymer of acrylonitrile-butadiene-styrene (ABS), whether or not mixed with polycarbonate, and — a PVC foil, — not containing layers of copper, nickel or chromium, for use in the manufacturing of parts for motor vehicles of heading 8701 to 8705 (1)	0 %	p/st	31.12.2027
0.2764	ex 3926 90 97	10	Microspheres of a polymer of divinylbenzene, of a diameter of 4,5 µm or more but not more than 80 µm	0 %	-	31.12.2029
0.8664	ex 3926 90 97	22	Gaskets for road vehicles mirrors and their components, made of polyethylene foam, produced by a thermoforming process and with: — a density of 20 kg/m^3 or more, but not more than 40 kg/m^3, — a tensile strength of not less than 170 kPa, — water absorption coefficient of not greater than 1 %, — a length of 5 mm or more but not more than 300 mm, — a height of 10 mm or more but not more than 400 mm, — a depth of 5 mm or more but not more than 250 mm	0 %	-	31.12.2028
0.6717	ex 3926 90 97	23	Plastic cover with clips for the exterior rear-view mirror of motor vehicles	0 %	p/st	31.12.2030
0.7445	ex 3926 90 97	27	Gasket of polyethylene foam, intended to fill-up the space between the body of a motor vehicle and the base of a rear-view mirror	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.5474	*ex 3926 90 97	30	Parts of car radio and car air-conditioner front panels — of acrylonitrile-butadiene-styrene with or without polycarbonate, — coated with a copper, a nickel and a chrome layers, — with a total thickness of coating of 5,54 µm or more but not more than 49,6 µm	0 %	-	31.12.2031
0.6301	ex 3926 90 97	33	Housings, housing parts, drums, setting wheels, frames, covers, upper part, design plate and other parts of acrylonitrile-butadiene-styrene, polycarbonate, polymethylmethacrylate or thermoplastic polyurethane, of a kind used for the manufacture of remote controls	0 %	p/st	31.12.2029
0.7061	*ex 3926 90 97	40	Silicone shell for breast implant	0 %	-	31.12.2031
0.3850	ex 3926 90 97	43	Mixture of water and by weight 19 % or more but not more than 35 % of expanded hollow microspheres of a copolymer of acrylonitrile, methacrylonitrile and isobornyl methacrylate or other methacrylate, of a diameter of 3 µm or more but not more than 4,95 µm	0 %	-	31.12.2029
0.9176	*ex 3926 90 97	53	Window panel: — made of a methyl methacrylate acrylonitrile butadiene styrene copolymer or polymethyl methacrylate, — with a weight of 39,7 g or more but not more than 108 g, — with a print in black, silver, metallic silver, or blue colors made using In-Mould Labelling technology or screen-printing technology, — with or without a hole with a diameter of 42 mm	0 %	-	31.12.2031
0.7196	*ex 3926 90 97	77	Silicone decoupling ring with an inner diameter of 13,2 mm or more but no more than 17,2 mm, in immediate packings of 2 500 pieces or more, of a kind used in car parking aid sensor systems	0 %	p/st	31.12.2031
0.8504	ex 4009 31 00 ex 4009 32 00	10 20	Multilayered rubber pipe, reinforced with aramide fabric, whether or not having polyamide connection elements and steel clamps, for use in the manufacture of automotive heat exchangers and/or condenser in automotive air conditioning systems (1)	0 %	-	31.12.2027
0.7042	ex 4010 31 00 ex 4010 33 00 ex 4010 39 00	10 10 10	Vulcanized rubber endless transmission belt of trapezoidal cross-section (V-belts) with longitudinal V-ribbed pattern on the inner side for use in the manufacture of goods of Chapter 87 (1)	0 %	-	31.12.2029
0.6844	ex 4016 93 00	30	Rectangular ethylene-propylene-diene rubber gasket, with: — a length of 72 mm or more but not more than 825 mm, — a width of 18 mm or more but not more than 155 mm, — a peak temperature of 150°C or more but not more than 240°C, — a permissible material outflow at the place of the mold split of not more than 0,3 mm	0 %	-	31.12.2030
0.8646	ex 4016 99 52	10	Hanger of the exhaust muffler consisting of: — a steel bracket with at least one mounting hole and — silent block, for use in the manufacture of goods of Chapter 87 (1)	0 %	-	31.12.2028
0.8925	ex 4016 99 57	40	Wiper rubber used in the manufacture of windshield wipers, — made of a mixture of natural rubber and chloroprene rubber — with a Shore hardness of 60A (1)	0 %	-	31.12.2030
0.5148	*ex 4016 99 97	30	Tyre moulding bladder	0 %	-	31.12.2031
0.5842	ex 4104 41 19	10	Buffalo leather, split, chrome tanned synthetic retanned ("crust"), dry	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.2555	4105 10 00 4105 30 90		Sheep or lamb skin leather, without wool on, tanned or retanned but not further prepared, whether or not split, other than leather of heading 4114	0 %	-	31.12.2029
0.2553	4106 21 00 4106 22 90		Goat or kid skin leather, without hair on, tanned or retanned but not further prepared, whether or not split, other than leather of heading 4114	0 %	-	31.12.2029
0.2554	4106 31 00 4106 32 00 4106 40 90 4106 92 00		Leather of other animals, without hair on, not further prepared than tanned, other than leather of heading 4114	0 %	-	31.12.2029
0.6223	ex 4408 39 30	10	Okoumé sheets for veneering for plywood panels — with a largest dimension of 900 mm or more, but not more than 3 250 mm, — with a smallest dimension of 95 mm or more but not more than 2 000 mm, — with a thickness of 0,5 mm or more, but not more than 4 mm, — unsanded, — not planed, and — sawn, sliced or peeled lengthwise	0 %	-	31.12.2029
0.8737	ex 4408 39 95	10	Iroko sheets for veneering for plywood panels: — with a largest dimension of 900 mm or more, but not more than 3 250 mm, — with a smallest dimension of 95 mm or more but not more than 2 000 mm, — with a thickness of more than 1 mm, but not more than 4 mm, — unsanded, — not planed, and — sawn, sliced or peeled lengthwise	0 %	-	31.12.2029
0.8733	ex 4408 39 95	20	Igaganga sheets for veneering for plywood panels: — with a largest dimension of 900 mm or more, but not more than 3 250 mm, — with a smallest dimension of 95 mm or more but not more than 2 000 mm, — with a thickness of more than 1 mm, but not more than 4 mm, — unsanded, — not planed, and — sawn, sliced or peeled lengthwise	0 %	-	31.12.2029
0.8738	ex 4408 39 95	30	Ozigo sheets for veneering for plywood panels: — with a largest dimension of 900 mm or more, but not more than 3 250 mm, — with a smallest dimension of 95 mm or more but not more than 2 000 mm, — with a thickness of more than 1 mm, but not more than 4 mm, — unsanded, — not planed, and — sawn, sliced or peeled lengthwise	0 %	-	31.12.2029
0.8372	ex 4411 12 92	10	Fibreboard: — with a thickness of 2,20 mm or more but not more than 2,80 mm, — with a density of 0,95 g/cm^3 or more, — lacquered or coated with melamine foil on both sides, and — with dimensions of 1 300 mm x 1 100 mm or less	0 %	-	31.12.2027
0.4217	*ex 5004 00 10	10	Silk yarn (other than yarn spun from silk waste) not put up for retail sale, unbleached, scoured or bleached, entirely of silk	0 %	-	31.12.2031
0.2551	ex 5005 00 10 ex 5005 00 90	10 10	Yarn spun entirely from silk waste (noil), not put up for retail sale	0 %	-	31.12.2029
0.2544	*5208 11 10		Fabrics for the manufacture of bandages, dressings and medical gauzes	5.2 %	-	31.12.2029
0.7372	ex 5311 00 90	10	Plain-woven fabric of paper yarns glued on a tissue paper layer: — with a weight of 190 g/m^2 or more but not more than 280 g/m^2, and — cut into rectangles with a side length of 40 cm or more but not more than 140 cm	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.9048	ex 5401 10 14	10	Core yarn of high tenacity polyester filament surrounded by polyester staple fibres: — with a twist of 410 TPM or more but not more than 1200 TPM, — with a linear density of 200 dtex or more but not more than 1500 dtex, — with an average tenacity of 46 cN/tex or more, — with an elongation at break of 13 % or more but not more than 23 %, — wound on a perforated dyeing tube, — with a weight, including tube, of 900 g or more	0 %	-	31.12.2030
0.9003	ex 5402 20 00	07	High tenacity polyester multifilament yarn: — with final twist in Z direction; — with a linear density of 100 dtex or more, but not more than 4000 dtex — with an average minimum tenacity of 64 cN/tex; — with an elongation at break of 12 % or more, but not more than 28 %; — with a shrinkage in 98 °C of 0 % or more, but not more than 3,5 %; — wound on the perforated dyeing tube with 0,9 kg of yarn or more ready for dyeing	0 %	-	31.12.2030
0.8916	ex 5402 33 00	10	Textured polyester yarn: — textured using single heater and double heater methods in accordance with DIN 53840-T1 standard, — with a linear density of 83 dtex or more, but not more than 666 dtex, — with an average minimum tenacity of 32 cN/tex, — with a filament count of 36 or more, but not more than 192, — with an elongation at break of 16 % or more, but not more than 33 %, — with a boiling water shrinkage of 3 % or more, but not more than 8 %, — containing by weight 1 % or more but not more than 3 % of mineral oil, synthetic oil or mixed oils	0 %	-	31.12.2030
0.2975	ex 5402 49 00	30	Yarn of a copolymer of glycollic acid with lactic acid, for the manufacture of surgical sutures (1)	0 %	-	31.12.2029
0.3098	ex 5402 49 00	50	Non-textured filament yarn of poly(vinyl alcohol)	0 %	-	31.12.2029
0.8108	*ex 5403 31 00	10	Continuous viscose rayon filament yarn of 105 dtex or more but not more than 117 dtex, and consisting of 36 monofilaments or more but not more than 40 monofilaments	0 %	-	31.12.2031
0.8225	*ex 5404 19 00	60	Chemically tapered synthetic filaments of polyester with: — a diameter of 0,1 mm or more but not more than 0,6 mm, — a length of 30 mm or more but not more than 120 mm, for use in the manufacture of paintbrushes (1)	0 %	-	31.12.2027
0.3311	ex 5404 90 90	20	Strip of polyimide	0 %	-	31.12.2029
0.8382	ex 5407 30 00	10	Open mesh fabric made of thermally cross-bonded filaments of a polyolefin, with a density of 0,94 g/cm^3 or more, with: — a weight of 21 g/m^2 or more but not more than 24 g/m^2, — a width of 560 mm or more but not more than 1 200 mm, — a thickness of 100 µm or more but not more than 120 µm, — an elongation at break of not more than 20 % (ASTM D5034, machine direction), — an elongation at break of not more than 22 % (ASTM D5034, cross direction), — with a stretch of not more than 100 N /5 cm (ASTM D882, machine direction), and — with a stretch of not more than 130 N /5 cm (ASTM D882, cross direction)	0 %	-	31.12.2027
0.3214	ex 5503 90 00 ex 5506 90 00 ex 5601 30 00	20 10 10	Poly(vinyl alcohol) fibres, whether or not acetalized	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.9063	ex 5503 90 00	40	Staple fibres with a poly(ethylene terephthalate) core fully encapsulated by polyethylene with: — a linear density of 0,60 dtex or more but not more than 1,60 dtex, — a staple fibre length of 37 mm or more but not more than 44 mm, — an elongation at break of 80 % or more, — a tenacity of 1 cN/dtex or more	0 %	-	31.12.2030
0.3212	ex 5603 11 10 ex 5603 11 90 ex 5603 12 10 ex 5603 12 90 ex 5603 91 10 ex 5603 91 90 ex 5603 92 10 ex 5603 92 90	10 10 10 10 10 10 10 10	Poly(vinyl alcohol) non-wovens, in the piece or cut into rectangles: — of a thickness of 200 µm or more but not more than 280 µm and — of a weight of 20 g/m^2 or more but not more than 50 g/m^2	0 %	m²	31.12.2029
0.2552	ex 5603 12 90 ex 5603 13 90 ex 5603 14 80 ex 5603 92 90 ex 5603 93 90 ex 5603 94 80	30 30 10 60 40 30	Non-wovens of aromatic polyamide fibres obtained by polycondensation of *m*-phenylenediamine and isophthalic acid, in the piece or cut into rectangles	0 %	m²	31.12.2028
0.2548	ex 5603 12 90 ex 5603 13 90	60 60	Non-woven of spunbonded polyethylene, of a weight of more than 60 g/m^2 but not more than 80 g/m^2 and an air resistance (Gurley) of 8 seconds or more but not more than 36 seconds (as determined by the ISO 5636/5 method)	0 %	m²	31.12.2029
0.5059	ex 5603 13 10	20	Non-woven of spunbonded polyethylene, with a coating, — of a weight of more than 80 g/m² but not more than 105 g/m² and — an air resistance (Gurley) of 8 seconds or more but not more than 75 seconds (as determined by the ISO 5636/5 method)	0 %	m²	31.12.2030
0.3042	ex 5603 92 90 ex 5603 94 80	70 40	Non-wovens, consisting of multiple layers of a mixture of meltblown fibres and staple fibres of polypropylene and polyester, whether or not laminated on one side or on both sides with spunbonded filaments of polypropylene	0 %	m²	31.12.2028
0.3210	ex 5603 94 80	20	Acrylic fibre rods, having a length of not more than 50 cm, for the manufacture of pen tips (1)	0 %	m²	31.12.2028
0.8939	ex 5603 94 80	50	Needle-punched spunbond nonwovens, consisting of polyamide fibres individually coated with polyvinylalcohol, containing by weight 20 % or more but not more than 40 % of polyvinylalcohol weighing 400 g/m2 or more	0 %	-	31.12.2030
0.2415	ex 5803 00 10	91	Gauze of cotton, of a width of less than 1 500 mm	0 %	-	31.12.2029
0.2453	*ex 5907 00 00	10	Textile fabrics, coated with adhesive in which are embedded spheres of a diameter of not more than 150 µm	0 %	-	31.12.2031
0.8024	ex 5911 40 00	10	Non-wovens, consisting of poly(ethylene terephthalate) spun bonded media: — in the piece, cut to length or simply cut to rectangular (including square) shape, — of weight of 160 g/m² or more but not more than 300 g/m², — with a filtration efficiency of class L or better (according to DIN 60335-2-69), — pleatable, with or without following treatments: — a coating or covering with polytetrafluoroethylene (PTFE), — a coating with aluminium particles, — a coating of phosphorous based flame retardants, — a nano fiber coating of a polyamide, a polyurethane or a fluorine-containing polymer — an expanded polytetrafluoroethylene (ePTFE) membrane	0 %	m²	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.3207	ex 5911 90 99 ex 8421 99 90	30 92	Parts of equipment for the purification of water by reverse osmosis, consisting essentially of plastic-based membranes, supported internally by woven or non-woven textile materials which are wound round a perforated tube, and enclosed in a cylindrical plastic casing of a wall-thickness of not more than 4 mm, whether or not housed in a cylinder of a wall-thickness of 5 mm or more	0 %	-	31.12.2029
0.4638	ex 5911 90 99	40	Multi-layered non-woven polyester polishing pads, impregnated with polyurethane	0 %	-	31.12.2029
0.7340	ex 5911 90 99	50	Loudspeaker vibration damper, made from round, corrugated, flexible and cut-to-size tissue of textile fibres of polyester, cotton or aramid or a combination hereof, of a kind used in car loudspeakers	0 %	-	31.12.2027
0.6469	ex 6804 21 00	20	Discs — of synthetic diamonds which are agglomerated with a metal alloy, ceramic alloy or plastic alloy, — having a self-sharpening effect by constant release of the diamonds, — suitable for abrasive cutting of wafers, — whether or not containing a hole in the centre, — whether or not on a support — with a weight of not more than 377 g per piece and — with an external diameter of not more than 206 mm	0 %	p/st	31.12.2029
0.8666	ex 6804 21 00	40	Steel wire used for cropping and squaring semiconductors: — coated with diamond grains of 5µm or more, but not more than 55µm — wire diameter 23 µm or more but not more than 350 µm, — having a breaking strength of 11 N or more, but not more than 170 N	0 %	-	31.12.2028
0.9053	*ex 6804 21 00	50	Wheels suitable for grinding, rounding, polishing, aligning or cutting: — composed of metal base and agglomerated synthetic or natural diamonds, — whether or not containing a hole in the centre, — with an external diameter not more than 870 mm, for machines for the manufacture of semiconductor wafers	0 %	-	31.12.2031
0.2755	ex 6813 89 00	20	Friction material, of a thickness of less than 20 mm, not mounted, for use in the manufacture of friction components (1)	0 %	-	31.12.2029
0.5931	ex 6814 10 00	10	Agglomerated mica with a thickness of not more than 0,15 mm, on rolls, whether or not calcined, whether or not reinforced with aramid fibres	0 %	-	31.12.2029
0.8998	ex 6814 10 00	20	Phlogopite mica tape bonded with silicone resin to a glass fabric reinforced polyethylene film, — with a thickness of 0,10 mm or more but not more than 1,60 mm, — with a width of 500 mm or more but not more than 1200 mm, — a mica content of 80 g/m² or more but not more than 165 g/m², — a tensile strength of 110 N/cm or more but not more than 130 N/cm	0 %	-	31.12.2030
0.2546	ex 6903 90 90	40	Silicon carbide reactor tubes and holders having a maximum service temperature of 1370 °C or more	0 %	-	31.12.2029
0.4978	ex 6909 19 00	20	Silicon nitride (Si_3N_4) rollers or balls	0 %	-	31.12.2030
0.6071	ex 6909 19 00	25	Ceramic proppants, containing aluminium oxide, silicon oxide and iron oxide	0 %	-	31.12.2029
0.3403	ex 6909 19 00	30	Supports for catalysts, consisting of porous cordierite or mullite ceramic pieces, of an overall volume of not more than 65 l, having, per cm^2 of the cross-section, not less than one continuous channel which may be open at both ends or stopped at one end	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8028	ex 6909 19 00	40	Ceramic-carbon absorption or adsorption cartridges of fuel motor vehicle systems, with the following characteristics: — extruded fired ceramic bound multicellular cylindrical structure, — 5 % or more by weight but not more than 70 % by weight of activated carbon, — 30 % or more by weight but no more than 90 % by weight of ceramic binder, — with a diameter of 29 mm or more but no more than 41 mm, — a length of not more than 150 mm, — fired at temperature of 800 °C or more	0 %	p/st	31.12.2030
0.2538	ex 6909 19 00 ex 6914 90 00	50 20	Ceramic articles made of continuous filaments of ceramic oxides, containing by weight: — 2 % or more of diboron trioxide, — 28 % or less of silicon dioxide and — 60 % or more of dialuminium trioxide	0 %	-	31.12.2029
0.3766	ex 6909 19 00	60	Supports for catalysts, consisting of porous ceramic pieces, of a blend of silicon carbide and silicon, with a hardness of less than 9 on the Mohs scale, with a total volume of not more than 65 litres, having, per cm² of the surface of the cross section one or more closed channels at the tail end	0 %	-	31.12.2029
0.4582	ex 6909 19 00	70	Supports for catalysts or filters, consisting of porous ceramics made primarily from oxides of aluminium and titanium; with a total volume of not more than 65 litres and at least one duct (open on one or both ends) per cm² of cross section	0 %	-	31.12.2029
0.3404	ex 6914 90 00	30	Ceramic microspheres, transparent, obtained from silicon dioxide and zirconium dioxide, of a diameter of more than 125 µm	0 %	-	31.12.2029
0.9059	ex 7002 20 90	10	Cylindrical shaped glass preforms of high-purity silica glass (quartz): — with an optical core made of germanium-doped silica glass (quartz), intended for the production of low-loss optical fiber: — with a length of not more than 2500 mm, — with a diameter of 115 mm or more but not more than 139 mm, — on one side with a conical end — on the other side with a handle with a diameter of 25,4 mm, coated at the end with aluminium oxide	0 %	-	31.12.2030
0.8860	ex 7007 19 80	86	A ready-to-install, circular graded tempered glass of the cover of door assembly in washing machines with: — a light transmittance of 34,2 % or more but not more than 37,8 %, — a diameter of 477,2 mm or more but not more than 477,8 mm, — a thickness of 2,9 mm or more but not more than 3,5 mm, — a weight of 1345 g or more but not more than 1445 g, — 3-zone structure including Euro Deep Gray colour printed zone [(1)]	0 %	-	31.12.2029
0.6380	ex 7009 10 00	30	Layered glass with mechanical dimming ability by different angles of incident light comprising: — whether or not a layer of chrome, — a break-resistance adhesive tape or hot-melt adhesive, and — a release film on the front side and protective paper at the back side, of a kind used for interior rear-view mirrors of vehicles	0 %	p/st	31.12.2029
0.5789	ex 7009 10 00	50	Unfinished electro-chromic auto-dimming mirror for motor vehicle rear-view mirrors: — whether or not equipped with plastic backing plate, — whether or not equipped with a heating element, — whether or not equipped with Blind Spot Module (BSM) display	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.6870	ex 7009 10 00	60	Electrochromic self-dimming inside rear-view mirror: — with a mirror support — in a plastic casing and — with an integrated circuit, — whether or not with a high beam assistant, — whether or not with a digital compass, — whether or not with a garage door opener, — whether or not with an integrated toll module, — whether or not with a camera for driver and/or cabin monitoring, — whether or not with an infrared filter, for use in the manufacture of motor vehicles of Chapter 87 (1)	0 %	-	31.12.2030
0.8682	*ex 7009 10 00	70	Aspherical, convex or flat chrome-plated glass, ready for framing: — with a length of 140 mm or more but not more than 215 mm, — with a height of 104 mm or more but not more than 138 mm, — with curvature radius of 0 mm or more but not more than 1 330 mm, — with a reflectance of more than 40 %, for the manufacture of automotive mirrors (1)	0 %	-	31.12.2028
0.8663	ex 7009 91 00	10	Chrome-plated glass mirror with: — a length of 155 mm or more, but not more than 158 mm, — a height of 115 mm or more, but not more than 120 mm, — a blind spot sensor with a blind spot motion detection light module, with an edge luminescence greater than or equal to 5 000 cd/m^2 and a central luminescence greater than or equal to 7 000 cd/m^2, — a heater foil, with a resistance of 1,1 kΩ or more, but not more than 1,35 kΩ, designed to be mounted in a housing as an exterior vehicle mirror, for use in the manufacture of car mirrors (1)	0 %	-	31.12.2028
0.3400	ex 7014 00 00	10	Optical elements of glass (other than those of heading 7015), not optically worked, other than signalling glassware	0 %	-	31.12.2029
0.9054	ex 7019 61 00	60	Flexible prepreg in sheets or rolls, — of modified epoxy resin with embedded glass fabric, — without halogenated flame retardants — with a TMA glass transition of 145 °C or more but not more than 200 °C (ASTM E1545) — specified according to IPC-4101/128, 130, 153 or 154	0 %	-	31.12.2030
0.7647	ex 7019 64 00	40	Epoxy resin coated glass woven fabric containing by weight: — 91 % or more but not more than 93 % of glass fibres, — 7 % or more but not more than 9 % of epoxy resin	0 %	-	31.12.2029
0.8915	ex 7019 80 10	40	Vacuum insulated panel consisting of hermetic aluminum foil and stiff core, without air inside, used for thermal reinforcement of fridges and freezers and combination of them, with: — a glass wool filling, — a thickness of 5,6 mm or more but not more than 35 mm, — a length of 195 mm or more but not more than 1 875 mm, — a width of 155 mm or more but not more than 545 mm, — a thermal conductivity lower than or equal to 2,5 mW/mK, — an internal pressure below 1,0 Pa, — an ambient operating temperature of -50 °C or more but not more than 80 °C	0 %	p/st	31.12.2030
0.3940	ex 7019 80 90	10	Glass wool in which fibres of a diameter of less than 4,6 µm predominate	0 %	-	31.12.2028
0.4024	ex 7019 90 00	30	High modulus glass cord (K) impregnated with rubber, obtained from twisted high modulus glass filament yarns, coated with a latex comprising a resorcinol-formaldehyde resin with or without vinylpyridine and/or hydrogenated acrylonitrile-butadiene rubber (HNBR)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8616	ex 7019 90 00	50	Insulating rigid panels made by vacuum compression of glass fibres wrapped in protective gas-tight film, for use in the manufacture of refrigerators and freezers and their combinations (1)	0 %	-	31.12.2028
0.8903	ex 7019 90 00	60	Vacuum insulation panel, consisting of a gas-tight aluminum foil housing surrounding a rigid, air-free core with: — a glass fiber filling, — a thickness of 5,6 mm or more but not more than 32,4 mm, — a length of 195 mm or more but not more than 1 835 mm, — a width of 155 mm or more but not more than 545 mm, — a thermal conductivity lower than or equal to 2,5 mW/mK, — an internal pressure below 1,0 Pa, — an ambient temperature during operation of -50 °C or more but not more than 80 °C	0 %	p/st	31.12.2029
0.5348	*ex 7020 00 10 ex 7616 99 90	10 77	Television pedestal stands with or without bracket for fixation to and stabilization of television cabinet case/body	0 %	p/st	31.12.2031
0.7266	ex 7020 00 10	20	Raw material for optical elements of fused silicon dioxide with: — a thickness of 10 cm or more but not more than 40 cm, and — a weight of 100 kg or more	0 %	p/st	31.12.2027
0.4128	*ex 7201 10 30	10	Pig iron ingots with a length of not more than 350 mm, a width of not more than 150 mm, a height of not more than 150 mm, containing by weight not more than 1 % of silicon	0 %	-	31.12.2031
0.3353	7202 50 00		Ferro-silico-chromium	0 %	-	31.12.2029
0.7502	ex 7318 24 00	40	Tube or pipe restraint joint elements: — of stainless steel according to specification 17-4PH or of steel according to specification tool steel S7, — produced by metal injection moulding, — with a rockwell hardness of 38 HRC (± 1) or 53 HRC (+ 2/– 1), — measuring 7 mm x 4 mm x 5 mm or more, but not more than 40 mm x 20 mm x 10 mm	0 %	-	31.12.2029
0.4126	*ex 7326 20 00	20	Metal fleece, consisting of a mass of stainless steel wires of diameters of 0,001 mm or more but not more than 0,070 mm, compacted by sintering and rolling	0 %	-	31.12.2031
0.6680	ex 7326 90 98 ex 7907 00 00	40 10	Iron, steel and/or zinc alloy weights: — with a weight of not more than 500 grams and measuring not more than 107 mm x 107 mm x 11 mm, — whether or not with parts of other material, — whether or not with parts of other metals, — whether or not surface treated, — whether or not printed, of a kind used for the production of remote controls	0 %	-	31.12.2030
0.8480	ex 7326 90 98	60	Vane ring of a kind for fastening gas flow control blades: — of iron or steel alloy, — with a heat resistance of 830 °C or more but not more than 1 050 °C, — with an external diameter of not more than 92 mm, — with holes for holding the gas flow control blades, for use in the manufacture of turbochargers (1)	0 %	-	31.12.2027
0.8512	ex 7326 90 98	70	Disc of a kind for ensuring the gas flow channel width: — of iron or steel alloy, — with a heat resistance of 830 °C or more but not more than 1 050 °C, — with an external diameter of not more than 92,5 mm, — with an internal diameter of not more than 62 mm, for use in the manufacture of turbochargers (1)	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.3352	ex 7410 21 00	10	Sheet or plate of polytetrafluoroethylene, containing aluminium oxide or titanium dioxide as filler or reinforced with glass-fibre fabric, covered on both sides with copper foil	0 %	-	31.12.2029
0.7509	ex 7410 21 00	20	Foils, rolls composed of one layer of glass epoxy of 100 µm colaminated with refined copper foil on one or two sides of 35 µm with a tolerance of 10 % for use in the production of smart cards (1)	0 %	m²	31.12.2029
0.3005	ex 7410 21 00	30	Film of polyimide, whether or not containing epoxide resin and/or glass fibre, covered on one side or on both sides with a copper foil	0 %	-	31.12.2029
0.9136	*ex 7410 21 00	35	Sheets or plates — Consisting of at least one layer of fibreglass fabric, coated with halogen free epoxy resin; — Coated on one or both sides with a copper foil with a thickness of not more than 0,10 mm; — With a glass transition temperature of 250 °C or more but not more than 270 °C (IPC-TM-650 section 2.4.24)	0 %	-	31.12.2031
0.3926	ex 7410 21 00	40	Sheet or plates: — consisting of at least a central layer of paper or one central sheet of any type of nonwoven fibre, laminated on each side with glass-fibre fabric and impregnated with epoxide resin, or — consisting of multiple layers of paper, impregnated with phenolic resin, coated on one or both sides with a copper film with a maximum thickness of 0,15 mm	0 %	-	31.12.2029
0.4479	ex 7410 21 00	50	Plates: — consisting of at least one layer of fibreglass fabric impregnated with thermosetting resin, — covered on one or both sides with copper foil with a thickness of not more than 0,15 mm, and — with a dielectric constant (DK) of less than 3,9 and a loss factor (Df) of less than 0,015 at a measuring frequency of 10 GHz, as measured according to IPC-TM-650	0 %	-	31.12.2029
0.9087	ex 7410 21 00	65	Sheets or Plates — consisting of at least one layer of fiberglass fabric impregnated with modified epoxy resin, without the use of halogenated flame retardants, — covered on one or both sides with copper foil with a thickness of 0,15 mm or less, — and with a TG of 145°C or more but not more than 280°C according to TMA, in agreement with IPC-4101/128 or 4101/130 or IPC-4101/153 or 4101/154	0 %	-	31.12.2030
0.7341	ex 7413 00 00	20	Loudspeaker centring ring, consisting of one or more vibration dampers and minimum two non-insulated copper cables, therein woven or pressed	0 %	-	31.12.2027
0.7911	ex 7506 20 00	10	Sheets and strips in coils of nickel alloy C276 (EN 2.4819) with — a thickness of 0,5 mm or more but not more than 3 mm, — a width of 770 mm or more but not more than 1 250 mm	0 %	-	31.12.2029
0.7913	ex 7506 20 00	20	Sheets and strips in coils of nickel alloy to standard ASME SB-582/UNS N06030 with: — a thickness of 0,5 mm or more but not more than 3 mm, — a width of 250 mm or more but not more than 1 219 mm	0 %	-	31.12.2030
0.2410	ex 7605 19 00	10	Not alloyed aluminium wire, of a diameter of 2 mm or more but not more than 6 mm, covered with a layer of copper of a thickness of 0,032 mm or more but not more than 0,117 mm	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8344	ex 7605 21 00	10	Aluminium alloy wire with a diameter of 9,50 mm or more but not more than 19,15 mm, in coils, for use in the manufacture of aeronautical fasteners (1)	0 %	-	31.12.2027
0.8194	*ex 7609 00 00 ex 8415 90 00	30 45	Aluminium connecting block for automotive air conditioning systems: — with a T6 hardening, — equipped with round stubs with a circumferential outer groove, — with through or non-through holes, made of profiles with an upper radius of 8 mm or more but not more than 11 mm, and a lower radius of 12 mm or more but not more than 17 mm, — with a distance between holes of 15 mm or more but not more than 22 mm, — with sockets designed for brazing or clamping, — with mounting holes for M6 or M8 mounting screw, threaded or not, — with a width of 5 mm or more but not more than 16 mm, — for connecting a compressor, a condenser, an evaporator, a chiller and other lines	0 %	-	31.12.2031
0.8464	ex 7609 00 00	40	Flame brazed aluminium block for connecting tubes in automotive heat exchangers and/or turbocharged air coolers and/or automatic transmission coolers: — with extruded, bent connection tubes with an outer diameter of 5 mm or more, but not more than 25 mm, — with a weight of 0,02 kg or more, but not more than 0,25 kg, for use in the manufacture of cooling system in vehicles of Chapter 87 (1)	0 %	p/st	31.12.2027
0.8503	ex 7609 00 00	50	Machined aluminium components: — containing by weight 0,55 %, or more but not more than 0,61 % of magnesium, — containing by weight 0,55 %, or more but not more than 0,61 % of silicon, — with a hardening state of T5 or T6, — with a mass of 0,05 kg or more, but not more than 0,2 kg, for use in the manufacture of CO_2 cooling systems in motor vehicles (1)	0 %	p/st	31.12.2027
0.8493	ex 7609 00 00	60	Aluminium connection block: — with a weight of 3 g or more but not more than 400 g, — manufactured from 6061-T6 or 6060-T6 or 6082-T6 aluminium grade, — being an integral part of an air conditioning hose assembly or oil cooling line hose assembly or air brake line hose assembly or water cooling line hose assembly, — with holes (sockets) or splines (pilots) or threads that allow installation in an automotive or other air conditioning system (also understood as installation in the line), — with sockets designed for brazing or fastening, — with at least 1 through-hole with a diameter of 3 mm or more but not more than 25 mm, for the manufacture of automotive cooling and air conditioning systems (1)	0 %	p/st	31.12.2027
0.5357	*ex 7616 99 90 ex 8482 80 00 ex 8807 30 00	70 10 40	Connecting components for use in the production of helicopter tail rotor shafts (1)	0 %	p/st	31.12.2031
0.6730	ex 8101 96 00	10	Tungsten wire containing by weight 99 % or more of tungsten with: — a maximum cross-sectional dimension of not more than 50 µm — a resistance of 40 Ω or more but not more than 300 Ω at length of 1 metre	0 %	-	31.12.2030
0.7245	ex 8101 96 00	20	Tungsten wire — containing by weight 99,95 % or more of tungsten, and — with a maximum cross-sectional dimension of not more than 1,02 mm	0 %	-	31.12.2027
0.5694	ex 8102 10 00	10	Molybdenum powder with: — a purity by weight of 99 % or more and — a particle size of 1,0 µm or more, but not more than 5,0 µm	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.5097	ex 8104 30 00	35	Magnesium powder: — of purity by weight of more than 99,5 %, and — with a particle size of not more than 0,8 mm	0 %	-	
0.3416	ex 8108 20 00	10	Titanium sponge	0 %	-	31.12.2029
0.4553	ex 8108 20 00	30	Titanium powder of which 90 % by weight or more passes through a sieve with an aperture of 0,224 mm	0 %	-	31.12.2029
0.3211	ex 8108 30 00	10	Waste and scrap of titanium and titanium alloys, except those containing by weight 1 % or more but not more than 2 % of aluminium	0 %	-	31.12.2029
0.4363	ex 8108 90 30	10	Titanium alloy rods complying with standard EN 2002-1, EN 4267 or DIN 65040	0 %	-	31.12.2029
0.7330	ex 8108 90 30	15	Rods and wire of an alloy of titanium with: — a uniform solid cross-section in the form of a cylinder, — with a diameter of 0,8 mm or more, but not more than 5 mm, — an aluminium content by weight of 0,3 % or more, but not more than 0,7 %, — a silicon content by weight of 0,3 % or more, but not more than 0,6 %, — a niobium content by weight of 0,1 or more, but not more than 0,3 %, and — an iron content by weight of not more than 0,2 %	0 %	-	31.12.2027
0.7942	ex 8108 90 30	35	Bars and wires of titanium with a titanium content of 98,8 % or more but not more than 99,9 % of a diameter less than 20 mm	0 %	-	31.12.2030
0.4904	ex 8108 90 30	45	Titanium-aluminium-vanadium alloy (TiAl6V4) wire, of a diameter less than 20 mm and complying with AMS standards 4928, 4965 or 4967	0 %	-	31.12.2030
0.8105	ex 8108 90 30	55	Wires of an alloy of titanium: — with a niobium content by weight of 42 % or more, but not more than 47 %, — with a diameter of 2,36 mm or more, but not more than 7,85 mm, — in coils of 15 kg or more, but not more than 45 kg, — complying with standard AMS 4982	0 %	-	31.12.2030
0.7285	ex 8108 90 50	45	Cold or hot rolled plates, sheets and strips of non-alloyed titanium with: — a thickness of 0,4 mm or more, but not more than 100 mm, — a length of not more than 14 m, and — a width of not more than 4 m	0 %	-	31.12.2027
0.5352	*ex 8108 90 50	55	Plates, sheets, strip and foil of an alloy of titanium	0 %	-	31.12.2031
0.6524	ex 8108 90 50	80	Plates, sheets, strips and foil of non-alloyed titanium — of a width of more than 750 mm, — of a thickness of not more than 3 mm	0 %	-	31.12.2029
0.6500	ex 8108 90 50	85	Strip or foil of non-alloyed titanium: — containing more than 0,07 % by weight of oxygen (O_2), — of a thickness of 0,4 mm or more but not more than 2,5 mm — conforming to the Vickers hardness HV1 standard of not more than 170 of a kind used in the manufacture of welded tubes for nuclear power plant condensers	0 %	-	31.12.2029
0.5353	*ex 8108 90 90 ex 9003 90 00	30 20	Parts of spectacle frames and mountings, including — temples, — blanks of a kind used for the manufacture of spectacle parts and — bolts of the kind used for spectacle frames and mountings, of a titanium alloy	0 %	p/st	31.12.2031

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8909	ex 8109 29 00	10	Non-alloy zirconium sponges or ingots containing by weight more than 0,01 % of hafnium for use in the manufacture of tubes, bars or ingots enlarged by remelting for the non-nuclear industry (1)	0 %	-	31.12.2030
0.3415	ex 8110 10 00	10	Antimony in the form of ingots	0 %	-	31.12.2029
0.9049	ex 8110 90 00	10	Antimony-Beryllium pellets containing by weight : — 20 % or more but not more than 25 % of beryllium (CAS 7440-41-7) — 77 % or more but not more than 83 % of antimony (CAS 7440-36-0)	0 %	-	31.12.2030
0.3413	ex 8112 99 50	10	Alloy of niobium (columbium) and titanium, in the form of bars and rods	0 %	-	31.12.2029
0.4316	ex 8113 00 90	10	Carrier plate of aluminium silicon carbide (AlSiC-9) for electronic circuits	0 %	-	31.12.2027
0.6805	ex 8113 00 90	20	Cuboid spacer made of aluminium silicon carbide (AlSiC) composite used for packaging in IGBT-modules	0 %	-	31.12.2030
0.5570	ex 8207 30 10	10	Set of transfer and/or tandem press tools for cold-forming, pressing, drawing, cutting, punching, bending, calibrating, bordering and throating of metal sheets, for use in the manufacture of frame parts or body parts of motor vehicles (1)	0 %	p/st	31.12.2027
0.5024	ex 8301 60 00 ex 8419 90 85 ex 8479 90 70 ex 8481 90 00 ex 8485 90 90 ex 8503 00 98 ex 8515 90 80 ex 8537 10 98 ex 8538 90 99 ex 8708 99 10 ex 8708 99 97	30 40 30 50 30 43 40 55 70 55 22	Silicone or plastic keyboards, comprising: — parts of common metal, and — whether or not comprising parts of plastic, — epoxy resin reinforced with fiberglass or wood, — whether or not printed or surface-treated, — with or without electrical conductors, — with or without a membrane bonded to the keyboard, — with or without mono or multilayer protective film	0 %	p/st	31.12.2030
0.8247	*ex 8302 10 00	20	Armrest hinge made of magnesium with: — a length of 239 mm or more but not more than 270 mm, — a width of 150 mm or more but not more than 175 mm, — a height of 110 mm or more but not more than 135 mm, — mounting holes for a lock mechanism	0 %	-	31.12.2031
0.8304	*ex 8302 30 00	20	Two cold-formed steel supports: — with a length of 120 mm or more but not more than 180 mm, — with a width of 50 mm or more but not more than 80 mm, — with a height of 35 mm or more but not more than 80 mm, — with a movable riveted connection, — with or without elastomeric bumper, — forming a mechanism for indirect movement of the mechanism of the longitudinal positioner of car seats, interacting with the safety latch, — attached to the mechanism of the longitudinal positioner by means of a detachable screw connection, riveting, welding or spot welding	0 %	-	31.12.2031
0.2602	ex 8309 90 90	10	Aluminium can ends: — with a diameter of 99,00 mm or more but not more than 136,5 mm (±1mm), — whether or not with a "ring-pull" aperture	0 %	p/st	31.12.2027
0.3947	ex 8401 30 00	20	Non-irradiated hexagonal fuel modules (elements) for use in nuclear reactors (1)	0 %	-	31.12.2029
0.6319	ex 8401 40 00	10	Stainless steel absorber control rods, filled with neutron absorbing chemical elements	0 %	p/st	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8818	ex 8406 81 00	10	Industrial steam turbine with: — an output of more than 40 MW but not more than 90 MW, — designed for a pressure of not more than 165 bar and a temperature of not more than 565 ° C, — equipped with individually controlled single or double seat valves on the live steam side which are operated with a hydraulic servo of not more than 30 bar	0 %	-	31.12.2029
0.8012	ex 8406 82 00	10	Industrial steam turbine with: — an output of 2 MW or more but not more than 40 MW, — designed for a pressure of not more than 140 bar and a temperature of not more than 540 °C, — equipped with single – or double seat valves on the live steam side which are operated with a hydraulic servo of not more than 30 bar	0 %	-	31.12.2030
0.3830	ex 8407 33 20 ex 8407 33 80 ex 8407 90 80 ex 8407 90 90	10 10 10 10	Spark-ignition reciprocating or rotary internal combustion piston engines, having a cylinder capacity of not less than 300 cm^3 and a power of not less than 6 kW or more but not more than 20,0 kW, for the manufacture of: — lawn mowers of subheadings 8433 11, 8433 19 and 8433 20, — tractors of subheadings 8701 91 90, 8701 92 90 whose main function is that of a lawn mower, — four stroke mowers with motor of a cylinder capacity of not less than 300 cm^3 of subheading 8433 20 10 or — snowploughs and snow blowers of subheading 8430 20 (1)	0 %	-	31.12.2027
0.8753	ex 8407 33 80	20	New, single-cylinder, four stroke, spark-ignition internal combustion engine with: — a cylinder capacity exceeding 500cm^3 but not exceeding 1000 cm^3, — overall dimensions of not more than: 490 mm (length) x 390 mm (width) x 590 mm (height), — a power of 22 kW or more but not more than 35 kW, — equipped with output shaft having an end diameter of 30 mm and a taper of 6 degrees (+/- 1 degree), — whether or not equipped with starter, throttle body, spark plug wire, fuel rail and injector, for use in the manufacture of all-terrain or utility task vehicles (1)	0 %	-	31.12.2029
0.8754	ex 8407 33 80	30	New, twin-cylinder, four-stroke, spark-ignition internal combustion engine with: — a cylinder capacity exceeding 500 cm^3 but not exceeding 1000 cm^3, — overall dimensions of not more than: 470 mm (length) x 450 mm (width) x 600 mm (height), — a power of 40 kW or more but not more than 86 kW, — whether or not equipped with overhead camshaft, starter motor, spark plug wires, fuel rail and injectors, for use in the manufacture of all-terrain or utility task vehicles (1)	0 %	-	31.12.2029
0.8751	ex 8407 34 91	10	New dual cylinder, four stroke internal combustion spark-ignition engine with: — a cylinder capacity exceeding 1000 cm^3 but not exceeding 1250 cm^3, — overall dimensions of not more than: 700 mm (length) x 430 mm (width) x 610 mm (height), — a power of 60 kW or more but not more than 110 kW, — whether or not equipped with a starter, outfitted with a throttle body, two or more fuel injectors, a stator, for use in the manufacture of motorcycle bikes (1)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8750	ex 8407 34 99	10	New dual cylinder, air cooled, four stroke 49 degree V-twin internal combustion spark-ignition engine with: — a cylinder capacity exceeding 1800 cm^3, — overall dimensions of not more than: 800 mm (length) x 500 mm (width) x 600 mm (height), — a power of 60 kW or more but not more than 75kW, — equipped with a dry sump system with an intermediate wet receptacle, — whether or not equipped with a starter, outfitted with a throttle body, two or more fuel injectors, a stator, for use in the manufacture of motorcycle bikes (1)	0 %	-	31.12.2029
0.3828	*ex 8407 90 10	10	Four-stroke petrol engines of a cylinder capacity of not more than 250 cm^3 for use in the manufacture of garden equipment of heading 8432, 8433, 8436 or 8508 (1)	0 %	-	31.12.2031
0.8403	ex 8407 90 10	40	A power unit with a two-stroke engine with: — an output of 900 W or more, but not more than 1 100 W, — a cylinder displacement of more than 24 cm^3 but not more than 30 cm^3, — a rotation speed of more than 8 400 rpm but not more than 8 600 rpm at maximum power, — an idling speed of more than 2 800 rpm but not more than 3 200 rpm, and — a fuel tank with a capacity of 0,5 l or more, for use in the manufacture of garden machinery and garden machinery components (1)	0 %	-	31.12.2027
0.4996	ex 8407 90 90	20	Compact Liquid Petroleum Gas (LPG) Engine System, with: — 6 cylinders, — an output of 75 kW or more, but not more than 80 kW, — inlet and exhaust valves modified to operate continuously in heavy duty applications, for use in the manufacture of vehicles of heading 8427 (1)	0 %	-	31.12.2030
0.8300	*ex 8408 90 65 ex 8408 90 67 ex 8408 90 81	20 20 20	Compression-ignition internal combustion piston engines: — of the inline type, — with a cylinder capacity of 7 000 cm^3 or more but not more than 18 100 cm^3, — with a power of 205 kW or more but not more than 597 kW, — with an exhaust after-treatment module, — with external width/height/depth dimensions of not more than 1 310/ 1 300/1 040 mm or 2 005/1 505/1 300 mm or 2 005/1 505/1 800 mm, for use in the manufacture of crushing, screening, separation or compost turning machines (1)	0 %	-	31.12.2027
0.8610	ex 8409 91 00	28	Carburetor with : — 2 mounting holes with a diameter of 31 mm, — a choke bore diameter of 18 mm or more, but not more than 19,05 mm for use in the manufacture of a two-stroke engine grass trimmer (1)	0 %	-	31.12.2028
0.8466	ex 8409 91 00	33	Camshaft carrier for a spark-ignition piston internal combustion engine, made of ADC12 aluminium alloy, with: — a weight of 4,0 kg or more but not more than 5,5 kg, — a wall thickness of 2,0 mm or more but not more than 6,0 mm, for use in the manufacture of motor vehicle engines (1)	0 %	p/st	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8216	*ex 8409 91 00	35	Fuel distribution pipe complete consisting of rail pipe, high pressure sensor and injectors for direct gasoline fuel injection with: — an operating pressure of not more than 22,5 MPa, — solenoid direct injector, — analog pressure sensor for not more than 22,5 MPa	0 %	-	31.12.2031
0.8469	ex 8409 91 00	38	Crankcase for 4-cylinder spark-ignition piston internal combustion engine, made of ADC12 aluminium alloy, for use in the manufacture of motor vehicle engines (1)	0 %	-	31.12.2027
0.7234	*ex 8409 91 00 ex 8409 99 00	45 70	Metal alloy intake and exhaust valve, with a Rockwell hardness HRC 20 or more, for use in the manufacture of spark or compression ignition engines of motor vehicles (1)	0 %	-	31.12.2031
0.6752	ex 8409 91 00 ex 8409 99 00	50 55	Exhaust manifold with turbine housing of turbochargers, with a hole to insert a turbine wheel, whereby the hole has a diameter of 28 mm or more, but not more than 181 mm	0 %	p/st	31.12.2029
0.7961	ex 8409 91 00 ex 8481 90 00	55 60	Nozzle body for the regulation of angle and distribution of fuel injection: — of a cylindrical shape, — made of stainless steel, — with 4 or more, but not more than 16 holes, — with a flow rate of 100 cm^3/minute or more, but not more than 500 cm^3/minute	0 %	-	31.12.2030
0.7965	ex 8409 91 00	75	Housing of fuel injection valve for generating an electromagnetic field to actuate the injection valve with: — an inlet diameter of 2 mm or more, but not more than 10 mm, — an outlet diameter of 2 mm or more, but not more than 10 mm, — an electric coil with a resistance of 10 Ω or more, but not more than 15 Ω, which ends in an electrical connection, — a plastic covering moulded around a stainless steel tube	0 %	-	31.12.2030
0.7967	ex 8409 91 00 ex 8481 90 00	80 70	Nozzle needle for opening and closing the flow of fuel in the engine, with: — 2 holes, — 4 grooves, — a diameter of 3 mm or more, but not more than 6 mm, — a length of 25 mm or more, but not more than 35 mm, — made of stainless steel with hard-chrome plating	0 %	-	31.12.2030
0.5199	*ex 8409 99 00 ex 8479 90 70	10 85	Injectors with solenoid valve for optimised atomisation in the engine combustion chamber	0 %	p/st	31.12.2027
0.7667	ex 8409 99 00	35	The exhaust gas recirculation assembly consisting of: — a control unit, — an air throttle, — an intake pipe, — an outlet hose, for use in the manufacture of compression-ignition combustion engines of motor vehicles (1)	0 %	-	31.12.2029
0.7718	ex 8409 99 00	75	High pressure fuel rail of galvanised ferrite-pearlite steel with: — at least one pressure sensor and one valve, — a length of 314 mm or more but not more than 322 mm, — an operating pressure not more than 225 MPa, — an inlet temperature not more than 95°C, — ambient temperature of -45°C or more but not more than 145°C, for use in the manufacture of compression ignition engines of motor vehicles (1)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.6751	ex 8411 99 00	20	Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: — of a precision-cast nickel based alloy complying with standard DIN G-NiCr13Al6MoNb or DIN G- NiCr13Al16MoNb or DIN G-NiCo10W10Cr9AlTi or DIN G- NiCr12Al6MoNb or AMS AISI:686, — with a heat-resistance of not more than 1 100 °C, — with a diameter of 28 mm or more, but not more than 180 mm, — with a height of 20 mm or more, but not more than 150 mm	0 %	p/st	31.12.2027
0.7225	*ex 8411 99 00	30	Turbine housing of turbochargers, with a hole to insert a turbine wheel, whereby the hole has a diameter of 28 mm or more, but not more than 181 mm	0 %	p/st	31.12.2031
0.8851	ex 8412 21 80	30	Linear acting hydraulic cylinder of a kind used in the machines for handling cargo containers: — with a weight of 45 kg or more but not more than 57 kg, — with a diameter of 119 mm or more but not more than 149 mm, — with a length of 779 mm or more but not more than 1141 mm, — with a stroke of 450 mm or more but not more than 610 mm, — adapted to work with hydraulic oil at a working pressure of 22 MPa or more but not more than 23 MPa, — whether or not with a maintenance-free bearing without the need for lubrication	0 %	-	31.12.2029
0.8850	ex 8412 21 80	40	Linear acting hydraulic cylinder of a kind used in the arms of machines for handling cargo containers: — with a weight of 827 kg or more but not more than 935 kg, — with a diameter of 250 mm or more but not more than 330 mm, — with a length of 3480 mm or more but not more than 4115 mm, — with a stroke of 2750 mm or more but not more than 3180 mm, — adapted to work with hydraulic oil at a working pressure of 23 MPa, — whether or not with a maintenance-free bearing without the need for lubrication	0 %	-	31.12.2029
0.5975	ex 8412 39 00	20	Actuator for a single-stage turbocharger, with: — -a pressure inlet pipe and a control rod with a working stroke of 15 mm or more but not more than 40 mm, — a maximum length of the actuator including control rod of not more than 400 mm, — -a maximum diameter of the can at the widest point of not more than 140 mm, and — a maximum height of the can without control rod of not more than 140 mm	0 %	p/st	31.12.2029
0.8148	ex 8412 90 70	20	Bedplate made of solution strengthened ductile iron castings (SSDI), for anchoring and aligning the drive train (gearbox, pedestal bearing, rotor shaft) of a wind turbine with: — a length of 3,5 m or more but not more than 4,5 m, — a width of 2 m or more but not more than 4,2 m, — a height of 1 m or more, but not more than 1,3 m, — a weight of 11 tons or more but not more than 21,5 tons, — mounting bores for yawdrive, — a mounting flange for gearbox support, — drivetrain mount, — different screw sockets	0 %	p/st	31.12.2027
0.8079	ex 8412 90 70	30	Gearbox support used as a support and load-carrying component between the gearbox and the bedplate of a wind turbine, made of solution strengthened ductile iron castings (SSDI), with: — a diameter of 2 m or more, but not more than 5 m, — a weight of 2 tons or more but not more than 7 tons	0 %	p/st	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7161	*ex 8413 30 20	30	Single-cylinder radial-piston high pressure pump for gasoline direct injection with: — an operating pressure of 200 bar or more, but not more than 350 bar, — a flow control, and — a pressure relief valve, for use in the manufacture of engines of motor vehicles (1)	0 %	-	31.12.2031
0.7969	ex 8413 30 20	40	High-pressure plunger pump for direct diesel injection, with: — an operating pressure of not more than 275 MPa, — a camshaft, — a fluid discharging of 15 cm^3 per minute or more, but not more than 1 800 cm^3 per minute, — an electric pressure regulating valve	0 %	-	31.12.2030
0.8215	*ex 8413 30 20	60	High-pressure plunger pump for direct petrol injection: — with an operating pressure of not more than 90 MPa, — designed to contact the crankshaft, — with an electromagnetic valve	0 %	-	31.12.2031
0.8332	ex 8413 30 80	20	Electric water pump ensuring the functionality of the water circuit also when the motor is temporarily switched off, for operating DC voltage of 9 V or more but not more than 16 V, with: — capacity - pressure 0,075 MPa at 3 800 rpm, — discharge of 12 l/min, — whether or not with connecting cable with connector, and — mounting bracket, for use in the manufacture of goods of Chapter 87 (1)	0 %	-	31.12.2027
0.9166	*ex 8413 30 80	30	Electric gerotor oil pump providing engine cooling and oil circulation: — with an operating voltage of 9 V DC or more, but not more than 16 V, — with an operating temperature of - 40 °C or more, but not more than 120 °C for use in the manufacture of electric drives for motor vehicles (1)	0 %	-	31.12.2031
0.8187	*ex 8413 70 51	40	Electric brushless direct current motor with single-stage, radial flow pump centrifugal single entry impeller mounted on motor's shaft, monobloc with the motor, volute with integrated heater, with: — a discharge outlet diameter of 20 mm or more, — 9 slots square or chain pole stator, — 6 pole rotor, — ferritic or rare earth magnets, — rated power of 95 W or 80 W, — heater of nominal power of 1800 W and soldered or laser welded safety, devices, — volute with or without clamped rubber outlet, — rotor chamber with ultrasonic welded sand filter	0 %	-	31.12.2031
0.6346	ex 8413 91 00	30	Fuel pump cover: — consisting of aluminium alloys, — with a diameter of 38 mm or 50 mm, — with two concentric, annular grooves formed on its surface, — anodized, of a kind used in motor vehicles with petrol engines	0 %	p/st	31.12.2029
0.7669	ex 8414 10 25	30	Tandem pump consisting of: — an oil pump with displacement of 21,6 cc/rev (± 2 cc/rev) and working pressure 1,5 bar at 1 000 revolutions per minute, — vacuum pump with displacement of 120 cc/rev (± 12 cc/rev) and performance of -666 mbar in 6 seconds at 750 revolutions per minute for use in the manufacture of engines of motor vehicles (1)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.9018	ex 8414 30 20	60	Hermetic compressor for R290 refrigerant for the production of refrigerators and freezers: — with a power not exceeding 0.4 kW, — pre-filled with lubricant from 190 ml to 210 ml, — suction and processing pipe inner diameter from 6.40 mm to 6.60 mm, — discharge pipe inner diameter from 4.80 mm to 5.00 mm, — driven by a brushless DC motor, — cooling capacity from 340 to 360 W at ASHRAE LBP 3000 rpm, — displacement from 6.5 cm^3 to 7.5 cm^3, — speed range from 1,600 rpm to 4,200 rpm (1)	0 %	-	31.12.2030
0.6160	ex 8414 30 81 ex 8414 80 73	60 30	Hermetic rotary compressors for either hydrofluorocarbon (HFC) or hydrocarbon refrigerants: — driven by 'on-off' single phase alternate current (AC) or 'brushless direct current' (BLDC) variable speed motors, — with a nominal power rating of not more than 1,5 kW, — a rated voltage of 100 V or more but not more than 240 V, — with a height of not more than 300 mm, — an external diameter of not more than 150 mm, — with a unit weight of not more than 15 kg, for use in the manufacture of heat pumps for household appliances, including clothes dryers (1)	0 %	-	31.12.2029
0.4727	*ex 8414 30 81	70	Hermetic or semi-hermetic electric rotary or scroll compressors with variable speed, with: — power consumption ranging from 0.35 kW to 37 kW, — swept volume ranging from 15 cm^3 to 280 cm^3, — weight ranging from 4 kg to 120 kg, — height ranging from 180 mm to 685 mm only suitable for heating, ventilation and/or air conditioning in heat pumps, air-conditioning machines or in other refrigerating equipment	0 %	-	31.12.2029
0.2593	ex 8414 30 89	20	Vehicle air conditioning system part, consisting of an open shaft reciprocating compressor of a power of more than 0,4 kW but not more than 10 kW	0 %	-	31.12.2029
0.8899	ex 8414 30 89	40	Electrical compressor for motor vehicle air conditioning system: — with a power output of more than 0,4 kW but not exceeding 10 kW, for use in the manufacture of motor vehicles of subheading 8703 40 (1)	0 %	p/st	31.12.2029
0.8651	ex 8414 59 25	50	Axial fans with built-in motor, for the generation of an air flow for the cooling of compressors and the distribution of air with — a direct current operating voltage of more than 10 V but not more than 14 V, or — an alternating current operating voltage of more than 185 V, but not more than 254 V, — an operating temperature of -40 °C or higher, but not higher than 70 °C, for use in the manufacture of heat pump tumble dryers and refrigerators or freezers (1)	0 %	-	31.12.2028

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8988	ex 8414 59 25	60	Axial Fan, for incorporation into instrument clusters, speedometers and infotainment systems of transport vehicles as motor vehicles of headings 8701 to 8705, with: — an air flow of not more than 0,75 m3/min (cubic meter per minute) — an air pressure of not more than 10 mmH2O — an overall acoustic noise of not more than 45 dB(A) — a diameter of not more than 65mm Equipped with DC Brushless motor with: — a rated voltage between: 3 to 16 VDC — an operating voltage between: 3 to 16 VDC — a rated current between: 0,03 to 0,30 A — an input power between: 0,3 to 1,5 W — a rotation speed between: 2500 to 10000 R.P.M, With or without a heat sink incorporated	0 %	p/st	31.12.2030
0.7595	ex 8414 59 35	20	Radial fan, with: — a dimension of 25mm (height) x 85mm (width) x 85mm (depth), — a weight of 120 g, — a rated voltage of 13,6 VDC (direct current voltage), — an operating voltage of 9 VDC or more but not more than 16 VDC (direct current voltage), — a rated current of 1,1 A (TYP), — a rated power of 15 W, — a rotation speed of 500 RPM (revolutions per minute) or more but not more than 4800 RPM (revolutions per minute) (free flow), — an air flow of not more than 17,5 litre/s, — an air pressure of not more than16 mm $H_2O \approx 157$ Pa, — an overall sound pressure of not more than 58 dB(A) at 4800 RPM (revolutions per minute), and with a FIN (Fan Interconnect Network) interface for communication with the heating and air-conditioning control unit used in car seat ventilation systems	0 %	-	31.12.2029
0.8648	ex 8414 59 35	40	Electric blower for cooling the battery module: — with an operating voltage of 9 VDC or more but not more than 16 VDC, — with a centrifugal electric fan, — with a connector, — with a plastic case, — with or without a control unit for the fan electric motor, for use in the production of rechargeable batteries for hybrid and electric vehicles [(1)]	0 %	-	31.12.2028
0.9045	ex 8414 59 35	50	DC motor centrifugal fan with: — a nominal voltage of 8 V or more, but not more than 13 V, — a nominal maximum speed of 1400 rpm or more, but not more than 1950 rpm, — a horizontal or vertical position of the fan blades shaft, — a boosting time of not more than 10 seconds, — a cable with a length of 30 cm or more, but not more than 50 cm, with RAST 2,5 connector, — a nominal power of 0,7 W or more, but not more than 3,5 W, — a tacho or feedback signal to monitor the speed	0 %	p/st	31.12.2030
0.7317	ex 8414 80 22	20	Air membrane compressor with: — a flow of 4,5 l/min or more, but not more than 12 l/min, — power input of not more than 14 W, and — a gauge pressure capacity not exceeding 400 hPa (0,4 bar), of a kind used in the production of motor vehicle seats	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8133	ex 8414 80 73	50	Hermetic heat pump compressor for R450A or R290 refrigerants: — not charged with refrigerant, — pre-charged with lubricant oil, — with a single phase induction permanent split capacitor motor or a DC brushless motor, — having suction and/or discharge connections, — with a displacement of 8,05 cm3 or more, but not more than 55 cm3, — running at 900 rpm or more, but not more than 7 800 rpm, and — with a cooling capacity of 920 W or more, but not more than 10 440 W in ASHRAE conditions	0 %	-	31.12.2030
0.8483	ex 8414 90 00	15	Fan assembly made of aluminium and magnesium alloy: — with an outer diameter of 54 mm or more but not more than 130 mm, — with a height of 8 mm or more but not more than 30 mm, — with two discs connected by blades of involute shape, — with or without dowel, and with or without washer, for use in the manufacture of electromotors (1)	0 %	-	31.12.2027
0.2507	ex 8414 90 00	20	Aluminium pistons, for incorporation into compressors of air conditioning machines of motor vehicles (1)	0 %	p/st	31.12.2029
0.8494	ex 8414 90 00	25	Scroll type compressor housing of an aluminium alloy of a kind with: — a heat resistance of 200 °C or more but not more than 250 °C, — one or more fixing points suitable for mounting an actuator, for use in the manufacture of turbochargers (1)	0 %	-	31.12.2027
0.8792	ex 8414 90 00	35	Compressor head unit made of impregnated aluminium alloy for installation in air-conditioning compressors for motor vehicles with: — a width of 115 mm or more but not more than 160 mm, — a length of 115 mm or more but not more than 170 mm, — a height of 30 mm or more but not more than 100 mm, — a piece of pressure branch with pipe connection, — one or two mounting holes and — more than one overflowing hole	0 %	-	31.12.2029
0.8785	ex 8414 90 00	45	Pressure casted rotor front plate or cover of an electric supercharger: — of EN AC-46000 aluminium, — shot-blasted and machined, — with a hardness of 60 or more on the Hardness Brinell Wolfram (HBW) scale (2,5/62,5, according to ISO 6506), — with a tensile strength of 240 N/mm2 or more, — with a height of 22 mm or more but not more than 26 mm, — with a diameter of 128 mm or more but not more than 136 mm, — with a weight of 220 g or more but not more than 250 g	0 %	-	31.12.2029
0.8964	ex 8414 90 00	55	Air conditioning compressor housing component made of aluminum alloy for installation in electric air conditioning compressors for motor vehicles: — with a width of 100 mm or more but not more than 220 mm, — with a length of 100 mm or more but not more than 230 mm, — with a height of 80 mm or more but not more than 180 mm, — with one single central bore, — machined by CNC milling or unwrought, — whether or not impregnated, — with one suction port or without	0 %	-	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8465	ex 8415 90 00	15	Electrically welded manifolds for the condenser in automotive air conditioning systems: — consisting of a tube produced by stamping an aluminium strip and joining the edges by electric arc welding, — containing internal baffles responsible for the proper flow of coolant, — with a length of 190 mm or more, but not more than 460 mm, — with a diameter of 9 mm or more, but not more than 42 mm, — with a weight of 0,01 kg or more, but not more than 0,45 kg, — whether or not having aluminium connection blocks, used in the production of air conditioning systems in vehicles of Chapter 87 (1)	0 %	p/st	31.12.2027
0.6842	ex 8415 90 00	60	Flame-soldered aluminium block, for connecting tube with condenser in car air-conditioning systems, with: — extruded, bent connector lines of aluminium with an external diameter of 5 mm or more, but not more than 25 mm, — a weight of 0,02 kg or more but not more than 0,25 kg	0 %	p/st	31.12.2030
0.7996	ex 8418 99 90	20	Aluminium connecting block for connecting to a condenser manifold in welding process: — hardened to T6 or T5 temper, — with a weight of not more than 150 g, — with a length of 20 mm or more but not more than 150 mm, — with a fixing rail in one piece	0 %	p/st	31.12.2030
0.8004	ex 8418 99 90	30	Receiver dryer profile for connecting to a condenser manifold in welding process with: — a braze flatness of not more than 0,2 mm, — a weight of 100 g or more but not more than 600 g, — a fixing rail in one piece	0 %	p/st	31.12.2030
0.8976	ex 8418 99 90	50	Heat exchanger evaporator, used in domestic refrigerators and freezers and their combinations: — with external dimensions of 362 mm x 244 mm x 60 mm or more but not more than 398,4 mm x 503 mm x 60 mm, — with 229 mm to 307 mm aluminium radiator fins with external dimensions of 60 mm x 26,7 mm or more but not more than 60,2 mm x 27,3 mm, — with an aluminium tube with an external diameter of 8,3 mm or more but not more than 8,5 mm, — with not more than two heaters with a power of 40 W or more but not more than 140 W, equipped with cables with connectors, — with or without two thermal fuses with a melting point of 77 °C, equipped with cables with connectors	0 %	-	31.12.2030
0.8978	ex 8418 99 90	60	Condenser for refrigerators or refrigerators with freezers of the household type equipped at least with: — a steel pipe with a diameter from 4,68 mm to 4,81 mm, a wall thickness from 0,52 mm to 0,65 mm, — 26-30 pcs of horizontal pipe sections, each straight with a length from 450 mm to 455 mm, placed every 40 mm between each horizontal part, — from 112 to 174 pcs welded steel rods with a diameter of 1,3 mm and a length of 1 002 mm or more but not more than 1 322 mm, — 3 clips, — 4 brackets welded between the rods	0 %	-	31.12.2030
0.9044	ex 8418 99 90	70	Household appliances condenser, being a type of heat exchanger, made entirely of aluminium A3102, A3003, A4045 or A4343, consisting of two vertical pipes and arranged horizontally between them 16 parallel flat tubes with fins, with: — one vertical pipe with inlet and outlet tubes, — a width of 297 mm or more, but not more than 373 mm, — a height of 154 mm or more, but not more than 158 mm, — a depth of 17 mm or more, but not more than 23 mm, — a flatness tolerance of less than 2 mm for the fin pack within the condenser core, — a weight of 224 g or more, but not more than 283 g	0 %	-	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8856	ex 8418 99 90	80	An evaporator being a type of heat exchanger, consisting of aluminium pipes with copper ends enclosed with aluminium radiators: — measuring 337 x 237 x 17 mm or more, but not more than 868 x 399 x 78 mm, — with a total weight of a set of 236 g or more, but not more than 1 750 g, — with a fixed sensor, — with or without noise absorber, — with 2, 5 or 7 control and power connection pins terminated with sensor temperature type of socket, with or without heater and fuse type of socket, for use in the manufacture of products of subheadings 8418 10, 8418 21, 8418 40 (1)	0 %	-	31.12.2029
0.8747	ex 8419 50 80	30	Aluminium heat exchanger for gas boilers designed for heat transfer: — with a height of 100 mm or more, but not more than 150 mm, — with a width of 235 mm or more, but not more than 300 mm, — with a length of 240 mm or more, but not more than 300 mm, — for a power output of 25 kW or more, but not more than 35 kW, — with a weight of 8 kg or more, but not more than 10 kg	0 %	-	31.12.2029
0.6193	ex 8431 20 00	40	Aluminium core, plastic tank radiator, with integral steel support structure and an open core square wave design of 9 fins per 2,54 cm of core length for use in the manufacture of vehicles of heading 8427 (1)	0 %	p/st	31.12.2029
0.8853	ex 8431 20 00	70	Container spreader for lifting empty 20' and 40' cargo containers: — without an integrated carriage, — suitable for machines with a load capacity of not more than 11 000 kg, — designed to carry one or two containers at a time, — with a top or side mounting, — with an anti-corrosion layer coated, — with a weight of 3 200 kg or more but not more than 4 000 kg for use in the manufacture of self-propelled container handlers (1)	0 %	-	31.12.2029
0.6821	*ex 8436 99 00	10	Part containing: — a single-phase AC motor, — an epicyclic gearing, — a cutter blade, and whether or not containing: — a capacitor, — a part fitted with a threaded bolt, for use in the manufacture of garden shredders (1)	0 %	p/st	31.12.2031
0.3374	ex 8439 99 00	10	Suction-roll shells, produced by centrifugal casting, not drilled, in the form of alloy-steel tubes, of a length of 3 000 mm or more and an external diameter of 550 mm or more	0 %	p/st	31.12.2029
0.8632	ex 8467 99 00	10	Pole hedge trimmer cutting elements: — in the form of hedge trimmer attachment, — with a knife length of 60 cm and teeth opening of 30 mm, — with angle adjustment of the blade, — with integrated single stage gearbox, — with a magnesium cast body, for use in the manufacture of garden machinery and power tools (1)	0 %	-	31.12.2028
0.2599	ex 8477 80 99	10	Machines for casting or for surface modification of plastic membranes of heading 3921	0 %	p/st	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8123	*ex 8479 89 97	28	Integrated electric brake unit for immediate generation of the hydraulic pressure during braking, full electronic brake control and enabling regenerative braking of motor vehicles with: — electronic brake assistants, — hydraulic unit driven by brushless electric motor, — brake fluid reservoir, for use in the manufacture of electric or hybrid passenger cars (1)	0 %	-	31.12.2030
0.8673	ex 8479 89 97	33	Pre-assembled process module unit of an ethane cracker unit, containing: — various distillation columns (depropanizer, debutanizer and degreenoiler) and their associated heat exchangers, pumps and drums, — a chilling train containing heat exchangers and a drum which condenses C2 in a gas stream, — a system to separate hydrogen and methane from cracked gas containing heat exchangers, drums, turbines, compressors and a hydrogen purification unit (pressure swing adsorption unit), — associated equipment of a C3 splitter distillation column, containing heat exchanger, pumps and drums, and — a vinyl acetylene hydrogenation system, containing hydrogenation reactors, filters, mixer, drum, condenser, heat exchangers	0 %	-	
0.8206	*ex 8479 89 97 ex 8501 31 00	38 68	Camshaft actuator for controlling the timing of valve opening by using electromotor in a continuous variable valve timing system of an internal combustion piston engine, of: — a length of 110 mm or more but not more than 140 mm, — a width of 90 mm or more but not more than 130 mm, — a height of 80 mm or more but not more than 110 mm for use in the manufacture of engines of motor vehicles (1)	0 %	-	31.12.2031
0.8681	ex 8479 89 97	43	Pre-assembled process module unit of an ethane cracker unit, containing: — a system for filtering and cooling of dried cracked gas, — a deethanizer distillation column and associated equipment for C2-/C3+ separation, — an acetylene hydrogenation system to remove acetylene within a C2 stream, — a fuel gas drum that stores fuel gas for cracker furnaces, and — a system to regenerate dryers in a cracker installation	0 %	-	
0.6230	*ex 8479 89 97	60	Bioreactor for biopharmaceutical cell culture — having interior surfaces of austenitic stainless steel, and — with a process capacity up to 15 000 litres, — whether or not combined with a “clean-in-process” system and/or a dedicated paired media hold vessel	0 %	p/st	31.12.2031
0.9152	*ex 8481 10 19	20	Electromagnetic fuel pressure reducing valve — with a plunger, — with an operating pressure of not more than 325 MPa, — with a plastic connector with 2 silver or tin, or silver-plated, or tin-plated, or silver and tin plated pins	0 %	-	31.12.2031
0.7424	ex 8481 10 99	40	Pressure reducing valves in a brass case with: — a length of not more than 30 mm (± 1 mm), — a width of not more than 18 mm (± 1 mm), of a kind used for incorporation in fuel delivery modules of motor vehicles	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.9140	*ex 8481 10 99	50	Electronic expansion valves, equipped with a stepping motor coil and consisting of a valve body, plunger, spring, needle valve and copper tube connections, mainly made of brass, copper and stainless steel, — with a valve body leakage resistance pressure of 6,3 MPa, — with an air-tightness test pressure of 4,2 MPa, — with an internal leakage rate of less than 300 ml/min, — suitable for use with R410A or R32 refrigerants, — for use in both indoor and outdoor air-conditioning units, for use in the manufacture of air conditioners (1)	0 %	-	31.12.2031
0.4668	ex 8481 30 91	91	Steel check (non-return) valves with: — an opening pressure of not more than 800 kPa, — an external diameter not more than 37 mm	0 %	p/st	31.12.2029
0.7380	ex 8481 80 59	30	Two-way flow control valve with housing, with: — at least 5, but not more than 16 outlet holes with at least 0,05 mm, but not more than 0,5 mm diameter, — at least 330 cm^3/minute, but not more than 5 000 cm^3/minute flow rate, — at least 19, but not more than 300 MPa operating pressure	0 %	-	31.12.2029
0.7377	ex 8481 80 59	40	Flow-control valve: — made of steel, — with an outlet hole with a diameter of 0,05 mm or more, but not more than 0,5 mm, — with an inlet hole with a diameter of 0,1 mm or more, but not more than 1,3 mm, — with chromium nitride coating, — with a surface roughness of Rp 0,4	0 %	-	31.12.2027
0.7381	ex 8481 80 59	50	Electromagnetic valve for quantity control with: — a plunger, — a solenoid with a of coil resistance of at least 1,85 Ohm, but not more than 8,2 Ohm	0 %	-	31.12.2027
0.7382	ex 8481 80 59	60	Electromagnetic valve for quantity control — with a solenoid with a coil resistance of at least 0,19 Ohm, but not more than 0,66 Ohm, and with an inductance of not more than 1 mH	0 %	-	31.12.2027
0.7960	ex 8481 80 59 ex 8481 90 00	70 80	Flow-control valve — made of steel, — with an outlet hole with a diameter of at least 0,05 mm, but not more than 0,5 mm, — with an inlet hole with a diameter of at least 0,1 mm, but not more than 1,3 mm	0 %	-	31.12.2030
0.8814	ex 8481 80 59	80	Solenoid valve for combustion engine oil pump to regulate the quantity of oil in the pump: — with a cable of length of 550 mm or more but not more than 700 mm incorporating an electrical connector, — with an operating pressure of not more than 5.5 bar, — with an operating voltage of 9 VDC or more but not more than 16 VDC, — with a valve's base width of 22 mm or more but not more than 27 mm, — with a valve's length of 55 mm or more but not more than 110 mm, for use in the manufacture of motor vehicle engines (1)	0 %	-	31.12.2029
0.5575	*ex 8481 80 69	60	Four-way reversing valve for refrigerants, consisting of: — a solenoid pilot valve — a brass or stainless steel valve body including valve slider and copper connections with a working pressure up to 4,5 MPa	0 %	p/st	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7519	ex 8481 80 73 ex 8481 80 99	20 70	Pressure- and flow-control valve controlled by external electromagnet: — made of steel and/or steel alloy(s), — without integrated circuit, — of not more than 1000 kPa operating pressure, — with a flow quantity of not more than 5 l/min, — without an electromagnet	0 %	-	31.12.2029
0.8956	ex 8481 80 79	40	Service valve which suits for R410A or R32 gas while connecting indoor and outdoor units with: — a withstanding pressure of the valve body of 6,3 MPa, — a leakage ratio of less than 1.6 g/a, — an impurity ratio of less than 1.2 mg/PCS, — an airtight pressure of the valve body of 4.2 Mpa for use in the manufacture of air conditioners (1)	0 %	-	31.12.2030
0.9171	*ex 8481 80 87	40	One, two or three-way solenoid water valve for installation in washing machines with: — a housing made of polyamide 66 modified with 30 % glass fibre, — a stainless-steel core, — diaphragm seals made of ethylene propylene diene monomer rubber, — an inner screen filter 60 mesh made of stainless steel, — an outer screen filter 60 mesh made of stainless steel and polyoxymethylene, — an additional plate made of galvanized steel mounted to the housing	0 %	-	31.12.2031
0.8752	ex 8481 80 99	80	Solenoid valve for combustion engine continuous variable valve timing system to control oil flow as a function of engine speed and load: — in metal cover, — with electrical connector, — with a force of not more than 10 N, — with an operating voltage of 9 VDC or more but not more than 16 VDC, — with a length of 80 mm or more but not more than 110 mm, — with a width of 80 mm or more but not more than 110 mm, — with a height of 20 mm or more but not more than 30 mm, for use in the manufacture of engines of motor vehicles (1)	0 %	-	31.12.2029
0.8784	ex 8481 90 00	25	Die-cast aluminium housing for electronic throttle control or exhaust gas recirculation systems, comprising the following features: — high-pressure die-cast aluminium EN AC-46000, — shot-blasted and machined, — height of 100 mm or more but not exceeding 135 mm, — width of 115 mm or more but not exceeding 150 mm, — weight of 210 g or more but not more than 500 g	0 %	-	31.12.2029
0.7735	ex 8482 10 10	15	Ball bearings with: — an internal diameter of 4 mm or more but not more than 9 mm, — an external diameter of not more than 26 mm, — a width of not more than 8 mm, for use in the manufacture of electromotors with a range of 40 000 rpm or more but not more than 80 000 rpm (1)	0 %	-	31.12.2029
0.8098	ex 8482 50 00	20	Axial roller bearing made of steel: — the retainer is made of cold-rolled steel with a carbon content of up to 0,25 percent, complying with standard ASTM A109-98, — the rollers are made of anti-friction steel according to ASTM 295-94, — with an external diameter of 63 mm or more but not more than 66 mm, — with an internal diameter of 44 mm or more but not more than 46 mm, — with a weight of 23 g or more but not more than 27 g, — with 36 rollers or more but not more than 38 rollers	0 %	p/st	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8588	ex 8483 10 95	30	Steel alloy splined shaft (torque shaft) with straight teeth and involute profile, with: — external toothing in a diametral pitch standard, — 17 teeth or more, but not more than 50 teeth, — a diameter of 35 mm or more, but not more than 145 mm, — a length of 200 mm or more, but not more than 1345 mm, — a hardness of 35 HRC or more, but not more than 45 HRC	0 %	-	31.12.2028
0.8746	ex 8483 10 95	40	Stepped shaft made of carbon steel with: — rolled, involute profiled, splined shaft end, the helix angle of which is at least 0°15,5’ but not more than 0° 21,5’, — a largest diameter of 16 mm or more, but not more than 18 mm, — a length of 137 mm or more, but not more than 155 mm, — a weight of 0,12 kg or more, but not more than 0,28 kg	0 %	-	31.12.2029
0.8857	*ex 8483 10 95	60	Drum shaft for torque transmission, in steel (to SM45C for shaft standard and STS430 for ring standard) with: — a length of 137,8 mm or more, but not more than 149,7 mm, — an external diameter of 22 mm or more, but not more than 48,025 mm, — a weight of 739 g or more, but not more than 1,0445 kg, — a shaft with a Rockwell C hardness of 40 or more but not more than 50, or a Rockwell B hardness of 87 or more but not more than 98, — a ring with a Rockwell B hardness of 90 or more but not more than 120, — an external 36-teeth or 37-teeth spline with a major diameter of 28,2 mm or more but not more than 48 mm	0 %	-	31.12.2029
0.5744	ex 8483 30 32 ex 8483 30 38	30 60	Bearing housing of a kind used in turbochargers: — of precision-cast grey cast iron complying with standard DIN EN 1561 or precision-cast ductile cast iron complying with DIN EN 1560, — with oil chambers, — without bearings, — with a diameter of 50 mm or more, but not more than 250 mm, — with a height of 40 mm or more, but not more than 150 mm, — whether or not with water chambers and connectors	0 %	p/st	31.12.2027
0.9023	ex 8483 30 80	30	Commutator end shield (bearing housing with plain shaft bearing) for starter motors of passenger cars and commercial vehicles — produced with high pressure precision die casting technology, — made of aluminium alloy (EN AC-46000 or EN AC-46000 S, according to the DIN EN 1706 and GB/T 16116 standards), — with sintered plain bearing	0 %	-	31.12.2030
0.8626	ex 8483 40 23	20	Bevel gear: — made of lightweight alloys and steel, — built on straight or helical bevel gears, — with an angle between the shafts of 30 degrees or more but not more than 90 degrees — with a gear 1:1,3 ratio or more but not more than 1:1,46, for use in the manufacture of grass trimmers, brushcutters and other types of garden machinery (1)	0 %	-	31.12.2028
0.8625	ex 8483 40 23	30	Bevel gear: — made of lightweight alloys and steel, — built on straight bevel gears, — with an angle between the shafts of 24 degrees or more but not more than 35 degrees, for use in the manufacture of grass trimmers, brushcutters and other types of garden machinery (1)	0 %	-	31.12.2028

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8303	*ex 8483 40 25	20	Worm gearbox: — in an aluminium alloy housing, — with a plastic or steel worm, — with mounting holes, — with a 90 degree reversible drive direction, — with a 4:19 transmission ratio, — equipped with a lead screw with a length of 310 mm or more but not more than 380 mm, — with a guide nut incorporated into the assembly bracket, — with or without a lead screw support, for indirect connection to the drive motor of a car seat guide system (1)	0 %	-	31.12.2031
0.5202	*ex 8483 40 29	50	Gear set of cycloid gear type with: — a rated torque of 50 Nm or more but not more than 9 000 Nm, — standard ratios of 1:50 or more but not more than 1:475, — lost motion of not more than one arc minute, — an efficiency of more than 80 % of a kind used in robot arms	0 %	p/st	31.12.2031
0.5977	ex 8483 40 29	60	Epicyclic gearing, of a kind used in driving hand-held power tools with: — a rated torque of 25 Nm or more, but not more than 70 Nm, — standard gear ratios of 1:12.7 or more, but not more than 1:65,3	0 %	p/st	31.12.2029
0.8585	ex 8483 40 29	70	Cast steel planetary cage, with: — external or internal toothing in a diametral pitch standard, — 27 teeth or more, but not more than 70 teeth, — a diameter of 300 mm or more, but not more than 725 mm, — a length of 225 mm or more, but not more than 800 mm, — 3 or 4 planetary gears, — a hardness of 40 HRC or more, but not more than 45 HRC	0 %	-	31.12.2028
0.7920	ex 8483 40 59	30	Hydrostatic speed changer: — with a hydro pump and a differential with wheel axle, — whether or not with a fan impeller and/or a pulley, for use in the manufacture of lawn mowers of subheadings 8433 11 and 8433 19 or other mowers of subheading 8433 20 (1)	0 %	p/st	31.12.2029
0.4997	ex 8483 40 90	80	Transmission gearbox, with: — not more than 3 gears, — an automatic deceleration system, and — a power reversal system, for use in the manufacture of goods of heading 8427 (1)	0 %	p/st	31.12.2030
0.8100	ex 8483 50 80	20	Pulley blocks of non-cast steel: — made of structural carbon steel complying with standard JIS G4051, — with an external diameter of 104 mm or more but not more than 142 mm, — with an internal diameter of 33 mm or more but not more than 37 mm, — with a width of 22 mm or more but not more than 40 mm, — with a weight of 0,4 kg or more but not more than 1,6 kg, — with 4 trapezoidal grooves or more but not more than 7	0 %	p/st	31.12.2030
0.8540	ex 8483 50 80	30	Mechanical tensioner for maintaining the tension of the drive belts of a passenger car engine: — with two pulleys made of polyamide, each of them with a diameter of 50 mm or more but not more than 70 mm, — with a spring made of a steel alloy containing chromium and silicon, — with two arms made of aluminum, — with a holder made of aluminum, for use in the manufacture of motor vehicle engines (1)	0 %	-	31.12.2028

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8984	ex 8483 50 80	40	Flywheel designed for damping torsional vibrations and oscillations within a vehicle drivetrain with: — a total moment of inertia of 0.082 kg·m², — a weight of 7 kg or more, but not more than 8 kg, — a diameter of 250 mm or more, but not more than 280 mm, for use in the manufacture of motor vehicles (1)	0 %	-	31.12.2030
0.9040	ex 8483 50 80	50	Metal spinned single or double pulley: — made of DC03 steel or similar non alloy steel or free cutting steel, — with a pitch diameter of 67 mm or more but not more than 145 mm, — with an inner hole designed for bearing mounting or key mounting	0 %	-	31.12.2030
0.9039	ex 8483 50 80	60	Metal spinned triple pulley: — made of DC03 steel or similar non-alloy steel or free cutting steel, — with a pitch diameter of 60 mm or more, but not more than 130 mm, — with an inner hole designed for bearing mounting	0 %	-	31.12.2030
0.9025	ex 8483 60 80	20	Overrunning clutch for passenger car and commercial vehicle starter motors with: — a total length of 49,4 mm or more but not more than 210 mm, — a starter motor pinion with 9 or more but not more than 16 teeth	0 %	-	31.12.2030
0.8584	ex 8483 90 89	30	Forged steel sprockets with external toothing, whether or not with internal splines in a diametral pitch standard, with: — a diameter of 400 mm or more, but not more than 630 mm, — 7 teeth or more, but not more than 15 teeth, — a tooth core hardness of 28 HRC or more, but not more than 45 HRC, — a tooth surface hardness of 50 HRC or more, but not more than 60 HRC, — whether or not, a spline hardness of 30 HRC or more, but not more than 45 HRC, — an effective carburized case depth of 4 mm or more, but not more than 5 mm	0 %	-	31.12.2028
0.8541	ex 8483 90 89	40	Steel alloy gear wheels with straight teeth and involute profile, with: — external and/or internal toothing in a diametral pitch standard, — a diameter of 35 mm or more, but not more than 600 mm, — 13 teeth or more, but not more than 80 teeth, — a tooth core hardness of 28 HRC or more, but not more than 45 HRC, — a tooth surface hardness of 50 HRC or more, but not more than 65 HRC, — an effective carburized case depth of 1,00 mm or more, but not more than 3,1 mm, — a spline hardness of 27 HRC or more, but not more than 62 HRC, — whether or not in combination with a shaft with a spline hardness of 27 HRC or more, but not more than 62 HRC	0 %	-	31.12.2028
0.6854	ex 8501 10 10	20	Synchronous motor for a dishwasher with a water flow control mechanism with — a length without axle of 24 mm (± 0,3), — a diameter of 49,3 mm (± 0,3), — a rated voltage of 220 V AC or more but not more than 240 V AC, — a rated frequency of 50 Hz or more but not more than 60 Hz, — an input power of not more than 4 W, — a rotation speed of 4rpm or more but not more than 4,8rpm, — an output torque of not less than 10kgf/cm	0 %	-	31.12.2027
0.7857	ex 8501 10 10	40	Synchronous hybrid stepper motor with: — an output not exceeding 18 W, — two phases, — a rated current of not more than 2,5 A/phase, — a rated voltage of not more than 20 V, — with or without a threaded shaft, for use in the manufacture of 3D printers (1)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8390	ex 8501 10 10 ex 8501 10 99	50 30	Linear actuator for automotive electric seat adjustment applications: — consisting of a permanently excited DC motor with an integrated gear mechanism and leadscrew, — whether brushed or brushless, — whether or not with electronic control unit, — whether or not with Hall Effect Sensor, — with a nominal voltage of 8 V or higher but not higher than 16 V, — with a rated output mechanical power not exceeding 20 W, and — with a specified temperature range from -40 °C to 160 °C, for use in the manufacture of automotive components for car seats (1)	0 %	-	31.12.2027
0.8389	ex 8501 10 10 ex 8501 10 99	60 40	Rotary actuator for automotive electric seat adjustment applications: — consisting of a permanently excited DC motor with an integrated gear mechanism, — whether brushed or brushless, — whether or not with electronic control unit, — whether or not with Hall Effect Sensor, — with a nominal voltage of 8 V or more but not more than 16 V, — with a rated output mechanical power not exceeding 35 W, and — with a specified temperature range from -40 °C to 160 °C, for use in the manufacture of automotive components for car seats (1)	0 %	-	31.12.2027
0.8394	ex 8501 10 99	20	Worm axis motor for automotive electric seat adjustment applications: — consisting of a permanently excited DC motor with a worm wheel, — whether brushed or brushless, — whether or not with electronic control unit, — whether or not with Hall Effect Sensor, — with a nominal voltage of 8 V or more but not more than 16 V, — with a rated output mechanical power not exceeding 35 W, and — with a specified temperature range from -40 °C to 160 °C, for use in the manufacture of automotive components for car seats (1)	0 %	-	31.12.2027
0.9155	*ex 8501 10 99	25	Indoor unit DC fan motor: — with a rotational speed not exceeding 1 650 rpm, — with a maximum power of less than 37,5 W, — with a voltage of 310 V, — with 8 poles, — with a maximum torque not exceeding 4.2 kgf·cm, — with a maximum current of 2.2 A, — with insulation class E, — with a counter-clockwise rotation direction, for use in the manufacture of air conditioners (1)	0 %	-	31.12.2031
0.8396	ex 8501 10 99	50	Electric (DC) motor powering height adjusting with: — a rated output mechanical power not exceeding 35 W, — frame integration with a length of 156 mm, a height of 59 mm, a thickness of 36 mm and a weight of 500 g, — a stall torque of 45 Nm and ultimate torque of 200 Nm, — a maximum current of 15 A, — no load speed of 7 RPM or more but not more than 10 RPM, — a rotation speed of 4 000 RPM or more but not more than 5 600 RPM, — a maximum noise level of 42 dB(A), — a maximum angular backlash up to 3 degrees, and — a 8 tooth pinion module, for use in the manufacture of automotive components for car seats (1)	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7197	*ex 8501 10 99	56	DC Motor: — with a speed rotation of not more than 7 000 rpm without load, — with a nominal voltage of not more than 18 V, — with a maximum power of 24 W, — for a specific temperature range from -40°C to 160°C, — with or without a gear connection, — with or without a mechanical attachment interface, — with 2 electrical connections, — with a maximum torque of 100 Nm	0 %	-	31.12.2031
0.7198	*ex 8501 10 99	58	DC Motor : — with a speed rotation of not more than 6500 rpm (without load), — with a nominal voltage of 12 V (± 4 V), — with a maximal power below than 20 W, — with a specified temperature range from -40°C to 160°C, — with a worm gear drive, — with a mechanical attachment interface, — with 2 electrical connections, — with a maximum torque of 75 Nm	0 %	-	31.12.2031
0.5846	ex 8501 10 99	60	DC motor: — with a rotor speed of 3 500 rpm or more but not more than 5 000 rpm loaded and not more than 6 500 rpm when not loaded — with a power supply voltage of 100 V or more but not more than 240 V for use in the manufacture of electric fryers (1)	0 %	-	31.12.2027
0.6880	ex 8501 10 99	65	Electric turbocharger actuator, with: — a DC motor, — an integrated gear mechanism, — a (pulling)force of 200 N or more at a minimum of 140°C elevated ambient temperature, — a (pulling) force of 250 N or more in each position of its stroke, — an effective stroke of 15 mm or more but not more than 25 mm, — with or without an on-board diagnostics interface	0 %	-	31.12.2030
0.6115	ex 8501 10 99	70	DC stepping motor, with: — a two-phase winding, — a rated voltage of 9 V or more, but not more than 16,0 V, — of a specified temperature range of - 40 °C or more but not more than + 105 °C, — with or without connection pinion, — with or without motor drive connector	0 %	-	31.12.2029
0.6627	ex 8501 10 99	75	Permanently excited DC motor with — a multiple-phase winding, — an external diameter of 24 mm or more but not more than 38 mm, — a rated speed of not more than 12 000 rpm, — a power supply voltage of 8 V or more but not more than 27 V, — with or without a pulley, — with or without a gear wheel	0 %	-	31.12.2030
0.2838	ex 8501 10 99	79	DC motor with brushes and an internal rotor with a three-phase winding, whether or not equipped with a worm or a pinion, of a specified temperature range covering at least - 20°C to + 70°C	0 %	-	31.12.2029
0.8345	ex 8501 20 00	50	Universal AC/DC motor, rotating: — with a nominal supply voltage of 230 V, — with a power of more than 37,5 W but not more than 2 000 W, — with a stator cross-section of 93 mm or more but not more than 103 mm and a thickness of 15 mm or more but not more than 45 mm, and — with or without a worm gear, gears or a gearbox, for the production of a torque to a transmission shaft for small domestic appliances (1)	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8349	ex 8501 20 00	60	Universal AC/DC motor, rotating: — with a nominal supply voltage of 230 V, — with a power of more than 37,5 W but not more than 1 200 W, — with a stator cross-section of 65 mm or more but not more than 75 mm and a thickness of 15 mm or more but not more than 45 mm, and — with or without a worm gear, gears or a gearbox, for the production of a torque to a transmission shaft for small domestic appliances (1)	0 %	-	31.12.2027
0.8367	ex 8501 20 00	70	Universal AC/DC motor, rotating: — with a nominal supply voltage of 230 V, — with a power of more than 37,5 W but not more than 700 W, — with a stator cross-section of 49 mm or more but not more than 59 mm and a thickness of 15 mm or more but not more than 45mm, and — with or without a worm gear, gears or a gearbox, for the production of a torque to a transmission shaft for small domestic appliances (1)	0 %	-	31.12.2027
0.5954	ex 8501 31 00	45	DC motors, brushless, with: — an external diameter of 90 mm or more, but not more than 110 mm, — a rated speed of not more than 3 680 rpm, — an output of 600 W or more but not more than 740 W at 2 300 rpm and at 80 °C, — a supply voltage of 12 V, — a torque of not more than 5,67 Nm, — a rotor position sensor, — an electronic star-point relay, and — for use with an electric power steering control module	0 %	-	31.12.2029
0.8395	ex 8501 31 00	47	Motor for automotive electric seat adjustment applications: — with a shaft output on both motor sides, — consisting of a permanently excited DC motor, — whether brushed or brushless, — whether or not with electronic control unit, — whether or not with Hall Effect Sensor, — with a nominal voltage of 8 V or more but not more than 16 V, — with a rated output mechanical power not exceeding 120 W, and — with a specified temperature range from -40 °C to 160 °C, for use in the manufacture of automotive components for car’s seats (1)	0 %	-	31.12.2027
0.8609	ex 8501 31 00	48	Brushless DC electric motors: — with a rated power of 240 W or more, but not more than 260 W, — with a voltage of 36 V or higher, but not higher than 52 V — with a torque of 20 Nm or more, but not more than 140 Nm, — with a housing made of aluminum, aluminum alloy or plastic, — with or without a built-in controller, — with a communication function in the LIN or UART interface, — weighing 1,5 kg or more, but not more than 5,0 kg, — adapted for mounting in a bicycle frame for use in the manufacture of e-bikes (1)	0 %	-	31.12.2028

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8608	ex 8501 31 00	49	Brushless DC electric motors: — with a rated power of 240 W or more, but not more than 260 W, — with a voltage of 24 V or higher, but not higher than 52 V, — with a torque of 30 Nm or more, but not more than 62 Nm, — with a LIN, UART or CAN communication interface, — with an internal planetary gearbox with fixed or variable ratio or direct drive, — with a housing made of aluminum or aluminium alloy, — with a weight of 1,5 kg or more, but not more than 6 kg, — adapted for mounting in the front or rear bicycle wheel, for use in the manufacture of e-bikes (1)	0 %	-	31.12.2028
0.5577	*ex 8501 31 00	50	DC motors, brushless, with: — an external diameter of 80 mm or more, but not more than 200 mm, — a supply voltage of 4V or more, but not more than 400 V, — an output at 20 °C of 60 W or more, but not more than 750 W, — a torque at 20 °C of 0,67 Nm or more, but not more than 7,00 Nm, — a rated speed at 20 °C of 600 rpm or more, but not more than 3 100 rpm, — with or without a pulley, — with or without an electronic power steering sensor/controller	0 %	-	31.12.2027
0.8847	ex 8501 31 00	52	Electric brushless direct current motor finished with biocompatible materials such as stainless steel according to specification 17-4 PH or type 303, 316L, 400 with: — a three-phase winding, — an output power not exceeding 280 W, — a length with gearhead of 116,1 mm or more but not more than 117,2 mm, — an external diameter of 13,86 mm or more but no more than 13,92 mm, — a maximum torque of motor with gearhead 246,6 mNm in 25°C, — a no-load radial speed of motor with gearhead with 9 900 rpm, at 24V in 25°C, — a weight of motor with gearhead of 70,5 g or more but not more than 71,5 g, a resistance to peak temperature of 140°C or more (non-operating), a maximal air leak between shaft and shaft seals of 15 Pa/s at given 2 Bars of pressure, — 14 functional pins for power and control purpose, — a flexible printed circuit with length of 245 mm but no longer than 255 mm with mounted 8 pin male connector for use in the manufacture of medical devices with right-left rotation and oscillation function (1)	0 %	p/st	31.12.2029
0.8855	ex 8501 31 00	54	Brushless DC electric motor, with: — a rated voltage of 310 V, — a rated power of 350 W or more but not more than 368 W, — an input power of 500 W or more but not more than 550 W, — output power of 350 W or more but not more than 400 W, — an external diameter without bracket connector and pulley of 143,2 mm or more but not more than 143,8 mm, — a rated speed of 16300 rpm or more but not more than 16500 rpm, — a weight of 2,33 kg or more but not more than 2,40 kg, — a pulley	0 %	p/st	31.12.2029
0.5978	ex 8501 31 00 ex 8501 32 00	55 40	DC motor with or without commutator, for driving hand-held power tools, lawn mowers or home appliances, with: — an external diameter of 24,2 mm or more, but not more than 140 mm, — a rated speed of 3 300 rpm or more, but not more than 26 200 rpm, — a rated supply voltage of 3,6 V or more, but not more than 230 V, — an output power of more than 37,5 W, but not more than 2 400 W, — a free load current of not more than 20,1 A, — a maximum efficiency of 50 % or more,	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8974	ex 8501 31 00	56	DC motor, brushless, integrated with an Electronic Control Unit (ECU), defined as a Power Pack with: — a safety feature and mechanism designed for prevention of critical hazards like self-steer by single failure, — a CAN-communication interface, — an external sensor interface, — operating temperature range of -40°C to 95°C or broader, — compliance with standard IP6K9K for water and dustproofness, — supply voltage of 9 V or more, but not more than 16 V, — rated power output of 500 W or more, but not higher than 750 W, — rated torque of 3 Nm or more, but not more than 6 Nm, — length of 150 mm or more, but not more than 250 mm, — width of 100 mm or more, but not more than 150 mm, — height of 80 mm or more, but not more than 120 mm	0 %	p/st	31.12.2030
0.8977	ex 8501 31 00	57	Brushless DC electric motor with LCD control indicator and/or control unit with buttons: — with an output power of 200 W or more, but not more than 700 W, — with a supply voltage of 30 V or more, but not more than 60 V, — with a torque of 30 Nm or more, but not more than 200 Nm, — with a height of 117 mm or more, but not more than 146 mm, — with a length of 117 mm or more, but not more than 223 mm, — with a width of 135 mm or more, but not more than 190 mm, — with a weight of 2 kg or more but not more than 5 kg, — designed to be mounted in a frame, front or rear bicycle wheel, — equipped with sockets, at least for cable connection with LCD control indicator, for use in the manufacture of electric bicycles (1)	0 %	p/st	31.12.2030
0.4731	ex 8501 31 00	58	Permanently excited DC motor with: — an external diameter of 27 mm or more but not more than 90 mm, including mounting flange, — a rated speed of not more than 25 000 rpm, — an output of 45 W or more but not more than 400 W, and — a supply voltage of 9 V or more but not more than 50 V, — whether or not a multiple-phase winding, — whether or not with a drive disc, — whether or not with a crankcase, — whether or not with a fan, — whether or not with a cap assembly, — whether or not with a sun gear, — whether or not with a speed and rotational direction encoder, — whether or not with or without a speed or rotational direction sensor of resolver type or Hall effect type, — whether or not with a mounting flange for use in the manufacture of air suspension seats in tractors, earthmoving machines and forklifts or for use in the manufacture of actuators for height-adjustable furniture (1)	0 %	-	31.12.2029
0.9141	*ex 8501 31 00	59	DC motor: — with a rotational speed not exceeding 1 000 rpm, — with a maximum output power of less than 124 W, — with a rated voltage of 310 V, — with 8 poles, — with a maximum torque not exceeding 12.1 kgf·cm, — with a maximum current of 0.6 A, — with insulation class, — with a counter-clockwise rotation direction, — with aluminium windings for use in the manufacture of air conditioners (1)	0 %	-	31.12.2031

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.6809	*ex 8501 31 00 ex 8501 32 00	63 65	Ready for installation in vehicles or equipment of headings 8432 and 8433, brushless and permanently excited direct current motor with: — a specified speed of not more than 4 100 rpm, — a minimum output of 400 W, but not more than 1,3 kW (at 12 V), or with a minimum output of 750 W but not more than 1,55 kW (at 36 V), — a flange diameter of 85 mm or more but not more than 200 mm, — a maximum length of 335 mm, measured from the beginning of the shaft to the outer ending, — a housing length of not more than 265 mm, measured from the flange to the outer ending, — a maximum of two-piece (basic housing including electric components and flange with minimum 2 and maximum 11 bore holes) aluminium diecast or sheet steel housing whether or not with a sealing compound (groove with an O-ring and grease), — a stator with single T-tooth design and single coil windings in 9/6 or 12/8 topology, and — surface magnets, — whether or not with electronic power steering controller, — whether or not with pulley, — whether or not with rotor position sensor	0 %	-	31.12.2030
0.4855	*ex 8501 33 90 ex 8501 40 80 ex 8501 53 50	30 50 10	Electric drive for motor vehicles, with an output of not more than 315 kW: — with an AC or DC motor with or without transmission, — with or without power electronics	0 %	-	31.12.2031
0.8982	ex 8501 40 20	75	Incomplete, single-phase brushless AC motor consisting of a rotor and a stator: — a rotor on the inside is equipped with a ring of 12 magnets housed in a steel casing, — a stator with an internal diameter of 206,6 mm (± 0,5 mm), external diameter of 265,0 mm (± 0,2 mm) and width of 37,2 mm or more but not more than 47,8 mm, — with a rated power not exceeding 750 W, — with a weight of 5 kg or more, for use in the production of washing machines, washer-dryers equipped with a drum with direct drive (1)	0 %	p/st	31.12.2030
0.8844	ex 8501 51 00	25	Electric permanent magnet synchronous motor with: — an output power of 550 W, — a rotor containing 8 poles generated by permanent magnets composed mainly with neodymium-iron-boron (per GB/T 13560 standard) enclosed in polyethylene cover, — an outer diameter of motor magnet shaft end with dimension of 10,001 mm or more but no more than 10,007 mm, — terminals located across the radius 32,5 mm and separated by an angle of 21,8°, — a motor housing made of ADC12 or AC46000 aluminium alloy die casting with composition of aluminium-silicon-copper (per JIS H5302 or EN1706 standard), — a back electromotive force constant (Ke) of 0,03306 V-sec/rad or more but no more than 0,03654 V-sec/rad, — a back electromotive force harmonic order - 5th of no more than 0,38 % (of fundamental) and 7th of no more than 0,25 % (of fundamental), — a cogging torque of no more than 13 mNm, — a friction torque in ambient temperature of no more than 22 mNm, — a maximum temperature of motor operation of no more than 200 °C	0 %	p/st	31.12.2029
0.5329	*ex 8501 51 00 ex 8501 52 20	30 50	AC synchronous servo motor with resolver and brake for a maximum speed of not more than 6 000 rpm, with: — an output of 340 W or more but not more than 7,4 kW, — a flange of dimensions of not more than 180 mm × 180 mm, and — a length from flange to extreme end of resolver of not more than 271 mm	0 %	-	31.12.2031

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8845	ex 8501 51 00	35	Electric permanent magnet synchronous motor with: — an output power of 600 W, — a rotor containing 8 poles generated by permanent magnets composed mainly with neodymium-iron-boron and dysprosium enclosed in aluminium cover, — an outer diameter of motor magnet shaft end with dimension of 10,001 mm or more but no more than 10,007 mm, — terminals located across the diameter 59,2 mm and separated by an angle 30,0°, — a housing made of electrogalvanized steel (per JIS G3313 Grade SECE standard) using a deep-drawing stamping process, — a diameter of 88,600 mm or less but no less than 88,546 mm at the motor-system assembly interface, — a back electromotive force constant (Ke) of 0,03277 V-sec/rad or more but no more than 0,03623 V-sec/rad, — a back electromotive force harmonic order - 5th of no more than 0,35 % (of fundamental) and 7th of no more than 0,30 % (of fundamental), — a cogging torque of no more than 12 mNm, — a friction torque in ambient temperature of no more than 23 mNm, — a maximum temperature of motor operation of no more than 200 °C	0 %	p/st	31.12.2029
0.8590	*ex 8501 51 00	45	Automotive-ready brushless, multi-phase, permanently excited magnet synchronous alternating current motor with: — a specified speed of not more than 10000 rpm, — an output of 400 W or more but not more than 750 W (at 12 V), — a flange diameter of 80 mm or more, but not more than 200 mm, — a maximum length of not more than 335 mm, measured from the beginning of the shaft to its outer end, — a housing length of not more than 265 mm, measured from the flange to the outer end, — a steel sheet or die-cast aluminium basic housing consisting of not more than two parts, including electrical components and a flange with two or more but not more than 11 holes, whether or not with a sealing connection (groove with O-ring and protective grease or liquid seal interface), — a stator with single T-tooth design and single coil winding with 9/6 or 12/10 or 12/8 topology and surface or buried magnets, — whether or not with electronic power steering controller, — whether or not with pulley or coupling, — whether or not with rotor position sensor	0 %	p/st	31.12.2028
0.8404	ex 8501 51 00	50	Three phase AC synchronous brushless permanent magnet motor with: — an output of 500 W or more but not more than 700 W, — an external diameter of 129,7 mm or more but not more than 180,3 mm, — a rated speed of 16 000 rpm or more but not more than 17 000 rpm, — a weight of 2,5 kg or more but not more than 3,1 kg, and — with a pulley, for use in the manufacture of home appliance products [(1)]	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.9037	ex 8501 52 20	55	Brushless synchronous alternating current electric motors with permanent magnets, with: — an output power of 1000 W or more, but not more than 1400 W, — a rotor containing 8 poles, generated by permanent magnets composed mainly of praseodymium-neodymium-iron-boron (GB/T 13560-2017 standard), enclosed in a stainless steel cover, — a motor magnet shaft end outer diameter of 10,001 mm or more, but not more than 10,007 mm, — motor terminals located across the 37,00 mm radius and separated by an angle of 30,00 °, — a motor housing made of ADC12 or EN AC46000 aluminium alloy die casting with composition of aluminium-silicon-copper (per JIS H5302-2000 or EN 1706 standard), — a back electromotive force constant (Ke) of 0,0265 V-sec/rad or more, but not more than 0,0293 V- sec/rad, — a back electromotive force (EMF) harmonic order – 5th of no more than 0,4 % (of fundamental) and 7th of no more than 0,2 % (of fundamental), — a synchronous inductance of 33,49 µH or more, but not more than 37,01 µH, — a cogging torque of not more than 15 mNm, — a friction torque in ambient temperature of not more than 20 mNm, — a maximum motor operation temperature of not more than 200 °C, — with or without a spline on the motor shaft	0 %	p/st	31.12.2030
0.9169	*ex 8501 52 20	65	Electric permanent magnet synchronous motor with: — an output power of 800 W or more, but not more than 850 W, — a rotor containing 8 poles generated by permanent magnets composed mainly of Neodymium-Cerium-Iron-Boron (per GB/T 13560-2017 standard) enclosed in a stainless steel cover, — an outer diameter of motor magnet shaft end with dimension of 10.001 mm or more, but not more than 10.007 mm, — three motor terminals located across the 28.000 mm radius and separated by an angle of 45.000 °, — a shaft end spline (per ANSI B92.2M standard), — a motor housing made of AlSi12(Fe) (EN AC-44300) aluminum alloy die casting with composition of aluminum-silicon-iron (per EN 1706 standard), — a back electromotive force constant (Ke) of 0.0408 V-sec/rad or more, but not more than 0.0450 V-sec/rad, — a back electromotive force (EMF) harmonic order - 5th of not more than 0.3 % (of fundamental) and 7th of not more than 0.3 % (of fundamental), — a maximum motor torque of 4.51Nm or more, — a specific synchronous inductance of 88.39 µH or more, but not more than 97.69 µH, — a cogging torque of not more than 15 mNm, — a friction torque in ambient temperature of not more than 18 mNm, — a maximum motor operation temperature of not more than 200 °C	0 %	-	31.12.2031
0.8902	ex 8501 52 20	70	Automotive-ready brushless permanently excited magnet synchronous alternating current motor with: — a specified speed of not more than 7000 rpm, — an output of 750 W or more but not more than 1,8 kW (at 12 V), — a flange diameter of 80 mm or more, but not more than 200 mm, — a maximum length of not more than 335 mm, measured from the beginning of the shaft to its outer end, — a housing length of not more than 265 mm, measured from the flange to the outer end, — a steel sheet or die-cast aluminium basic housing consisting of not more than two parts, including electrical components and a flange with two or more but not more than 11 holes, whether or not with a sealing connection (groove with O-ring and protective grease or liquid seal interface), — a stator with single T-tooth design and single coil winding with 9/6 or 12/10 or 12/8 topology and surface magnets, — whether or not with electronic power steering controller, — whether or not with pulley or coupling, — whether or not with rotor position sensor	0 %	p/st	30.06.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.9170	*ex 8501 52 20	75	Electric permanent magnet synchronous motor with: — an output power of 1000 W or more, but not more than 1050 W, — a rotor containing 8 poles generated by permanent magnets composed mainly of Neodymium-Cerium-Iron-Boron (per GB/T 13560-2017 standard) enclosed in a stainless steel cover, — an outer diameter of motor magnet shaft end with dimension of 10.001 mm or more, but not more than 10.007 mm, — six motor terminals located across the 28.000 mm radius and separated by an angle of 30.000 °, — a shaft end spline (per ANSI B92.2M standard), — a motor housing made of AlSi12(Fe) (EN AC-44300) aluminum alloy die casting with composition of aluminum-silicon-iron (per EN 1706 standard), — a back electromotive force constant (Ke) of 0.0375 V-sec/rad or more, but not more than 0.0415 V-sec/rad, — a back electromotive force harmonic order - 5th of not more than 0.3 % (of fundamental) and 7th of not more than 0.3 % (of fundamental), — a maximum motor torque of 5.60 Nm or more, — a specific synchronous inductance of 58.85 μH or more, but not more than 65.05 μH, — a cogging torque of not more than 15 mNm, — a friction torque in ambient temperature of not more than 23 mNm, — a maximum motor operation temperature of not more than 200 °C	0 %	-	31.12.2031
0.8846	ex 8501 52 20	80	Electric permanent magnet synchronous motor with: — an output power of 850 W, — a rotor containing 8 poles generated by permanent magnets composed mainly with neodymium-iron-boron (per GB/T 13560 standard) enclosed in polyethylene cover, — an outer diameter of motor magnet shaft end with dimension of 10,001 mm or more but no more than 10,007 mm, — terminals located across the radius 26,2 mm and separated by an angle 30,0°, — a housing made of ADC12 or AC46000 aluminium alloy die casting with composition of aluminium-silicon-copper (per JIS H5302 or EN1706 standard) and anodized coating (per ASTM B580 type E standard), — a back electromotive force constant (Ke) of 0,04009 V-sec/rad or more but no more than 0,04431 V-sec/rad, — a back electromotive force harmonic order - 5th of no more than 0,36 % (of fundamental) and 7th of no more than 0,24 % (of fundamental), — a cogging torque of no more than 20 mNm, — a friction torque in ambient temperature of no more than 26,5 mNm, — a maximum temperature of motor operation of no more than 200 °C	0 %	p/st	31.12.2029
0.8129	ex 8501 53 50	30	Permanent magnet synchronous traction motor, with: — a continuous power of 110 kW or more but not more than 180 kW, — a liquid cooled system, — a total length of 500 mm or more but not more than 650 mm, — a total width of 600 mm or more but not more than 700 mm, — a total height of 550 mm or more but not more than 650 mm, — weighing of not more than 350 kg, — 3 suspension points	0 %	-	31.12.2030
0.8458	ex 8501 53 50	50	Asynchronous traction motor, with: — a continuous power of 140 kW or more but not more than 180 kW, — a liquid cooled system, — a total length of 580 mm or more but not more than 730 mm, — a total width of 550 mm or more but not more than 670 mm, — a total height of 510 mm or more but not more than 630 mm, — with a weight of not more than 390 kg, — with or without reduction gear, — with or without starter generator, — 2 mounting points, for use in the manufacture of the electric drive of hybrid buses (1)	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8130	ex 8501 62 00	40	AC, 3-phase generator, with: — a continuous power of 147 kVA or more but not more than 222 kVA, — a continuous torque of 650 Nm or more but not more than 900 Nm, — a maximum working speed of 2700 revolutions per minute (rpm), — a liquid cooled system, — a length of 100 mm or more but not more than 200 mm, — a width of 550 mm or more but not more than 650 mm, — a height of 550 mm or more but not more than 650 mm, — weighing of not more than 150 kg	0 %	-	31.12.2030
0.9020	ex 8503 00 20	20	Plated steel core of the electric motor rotor of electric air conditioning compressors for motor vehicles: — with an outer diameter of 65 mm or more but not more than 80 mm, — with an inner diameter of 15 mm or more but not more than 25 mm, — with a height of 30 mm or more but not more than 45 mm, — with a weight of 0,5 kg or more but not more than 0,8 kg, — without windings	0 %	-	31.12.2030
0.9019	ex 8503 00 20	30	Plated steel core of the electric motor stator of electric air conditioning compressors for motor vehicles: — with an outer diameter of 90 mm or more but not more than 120 mm, — with an inner diameter of 65 mm or more but not more than 80 mm, — with a height of 30 mm or more but not more than 45 mm, — with a weight of 0,7 kg or more but not more than 1,2 kg, — without windings	0 %	-	31.12.2030
0.2837	*ex 8503 00 92 ex 8503 00 97	31 32	Rotor, at the inner side provided with one or two magnetic rings (uniform or sectional) whether or not incorporated in a steel ring or bearing mounted in steel housing	0 %	p/st	31.12.2029
0.7496	*ex 8503 00 97	37	Rotor for electric motor, with the rotor cylindrical body made of agglomerated ferrite or sintered neodymium or plastoneodymium, with or without metal shaft and with or without plastic elements: — diameter of the rotor body of 15 mm or more but not more than 37 mm, — length of the rotor body of 12 mm or more but not more than 36 mm	0 %	-	31.12.2029
0.8658	*ex 8503 00 97	40	Pressure casted inner housing of a cooling channel system for an electrical motor: — of EN AC-47100 aluminum, — shot-blasted and machined, — leakproof to the degree of 3 ml per minute or less under 2,75 bar pressure, — with a hardness of 70 or more on the Hardness Brinell Wolfram (HBW) scale (2,5/62,5, according to ISO 6506), — with a tensile strength of 190 N/mm² or more, — with a height of 160 mm or more, but not more than 330 mm, — with a diameter of 240 mm or more, but not more than 368 mm, — with a weight of 3 kg or more, but not more than 5,84 kg	0 %	-	31.12.2028
0.9021	*ex 8503 00 97	45	Armature for the electric motor in starter motors of passenger cars and commercial vehicles with: — an outer diameter of 52 mm or more but not more than 80 mm, — a commutator copper wire diameter of 2 mm or more but not more than 4 mm	0 %	-	31.12.2030
0.8662	*ex 8503 00 97	53	Pressure casted rotor cover of the cooling channel system in the electrical motor: — of EN AC-47100-F aluminum, — with a sealing cap of stainless steel, — shot-blasted and machined, — leakproof to the degree of 1 ml per minute or less under 2,75 bar pressure, — with a hardness of 70 HBW or more (2,5/62,5, according to ISO 6506), — with a tensile strength of 190 N/mm² or more, — with a height of 42 mm or more, but not more than 64 mm, — with a diameter of 88 mm or more, but not more than 132 mm, — with a weight of 0,3 kg or more, but not more than 0,5 kg	0 %	-	31.12.2028

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.6161	*ex 8503 00 97	55	Stator for brushless motor, with: — an internal diameter of 206,6 mm (± 0,5), — an external diameter of 265,0 mm (± 0,2), and — a width of 37,2 mm or more but not more than 47,8 mm, of a kind used in the manufacture of washing machine, washer-dryer or dryer equipped with direct drive drums	0 %	p/st	31.12.2031
0.8659	*ex 8503 00 97	63	Pressure casted outer housing of an electrical motor: — of EN AC-47100 aluminum, — with or without overmolded bearing sleeves of martensitic stainless steel and assembled sealing caps of stainless steel, — shot-blasted and machined, — with or without a rotor chamber, leakproof to the degree of 3 ml per minute or less under 2,75 bar pressure, — with a hardness of 70 or more on the Hardness Brinell Wolfram (HBW) scale (2,5/62,5, according to ISO 6506), — with a tensile strength of 190 N/mm² or more, — with a height of 195 mm or more, but not more than 430 mm, — with a width of 290 mm or more, but not more than 625 mm, — with a length of 270 mm or more, but not more than 535 mm, — with a weight of 5,2 kg or more, but not more than 12,5 kg	0 %	-	31.12.2028
0.8783	*ex 8503 00 97	73	Pressure die-cast electric motor stator housing: — of EN AC-46000 aluminium, — shot-blasted and machined, — with a height of 70 mm or more but not more than 76 mm, — with a width of 155 mm or more but not more than 162 mm, — with a weight of 330 g or more but not more than 360 g	0 %	-	31.12.2029
0.7761	*ex 8503 00 97	75	Stator body of stacked electrical sheet having: — an inner diameter of 18 mm or more but not more than 35 mm, — an outer diameter of 35 mm or more but not more than 65 mm, and — a length of 20 mm or more but not more than 65 mm, — whether or not incorporated in a housing	0 %	-	31.12.2029
0.7549	ex 8504 31 80	15	Electrical Transformer with — a capacity of 192 Watts or 216 Watts — dimensions of not more than 27,1 x 26,6 x 18 mm — an operating temperature range of – 40 °C or more, but not more than + 125 °C — three or four inductively coupled copper wire windings and — 9 connection pins at the bottom	0 %	-	31.12.2029
0.4450	ex 8504 31 80	30	Transformers, having a power handling capacity of not more than 1 kVA for use in the manufacture of static converters and goods of heading 8537 (1)	0 %	-	31.12.2029
0.7000	*ex 8504 31 80	50	Transformers for use in the manufacture of electronic drivers, control devices and LED light sources for lighting industry (1)	0 %	-	31.12.2031
0.7029	*ex 8505 11 20	20	Articles, of an alloy of neodymium, containing a combined weight of 5 % or more of neodymium or praseodymium, in the shape of a rectangle, triangle, square, or trapezoid, — whether or not arched, — whether or not with rounded corners or oblique sides, — whether or not colour marked — whether or not coated or passivated with a surface treatment, — whether or not consisting of segments bonded together and electrically insulated from one another with: — a length of 9 mm or more, but not more than 105 mm, — a width of 5 mm or more, but not more than 105 mm, — a thickness of 2 mm or more, but not more than 55 mm intended to become permanent magnet after magnetisation	0 %	-	31.12.2031

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.5584	*ex 8505 11 20	23	Bars in the form of arched rectangles, containing alloy containing neodymium, with: — a length of 15 mm or more but not more than 52 mm, — a width of 5 mm or more but not more than 42 mm, — whether or not coated or passivated with a surface treatment, intended to become permanent magnets after magnetisation	0 %	p/st	31.12.2027
0.5585	*ex 8505 11 20	28	Articles containing alloy containing neodymium, in the form of rings, tubes, bushings or collars: — with an external diameter of not more than 45 mm, — with a height of not more than 45 mm, — whether or not coated or passivated with a surface treatment, intended to become permanent magnets after magnetisation	0 %	p/st	31.12.2027
0.3740	*ex 8505 11 20	30	Permanent magnets of an alloy of neodymium, either in the shape of a rectangle, whether or not rounded, whether or not coated or passivated with a surface treatment, with: — a rectangular or a trapezoidal cross-section, — a length of not more than 140 mm, — a width of not more than 90 mm and — a thickness of not more than 55 mm, or in the shape of an arched rectangle with: — a length of not more than 75 mm, — a width of not more than 40 mm, — a thickness of not more than 7 mm and — a radius of curvature of more than 86 mm but not more than 241 mm, — layers of nickel and copper or in the shape of a disc with: — a diameter of not more than 90 mm, — whether or not a hole in the centre	0 %	p/st	31.12.2029
0.5948	*ex 8505 11 20	35	Article of an alloy of neodymium, in the shape of a disc, with: — a diameter of not more than 90 mm, — whether or not a hole in the centre, — layers of copper, nickel and/or zinc, intended to become permanent magnets after magnetisation	0 %	-	31.12.2029
0.9168	*ex 8505 11 20	40	Magnetized upper rotor made with steel stack according to standards ASTM A677-07 grade 47F180 or JIS C 2552 Grade 50A310, with: — twelve permanent magnets made with neodymium-iron-boron, enclosed in stamped steel stack ring, — a residual induction value 1.21 T or more, but not more than 1.32 T at 25 °C, — an inner diameter of 22.735 mm or more, but not more than 22.835 mm, — an outer diameter of 30.725 mm or more, but not more than 38.025 mm for use in the manufacture of vehicle's steering system (1)	0 %	-	31.12.2031
0.8508	*ex 8505 11 20	78	Two permanent magnets made of a praseodymium-neodymium alloy, in a rectangular steel holder with an outer casing of rubber with outer dimensions: — a length of 200 mm or more but not more than 205 mm, — a width of 58 mm or more but not more than 62 mm, — a height of 25 mm or more but not more than 30 mm, with a stud mounted in the middle	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.9192	*ex 8505 11 30	20	Articles, of an alloy of neodymium, containing a combined weight of 5 % or more of samarium, in the shape of a rectangle, triangle, square, or trapezoid, — whether or not arched, — whether or not with rounded corners or oblique sides, — whether or not colour marked — whether or not coated or passivated with a surface treatment, — whether or not consisting of segments bonded together and electrically insulated from one another with: — a length of 9 mm or more, but not more than 105 mm, — a width of 5 mm or more, but not more than 105 mm, — a thickness of 2 mm or more, but not more than 55 mm intended to become permanent magnet after magnetisation	0 %	-	31.12.2031
0.9159	*ex 8505 11 30	30	Articles of an alloy of samarium and cobalt, containing 21 % of samarium or more but not more than 30 % — whether or not coated or passivated with a surface treatment, — whether or not covered with zinc, — in the shape of a hollow cylinder, with: — an inner diameter of 7 mm or more but not more than 20 mm, — an outer diameter of 15 mm or more but not more than 30 mm, — a height of 15 mm or more but not more than 44 mm intended to become permanent magnets after magnetisation	0 %	-	31.12.2031
0.5937	ex 8505 19 90	30	Articles of agglomerated ferrite in the shape of a disc, whether or not coated or passivated with a surface treatment, with: — a diameter of not more than 120 mm, — a hole in the centre, intended to become permanent magnets after magnetisation with a remanence between 245 mT and 470 mT	0 %	-	31.12.2029
0.7299	ex 8505 19 90	45	Article of agglomerated ferrite in the shape of a rectangle, whether or not with oblique sides, with: — a length of 26,85 mm or more but not more than 32,15 mm, — a width of 7,6 mm or more but not more than 9,55 mm, — a thickness of 5,3 mm or more but not more than 5,8 mm, and — a weight of 6,1 g or more but not more than 8,3 g, intended to become a permanent magnet after magnetisation	0 %	p/st	31.12.2027
0.7511	ex 8505 19 90	60	Articles of agglomerated ferrite in the shape of arched rectangles, — whether or not coated or passivated with a surface treatment, — whether or not with rounded corners, with: — a length of 9 mm or more but not more than 101 mm, — a width of 9 mm or more but not more than 101 mm, — a thickness of 1,85 mm or more but not more than 15,15 mm, intended to become permanent magnets after magnetisation	0 %	-	31.12.2029
0.4029	ex 8505 20 00	30	Electromagnetic clutch, for use in the manufacture of compressors of air conditioning machines of motor vehicles (1)	0 %	p/st	31.12.2029
0.8627	ex 8505 20 00	40	Electromagnetic clutch: — transmitting torque from the motor shaft to the cutting device pulley, — containing field coil, rotor, hub and armature, — with an operating voltage of 12 V — a current of 3,93 A current or more but not more than 6,86 A, — a resistance of 1,84 ohm or more but not more than 3,05 ohm (operating at 20 °C), — a static torque of 108 Nm or more but not more than 305 Nm for use in the manufacture of rider type self-propelled mowers (1)	0 %	-	31.12.2028

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8095	ex 8505 90 90	20	Electromagnetic clutch coil in a cylindrical metal housing: — the metal housing is made of hot-rolled steel complying with standard JIS G 3131 - SPHE, — the coil is made of copper wire, — with a weight of 0,4 kg or more but not more than 0,85 kg, — with a width of 20 mm or more but not more than 45 mm, — with a plate reinforced to the coil (coil backplate) with an internal diameter of 44 mm or more but not more than 46 mm, — with an external diameter of 87 mm or more but not more than 110 mm, — without plunger, — with one connector	0 %	p/st	31.12.2027
0.2490	ex 8506 50 90	10	Lithium iodine single cell battery the dimensions of which do not exceed 9 mm × 23 mm × 45 mm and a voltage of not more than 2,8 V	0 %	-	31.12.2029
0.2488	ex 8506 50 90	30	Lithium-iodine or lithium-silver vanadium oxide single cell battery of dimensions of not more than 28 mm × 45 mm × 15 mm and a capacity of not less than 1,05 Ah	0 %	-	31.12.2029
0.8645	*ex 8507 60 10	25	Lithium-ion rechargeable battery cell with: — a length of 190 mm or more but not more than 380 mm; — a width of 90 mm or more but not more than 150 mm; — a height of 4 mm or more but not more than 40 mm, — a weight of 0,1 kg or more but not more than 3,2 kg, — a nominal voltage of 3,0 VDC or more but not more than 5,0 VDC — a nominal capacity of not more than 170 Ah, for use in the manufacture of rechargeable hybrid and electric vehicle batteries (1)	1.3 %	-	31.12.2027
0.2907	*ex 8507 60 10 ex 8507 60 90	30 30	Cylindrical lithium-ion accumulator or module, with a length of 63 mm or more and a diameter of 17,2 mm or more, having a nominal capacity of 1 200 mAh or more, for use in the manufacture of rechargeable batteries (1)	1.3 %	-	31.12.2027
0.7641	*ex 8507 60 10 ex 8507 60 90	59 59	Prismatic lithium-ion electric accumulator with: — a width of 120,0 mm or more but not more than 305,0 mm — a thickness of 12,0 mm or more but not more than 67,0 mm — a height of 72,0 mm or more but not more than 126,0 mm — a nominal voltage of 3,6 V or more but not more than 3,75 V, and — a nominal capacity of 6,9 Ah or more not more than 265 Ah, for use in the manufacture of rechargeable electric or hybrid vehicle batteries (1)	1.3 %	-	31.12.2027
0.6685	*ex 8507 60 90	15	Cylindrical lithium-ion-accumulators or modules with: — a nominal capacity of 8,8 Ah or more, but not more than 18 Ah, — a nominal voltage of 36 V or more, but not more than 48 V, — a power of 300 W or more, but not more than 648 W, for use in the manufacture of electric bicycles (1)	1.3 %	-	31.12.2027
0.7663	*ex 8507 60 90	19	Lithium-ion polymer accumulator pack equipped with a battery management system and can-bus interface with: — 4 modules or more, but not more than 8 modules with 90 cells or more but not more than 192 cells, — a nominal voltage of 280 V or more but not more than 400 V, — a nominal capacity of 9,7 Ah or more but not more than 120 Ah, — a charging voltage of 110 V or more but not more than 495 V, and in a metal casing with: — a length of not more than 1 723 mm, — a width of not more than 1 162,23 mm, — a height of not more than 395 mm, for use in the manufacture of vehicle capable of being charged by plugging to external source of electric power of heading 8703 (1)	1.3 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8660	*ex 8507 60 90	27	Modules for the assembly of electric accumulators using lithium ferrophosphate technology (LFP) with: — a length of 670 mm or more, but not more than 882 mm, — a width of 390 mm or more, but not more than 655 mm, — a height of 110 mm or more, but not more than 137 mm, — a weight of 60 kg or more, but not more than 165 kg, and — a nominal energy of 11 300 Wh or more, but not more than 29 360 Wh	1.3 %	-	31.12.2027
0.8368	*ex 8507 60 90	29	Lithium-ion rechargeable battery pack in a specific housing, suitable for use in digital still cameras, having: — a length of 50 mm or more, but not more than 120 mm, — a width of 35 mm or more, but not more than 80 mm, — a height of 15 mm or more, but not more than 45 mm, — a weight of 0,040 kg or more but not more than 0,085 kg; and — a capacity of not more than 2200 mAh	1.3 %	-	31.12.2027
0.5548	*ex 8507 60 90	31	Modules for the assembly of lithium-ion battery packs, using a technology other than lithium ferrophosphate (LFP) with: — a length of 298 mm or more, but not more than 500 mm, — a width of 33,5 mm or more, but not more than 209 mm, — a height of 75 mm or more, but not more than 228 mm, — a weight of 3,6 kg or more, but not more than 17 kg, — a nominal energy of 458 Wh or more, but not more than 3 510 Wh, and — a voltage of less than 45 V or more than 70 V	1.3 %	-	31.12.2027
0.6703	*ex 8507 60 90	33	Lithium-ion battery module or accumulator, with: — a length of 150 mm or more, but not more than 1 310 mm, — a width of 100 mm or more, but not more than 1 000 mm, — a height of 200 mm or more, but not more than 1 500 mm, — a weight of 50 kg or more, but not more than 200 kg, — cells of a nominal capacity of 58 Ah or more but not more than 500Ah, — a nominal output voltage of 230 V AC or 45 V or more but not more than 980 V DC	1.3 %	-	31.12.2027
0.8654	*ex 8507 60 90	36	Lithium-ion accumulator, with — multiple connected lithium-ion accumulator cells, — charging and monitoring electronics, — a nominal energy of 74 Wh or more, but not more than 75 Wh, — in a plastic housing with electrical connection contacts and LCD display, for use in the manufacture of cordless vacuum cleaners or rechargeable power sources therefor (1)	1.3 %	-	31.12.2027
0.8115	*ex 8507 60 90	48	Integrated battery system in a metal or plastic case with or without holders, consisting of: — a lithium-ion battery with a voltage of 36 V or more but not more than 50,4 V and a nominal energy between 0,3 kWh and 0,9 kWh, — a Battery Management System, — a power relay or power semiconductor switches (MOSFETs - Metal-Oxide-Semiconductor Field-Effect Transistor), — a cooling system, — one to four connectors, for use in the manufacture of Mild-hybrid (mHEV) motor vehicles (1)	1.3 %	-	31.12.2027
0.6753	*ex 8507 60 90	76	Lithium-ion accumulator, with: — a length of 700 mm or more, but not more than 2 820 mm, — a width of 935 mm or more, but not more than 1 660 mm, — a height of 85 mm or more, but not more than 700 mm, — a weight of 230 kg or more, but not more than 700 kg, — a nominal energy of not more than 175 kWh, — a nominal voltage of 320 V or more, but not more than 430 V for use in the manufacture of vehicles of subheadings 8701 to 8705 (1)	1.3 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8275	*ex 8507 60 90	83	Modules for the assembly of lithium-ion electric accumulators with: — a length of 570 mm or more, but not more than 610 mm, — a width of 210 mm or more, but not more than 240 mm, — a height of 100 mm or more, but not more than 125 mm, — a weight of 28 kg or more, but not more than 35 kg, and — a capacity of not more than 2500 Ah and a nominal energy of less than 8,4 kWh, for use in the manufacture of vehicles of subheadings 8703 60, 8703 70, 8703 80 and 8704 60 (1)	1.3 %	-	31.12.2027
0.8991	*ex 8507 90 31	20	Separator for the manufacture of lithium-ion batteries, in rolls, made of transparent, microporous, acrylic acid grafted polyethylene film, with: — a width of 98 mm or more but not more than 170 mm, — a thickness of 15 µm or more but not more than 36 µm	1.3 %	-	31.12.2027
0.8992	*ex 8507 90 31	30	Separator for the manufacture of lithium-ion batteries, in rolls, made of microporous monolayer film of polypropylene or a microporous trilayer film of polypropylene, polyethylene and polypropylene, each film with: — zero transversal production direction (TD) shrinkage, — a total thickness of 8 µm or more, but not more than 40 µm, — a width of 15 mm or more, but not more than 900 mm, — a length of more than 200 m, but not more than 8 000 m, — an average pore size between 0,02 µm and 0,1 µm, — whether or not coated with surfactant, — whether or not coated on 1 or 2 sides with a ceramic layer of min 1 µm thickness or more, but not more than 5 µm, — whether or not coated on 1 or 2 sides with a sticky binder, PVdF type or similar of min 0,5 µm thickness or more, but not more than 5 µm	1.3 %	-	31.12.2027
0.7280	*ex 8507 90 31	40	Separator for the manufacture of lithium-ion batteries made of a multi-porous multilayer separator foil with: — one microporous polyethylene layer between two microporous polypropylene layers and whether or not coated with aluminium oxide on both sides, — a width of 65 mm or more but not more than 170 mm, — a total thickness of 10 µm or more but not more than 30 µm, — a porosity of 25 % (vol.) or more but not more than 65 % (vol.)	1.3 %	m²	31.12.2027
0.8419	*ex 8507 90 80	55	Top cap or housing made of aluminium or ferrous alloy or stainless steel: — whether or not including parts made of aluminum and aluminium alloy, — with or without sealing elements or other elements made of polymer material, — with or without a "current interrupt device " and an "evacuation valve" — with or without plastic sockets — with an outer diameter of 17 mm or more, but not more than 18 mm, or rectangular with: — length not greater than 450 mm, — width not greater than 200 mm, and — hight not greater than 150 mm, for use in the manufacture of lithium-ion batteries (1)	1.3 %	-	31.12.2027
0.6304	ex 8511 30 00	30	Igniter integrated coil assembly with: — an igniter, — a coil on plug assembly with an integrated mounting bracket, — a housing, — a length of 90 mm or more but not more than 200 mm (± 5 mm), — an operating temperature of -40 °C or more but not more than 130 °C, — a voltage of 10,5 V or more, but not more than 16 V	0 %	p/st	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7024	*ex 8511 30 00	55	Ignition coil: — with a length of 50 mm or more, but not more than 200 mm, — with an operating temperature of – 40 °C or more, but not more than 140 °C, and — with a voltage of 9 V or more, but not more than 16 V, — with or without connection cable, for use in the manufacture of engines of motor vehicles (1)	0 %	-	31.12.2031
0.8628	ex 8511 80 00	30	Ignition module: — made with plastics and non-ferrous metals, — with the electric components cast in epoxy resin, — to generate the ignition energy and to electronically control the ignition timing, — to connect spark plug and circuit breaker, for use in the manufacture of two-stroke engines (1)	0 %	-	31.12.2028
0.9026	ex 8511 90 00	20	Drive end shield for starter motors and alternators of passenger cars and commercial vehicles — produced with high pressure precision die casting technology, — made of aluminium alloy (EN 1706 grade AC-47100 or AC-47100 S or AC-46000 or AC-46000 S or AC-44300), — whether or not with bearing	0 %	-	31.12.2030
0.9022	ex 8511 90 00	30	Commutator for passenger car and commercial vehicle starter motors — with a length of 27,7 mm or more but not more than 44,6 mm, — with umbrella or drum design	0 %	-	31.12.2030
0.8633	ex 8512 20 00	25	An electrical component with an integrated LED, in an ABS housing, with: — a voltage of 11 V or more, but not more than 15 V, — a circular shape, — 2 terminals, — an outer diameter of the housing of 36 mm or more, but not more than 42,5 mm, — a diode voltage of 42 V or more, but not more than 48 V, and — a current of 55 mA or more, but not more than 65 mA	0 %	-	31.12.2028
0.8961	ex 8512 20 00	35	Sub-assembly reflectors and components for car rear lights: — containing two or three PCBA with a connection socket and LED, — with central control module (CCE) connected through wired harness, — with a main reflector, a sub-reflector and inner lens scattering the light made of plastic, — with depth of 119 mm or more, but not more than 146 mm, — with width of 142 mm or more, but not more than 490 mm, — with a height of 93 mm or more, but not more than 100 mm, — a weight of 414 g or more, but not more than 578 g, — with lightguide	0 %	-	31.12.2030
0.6562	ex 8512 20 00	60	Information screen displaying: — at least time, date and status of safety features in a vehicle, or — safety information on driving in the lane, blind spot, distance from the vehicle in front, current speed, speed limit, with an operating voltage of 12 V or more but not more than 14,4 V, of a kind used in the manufacturing of goods of Chapter 87	0 %	p/st	31.12.2029
0.8409	ex 8512 20 00	70	Electrical component with light guide integrated with LED, for motor vehicles with: — two parallel ribs in the front area with a distance between them of 1,4 mm or more but not more than 1,8 mm, — four holes with the dimension of 7,3 mm or more but not more than 7,9 mm in the short direction of the guide, and — a 3 pin connector, for use in the manufacture of automotive components (1)	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8410	ex 8512 20 00	80	Grab handle light with integrated LED, for motor vehicles: — a distance between integrated spring clip and surface of 0,85 mm or more but not more than 1,85 mm, — a length of the housing to two front vertical ribs of 26,45 mm or more but not more than 26,75 mm, and — four horizontal ribs where the distance on the lower area over the base radia between the two is 18,5 mm or more but not more than 18,7 mm, for use in the manufacture of automotive components (1)	0 %	-	31.12.2027
0.6863	ex 8512 30 90	20	Warning buzzer for parking sensor system in a plastic casing operating on the piezo-mechanic principle, containing: — a printed circuit board, — a connector, — whether or not a metal holder, for use in the manufacture of goods of chapter 87 (1)	0 %	p/st	31.12.2029
0.5983	ex 8512 40 00 ex 8516 80 20	10 20	Car door mirror heating foil: — with two electrical contacts, — with an adhesive layer on both sides (on the side of the plastic holder of the mirror and on the side of the mirror glass), — with a protective paper film on both sides	0 %	-	31.12.2029
0.8391	ex 8516 10 80	10	Tubular Heating Element with mounting flange for washing machines, with: — a nominal output power of 1 700 W at 230 V AC supply voltage, — a weight of 230 g or more but not more than 250 g, — a thickness of the external flange of 2 mm or more, — isolation bushes of steatite or ceramic, and — no flat zones in the design, for use in the manufacture of home appliance products and their components (1)	0 %	p/st	31.12.2027
0.9153	*ex 8516 80 20	30	Electric heating resistor with an insulated former, made of stainless steel, for heating automotive coolant: — with at least 1 insulating layer, 1 conductive layer, 1 resistive layer, 2 contact pads, and 1 protective layer; — with at least 9 screw holes of 3,5 mm or more, but not more than 6,0 mm in diameter; — with a width of 138 mm or more, but not more than 168 mm; — with a depth of 85 mm or more, but not more than 115 mm; — with a height of 0,5 mm or more, but not more than 3,6 mm	0 %	-	31.12.2031
0.9043	ex 8516 80 80	10	Electric heating resistor with a triple loop design: — mainly made of AISI 316L stainless steel, — with a rated voltage of 230V, — with a rated power of 2000W, — with a total heating element length of 217 mm or more, but not more than 223 mm, — with a heating element working length of 169,5 mm or more, but not more than 174,5 mm, — with a mounting flange diameter of 28 mm or more, but not more than 32 mm, — with a heating element bending radius of 10,75 mm, — equipped with thermal fuses, — without a built-in NTC sensor, — with nickel plated terminal pin and connector	0 %	-	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.9182	*ex 8516 80 80	20	Integrated liquid heater of the battery preheating system: — in a housing with a mounting device, an integrated heating coil and temperature sensor, — with one or more electrical connectors and an inlet and outlet for a liquid medium, — with a rated supply voltage of 220 V or more, but not more than 450 V, — with a rated power input of 3 000 W or more, but not more than 5 000 W for use in the manufacture of goods of Chapter 87 (1)	0 %	-	31.12.2031
0.9157	*ex 8516 90 00	20	Multilayer printed circuit board with active and passive components for controlling an automotive electric heating resistor: — with at least one microcontroller and two Insulated-gate Bipolar Transistor (IGBT) chips, — with at least four 1,5 mm pins, — with at least three connector elements, — with plated copper layers, — with a maximum of 1,5 µm tin surface coating, — with pressed boreholes	0 %	-	31.12.2031
0.9154	*ex 8516 90 00	30	Cast aluminium housing designed for integration into automotive electric heating resistor: — with at least one electrical chamber and one fluid chamber, — a width of 220 mm or more, but not more than 280 mm, — a length of 140 mm or more, but not more than 190 mm, — a height of 50 mm or more, but not more than 90 mm	0 %	-	31.12.2031
0.9150	*ex 8516 90 00	40	Heating Element: — electrically operated, — with a diameter of 145 mm, 180 mm, 210 mm, or 290 mm, — with power ratings of 1.2 kW, 1.8 kW, 2.3 kW, or 2.7 kW, — converting electrical energy into heat energy by means of electrical resistance, — containing a bare and coiled electric heating resistance wire, — having connection terminals for power supply, — including a thermostat, — not containing any energy regulator, power control unit, or electronic control board that adjusts the operating power of the heating elements for use in glass-ceramic cooktops or electric ovens with cooktops (1)	0 %	-	31.12.2031
0.5845	ex 8516 90 00	70	Inner pot: — containing side and central openings, — of annealed aluminium, — with a ceramic coating, heat resistant to more than 200° C for use in the manufacture of an electric fryer (1)	0 %	p/st	31.12.2027
0.6316	ex 8528 59 00	20	Liquid crystal display colour video monitor assembly mounted on a frame, — excluding those combined with other apparatus, — comprising touch screen facilities, a printed circuit board with drive circuitry and power supply, used for permanent incorporation or permanent mounting into entertainment systems for vehicles (1)	0 %	-	31.12.2029
0.9185	*ex 8536 10 90	20	High voltage traction battery fuse — with a rated voltage of 400 V or more, but not more than 600 V, — with a rated current of 200 A or more, but not more than 700 A, — with or without connector for current sensor, for use in the manufacture of battery systems for hybrid or electric vehicles (1)	0 %	p/st	31.12.2031

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7048	*ex 8536 41 10	20	Photoelectric (so called photovoltaic) relay consisting of a GaAlAs light-emitting diode, a galvanically isolated input circuit with a photovoltaic generator and a power MOSFET output switch in a casing with connections for a voltage of 60 volts or less and a current of 2 amps or less	0 %	-	31.12.2031
0.6180	*ex 8536 41 90	40	Power relay with: — electromechanical and/or electromagnetical switching function, — a load current of 3 A or more but not more than 36 A, — a coil voltage of 5 V or more but not more than 24 V, and — a distance between the connector pins of the load circuit not more than 27,6 mm	0 %	p/st	31.12.2029
0.8735	*ex 8536 41 90	60	Power relay with the function of safely connecting or disconnecting the charging and/or power circuit of 48V batteries in a plastic housing, containing: — current sensor 50A/400V, — high voltage MILD fuse 70V/300A, — whether or not cable with connector, for use in the production of rechargeable batteries for hybrid and electric vehicles (1)	1.1 %	-	31.12.2027
0.7052	*ex 8536 49 00	40	Photoelectric (so called photovoltaic) relay consisting of two GaAlAs light-emitting diodes, two galvanically isolated input circuits with photovoltaic generator(s) and four power MOSFET output switches in a casing with connections for a voltage of more than 60 volts	0 %	-	31.12.2031
0.7796	ex 8536 49 00	60	Relay in the shape of a cube with: — a coil operating voltage of 12 VDC (Voltage Direct Current) or more, but not more than 24 VDC (Voltage Direct Current), — a contact current carrying capacity of 5A or more, but not more than 15A, — a contact voltage of 80 VAC (Voltage Alternating Current) or more, but not more than 270 VAC (Voltage Alternating Current), — outer dimensions of 19 mm (± 0,4 mm) x 15,2 mm (± 0,4 mm) x 15,5 mm (± 0,4 mm), for use in the production of control board of household appliances (1)	0 %	-	31.12.2029
0.4614	ex 8536 69 90	82	Modular socket or plug for local area networks, whether or not combined with other sockets, integrating at least: — a pulse transformer, including a wide-band ferrite core, — a common mode coil, — a resistor, — a capacitor, for use in the manufacture of products falling within headings 8521 or 8528 (1)	0 %	p/st	31.12.2029
0.4616	ex 8536 69 90	83	AC socket with a noise filter, composed of: — AC socket (for power cord connection) of 230 V, — integrated noise filter composed of capacitors and inductors, — cable connector for connecting an AC socket with the PDP (Plasma display panel) power supply unit, whether or not equipped with a metal support, which joins the AC socket to the PDP TV set	0 %	p/st	31.12.2029
0.5318	*ex 8536 69 90	85	Socket or plug, built into a plastic or metal housing, with no more than 96 pins, for use in the manufacture of products falling within headings 8521 or 8528 (1)	0 %	p/st	31.12.2031
0.5316	*ex 8536 69 90	86	High-Definition Multimedia Interface (HDMI) type socket or plug, built into a plastic or metal housing, with 19 pins or 20 pins in 2 rows, for use in the manufacture of products falling within headings 8521 or 8528 (1)	0 %	p/st	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8405	ex 8537 10 91	25	A control unit being a printed circuit board with at least: — a microprocessor, — a programmable memory, — a single connector, — a PPE housing, — a supply of voltage of 220 V or more but not more than 240 V, — a length of 200 mm or more but not more than 210 mm, — a width of 70 mm or more but not more than 100 mm, and — a height of 20 mm or more but not more than 30 mm, for use in the manufacture of dishwashers (1)	0 %	-	31.12.2027
0.9184	*ex 8537 10 91	30	Control unit for an interior infrared camera for monitoring driver behaviour: — with an operating voltage of 9 V DC or more but not more than 16 V, — with at least one input and at least one output connector for use in the manufacture of goods of Chapter 87 (1)	0 %	p/st	31.12.2027
0.8392	ex 8537 10 91	35	A control unit being a printed circuit board with at least: — a microprocessor, — a programmable memory, — two or more connectors, but not more than twelve, — with or without LCD display, — with or without WiFi module, and — with or without an integrated speaker, for use in the manufacture of built-in ovens (1)	0 %	-	31.12.2027
0.8460	ex 8537 10 91	43	Electronic suspension control unit with: — a printed circuit board in plastic housing, — LIN and CAN buses, — a programmable memory, — a signal processor, — an operating direct current voltage of 9 V or more but not more than 16 V, — at least one connector, — whether or not with metal mounting bracket, for use in the manufacture of goods of Chapter 87 (1)	0 %	-	31.12.2027
0.8985	ex 8537 10 91	48	Control unit for the automatic transmission oil pump for efficient cooling and oil pressure regulation in the car's drivetrain: — liquid-cooled, — with an operating voltage of 9 V DC or more, but not more than 16 V, — with a height of 165 mm or more, but not more than 190 mm, — with a width of 40 mm or more, but not more than 60 mm, — with a length of 170 mm or more, but not more than 195 mm, — in a casing, — with one or more connectors, and for use in the manufacture of hybrid motor vehicles (1)	0 %	-	31.12.2030
0.7627	ex 8537 10 91	57	Programmable memory control board with: — 4 or more stepper motor drivers, — 4 or more outputs with MOSFET transistors, — a main processor, — 3 or more inputs for temperature sensors, — for a voltage of 10 V or more but not more than 30 V, for use in the manufacture of 3D printers (1)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.6163	ex 8537 10 91 ex 8537 10 98	60 45	Electronic control units, manufactured according to class 2 of IPC-A-610E standard, with at least: — an AC power input of 208 V or more but not more than 400 V, — a logic power input of 24 V DC, — an automatic circuit breaker, — a main power switch, — internal or external electrical connectors and cables, — in a housing with dimension of 281 mm x 180 mm x 75 mm or more, but not more than 630 mm x 420 mm x 230 mm, of a kind used for manufacturing recycling or sorting machines	0 %	p/st	31.12.2029
0.7251	ex 8537 10 91	70	Programmable motor memory controller for a voltage not exceeding 1 000 V, comprising at least: — a printed circuit with active and passive components, — an aluminium housing, and — multiple connectors	0 %	p/st	31.12.2027
0.8841	ex 8537 10 91	75	Printed circuit board equipped with a microcontroller for operating and/or control purposes — with or without operating components, signal components and display, — for operating voltages of 5V DC or more but not more than 24V DC or 220V AC or more but not more than 400V AC, — with or without housing for use in the manufacture of household appliances of subheadings 7321 11, 8414 60, 8418 10, 8418 21, 8418 29, 8418 40, 8422 11, 8450 11, 8450 12, 8450 19, 8450 20, 8451 21, 8451 29, 8516 60 (1)	0 %	-	31.12.2029
0.6140	ex 8537 10 98	30	Motor bridge ICs without programmable memory consisting of: — one or more integrated circuits, not interconnected, on separate lead frames, — also with discrete Metal Oxide Field Effect Transistors (MOSFET) for controlling DC motors in cars — mounted in a plastic housing	0 %	p/st	31.12.2029
0.7194	*ex 8537 10 98	33	Lever for control module under the steering wheel: — with several single or multi-positional electrical switches (push-button, rotary or other), — equipped with printed circuit boards and/or electrical cables, — for a voltage of 9 V or more but not more than 16 V, of a kind used in the manufacture of motor vehicles of Chapter 87	0 %	p/st	31.12.2031
0.8401	ex 8537 10 98	38	Control panel with switches for mirror, windows and other functions in vehicles, with: — a total length of 144 mm or more but not more than 150 mm, — a distance between intended screwing interface center points of 31 mm or more but not more than 31,50 mm, and — electric components inside the panel with integrated LEDs, for use in the manufacture of automotive components (1)	0 %	-	31.12.2027
0.8408	ex 8537 10 98	43	Switch for motor vehicle seat regulation with a memory function, with: — three single switches, — a five-pin connector, — for a voltage of 9 VDC or more but not more than 16 VDC, and — electric components inside the panel with integrated LED, for use in the manufacture of automotive components (1)	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8400	ex 8537 10 98	48	Memory switch control panel for seat and lock switch for vehicles with: — a width of 70,2 mm or more but not more than 70,5 mm, — parallel ribs with a distance between them of 2,6 mm or more but not more than 2,8 mm on the rear side, — a 5 pin connector, and — electric components inside the panel with integrated LED, for use in the manufacture of automotive components [(1)]	0 %	-	31.12.2027
0.6507	ex 8537 10 98	50	Electronic control unit BCM (Body Control Module) or IBM (Integrated Body Control Module) or similar: — comprising at least a plastic box with printed circuit board, with operating direct voltage of 9 V or more, but not more than 16 V, — whether or not with metal holder, — able to control, evaluate and manage functions of assisting services in an automobile, at least wiper timing, window heating, interior lighting, seat belt reminder, of a kind used in the manufacture of goods of Chapter 87	0 %	p/st	31.12.2029
0.8407	ex 8537 10 98	53	A control unit being a printed circuit board with at least: — a microprocessor, — two or more connectors but not more than four, — modified resins, — a length of 180 mm or more but not more than 250 mm, — a width of 130 mm or more but not more than 200 mm, and — a height of 40 mm or more but not more than 60 mm, for use in the manufacture of washing machines [(1)]	0 %	-	31.12.2027
0.8393	ex 8537 10 98	57	A control unit being a printed circuit board with at least: — a microprocessor, — eight connectors or more but not more than eleven, — a supply voltage of 215 V or more but not more than 245 V, — a housing of PA6-MR30, — with or without a transformer, — with or without a high power relay, — with or without insulated-gate bipolar transistor, — a length of 280 mm or more but not more than 345 mm, — a width of 400 mm or more but not more than 470 mm, — a height of 28 mm or more but not more than 45 mm, for use in the manufacture of induction stoves [(1)]	0 %	-	31.12.2027
0.8406	ex 8537 10 98	63	A control unit being a printed circuit board with at least: — a microprocessor, — two connectors, — a supply voltage of 215 V or more but not more than 245 V, — no housing, — a length of 100 mm or more but not more than 120 mm, — a width of 40 mm or more but not more than 50 mm, and — a height of 20 mm or more but not more than 30 mm, for use in the manufacture of refrigerators [(1)]	0 %	-	31.12.2027
0.3663	ex 8537 10 98	93	Electronic control units for a voltage of 12 V, for use in the manufacture of vehicle mounted temperature control systems [(1)]	0 %	p/st	31.12.2027
0.6866	ex 8538 90 91 ex 8538 90 99	20 50	Interior antenna for a car door locking system, comprising: — an antenna module in a plastic housing, — whether or not a connection cable with a plug, — whether or not a connector, — at least one mounting bracket, — whether or not PCB including integrated circuits, diodes and transistors, for use in the manufacture of goods of Chapter 87 [(1)]	0 %	p/st	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.2580	*ex 8540 20 80	91	Photomultiplier	0 %	-	31.12.2031
0.3445	ex 8540 89 00	91	Displays in the form of a tube consisting of a glass housing mounted on a board the dimensions of which do not exceed 300 mm × 350 mm excluding leads. The tube contains one or more rows of characters or lines arranged in rows, each character or line consisting of fluorescent or phosphorescent elements. These elements are mounted on a metallised base which is covered with fluorescent substances or phosphorescent salts which give off light when bombarded with electrons	0 %	-	31.12.2029
0.7409	ex 8540 91 00	20	Thermionic electron source (emitter point) of lanthanum hexaboride (CAS RN 12008-21-8) or cerium hexaboride (CAS RN 12008-02-5), with electric connectors — with or without a metal housing, — with or without a graphite carbon shield mounted in a mini-Vogel type system, — with or without separate pyrolytic carbon blocks used as heating elements, and — a cathode temperature of less than 1 800 K at a filament current of 1,26 A	0 %	-	31.12.2027
0.8333	ex 8543 70 90	27	Electronic control unit of the 360-degree vehicle situation display system with: — an operating DC voltage of 9 V or more but not more than 16 V, — a videoprocessor, — a signal processor, — one or more connectors, and — whether or not with a metal mounting bracket, for use in the manufacture of goods of Chapter 87 (1)	0 %	-	31.12.2027
0.2826	ex 8543 70 90	30	Amplifier, consisting of active and passive elements mounted on a printed circuit, contained in a housing	0 %	p/st	31.12.2029
0.2590	ex 8543 70 90	45	Piezo-electric crystal oscillator with a fixed frequency, within a frequency range of 1,8 MHz to 67 MHz, contained in a housing	0 %	p/st	31.12.2029
0.3131	ex 8543 70 90	55	Opto-electronic circuit comprising one or more light-emitting diodes (LEDs), whether or not equipped with an integrated driving circuit, and one photodiode with amplifier circuit, whether or not with an integrated logic gate arrays circuit or one or more light-emitting diodes and at least 2 photodiodes with an amplifier circuit, whether or not with an integrated logic gate arrays circuit or other integrated circuits, contained in a housing	0 %	p/st	31.12.2029
0.2816	ex 8543 70 90	85	Voltage controlled oscillator (VCO), other than temperature compensated oscillators, consisting of active and passive elements mounted on a printed circuit, contained in a housing	0 %	p/st	31.12.2029
0.6709	*ex 8544 20 00	30	Antenna connecting cable for the transmission of radio (AM/FM) signal and whether or not GPS signal, containing: — a coaxial cable, — two or more connectors, and — 3 or more plastic clips for attachment to the dashboard of a kind used in the manufacture of goods of Chapter 87	0 %	-	31.12.2031
0.8849	ex 8544 30 00	20	Insulated electrical multicore cable for the EPS-system (Electrical Power Steering) of a motor vehicle: — with a length of 170 mm or more but not more than 301 mm, — with an external diameter of 4,5 mm or more but not more than 7 mm, — with an operating temperature of -40°C or more but not more than 125°C, — with Cross-Linked Polyethylene (XLPE) or Thermoplastic Polyester Elastomer (TPE-E) wire insulation material, — with an operating voltage of 5 V, — fitted with connectors at both ends, — whether or not gold-plated or tin-plated	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.9014	*ex 8544 30 00	23	High-voltage single-core battery supply cable fitted with: — a high-voltage connector, — a metal flat lug with an eyelet in a plastic housing, — three or more plastic mounting clips for use in the manufacture of rechargeable batteries for hybrid and electric vehicles (1)	0 %	-	31.12.2027
0.9000	*ex 8544 30 00	33	Wiring harness for transmitting safety parameters from battery modules fitted with: — input and output connectors, — three or more plastic mounting clips for use in the manufacture of rechargeable batteries for hybrid and electric vehicles (1)	0 %	-	31.12.2027
0.9002	*ex 8544 30 00	43	High voltage battery cable assembly, comprising: — a single core high voltage cable terminated with a flat lug, — a safety fuse for an electric current of 10 A or more but not more than 400 A, — a flat copper conductor with surface insulation terminated with a flat lug, — three or more plastic clips for attachment for use in the manufacture of rechargeable batteries for hybrid and electric vehicles (1)	0 %	-	31.12.2027
0.6377	ex 8544 30 00 ex 8544 42 90	53 75	Electrical wiring harness or cable for the steering system: — with a rated voltage of 12 V, — fitted with connectors on both ends or/and with special adapter providing sealing and anti-rotation feature, — with or without plastic anchoring jaws for mounting the steering gear housing of motor vehicles, for use in the manufacture of power steering systems for motor vehicles (1)	0 %	p/st	31.12.2029
0.6710	ex 8544 30 00 ex 8544 42 90	60 50	Four-core connecting cable containing two female connectors for the transmission of digital signals from navigation and/or audio systems to a USB connector and/or LCD monitor, for use in the manufacture of goods of Chapter 87 (1)	0 %	-	31.12.2030
0.8331	ex 8544 30 00	65	Six core cable connecting the oil pressure sensor and the differential controller of vehicles: — with PVC-coating, — with three multiple connectors, and — with or without plastic clip, for use in the manufacture of goods of Chapter 87 (1)	0 %	-	31.12.2027
0.6867	*ex 8544 30 00	85	Extension two-core cable with two connectors, containing at least: — a rubber grommet, — a metal attachment bracket, of a kind used to connect vehicle speed sensors in the manufacture of vehicles of Chapter 87	0 %	p/st	31.12.2027
0.4980	ex 8544 42 90	10	Data transmission cable capable of a bit rate transmission of 600 Mbit/s or more, with: — a voltage of 1,25 V (± 0,25 V) — connectors fitted at one or both ends, at least one of which contains pins with a pitch of 1 mm, — outer screening shielding, used solely for communication between LCD, PDP or OLED panel and video processing electronic circuits	0 %	p/st	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.4464	ex 8544 42 90 ex 8544 49 93 ex 8544 49 95	20 20 10	PET or PVC insulated flexible cable with or without connector with: — voltage of not more than 250 V, — a current of not more than 1 A, — a heat resistance of not more than 105 °C, — individual wires of a thickness of not more than 0,1 mm (± 0,01 mm) and a width of not more than 0,8 mm (± 0,03 mm), — a distance between conductors of not more than 0,5 mm and — a pitch (distance from centreline to centreline of conductors) of not more than 1,25 mm	0 %	-	31.12.2028
0.8572	ex 8544 42 90 ex 8544 60 10	45 10	Specially designed connector for solar power system: — as 1-part system with 1 plastic housing with 1 or more but not more than 4 diodes and 2 insulated copper cables with connectors or — as 3-part system with one plastic housing with 1 or more but not more than 4 diodes and 2 plastic housings with insulated copper cables with connectors, — with a current for the diodes of 3 A or more but not more of 50 A, — with a cable length of not more than 1 500 mm, — with a maximum rated voltage of 1 500 V	0 %	-	31.12.2028
0.8859	ex 8544 42 90	55	Wire harness for the transmission of signals and/or electrical power, — with a 26-PIN or 28-PIN wire to board connectors in crimping technology, — bound by rubber or vinyl or electrical tape or conduit or a weave of extruded string or a combination thereof, for connection of power supply with main printed (circuit) board assembly (PBA) and electrical components of refrigerator or washing machine (1)	0 %	-	31.12.2029
0.6853	ex 8544 42 90	70	Electric conductors: — of a voltage of not more than 80 V, — with a length of not more than 120 cm, — fitted with connectors, for use in the manufacture of hearing aids, accessory kits and speech processors (1)	0 %	p/st	31.12.2030
0.2424	ex 8544 49 93	10	Elastomeric connector, of rubber or silicone, consisting of one or more conductor elements	0 %	p/st	31.12.2029
0.6861	ex 8544 49 93	30	Electric conductors: — of a voltage of not more than 80 V, — of a platinum-iridium-alloy, — coated with poly(tetrafluoroethylene), — without connectors, for use in the manufacture of hearing aids, implants and speech processors (1)	0 %	m	31.12.2030
0.9027	*ex 8547 90 00	10	Li-ion battery module component made of mica for fire protection, with a specially designed shape for the top and sides with: — a length of 480,0 or more but not more than 630,0 mm, — a width of 78,0 or more but not more than 233,0 mm and — a thickness of 0,75 or more but not more than 2,50 mm	1.8 %	-	31.12.2027
0.3144	ex 8548 00 90	41	Unit, consisting of a resonator operating within a frequency range of 1,8 MHz or more but not more than 40 MHz and a capacitor, contained in a housing	0 %	p/st	31.12.2029
0.3193	ex 8548 00 90	43	Contact image sensor	0 %	p/st	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.9038	ex 8548 00 90	45	Electromagnetic Interference filter designed to eliminate conducted electromagnetic interference from a power line, — with a rated voltage of 250 V AC, — with a rated current of not more than 15 A, — with an operating frequency of 50/60 Hz, — with a dielectric strength of 1500V AC for 1 minute, — containing a bleeder resistor with a resistance of 470 kΩ, — containing three varistors: one with rated voltage of 680 V, one of 910 V and one of 1800 V, each ±10 %, — mounted with an M8 screw with an average breaking force of 93 kgf/cm	0 %	-	31.12.2030
0.8972	*ex 8549 13 20	10	Spent electric accumulators of lithium-ion or nickel metal hydride	0 %	-	31.12.2027
0.6590	ex 8708 30 10 ex 8708 30 91	40 30	Body of disc type brake in BIR (“Ball in Ramp”) or EPB (“Electronic Parking Brake”) or with hydraulic function only, containing functional and mounting openings and guide grooves, of a kind used in the manufacture of goods of Chapter 87	0 %	p/st	31.12.2029
0.6707	ex 8708 30 10 ex 8708 30 91	70 40	Ductile cast iron brake caliper jaw, of a kind used in the manufacture of goods of Chapter 87	0 %	p/st	31.12.2030
0.6869	ex 8708 40 20 ex 8708 40 50	20 10	Automatic hydrodynamic gearbox — with a hydraulic torque converter, — without transfer box and cardan shaft, — whether or not with front differential, for use in the manufacture of motor vehicles of Chapter 87 (1)	0 %	p/st	31.12.2030
0.8820	ex 8708 40 20	25	Transmission assembly consisting of: — double pinion type planetary gear shifting mechanism, — sport sequential shiftmatic system with a speed of 7 or more but not more than 10, — a width of 280 mm or more but no more than 470 mm, — a height of 350 mm or more but no more than 595 mm, — a length of 410 mm or more but no more than 690 mm, — a weight of 70 kg or more but no more than 110 kg, for use in the manufacture of motor vehicles of subheading 8703 22 and 8703 23 (1)	0 %	-	31.12.2029
0.7856	ex 8708 40 20 ex 8708 40 50	70 60	Manual gearbox in cast aluminium housing for transverse installation with: — maximum dimensions of 550 x 500 x 600 mm — five or six gears, — a differential gear, — an engine torque of 400 Nm or less, for use in the manufacture of motor vehicles of Heading 8703 (1)	0 %	-	31.12.2029
0.8279	*ex 8708 40 20	80	Transmission gearbox without torque converter, with: — dual clutch, — 7 or more forward gears, — 1 reverse gear, — a maximum torque of 450 Nm, — whether or not with electric motor integrated, — a height of 350 mm or more but not more than 600 mm, — a width 350 mm or more but not more than 600 mm, and — a weight of 70 kg or more but not more than 110 kg, for use in the manufacture of motor vehicles of Heading 8703 (1)	0 %	p/st	31.12.2031

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8819	ex 8708 40 50	25	Transmission assembly housing 3 other shafts inside it and offering a rotating switch for shift position, consisting of: — cast aluminium body, — differential gear, — 2 electrical motors and gears, — a width of 280 mm or more but no more than 470 mm, — a height of 350 mm or more but no more than 595 mm, — a length of 410 mm or more but no more than 690 mm, for use in the manufacture of motor vehicles of subheadings 8703 40 and 8703 60 (1)	0 %	-	31.12.2029
0.8377	ex 8708 40 50	70	Automatic transmission equipped with double clutch system with: — at least 8 gears, — an engine torque of 800 Nm or more, — an electronic differential, — a P-lock safety system, and — a TCU transmission control unit, for use in the manufacture of motor vehicles of heading 8703 (1)	0 %	-	31.12.2027
0.7987	ex 8708 50 20 ex 8708 50 55	15 50	Spherical outboard constant velocity joint ball bearing cage, part of the vehicle's drive system, made of material suitable to be carburized with a carbon content of 0,14 % or more but not more than 0,57 %, forged, turned, punched, milled and hardened	0 %	-	31.12.2030
0.8461	ex 8708 50 20	18	Propeller shaft for torque transmission from the gearbox to the rear axle, consisting of: — two cardan rods, — central universal joint, — central bearing with suspension in a plastic cover, — universal joints on both ends of the shaft, — slip, tube and end yokes, — of a length of 1,4 m or more but not more than 2,4 m, for use in the production of goods of Chapter 87 (1)	0 %	-	31.12.2027
0.6648	ex 8708 50 20 ex 8708 50 99	20 10	Transmission shaft in carbon fibre reinforced plastics consisting of a unique piece without any joint in the middle — of a length of 1 m or more but not more than 2 m, — of a weight of 6 kg or more but not more than 9 kg	0 %	p/st	31.12.2030
0.7988	ex 8708 50 20 ex 8708 50 99	25 45	Ball-type outboard constant velocity joint housing for transmitting a torque from the engine and transmission to the wheels of motor vehicles, in a form of an outer race, with: — 6 ball tracks or more but not more than 8, with — a thread, — an external involute spline with 21 or more but not more than 38 teeth, — for running with bearing balls made of steel with a carbon content of 0,48 % or more but not more than 0,57 %, — forged, turned, milled and hardened	0 %	-	31.12.2030
0.7989	ex 8708 50 20 ex 8708 50 99	35 50	Inboard constant velocity joint tripod housing, with: — an outer diameter of 67,0 mm or more but not more than 99,0 mm, — 3 cold calibrated roller tracks with a diameter of 29,95 mm or more but not more than 49,2 mm, — an external spline with 21 teeth or more but not more than 41, — forged, turned, rolled and hardened	0 %	-	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7359	ex 8708 50 20 ex 8708 50 55 ex 8708 50 91 ex 8708 50 99	50 20 10 40	Double flange bearing of 3rd generation, for motor vehicles, — with double-row ball bearing, — whether or not with impulse (encoder) ring, — whether or not with antilock brake system (ABS) sensor, — whether or not with mounted screws, for use in the manufacture of goods of chapter 87 [(1)]	0 %	-	31.12.2027
0.7991	ex 8708 50 20 ex 8708 50 99	55 60	Inboard constant velocity joint tripod spider, part of the vehicle's drive system, with: — 3 trunnions with a diameter of 17,128 mm or more but not more than 25,468 mm, — forged, turned, broached and hardened	0 %	-	31.12.2030
0.7593	ex 8708 50 20 ex 8708 50 99	70 25	Housing of tripod type half shaft inboard joint for transmitting a torque from engine and transmission to wheels of motor vehicles with: — an outer diameter of 67,0 mm or more but not more than 84,5 mm, — 3 cold calibrated roller tracks with a diameter of 29,90 mm or more but not more than 36,60 mm, — sealing diameter 34,0 mm or more but not more than 41,0 mm, without lead angle, — spline with 21 teeth or more but not more than 35, — bearing seat diameter of 25,0 mm or more but not more than 30,0 mm, with or without oil grooves	0 %	-	31.12.2029
0.7640	ex 8708 50 20 ex 8708 50 99	75 35	Constant velocity joint assembly for transmitting a torque from engine and transmission to wheels of motor vehicles, consisting of: — an inner race with 6 ball tracks or more but not more than 8 for running with the bearing balls with a diameter of 13,0 mm or more but not more than 28,0 mm, — an outer race with 6 ball tracks or more but not more than 8 for running with the bearing balls, made of steel with carbon content of 0,45 % or more but not more than 0,58 %, with thread and with a spline with 22 teeth or more but not more than 44, — a spherical cage keeping bearing balls in the ball tracks of outer race and inner race in proper angular position, made of material suitable for carburizing with carbon content of 0,14 % or more but not more than 0,55 %, and — with a grease compartment, — capable of working at constant speed at variable articulation angle not higher than 52 degrees	0 %	-	31.12.2029
0.6711	ex 8708 80 20 ex 8708 80 35	10 10	Upper strut insulator containing: — a metal holder with three mounting screws, and — a rubber bump, for use in the manufacture of goods of Chapter 87 [(1)]	0 %	p/st	31.12.2030
0.7365	ex 8708 80 99	30	Surface-hardened, steel piston rod for a hydraulic or hydropneumatic shock absorber of motor vehicles: — with a chrome coating, — of a diameter of 11 mm or more, but not more than 28 mm, — of a length of 80 mm or more, but not more than 600 mm, with a threaded end or a mandrel for resistance welding	0 %	-	31.12.2027
0.6509	ex 8708 91 20 ex 8708 91 35	20 10	Aluminium cooler using compressed air with a ribbed design of a kind used in the manufacture of goods of Chapter 87	0 %	p/st	31.12.2029
0.6859	ex 8708 91 20 ex 8708 91 99	30 30	Aluminium alloy inlet or outlet air tank of heat exchangers for car cooling systems, manufactured to standard EN AC 42100 or EN AC 43000 T6 with: — an insulating area flatness of not more than 0,1 mm, — a permissible particle quantity of 0,3 mg per tank, — a distance between pores of 2 mm or more, — pore sizes of not more than 0,4 mm, and — not more than 3 pores larger than 0,2mm, — with a weight of 0,2 kg or more but not more than 3 kg	0 %	p/st	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7716	ex 8708 91 35	20	Turbocharger cooling duct containing: — an aluminum alloy duct with at least one metal holder and at least two mounting holes, — a rubber pipe with clips, — a stainless steel flange highly resistant to corrosion [SUS430JIL], for use in the manufacture of compression ignition engines of motor vehicles (1)	0 %	-	31.12.2029
0.8538	ex 8708 91 35	30	Two-circuit aluminum heat exchanger for automatic transmission of passenger cars: — of the stack-plate type, — with two pairs of inlet and outlet, each for the coolant/water circuit and the transmission oil circuit, — with at least two mounting holes, — whether or not with the connection hoses, for use in the manufacture of goods of Chapter 87 (1)	0 %	-	31.12.2028
0.8812	ex 8708 91 35	40	Radiators: — with corrosion protection, — for pressures up to 150 PSI (1034 kPa), — with individual replaceable, cooling tubes in brass or copper, for use in the production of engine and charge air cooling with a weight of 265 kg or more but not more than 599 kg (1)	0 %	-	31.12.2029
0.8775	ex 8708 94 99	10	Hub gear made of cold rolled carbon steel (per ASTM A1008), molded into the plastic and pressed on pinion, with: — an outer diameter of 81,2 mm or more, but not more than 82,55 mm, — an inner diameter of 25,9 mm or more, but not more than 25,97 mm, — a height of the lower side of inner diameter of 11,63 mm or more, but not more than 12,13 mm, — a height of the upper side of inner diameter of 3,25 mm or more, but not more than 3,5 mm, — an overall height of 11,63 mm or more, but not more than 19,5 mm for use in the manufacture of vehicle’s steering system (1)	0 %	-	31.12.2029
0.8777	ex 8708 94 99	20	Intermediate steering shaft forming part of the steering column with: — a torsional rigidity of 25 Nm/degree or more, — a tubular male shaft in welded carbon steel tube (per GB/T 699 grade 20), — a tubular female shaft in welded carbon steel tube (per with GB/T 699 grade 20), — two spiders universal joint made of chromium alloy steel (per GB/T 5216 grade 20CrMnTiH), — a length in nominal telescope position of 396 mm or more but not more than 467 mm, — a coupling interface on both ends with internal toothing, — two cardan joints on both sides, — a telescope shaft function with a range of 74 mm or more but not more than 115 mm, for use in the manufacture of vehicle’s steering system (1)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8778	ex 8708 94 99	30	Lower assist shaft as part of the steering column made of carbon steel (per GB/T699 grade 45 or JIS G4051 grade S45C) with: — an ultimate torsional strength load of 325 Nm or more and Johnson Apparent Elastic Limit (J.A.E.L) values of 275 Nm or more, — a length of 66,39 mm or more but not more than 88,64 mm, — an outer diameter of 27,47 mm or more but not more than 28,38 mm, — an inner hole of diameter 6,50 mm or more but not more than 6,58 mm, — an external 26-teeth spline with major diameter 21,18 mm or more but not more than 21,44 mm, — a knurling on a part of outer surface of major diameter 26,0 mm or more but not more than 26,1 mm, — with or without an external 24-tooth spline and with a major diameter 24,75 mm or more but not more than 25 mm, for use in the manufacture of vehicle's steering system [(1)]	0 %	-	31.12.2029
0.8779	ex 8708 94 99	40	Upper assist shaft as part of the steering column made of carbon steel (per GB/T699 grade 45) with: — an ultimate torsional strength load of 325 Nm or more and Johnson Apparent Elastic Limit (J.A.E.L) values of 275 Nm or more, — a length of 165,3 mm or more but not more than 204,2 mm, — an outer diameter of 22,87 mm or more but not more than 22,92 mm, — an internal hole of diameter 6,50 or more but not more than 6,58 mm, — an external spline, for use in the manufacture of vehicle's steering system [(1)]	0 %	-	31.12.2029
0.8780	ex 8708 94 99	50	Lower shaft as part of the steering column made of aluminium alloy (per ASTM B221M grade 6105), air quenched and tempered with: — an ultimate torsional strength of 260 Nm or more, — a length of 296,7 mm or more but not more than 297,8 mm, — an external 18-tooth spline on all shaft length with major diameter of 28,7 mm or more but not more than 29 mm, — an 18-tooth internal spline with a minor diameter of 19,7 mm or more but not more than 20 mm, for use in the manufacture of vehicle's steering system [(1)]	0 %	-	31.12.2029
0.8782	ex 8708 94 99	60	Torsion bar as part of the steering column made of carbon alloy steel (per SAE J1268, grade 5160H of modified chemistry for carbon content of 0,53 or more, but not more than 0,56) with: — a shaft torsional stiffness of 2,5 Nm/degree or more but not more than 2,7 Nm/degree, — a length of 107,75 mm or more but not more than 108,25 mm, — an outer diameter of 6,38 mm or more but not more than 6,42 mm, — two external 18-tooth splines on both shaft ends with a major diameter of 6,70 mm or more but not more than 6,85 mm, as interface to pressing with matting input and output shafts, — entire surface shot peened, for use in the manufacture of vehicle's steering system [(1)]	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8781	ex 8708 94 99	70	Tubular steering shaft as part of the steering column made of carbon steel welded tube (per EN 10305/2, E235 + C or GB/T699 grade 20) with: — an ultimate torsional strength of 300 Nm or more and Johnson Apparent Elastic Limit (J.A.E.L) values of 275 Nm or more, — a length of 245,48 mm or more but not more than 287,5 mm, — an outer diameter of 23,95 mm or more but not more than 32,25 mm, — an interface for steering wheel connection either in a form of an external 40-tooth spline with major diameter of 17,1 mm or more but not more than 17,5 mm and an internal thread M12x1,75-6H or in a form of an external hexagon with a short diagonal of 15,05 mm or more but not more than 15,35mm and an internal thread M10x1.5-6H, — an interface either in a form of an internal 10-tooth spline of length of 98.0 mm or more but not more than 160 mm, with minor diameter of 16,1 mm or more but not more than 16,4 mm or in a form of an internal 48-tooth spline of length of 151 mm or more but not more than 160 mm, with minor diameter of 23,2 mm or more but not more than 23,3 mm, for use in the manufacture of vehicle's steering system (1)	0 %	-	31.12.2029
0.9033	ex 8708 94 99	80	Blank assembly worm gear, consisting of a hub of carbon steel (GB/T 699 grade 25 or DIN EN 10277 grade 11SMn30) and a ring of cast polyamide 6/12 with: — an outer diameter of 97,35 mm or more, but not more than 102,65 mm, — an inner diameter of 27,91 mm or more, but not more than 27,93 mm, — a height of the hub of 11,75 mm or more, but not more than 12,00 mm, — an overall height of 16,00 mm or more, but not more than 18,00 mm	0 %	-	31.12.2030
0.6688	ex 8708 95 10 ex 8708 95 99	20 30	Inflatable safety cushion of high strength polyamide fibre: — sewn, — folded, — with three-dimensionally applied silicone bonding for air bag cavity forming and load-regulated air bag sealing, — suitable for cool inflator technology	0 %	p/st	31.12.2030
0.6687	ex 8708 95 10 ex 8708 95 99	30 40	Inflatable sewn safety cushion of high strength polyamide fibre: — folded into three-dimensional packing form, fixed by thermal forming, dedicated fixation seams, fabric cover or plastic staples, or — flat safety cushion with or without thermal folding	0 %	p/st	31.12.2030
0.8292	*ex 8708 95 99	50	Airbag inflator containing pyrotechnics, whether or not cold gas, as propellant for safety airbags of vehicles, in each individual consignment of 1 000 pieces or more	0 %	p/st	31.12.2031
0.6583	ex 8708 99 10 ex 8708 99 97	60 50	Aluminium engine bracket, with dimensions of: — height of more than 10 mm but not more than 200 mm, — width of more than 10 mm but not more than 250 mm, — length of more than 10 mm but not more than 200 mm, equipped with at least two fixing holes, made of aluminium alloys ENAC-46100 or ENAC-42100 (based on the norm EN:1706) with following characteristics: — internal porosity not more than 1 mm, — outer porosity not more than 2 mm, — rockwell hardness HRB 10 or more, of a kind used in the production of suspensions systems for engines in motor vehicles	0 %	p/st	31.12.2029
0.9029	ex 8708 99 97	27	Inner pole electromagnet core used in Magneto-Rheological engine mounts to reduce shocks and for isolation and damping in passenger cars: — of a powder metal assembly, — with a diameter of not more than 90,95 mm, — with an overall height of 24,5 mm, — impregnated with sealant, — zinc plated	0 %	-	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8986	ex 8708 99 97	53	Roll rod assembly for the front suspension in vehicles for connecting the stabilizer to the suspension components: — made of aluminum, rubber, and plastic, — with a height of 270 mm or more, but not more than 300 mm, — with a width of 50 mm or more, but not more than 65 mm, — with a length of 150 mm or more, but not more than 170 mm, for use in the manufacture of motor vehicles (1)	0 %	-	31.12.2030
0.8973	ex 8708 99 97	58	Mounting bracket of front radiator or intercooler: — made of iron or steel or of plastics, — whether or not with rubber cushioning, for use in the manufacture of goods of heading 8708 (1)	0 %	-	31.12.2030
0.9138	*ex 8708 99 97	63	Dynamic vibration damper consisting of metal-reinforced rubber, intended to be mounted on the front axle of a motor vehicle, for use in the manufacture of goods of Chapter 87 (1)	0 %	-	31.12.2031
0.6848	ex 8714 10 90	70	Motor bikes radiators in consignment of 100 pieces or more	0 %	p/st	31.12.2027
0.6172	ex 8714 91 30 ex 8714 91 30 ex 8714 91 30	25 35 72	Front forks, except rigid (non-telescopic) front forks made entirely of steel, for use in the manufacture of bicycles (including electric bicycles) (1)	0 %	-	31.12.2029
0.8959	ex 8714 93 00	20	Gear set to connect sprockets: — for mounting on a hub drum, — with 7 sprockets or more but not more than 12 sprockets, — with 10 or more but not more than 52 teeth for each sprocket, — with a weight of 200 g or more but not more than 800 g, — sprockets made of nickel-plated steel or aluminium, — with connectors (spacers) between the sprockets made of plastic or aluminium, — without a pawl mechanism, for use in the manufacture of bicycles and e-bikes (1)	0 %	-	31.12.2030
0.6879	ex 8714 96 10	10	Pedals, for use in the manufacture of bicycles (including electric bicycles) (1)	0 %	-	31.12.2030
0.7421	ex 8714 99 10 ex 8714 99 10	20 89	Bicycle handlebars: — with or without an integrated stem, — either made out of carbon fibres and synthetic resin or made of aluminium, for use in the manufacture of bicycles (including electric bicycles) (1)	0 %	-	31.12.2027
0.7710	ex 8714 99 50 ex 8714 99 50	11 91	Derailleur gears, consisting of: — rear derailleur and mounting articles, — with or without front derailleur, for use in the manufacture of bicycles (including electric bicycles) (1)	0 %	p/st	31.12.2029
0.6878	ex 8714 99 90	30	Seat posts, for use in the manufacture of bicycles (including electric bicycles) (1)	0 %	p/st	31.12.2030
0.7708	ex 8714 99 90	40	Stem for bicycle handlebars, for use in the manufacture of bicycles (including electric bicycles) (1)	0 %	p/st	31.12.2029
0.8507	ex 8714 99 90	50	Rear air shock absorber in form of a pneumatic spring element with oil damper for use in the manufacture of bicycles, including electrical bicycles (1)	0 %	p/st	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.3191	ex 9001 10 90	10	Image reverser made up from an assembly of optical fibres	0 %	-	31.12.2029
0.6402	ex 9001 50 41 ex 9001 50 49	40 40	Organic uncut corrective eyeglass lens, finished on both sides, to undergo a coating, colouring, edging, mounting or any other substantial process for use in the manufacture of corrective glasses (1)	0 %	-	31.12.2027
0.6401	*ex 9001 50 80	30	Round organic uncut, semi-finished eyeglass lens with corrective effect, finished on one side, of a kind used for the manufacture of finished eyeglass lenses	0 %	-	31.12.2031
0.7590	ex 9002 11 00	18	Lens assembly consisting of a cylinder-shaped cover made of metal or plastic and optical elements with: — a horizontal field of view range to a maximum of 120 deg, — a diagonal field of view range to a maximum of 105 deg, — a focal length to a maximum of 7,50 mm, — a relative aperture of a maximum of F/2,90, — a maximum diameter of 22 mm	0 %	-	31.12.2029
0.5692	ex 9002 11 00	20	Lenses: — measuring not more than 95 mm × 55 mm × 50 mm, — with a resolution of 160 lines/mm or better, and — with a zoom ratio of 3 or more times	0 %	-	31.12.2027
0.7973	ex 9002 11 00	23	Lens with: — motorized focus, zoom, aperture, — electronically switchable infrared cut filter, — an adjustable focal length not less than 2,7 mm and not more than 55mm, — a weight of not more than 120 g, — a length of less than 70 mm, — a diameter of not more than 70 mm	0 %	-	31.12.2030
0.7103	*ex 9002 11 00	45	Infrared optical unit — with lenses of silicon, germanium or chalcogenide glass of a diameter not more than 62 mm (± 0,05 mm), — whether or not mounted on a machined aluminium alloy support of a kind used for thermal cameras or IP network cameras	0 %	-	31.12.2031
0.3177	ex 9002 11 00	50	Lens unit: — having a focal length of 25 mm or more but not more than 150 mm, — consisting of glass or plastic lenses, with a diameter of 60 mm or more but not more than 190 mm	0 %	-	31.12.2029
0.6572	ex 9002 11 00	85	Lens with — a horizontal field of view of 20° or more, but not more than 220°, — a focal length of 1.16 mm or more, but not more than 20 mm, — a relative aperture of f/1.2 or more, but not more than f/4, and — a diameter of 5 mm or more, but not more than 40 mm, for use in the manufacture of CMOS vehicle-mounted cameras or IP network cameras (1)	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.9164	*ex 9018 39 00	10	Tube made of stainless steel per grade AISI 304L: — with a total length of 1050 mm or more, but not more than 1610 mm, — with a single- or four-segment blue polytetrafluoroethylene (PTFE) coating with a thickness of 0,005 mm or more, but not more than 0,02286 mm, — with an outer tube diameter of 0,61 mm or more, but not more than 0,82 mm, — with an inner tube diameter of 0,42 mm or more, but not more than 0,57 mm, — with a special finish in the form of a fragment ground at an angle with a length of 50 mm or more, but not more than 54 mm, — with a radius of curvature at the entrance of the grind and at the end of the tube of 0,1 mm or more, but not more than 0,3 mm, — whether or not with a surface finish using laser engraving technology over a length 9,5 mm or more but not more than 11,5 mm with a roughness Ra ≥ 0,6 µm	0 %	-	31.12.2031
0.6288	ex 9025 80 40	50	Electronic semiconductor sensor for measuring at least two of the following quantities: — Atmospheric pressure, temperature, (also for temperature compensation), humidity, or volatile organic compounds, — in a housing suitable for the automatic printing of conductor boards or Bare Die technology, containing : — one or more monolithic application-specific integrated circuits (ASIC), — one or more microelectromechanical sensor elements (MEMS) manufactured with semiconductor technology, with mechanical components arranged in three-dimensional structures on the semiconductor material, of a kind used for incorporation into products of Chapters 84-90 and 95	0 %	p/st	31.12.2029
0.3292	ex 9032 89 00	30	Electronic controller of electric power steering (EPS controller)	0 %	p/st	31.12.2029
0.4253	ex 9032 89 00	40	Digital valve controller for controlling liquids and gases	0 %	p/st	31.12.2027
0.9041	*ex 9032 90 00	20	Electric Power Steering (EPS) Electronic Control Unit (ECU) covers of aluminium alloy (EN 1706 grade AC-46000) with: — a heat radiating functionality, — an as-cast volume of not more than 128 000 mm3, — a machined volume of not more than 126 000 mm3, — a length and width of not more than 130 mm, — a height of not more than 40 mm, — a wall thickness of 2,5 mm or more but not more than 16 mm, — 6 or more but not more than 20 mounting screw holes with a diameter of 2,5 mm or more but no more than 4,0 mm, — with critical assembly areas with a flatness of not more than of 0,1 mm, — tolerance machining of 0,05 mm or lower diameter tolerance and flatness of 0,1 mm or lower	0 %	-	31.12.2031
0.5025	ex 9401 99 20	10	Ratchet disk for use in the manufacture of reclining car seats (1)	0 %	p/st	31.12.2028
0.8989	ex 9401 99 20	20	A high-mobility positioning cassette, — capable of operating within a temperature range of -40°C to +85°C, — enables controlled forward and backward movement of a vehicle seat, — integrated with the seat backrest via a steel cable system, preventing seat removal when the backrest is open and allowing it only when the backrest is closed, — constructed from glass fiber-reinforced, special alloy aluminum components and fitted with self-lubricating bushings made of polyoxymethylene (POM) and polytetrafluoroethylene (PFTE) to minimize friction, — equipped with a locking system designed to remain secure under forces up to 20G, — requires a minimum force of 40N for normal operation	0 %	-	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.9030	ex 9401 99 20	30	Latch seat system modules enabling seat sliding, latching and unlatching in random, independent positions along the rails: — with an integrated safety locking mechanism, — with a cassette architecture for integration with seat through screw connections, — with a housing made of a magnesium die-cast alloy, — with an anti-noise system, — interfacing with car rail systems, — without electronic control unit, — without semiconductors, — with a weight of 1475 g or more, but not more than 1619 g	0 %	-	31.12.2030
0.8786	ex 9503 00 95	30	Miniature engine: — consisting of a plastic body, — containing a spring, — providing movement of gear shafts with spring tension, for use in the manufacture of the toys under heading 9503 (1)	0 %	-	31.12.2029
0.8789	ex 9503 00 95	40	Miniature engine driven by mechanical friction: — consisting of a plastic body, — with shaft length 10,5 cm or more but not more than 14,5 cm, — containing a metal disc, — creating movement by causing the gears to rotate with the friction force, for use in the manufacture of the toys under heading 9503 (1)	0 %	-	31.12.2029
0.3286	ex 9608 91 00	10	Non-fibrous plastic pen-tips with an internal canal	0 %	-	31.12.2029
0.3289	ex 9608 91 00	20	Felt tips and other porous-tips for markers, without internal canal	0 %	-	31.12.2029

(1) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013.

(2) However, the suspension of tariff duties does not apply where the processing is carried out by retail or catering undertakings.

(3) Only the *ad valorem* duty is suspended. The specific duty shall continue to apply.

* New or amendment request.'.